chanhvinh.com

SAFETY DATA SHEET

In accordance with OSHA 29 CFR 1910.1200

BOSTIK® GLIDECOTE
Revision Number 4

Revision date 01-Jul-2025
Supersedes date 15-Feb-2024

1. Identification

1.1. Product identifier

Product Name BOSTIK® GLIDECOTE

Other means of identification
Other information Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Lubricant
Restrictions on use No information available

1.3. Details of the supplier of the safety data sheet

Responsible Party
Bostik Inc.
11320 W. Watertown Plank Road
Wauwatosa, Wisconsin 53226 USA
Phone: +1(800) 726-7845 (Domestic Toll Free)
Phone: +1 (414) 774-2250 (International)

E-mail msds@bostik.com

1.4. Emergency telephone number

Emergency Telephone CHEMTREC (Chemical Transportation Emergency Center)
Chemtrec: 1-800-424-9300 (US) , 1-703-527-3887 (Outside U.S.)
Rocky Mountain Poison Center: 1-866-767-5089

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Aerosols	Category 1
Gases Under Pressure	Compressed gas
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Aspiration hazard	Category 1

Hazards not otherwise classified (HNOC)
Not applicable

2.2. Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements
Causes skin irritation

chanhvinh.com

SAFETY DATA SHEET

Causes serious eye irritation
May cause drowsiness or dizziness
May be fatal if swallowed and enters airways
Extremely flammable aerosol
Contains gas under pressure; may explode if heated



Appearance Aerosol

Physical state Liquid

Odor Solvent

Precautionary Statements - Prevention
Wash face, hands and any exposed skin thoroughly after handling
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Do not spray on an open flame or other ignition source
Pressurized container: Do not pierce or burn, even after use
Wear protective gloves/eye protection/face protection

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN: Wash with plenty of water and soap
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash it before reuse
IF INHALED: Remove person to fresh air and keep comfortable for breathing
Call a POISON CENTER or doctor if you feel unwell
IF SWALLOWED: Immediately call a POISON CENTER or doctor
Do NOT induce vomiting

Precautionary Statements - Storage
Store locked up
Store in a well-ventilated place. Keep container tightly closed
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
Protect from sunlight

Precautionary Statements - Disposal
Dispose of contents/container to an approved waste disposal plant

2.3. Other Information

In case of insufficient ventilation and/or through use, the formation of an explosive/highly flammable mixture is possible. May be harmful if inhaled.

3. Composition/information on ingredients

3.1. Substances

chanhvinh.com

SAFETY DATA SHEET

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%
Acetone	67-64-1	30 - 60
Naphtha, petroleum, light alkylate	64741-66-8	7 - <13
2,2,4-Trimethylpentane	540-84-1	5 - <10
Naphtha, petroleum, hydrotreated heavy, <0.1% Benzene	64742-48-9	1 - <5

**The exact percentage (concentration) of composition has been withheld as a trade secret*

4. First-aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Inhalation Remove to fresh air. If breathing is difficult, (trained personnel should) give oxygen. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Aspiration into lungs can produce severe lung damage. Delayed pulmonary edema may occur. Get immediate medical attention.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.

Skin contact Wash off immediately with soap and plenty of water for at least 15 minutes. In case of contact with liquefied gas, thaw frosted parts with lukewarm water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. Get immediate medical attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Effects of Exposure No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances. Treat

chanhvinh.com

SAFETY DATA SHEET

symptomatically.

5. Fire-Fighting Measures

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray.
Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket.

Hazardous combustion products Carbon oxides. Hydrogen fluoride.

Explosion data
Sensitivity to mechanical impact Yes.

Sensitivity to static discharge Yes.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Contents under pressure. Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Ensure adequate ventilation. Do not breathe vapor or mist. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Wash thoroughly after handling. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Avoid release to the environment. Do not allow into any sewer, on the ground or into any body of water. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches

chanhvinh.com

SAFETY DATA SHEET

and waterways. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up

Use personal protective equipment as required. Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

Reference to other sections

See section 8 for more information. See section 13 for more information.

7. Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Contents under pressure. Use personal protection equipment. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Avoid breathing vapors or mists. Handle product only in closed system or provide appropriate exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Do not puncture or incinerate cans. In case of rupture. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep/store only in original container. Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials. Store in a dry place. Store in a closed container.

7.3 References to other sections

Reference to other sections

Section 10: STABILITY AND REACTIVITY
Section 13: DISPOSAL CONSIDERATIONS

8. Exposure Controls/Personal Protection

8.1. Control parameters

Exposure Limits

The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Acetone 67-64-1	TWA: 250 ppm STEL: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m^3 (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m^3	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m^3

chanhvinh.com

SAFETY DATA SHEET

		(vacated) STEL: 2400 mg/m³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	
2,2,4-Trimethylpentane 540-84-1	TWA: 300 ppm	-	-

Chemical name	Argentina	Brazil	S.D. 594/1999	Colombia
Acetone 67-64-1	TWA-CMP: 500 ppm; STEL (CMP-CPT): 750 ppm;	TWA-LT: 780 ppm; TWA-LT: 1870 mg/m³; STEL: 500 ppm;	TWA-LPP: 438 ppm; TWA-LPP: 1040 mg/m³; STEL-LPT: 750 ppm; STEL-LPT: 1782 mg/m³;	STEL: 500ppm TWA: 250ppm
2,2,4-Trimethylpentane 540-84-1	TWA-CMP: 300 ppm;	TWA-LT: 300 ppm;	-	TWA: 300ppm

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Acetone 67-64-1	STEL: 500ppm TWA: 250ppm	STEL: 750ppm STEL: 1781mg/m³ TWA: 500ppm TWA: 1187mg/m³	500 ppm STEL 250 ppm TWA	STEL: 750 ppm TWA: 500 ppm
2,2,4-Trimethylpentane 540-84-1	-	-	300 ppm TWA	-

8.2. Exposure controls

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles. Avoid contact with eyes. If splashes are likely to occur:. Face protection shield.

Hand protection Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Wear suitable gloves and eye/face protection. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash hands before breaks and immediately after handling the product. Contaminated work clothing must not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

chanhvinh.com

SAFETY DATA SHEET

9. Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Aerosol
Color	Colorless
Odor	Solvent
Odor threshold	No information available

Property	**Values**	**Remarks • Method**
pH	No data available	Not applicable Insoluble in water
pH (as aqueous solution)	No data available	None known
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	Not applicable, Aerosol
Flash point	-50 °C / -58 °F	None known
Evaporation rate	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	None known
Relative vapor density	No data available	None known
Relative density	No data available	None known
Water solubility	Insoluble in water	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

9.2. Other information

Explosive properties	No information available	
Oxidizing properties	No information available	
Solvent content (%)	No information available	
Solid content (%)	approx 2.3	
Softening point	No information available	
Molecular weight	No information available	
VOC content	No information available	No information available
Density	0.800 g/ml	
Bulk density	No information available	

10. Stability and Reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Chemical stability Stable under normal conditions.

chanhvinh.com

SAFETY DATA SHEET

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Excessive heat. Keep away from open flames, hot surfaces and sources of ignition. Extremes of temperature and direct sunlight.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents. Incompatible with oxidizing agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None known based on information supplied

11. Toxicological information

11.1. Information on toxicological effects

Product Information

Inhalation Specific test data for the substance or mixture is not available. May be harmful if inhaled. May cause irritation of respiratory tract. May cause drowsiness or dizziness. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components). Repeated exposure may cause skin dryness or cracking.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause lung damage if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>5000 mg/kg
ATEmix (dermal)	15,351.20 mg/kg
ATEmix (inhalation-gas)	1,352,330.00 ppm
ATEmix (inhalation-dust/mist)	33.20 mg/l
ATEmix (inhalation-vapor)	115.4513 mg/l

chanhvinh.com

SAFETY DATA SHEET

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	=5800 mg/kg (Rattus) 3000 mg/Kg (mouse)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Naphtha, petroleum, light alkylate 64741-66-8	>7000 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus cuniculus)	>6.31 mg/L (Rattus) 4 h
2,2,4-Trimethylpentane 540-84-1	>5000 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus cuniculus)	>14.38 mg/L (Rattus) 4 h
Naphtha, petroleum, hydrotreated heavy, <0.1% Benzene 64742-48-9	>6000 mg/kg (Rattus)	> 3160 mg/kg (Oryctolagus cuniculus)	LC50 Vapour (4h) >5020 mg/m^3 (Rattus)

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Acetone (67-64-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			irritant

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

Acetone (67-64-1)

Method	Species	Exposure route	Results
GPMT - Guinea pig maximisation test	Guinea pig	Dermal	Not a skin sensitizer

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Acetone 67-64-1	A4 - Not Classifiable as a Human Carcinogen	-	-	-

Legend
ACGIH (American Conference of Governmental Industrial Hygienists)
A4 - Not classifiable as a human carcinogen

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

Acetone (67-64-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results

chanhvinh.com

SAFETY DATA SHEET

Experiences made in practice					Narcotic effects

STOT - repeated exposure Based on available data, the classification criteria are not met.

Acetone (67-64-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 408: Repeated Dose 90-Day Oral Toxicity Study in Rodents	Rat	Oral	200-3400 mg/kg bw/day	91 days	No Observed Adverse Effect Level LOAEL 1700 mg/kg bw/day
Not specified	Rat	Inhalation	19000 ppm	14, 28, 56 days	NOAEC 19000 ppm No Observed Adverse Effect Level

Aspiration hazard May be fatal if swallowed and enters airways.

Other adverse effects No information available.

Interactive effects No information available.

12. Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)
Naphtha, petroleum, light alkylate 64741-66-8	EC50 72 h = 6.4 mg/L (Pseudokirchneriella subcapitata)	-	-	LC50: =2mg/L (48h, Mysidopsis bahia)
Naphtha, petroleum, hydrotreated heavy, <0.1% Benzene 64742-48-9	EL50 (72h) > 1000 mg/l (Pseudokirchneriella subcapitata) OECD 201	LC50: =2200mg/L (96h, Pimephales promelas)	-	LL50 (48h) > 1000 mg/l (Daphnia magna) OECD 202

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24

chanhvinh.com

SAFETY DATA SHEET

12.4. Mobility in soil

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

13. Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. Should not be released into the environment. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Dispose of in accordance with federal, state and local regulations.

14. Transport information

Note: The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material. 49 CFR 171.4(c) "Exceptions. Except when all or part of the transportation is by vessel, the requirements of this subchapter specific to marine pollutants do not apply to non-bulk packagings transported by motor vehicle, rail car or aircraft.".

DOT

UN number or ID number	UN1950
Extended proper shipping name	Aerosols
Transport hazard class(es)	2.1
Reportable quantity (lbs)	2,2,4-Trimethylpentane: RQ (lb)= 1000.00, Acetone: RQ (lb)= 5000.00
Reportable Quantity (RQ)	(2,2,4-Trimethylpentane: RQ (kg)= 454.00, Acetone: RQ (kg)= 2270.00)
Special Provisions	N82
DOT Marine Pollutant	I
Marine pollutant	Naphtha, petroleum, light alkylate, 2,2,4-Trimethylpentane
Description	UN1950, Aerosols, 2.1, Marine pollutant (Naphtha, petroleum, light alkylate, 2,2,4-Trimethylpentane)
Emergency Response Guide Number	126

IATA

UN number or ID number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	2.1
Special Provisions	A145, A167, A802
Description	UN1950, Aerosols, flammable, 2.1

IMDG

UN number or ID number	UN1950
UN proper shipping name	Aerosols
Transport hazard class(es)	2.1
EmS-No.	F-D, S-U
Special Provisions	63,190, 277, 327, 344, 381, 959

chanhvinh.com

SAFETY DATA SHEET

Marine pollutant	P
IMDG Marine Pollutant Name	Naphtha, petroleum, light alkylate, 2,2,4-Trimethylpentane
Description	UN1950, Aerosols, 2.1, Marine pollutant (Naphtha, petroleum, light alkylate, 2,2,4-Trimethylpentane)

15. Regulatory Information

International Inventories

TSCA	Complies
DSL	Not Listed

Legend:
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL - Canadian Domestic Substances List
Complies - The components of this product are either listed or exempt from listing on inventory. Active
Not Listed - One or more components of this product are not listed on inventory.

US Federal Regulations

SARA 313
Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories
Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

16. Other Information

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend
SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances
STOT: Specific Target Organ Toxicity
ATE: Acute Toxicity Estimate
LC50: 50% Lethal Concentration
LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	Sk*	Skin designation

Prepared By	Product Stewardship and Regulatory Affairs.
Revision date	01-Jul-2025
Revision Note	SDS sections updated. 2. 5. 6. 8. 11. 13. 14. 15.

Disclaimer
All information contained herein is believed to be accurate as of the date of publication, is provided "as-is" and is subject to change without notice. This is not a warranty, an agreement, or substitute for expert or professional advice. Bostik Inc. ("Company") expressly disclaims and assumes no liability for the use of the products or reliance on this information.

chanhvinh.com

SAFETY DATA SHEET

It is the sole responsibility of the user to determine the suitability of any products for user's application(s). NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED (INCLUDING SUITABILITY FOR USE IN ANY MEDICAL DEVICE OR MEDICAL APPLICATION), IS MADE CONCERNING THE PRODUCTS OR THE INFORMATION PROVIDED HEREIN. The information provided relates only to the specific products designated herein and may not be valid where such products are used in combination with other materials or in any process. The performance of the product, its shelf life, and application characteristics depends on many variables, and changes in these variables can impact product performance. You are responsible to test the suitability of any product in advance for any intended use or application and before commercialization. Nothing herein shall be construed as a license for the use of any product in a manner that might infringe any patent and it should not be construed as an inducement to infringe any patent. Please carefully review the Safety Data Sheet for the product.

The Company adheres to a strict policy that applies to the use of any of its products in medical device applications. This policy can be found at https://www.arkema.com/global/en/social-responsibility/innovation-and-sustainable-solutions/responsible-product-management/medical-device-policy/ which is incorporated herein by reference and made a part hereof. Except as expressly authorized, the Company (i) has designated specific medical grade compositions for products used in medical device applications and Company products not so designated are not authorized for use in medical device applications and (ii) strictly prohibits the use of any of its products in medical device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Company does not design, manufacture and/or directly sell any medical devices. The Company does not co-design, or offer assistance to any purchaser of its products, in their design, manufacture and/or sale of products for medical devices. It is the sole responsibility of the manufacturer of medical devices to determine the suitability of all raw material, products and components, including any medical grade products, in order to ensure that the medical device is safe for end-use and complies with all applicable legal and regulatory requirements and to conduct all necessary tests and inspections.

End of Safety Data Sheet