chanhvinh.com

SAFETY DATA SHEET

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC

Product name: MOLYKOTE® BR2 Plus High Performance Grease

Issue Date: 11/20/2025

Print Date: 11/26/2025

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: MOLYKOTE® BR2 Plus High Performance Grease

Recommended use of the chemical and restrictions on use
Identified uses: Lubricants and lubricant additives

COMPANY IDENTIFICATION
DDP SPECIALTY ELECTRONIC MATERIALS
US 9, LLC
974 Centre Road
Wilmington DE 19805
UNITED STATES

Customer Information Number: 833-338-7668
SDSQuestion-NA@dupont.com

EMERGENCY TELEPHONE NUMBER
24-Hour Emergency Contact: +1 800-424-9300
Local Emergency Contact: +1 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification
GHS classification in accordance with 29 CFR 1910.1200
Serious eye damage - Category 1

Label elements
Hazard pictograms



Signal word: **DANGER!**

chanhvinh.com

Hazards
Causes serious eye damage.

Precautionary statements

Prevention
Wear eye protection/ face protection.

Response
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

Other hazards
No data available
Further information
The values listed below represent the percentages of ingredients of unknown toxicity.
The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: 7.3868 %

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Molybdenum disulfide grease
This product is a mixture.

Component	CASRN	Concentration
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 38.0 - <= 46.0 %
Solvent dewaxed heavy paraffinic distillates	64742-65-0	>= 34.0 - <= 41.0 %
Lithium 12-hydroxyoctadecanoate	7620-77-1	>= 3.0 - <= 7.0 %
Solvent dewaxed residual oil (petroleum)	64742-62-7	>= 3.0 - <= 5.0 %
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	68457-79-4	>= 3.0 - <= 4.0 %
Graphite	7782-42-5	>= 0.5 - <= 2.5 %
Molybdenum disulfide	1317-33-5	>= 0.5 - <= 2.5 %

chanhvinh.com

4. FIRST AID MEASURES

Description of first aid measures
General advice:
First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: If inhaled Move person to fresh air; if effects occur, consult a physician.

Skin contact: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation occurs: Get medical advice/ attention.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist. Suitable emergency eye wash facility should be available in work area.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel. Consult a physician if necessary.

Most important symptoms and effects, both acute and delayed:
Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed
Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical

Unsuitable extinguishing media: None known.

Special hazards arising from the substance or mixture
Hazardous combustion products: Metal oxides Oxides of phosphorus Sulphur oxides Carbon oxides

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health.

Advice for firefighters
Fire Fighting Procedures: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage.

chanhvinh.com

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Do not release the product to the aquatic environment above defined regulatory levels Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
See sections: 7, 8, 11, 12 and 13.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not get on skin or clothing. Do not swallow. Do not get in eyes. Keep container tightly closed. Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice.
Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Advice on general occupational hygiene
Handle in accordance with good industrial hygiene and safety practice. Use good personal hygiene. Do not consume or store food in the work area. Wash hands before smoking or eating. Ensure that eye flushing systems and safety showers are located close to the working place.

Conditions for safe storage: Keep in properly labelled containers. Keep tightly closed. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents.
Unsuitable materials for containers**:** None known.

chanhvinh.com

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Distillates (petroleum), hydrotreated heavy naphthenic	ACGIH	TWA Inhalable particulate matter	5 mg/m3
	Further information: A4: Not classifiable as a human carcinogen		
	CAL PEL	PEL particulate	5 mg/m3
	Further information: (l): As sampled by method that does not collect vapor.		
Solvent dewaxed heavy paraffinic distillates	ACGIH	TWA Inhalable particulate matter	5 mg/m3
	Further information: A4: Not classifiable as a human carcinogen		
	CAL PEL	PEL particulate	5 mg/m3
	Further information: (l): As sampled by method that does not collect vapor.		
	OSHA Z-1	TWA Mist	5 mg/m3
	NIOSH REL	TWA Mist	5 mg/m3
	NIOSH REL	ST Mist	10 mg/m3
Lithium 12-hydroxyoctadecanoate	ACGIH	TWA Inhalable particulate matter	10 mg/m3
	Further information: A4: Not classifiable as a human carcinogen		
	ACGIH	TWA Respirable particulate matter	3 mg/m3
	Further information: A4: Not classifiable as a human carcinogen		
Solvent dewaxed residual oil (petroleum)	ACGIH	TWA Inhalable particulate matter	5 mg/m3
	Further information: A4: Not classifiable as a human carcinogen		
	OSHA Z-1	TWA Mist	5 mg/m3
	NIOSH REL	TWA Mist	5 mg/m3
	NIOSH REL	ST Mist	10 mg/m3
Graphite	OSHA Z-3	TWA Dust	15 Million particles per cubic foot
	OSHA Z-1	TWA total dust	15 mg/m3
	OSHA Z-1	TWA respirable fraction	5 mg/m3
	ACGIH	TWA Respirable particulate matter	2 mg/m3
	CAL PEL	PEL Total dust	10 mg/m3
	CAL PEL	PEL respirable dust fraction	5 mg/m3
	Further information: (n): The concentration and percentage of the particulate used for this limit are determined from the fraction passing a size selector with the following characteristics: Aerodynamic Diameter in Micrometers (unit density sphere)..... Percent Passing Selector 0 ..... 100 1 ..... 97 2 ..... 91 3 ..... 74 4 ..... 50 5 ..... 30 6 ..... 17 7 ..... 9 8 ..... 5 10 1		

chanhvinh.com

	CAL PEL	PEL Respirable dust	2.5 mg/m3
	NIOSH REL	TWA Respirable	2.5 mg/m3
	OSHA P0	TWA Total dust	10 mg/m3
	OSHA P0	TWA respirable dust fraction	5 mg/m3
	OSHA P0	TWA respirable dust fraction	2.5 mg/m3
Molybdenum disulfide	OSHA Z-1	TWA total dust	15 mg/m3 , Molybdenum
	ACGIH	TWA Inhalable particulate matter	10 mg/m3 , Molybdenum
	ACGIH	TWA Respirable particulate matter	3 mg/m3 , Molybdenum
	CAL PEL	PEL Total dust	10 mg/m3 , Molybdenum
	CAL PEL	PEL respirable dust fraction	3 mg/m3 , Molybdenum
	Further information: (n): The concentration and percentage of the particulate used for this limit are determined from the fraction passing a size selector with the following characteristics: Aerodynamic Diameter in Micrometers (unit density sphere)..... Percent Passing Selector 0 ..... 100 1 ..... 97 2 ..... 91 3 ..... 74 4 ..... 50 5 ..... 30 6 ..... 17 7 ..... 9 8 ..... 5 10 1		

Exposure controls
Engineering measures: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Use good personal hygiene. Do not consume or store food in the work area. Wash hands before smoking or eating. Ensure that eye flushing systems and safety showers are located close to the working place.

Individual protection measures
Eye/face protection: Use safety glasses (with side shields). If there is a potential for exposure to particles which could cause eye discomfort, wear chemical goggles.
Skin protection
Hand protection: Use gloves chemically resistant to this material. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.
Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.
Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process.

chanhvinh.com

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	
Physical state	Grease
Color	black
Odor	slight
Odor Threshold	No data available
pH	Substance/mixture is non-soluble (in water).Substance/mixture is non-soluble (in water).
Melting point/ range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	Not applicable
Flash point	**closed cup** >200 °C (392 °F)
Evaporation Rate (Butyl Acetate = 1)	Not applicable
Flammability (solid, gas)	Not classified as a flammability hazard
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapor Pressure	Not applicable
Relative Vapor Density (air = 1)	No data available
Relative Density (water = 1)	0.89
Water solubility	No data available
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Dynamic Viscosity	Not applicable
Kinematic Viscosity	Not applicable
Explosive properties	Not explosive
Oxidizing properties	The substance or mixture is not classified as oxidizing.
Molecular weight	No data available
Particle size	No data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

chanhvinh.com

10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents.

Conditions to avoid: None known.

Incompatible materials: Oxidizing agents

Hazardous decomposition products
No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity
Product test data not available. Refer to component data.

Acute dermal toxicity
Product test data not available. Refer to component data.

Acute inhalation toxicity
Product test data not available. Refer to component data.

Skin corrosion/irritation
Product test data not available. Refer to component data.

Serious eye damage/eye irritation
Product test data not available. Refer to component data.

Sensitization
Product test data not available. Refer to component data.

Specific Target Organ Systemic Toxicity (Single Exposure)
Product test data not available. Refer to component data.

Specific Target Organ Systemic Toxicity (Repeated Exposure)
Product test data not available. Refer to component data.

Carcinogenicity
Product test data not available. Refer to component data.

chanhvinh.com

Teratogenicity
Product test data not available. Refer to component data.

Reproductive toxicity
Product test data not available. Refer to component data.

Mutagenicity
Product test data not available. Refer to component data.

Aspiration Hazard
Product test data not available. Refer to component data.

COMPONENTS INFLUENCING TOXICOLOGY:

Distillates (petroleum), hydrotreated heavy naphthenic

Acute oral toxicity
LD50, Rat, > 5,000 mg/kg

Acute dermal toxicity
LD50, Rabbit, > 2,000 mg/kg

Acute inhalation toxicity
Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs.

LC50, Rat, 3 Hour, dust/mist, > 3.11 mg/l No deaths occurred at this concentration.

Skin corrosion/irritation
Prolonged contact is essentially nonirritating to skin.
Repeated contact may cause moderate skin irritation with local redness.

Serious eye damage/eye irritation
Essentially nonirritating to eyes.

Sensitization
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:
No relevant information found.

Specific Target Organ Systemic Toxicity (Single Exposure)
Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)
In animals, effects have been reported on the following organs after dermal exposure:
Skin.

Carcinogenicity
Has caused tumors in skin painting tests in animals. Not classifiable as a human carcinogen.

chanhvinh.com

Teratogenicity
Did not cause birth defects or any other fetal effects in laboratory animals.

Reproductive toxicity
In animal studies, did not interfere with reproduction.

Mutagenicity
In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative.

Aspiration Hazard
Based on physical properties, not likely to be an aspiration hazard.

Solvent dewaxed heavy paraffinic distillates

Acute oral toxicity
Information given is based on data obtained from similar substances. LD50, Rat, > 2,000 mg/kg OECD Test Guideline 401

Acute dermal toxicity
Information given is based on data obtained from similar substances. LD50, Rabbit, > 5,000 mg/kg OECD Test Guideline 402

Acute inhalation toxicity
LC50, Rat, 4 Hour, dust/mist, > 5.53 mg/l

Skin corrosion/irritation
Brief contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation
May cause slight temporary eye irritation.

Sensitization
Did not cause allergic skin reactions when tested in guinea pigs.

Specific Target Organ Systemic Toxicity (Single Exposure)
The substance or mixture is not classified as specific target organ toxicant, single exposure.

Specific Target Organ Systemic Toxicity (Repeated Exposure)
The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Carcinogenicity
Animal testing did not show any carcinogenic effects.

Mutagenicity
In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative.

Aspiration Hazard
No aspiration toxicity classification

chanhvinh.com

Lithium 12-hydroxyoctadecanoate

Acute oral toxicity
Information given is based on data obtained from similar substances. LD50, Rat, > 2,000 mg/kg

Acute dermal toxicity
Information given is based on data obtained from similar substances. LD50, Rat, > 2,000 mg/kg OECD Test Guideline 402

Acute inhalation toxicity
The LC50 has not been determined.

Skin corrosion/irritation
Brief contact is essentially nonirritating to skin.

Serious eye damage/eye irritation
May cause slight temporary eye irritation.

Sensitization
Did not demonstrate the potential for contact allergy in mice.
Information given is based on data obtained from similar substances.

Specific Target Organ Systemic Toxicity (Single Exposure)
The substance or mixture is not classified as specific target organ toxicant, single exposure.

Specific Target Organ Systemic Toxicity (Repeated Exposure)
Based on available data, repeated exposures are not anticipated to cause additional significant adverse effects.

Carcinogenicity
No data available

Teratogenicity
Has been toxic to the fetus in laboratory animals at doses toxic to the mother.

Reproductive toxicity
In animal studies, did not interfere with reproduction.

Mutagenicity
In vitro genetic toxicity studies were negative. Information given is based on data obtained from similar substances.

Aspiration Hazard
No aspiration toxicity classification

Solvent dewaxed residual oil (petroleum)

Acute oral toxicity
Information given is based on data obtained from similar substances. LD50, Rat, > 5,000 mg/kg OECD Test Guideline 401

Acute dermal toxicity

chanhvinh.com

Information given is based on data obtained from similar substances. LD50, Rabbit, > 5,000 mg/kg OECD Test Guideline 402

Acute inhalation toxicity
Information given is based on data obtained from similar substances. LC50, Rat, 4 Hour, dust/mist, > 5.53 mg/l OECD Test Guideline 403

Skin corrosion/irritation
Brief contact may cause slight skin irritation with local redness.
Information given is based on data obtained from similar substances.

Serious eye damage/eye irritation
May cause slight temporary eye irritation.
Information given is based on data obtained from similar substances.

Sensitization
Did not cause allergic skin reactions when tested in guinea pigs.
Information given is based on data obtained from similar substances.

Specific Target Organ Systemic Toxicity (Single Exposure)
The substance or mixture is not classified as specific target organ toxicant, single exposure.

Specific Target Organ Systemic Toxicity (Repeated Exposure)
Based on available data, repeated exposures are not anticipated to cause additional significant adverse effects.

Teratogenicity
Did not cause birth defects or any other fetal effects in laboratory animals. Information given is based on data obtained from similar substances.

Reproductive toxicity
In animal studies, did not interfere with reproduction. Information given is based on data obtained from similar substances.

Mutagenicity
In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative. Information given is based on data obtained from similar substances.

Aspiration Hazard
No aspiration toxicity classification

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts

Acute oral toxicity
LD50, Rat, male, 3,600 mg/kg

Acute dermal toxicity
LD50, Rabbit, male and female, > 20,000 mg/kg

Acute inhalation toxicity
The LC50 has not been determined.

chanhvinh.com

Skin corrosion/irritation
Brief contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation
May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

Sensitization
For skin sensitization:
Based on data from similar materials
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)
Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)
Observations in animals include:
Gastrointestinal irritation.

Carcinogenicity
No relevant data found.

Teratogenicity
No relevant data found.

Reproductive toxicity
No relevant data found.

Mutagenicity
For similar material(s): In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Aspiration Hazard
Based on physical properties, not likely to be an aspiration hazard.

Graphite

Acute oral toxicity
LD50, Rat, > 2,000 mg/kg OECD Test Guideline 423

Acute dermal toxicity
The dermal LD50 has not been determined.

Acute inhalation toxicity
An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration. LC50, Rat, 4 Hour, dust/mist, > 2 mg/l OECD Test Guideline 403

chanhvinh.com

Skin corrosion/irritation
Brief contact is essentially nonirritating to skin.

Serious eye damage/eye irritation
May cause slight temporary eye irritation.

Sensitization
Did not demonstrate the potential for contact allergy in mice.

Specific Target Organ Systemic Toxicity (Single Exposure)
The substance or mixture is not classified as specific target organ toxicant, single exposure.

Specific Target Organ Systemic Toxicity (Repeated Exposure)
Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Teratogenicity
Did not cause birth defects or any other fetal effects in laboratory animals.

Reproductive toxicity
In animal studies, did not interfere with reproduction.

Mutagenicity
In vitro genetic toxicity studies were negative.

Aspiration Hazard
No aspiration toxicity classification

Molybdenum disulfide

Acute oral toxicity
LD50, Rat, > 2,000 mg/kg No deaths occurred at this concentration.

Acute dermal toxicity
LD50, Rat, male and female, > 2,000 mg/kg No deaths occurred at this concentration.

Acute inhalation toxicity
LC50, Rat, 4 Hour, dust/mist, > 2.82 mg/l No deaths occurred at this concentration.

Skin corrosion/irritation
Brief contact is essentially nonirritating to skin.
Prolonged contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation
May cause slight temporary eye irritation.
Corneal injury is unlikely.

Sensitization
For skin sensitization:
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

chanhvinh.com

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)
Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)
No relevant data found.

Carcinogenicity
No relevant data found.

Teratogenicity
No relevant data found.

Reproductive toxicity
No relevant data found.

Mutagenicity
For similar material(s): In vitro genetic toxicity studies were negative.

Aspiration Hazard
Based on physical properties, not likely to be an aspiration hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

Distillates (petroleum), hydrotreated heavy naphthenic

Acute toxicity to fish
Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LC50, Oncorhynchus mykiss (rainbow trout), static test, 96 Hour, > 1,000 mg/l, OECD Test Guideline 203 or Equivalent
LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, > 5,000 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates
EC50, Daphnia magna (Water flea), static test, 48 Hour, > 1,000 mg/l, OECD Test Guideline 202 or Equivalent
EC50, scud Gammarus sp., 96 Hour, > 10,000 mg/l, Method Not Specified.

Acute toxicity to algae/aquatic plants
EbC50, alga Scenedesmus sp., static test, 96 Hour, Biomass, > 1,000 mg/l, OECD Test Guideline 201 or Equivalent

Chronic toxicity to fish
NOEC, Pimephales promelas (fathead minnow), 7 d, growth, > 5,000 mg/l

chanhvinh.com

Chronic toxicity to aquatic invertebrates
NOEC, Daphnia magna (Water flea), 21 d, number of offspring, > 1,000 mg/l

Solvent dewaxed heavy paraffinic distillates

Acute toxicity to fish
Information given is based on data obtained from similar substances.
LC50, Pimephales promelas (fathead minnow), > 100 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates
Information given is based on data obtained from similar substances.
LL50, Daphnia magna (Water flea), > 10,000 mg/l, OECD Test Guideline 202

Toxicity to bacteria
Based on data from similar materials
NOEC, 10 min, > 1.93 mg/l, DIN 38 412 Part 8

Chronic toxicity to fish
NOEC, Oncorhynchus mykiss (rainbow trout), 14 d, >= 1,000 mg/l

Chronic toxicity to aquatic invertebrates
NOEC, Daphnia magna (Water flea), 21 d, 10 mg/l

Lithium 12-hydroxyoctadecanoate

Acute toxicity to fish
LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, > 100 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates
EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants
EC50, Raphidocelis subcapitata (freshwater green alga), 72 Hour, > 100 mg/l, OECD Test Guideline 201
NOEC, Raphidocelis subcapitata (freshwater green alga), 72 Hour, 100 mg/l, OECD Test Guideline 201

Chronic toxicity to aquatic invertebrates
No data available

Solvent dewaxed residual oil (petroleum)

Acute toxicity to fish
LC50, Pimephales promelas (fathead minnow), 96 Hour, > 100 mg/l

Acute toxicity to aquatic invertebrates
Information given is based on data obtained from similar substances.
EC50, Daphnia magna (Water flea), 48 Hour, > 10,000 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants
NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, 100 mg/l, OECD Test Guideline 201

chanhvinh.com

Toxicity to bacteria
Based on data from similar materials
NOEC, 10 min, > 1.93 mg/l

Chronic toxicity to aquatic invertebrates
NOEC, Daphnia magna (Water flea), 21 d, 10 mg/l

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts

Acute toxicity to fish
Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).
Based on data from similar materials
LL50, Cyprinodon variegatus (sheepshead minnow), semi-static test, 96 Hour, 4.5 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates
Based on data from similar materials
EL50, Daphnia magna (Water flea), static test, 48 Hour, 23 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants
Based on data from similar materials
EL50, Desmodesmus subspicatus (green algae), 72 Hour, 24 mg/l, OECD Test Guideline 201

Toxicity to bacteria
Based on data from similar materials
EC50, 3 Hour, > 1,000 mg/l, OECD Test Guideline 209

Chronic toxicity to aquatic invertebrates
Based on data from similar materials
NOEC, Daphnia magna (Water flea), 21 d, 0.4 mg/l

Graphite

Acute toxicity to fish
No toxicity at the limit of solubility
LC50, Danio rerio (zebra fish), 96 Hour, > 100 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates
No toxicity at the limit of solubility
EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants
EC50, Raphidocelis subcapitata (freshwater green alga), 72 Hour, > 100 mg/l, OECD Test Guideline 201
NOEC, Raphidocelis subcapitata (freshwater green alga), 72 Hour, >= 100 mg/l, OECD Test Guideline 201

Toxicity to bacteria
EC50, 3 Hour, > 1,012.5 mg/l, OECD Test Guideline 209

Molybdenum disulfide

Acute toxicity to fish

chanhvinh.com

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
For similar material(s):
LC50, Fish, 96 Hour, > 100 mg/l

Acute toxicity to aquatic invertebrates
Based on data from similar materials
EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l

Acute toxicity to algae/aquatic plants
Based on data from similar materials
ErC50, algae, 72 Hour, Growth rate, > 100 mg/l

Toxicity to bacteria
EC50, 30 Hour, Respiration rates., > 100 mg/l

Chronic toxicity to fish
Based on data from similar materials
NOEC, Fish, 34 d, > 10 mg/l

Chronic toxicity to aquatic invertebrates
Based on data from similar materials
NOEC, Daphnia magna, 21 d, > 10 mg/l

Persistence and degradability

Distillates (petroleum), hydrotreated heavy naphthenic
Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability. Material is inherently biodegradable (reaches > 20% biodegradation in OECD test(s) for inherent biodegradability).
10-day Window: Fail
Biodegradation: 6 %
Exposure time: 28 d
Method: OECD Test Guideline 301B or Equivalent
10-day Window: Fail
Biodegradation: 22 - 51 %
Exposure time: 21 - 28 d

Photodegradation
Test Type: Half-life (indirect photolysis)
Sensitization: OH radicals

Solvent dewaxed heavy paraffinic distillates
Biodegradability: Inherently biodegradable.
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Lithium 12-hydroxyoctadecanoate

chanhvinh.com

Biodegradability: Readily biodegradable.
Biodegradation: 93 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

Solvent dewaxed residual oil (petroleum)

Biodegradability: Not readily biodegradable. Information given is based on data obtained from similar substances.

Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.
Based on data from similar materials 10-day Window: Fail
Biodegradation: 1.5 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Graphite

Biodegradability: Not applicable

Molybdenum disulfide

Biodegradability: Biodegradability is not applicable to inorganic substances.

Bioaccumulative potential

Distillates (petroleum), hydrotreated heavy naphthenic

Partition coefficient: n-octanol/water(log Pow): 1.99 - 18.02

Solvent dewaxed heavy paraffinic distillates

Bioaccumulation: Bioaccumulation is unlikely. Not applicable

Lithium 12-hydroxyoctadecanoate

Bioaccumulation: Bioaccumulation is unlikely. Information given is based on data obtained from similar substances.
Partition coefficient: n-octanol/water(log Pow): > 0.915 at 25 °C OECD Test Guideline 123
Bioconcentration factor (BCF): 8 estimated

Solvent dewaxed residual oil (petroleum)

Bioaccumulation: No relevant data found.
Partition coefficient: n-octanol/water(log Pow): 2 - 6

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts

Bioaccumulation: For similar material(s): Bioconcentration potential is low (BCF < 100 or Log Pow < 3).
Partition coefficient: n-octanol/water(log Pow): 0.69 OECD Test Guideline 107

Graphite

chanhvinh.com

Bioaccumulation: Not applicable Not applicable

Molybdenum disulfide

Bioaccumulation: Partitioning from water to n-octanol is not applicable.

Mobility in soil

Solvent dewaxed heavy paraffinic distillates

Substance is very mobile in soil (Log Koc < 2).

Lithium 12-hydroxyoctadecanoate

Expected to be relatively immobile in soil (Log Koc > 3).
OECD Test Guideline 121

Solvent dewaxed residual oil (petroleum)

No relevant data found.

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts

No specific, relevant data available for assessment.

Graphite

No relevant data found.

Molybdenum disulfide

No relevant data found.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

chanhvinh.com

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Not regulated for transport

Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code: Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312
Serious eye damage or eye irritation

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313
The following components are subject to reporting levels established by SARA Title III, Section 313:

Components	CASRN	Concentration %
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	68457-79-4	>= 1.0 - < 5.0 %
Zinc sulfide	1314-98-3	>= 0.1 - < 1.0 %
Zinc Oxide	1314-13-2	< 0.1 %

Pennsylvania Right To Know
The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components	CASRN
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5

chanhvinh.com

Solvent dewaxed heavy paraffinic distillates	64742-65-0
Lithium 12-hydroxyoctadecanoate	7620-77-1
Solvent dewaxed residual oil (petroleum)	64742-62-7
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	68457-79-4
Graphite	7782-42-5

California Prop. 65
WARNING: This product can expose you to chemicals including Quartz, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.
WARNING: This product can expose you to chemicals including Quartz, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

United States TSCA Inventory (TSCA)
All components of this product are in compliance with the Active inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System
NFPA

Health	Flammability	Instability
3	1	0

HMIS

Health	Flammability	Physical Hazard
3/	1	0

Revision
Identification Number: 1512986 / A776 / Issue Date: 11/20/2025 / Version: 11.1
Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
CAL PEL	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
NIOSH REL	USA. NIOSH Recommended Exposure Limits
OSHA P0	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
PEL	Permissible exposure limit
ST	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
TWA	8-hour time weighted average

Full text of other abbreviations

chanhvinh.com

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References
This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

chanhvinh.com

US