chanhvinh.com

Safety Data Sheet according to Regulation (EC) No 1907/2006

SDS No. : 377141
V001.0

LOCTITE ABLESTIK 8387B known as Ablebond 8387B (14g),

Revision: 27.06.2018
printing date: 17.10.2019
Replaces version from: -

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE ABLESTIK 8387B known as Ablebond 8387B (14g),

Contains:

Bisphenol F diglycidyl ether
1,4-Bis(2,3-epoxypropoxy)butane
Polyglycidyl ester
Phenol-formaldehyde polymer

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Epoxy adhesive

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA
Henkelstr. 67
40589 Düsseldorf

Germany

Phone: +49 211 797 0
Fax-no.: +49 211 798 2009

ua-productsafety.de@henkel.com

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye damage	Category 1
H318 Causes serious eye damage.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Chronic hazards to the aquatic environment	Category 2
H411 Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

chanhvinh.com

Hazard pictogram:



Signal word: Danger

Hazard statement:
H318 Causes serious eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statement: Prevention
P273 Avoid release to the environment.
P280 Wear protective gloves/eye protection.

Precautionary statement: Response
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards
None if used properly.
Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:
Adhesive
Base substances of preparation:
Epoxy resin

chanhvinh.com

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Bisphenol F diglycidyl ether 39817-09-9	254-641-8	25- 50 %	Skin Irrit. 2; Dermal H315 Skin Sens. 1; Dermal H317 Eye Irrit. 2 H319 Aquatic Chronic 2 H411
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	219-371-7 01-2119494060-45	10- 20 %	Acute Tox. 4 H302 Acute Tox. 4 H312 Acute Tox. 4 H332 Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Dam. 1 H318 Aquatic Chronic 3 H412
Polyglycidyl ester 68475-94-5	500-215-4	1- < 5 %	Eye Irrit. 2 H319 STOT SE 3; Inhalation H335 Skin Sens. 1 H317 Aquatic Chronic 2 H411
Poly(oxypropylene)diamine 9046-10-0	01-2119557899-12	1- < 5 %	Skin Corr. 1C H314 Aquatic Chronic 3 H412
1H-Imidazole, 4-methyl-2-phenyl- 827-43-0	212-571-5	1- < 5 %	STOT SE 3; Inhalation H335 Skin Irrit. 2; Dermal H315 Eye Dam. 1 H318
Phenol-formaldehyde polymer 9003-35-4	500-005-2	0,1- < 1 %	Eye Irrit. 2 H319 STOT SE 3 H335 Skin Sens. 1 H317

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Should not be a problem as product is of low volatility. However, if feeling unwell remove patient to fresh air.

Skin contact:
Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eye contact:
Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:
Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

chanhvinh.com

4.2. Most important symptoms and effects, both acute and delayed
SKIN: Redness, inflammation.

SKIN: Rash, Urticaria.

After eye contact: Corrosive, may cause permanent damage to eyes (impairment of vision).

4.3. Indication of any immediate medical attention and special treatment needed
See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media
Suitable extinguishing media:
water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:
High pressure waterjet

5.2. Special hazards arising from the substance or mixture
In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters
Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:
In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Avoid contact with skin and eyes.
Wear protective equipment.
Ensure adequate ventilation.
Remove sources of ignition.

6.2. Environmental precautions
Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up
For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.
Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections
See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Avoid skin and eye contact.
See advice in section 8

Hygiene measures:
Good industrial hygiene practices should be observed.
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities
Ensure good ventilation/extraction.
Keep container tightly sealed.
Keep frozen.
Refer to Technical Data Sheet

chanhvinh.com

7.3. Specific end use(s)
Epoxy adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Germany

None

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Poly[oxy(methyl-1,2-ethanediyl)], a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)- 9046-10-0	aqua (freshwater)		0,015 mg/l				
Poly[oxy(methyl-1,2-ethanediyl)], a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)- 9046-10-0	aqua (marine water)		0,0142 mg/l				
Poly[oxy(methyl-1,2-ethanediyl)], a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)- 9046-10-0	aqua (intermittent releases)		0,15 mg/l				
Poly[oxy(methyl-1,2-ethanediyl)], a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)- 9046-10-0	sewage treatment plant (STP)		7,5 mg/l				
Poly[oxy(methyl-1,2-ethanediyl)], a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)- 9046-10-0	sediment (freshwater)				0,132 mg/kg		
Poly[oxy(methyl-1,2-ethanediyl)], a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)- 9046-10-0	sediment (marine water)				0,125 mg/kg		
Poly[oxy(methyl-1,2-ethanediyl)], a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)- 9046-10-0	soil				0,0176 mg/kg		
Poly[oxy(methyl-1,2-ethanediyl)], a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)- 9046-10-0	oral				6,93 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Poly[oxy(methyl-1,2-ethanediyl)], a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)- 9046-10-0	Workers	dermal	Long term exposure - systemic effects		2,5 mg/kg	

chanhvinh.com

Biological Exposure Indices:
None

8.2. Exposure controls:

Engineering controls:
Ensure good ventilation/extraction.

Respiratory protection:
Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

Hand protection:
Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.
Protective eye equipment should conform to EN166.

Skin protection:
Wear suitable protective clothing.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	paste
	black
Odor	Slight
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	Polymerization.
Flash point	> 93 °C (> 199.4 °F)
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	Not applicable
Relative vapour density:	No data available / Not applicable
Density	No data available / Not applicable
Bulk density	No data available / Not applicable

chanhvinh.com

Solubility	No data available / Not applicable
Solubility (qualitative) (Solvent: Water)	Insoluble
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity
Reacts with alcohols and amines.
Reacts with oxidants, acids and lyes
Reaction with some curing agents may produce an exothermic reaction which in large masses could cause runaway polymerization.

10.2. Chemical stability
Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions
See section reactivity

10.4. Conditions to avoid
No decomposition if stored and applied as directed.

10.5. Incompatible materials
See section reactivity.

10.6. Hazardous decomposition products
Hydrocarbons
carbon oxides.
nitrogen oxides
Rapid polymerisation may generate excessive heat and pressure.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Bisphenol F diglycidyl ether 39817-09-9	LD50	> 5.000 mg/kg	rat	
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	LD50	1.118 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Polyglycidyl ester 68475-94-5	LD50	2.002 mg/kg	rat	
Polyglycidyl ester 68475-94-5	LD50	> 2.000 mg/kg	rat	
Poly(oxypropylene)diamine 9046-10-0	LD50	2.885,3 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Phenol-formaldehyde polymer 9003-35-4	LD50	4.100 mg/kg	rat	not specified

chanhvinh.com

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Bisphenol F diglycidyl ether 39817-09-9	LD50	> 6.000 mg/kg	rabbit	
Poly(oxypropylene)diamine 9046-10-0	LD50	2.979,7 mg/kg	New Zealand white rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

No substance data available.
No data available.

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Poly(oxypropylene)diamine 9046-10-0	corrosive	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Poly(oxypropylene)diamine 9046-10-0	corrosive		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	positive	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	positive	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

chanhvinh.com

Carcinogenicity

No data available.

Reproductive toxicity:

No data available.

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	NOAEL 200 mg/kg	oral: gavage	28 d daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)

Aspiration hazard:

No data available.

chanhvinh.com

SECTION 12: Ecological information

General ecological information:
Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Bisphenol F diglycidyl ether 39817-09-9	LC50	> 1 - 10 mg/l	96 h		OECD Guideline 203 (Fish, Acute Toxicity Test)
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	LC50	24 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Polyglycidyl ester 68475-94-5	LC50	> 1 - 10 mg/l	96 h		OECD Guideline 203 (Fish, Acute Toxicity Test)
Poly(oxypropylene)diamine 9046-10-0	LC50	> 100 mg/l	96 h	not specified	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Bisphenol F diglycidyl ether 39817-09-9	EC50	> 1 - 10 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	EC50	75 mg/l	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Poly(oxypropylene)diamine 9046-10-0	EC50	15 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

No data available.

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Poly(oxypropylene)diamine 9046-10-0	EC50	15 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Poly(oxypropylene)diamine 9046-10-0	EC10	1,4 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	EC 50	> 100 mg/l	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Polyglycidyl ester 68475-94-5	EC 50	> 1 - 10 mg/l	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

chanhvinh.com

12.2. Persistence and degradability

The product is not biodegradable.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Bisphenol F diglycidyl ether 39817-09-9	under test conditions no biodegradation observed		< 10 %	28 d	OECD 301 A - F
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8		aerobic	38 %	28 d	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
Polyglycidyl ester 68475-94-5		no data	0 - 60 %	28 d	OECD 301 A - F
Poly(oxypropylene)diamine 9046-10-0	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

12.3. Bioaccumulative potential

No data available.

No substance data available.

12.4. Mobility in soil

Cured adhesives are immobile.

Hazardous substances CAS-No.	LogPow	Temperature	Method
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	-0,269	25 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Poly(oxypropylene)diamine 9046-10-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Phenol-formaldehyde polymer 9003-35-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:
Do not empty into drains / surface water / ground water.
Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:
After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances
The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

chanhvinh.com

SECTION 14: Transport information

14.1. UN number

ADR	3082
RID	3082
ADN	3082
IMDG	3082
IATA	3082

14.2. UN proper shipping name

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
RID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
IATA	Environmentally hazardous substance, liquid, n.o.s. (Epoxy resin)

14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	9
IMDG	9
IATA	9

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode:
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), 197 (IATA), 969 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

chanhvinh.com

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content (2010/75/EC)	< 3 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK:	WGK = 3, highly water endangering product. Classification according to the mixture rules in German VwVwS regulation annex 4 from 27 July 2005.
WGK:	WGK = 3, highly water endangering mixture. Classification according to the mixture rules in German AwSV regulation annex 1, number 5.2 from 18. April 2017.
Storage class according to TRGS 510:	10

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.