

3. THE SOLE
PART OR WHOLE
PROHIBITED.



RoHS Compliant ✓


REVISIONS

REV	DESCRIPTION	DATE	APPROVED
A	RELEASED FOR CN PRODUCTION	12/3/07	D.CASTRO
B	ECN 5673; NEW FORMAT, ADDED ROHS, REVISED PACKING NOTE	8/18/11	D.FRISIELLO

D

LENGTH

X, MOLDED STRAIN RELIEF
VC, BLACK



X, LOGO BOTH SIDES

RG174/U, 50-OHM COAXIAL CABLE
JACKET: PVC, BLACK

PLUG

PART NUMBER	LENGTH FEET [METERS]
CC174S-05	0.5 [.15]
CC174S-1	1.0 [.30]
CC174S-1.5	1.5 [.46]
CC174S-2	2.0 [.61]
CC174S-2.5	2.5 [.76]
CC174S-3	3.0 [.91]
CC174S-4	4.0 [1.22]
CC174S-5	5.0 [1.52]
CC174S-7.5	7.5 [2.28]
CC174S-10	10.0 [3.05]

B

A

LC-conn Global
Connectivity

45 BEECHWOOD DRIVE
NORTH ANDOVER, MA
01845

CATEGORY

COAXIAL

CONTINUITY.

PACKAGED IN
SPECIFICATION PS-0031.

PRODUCT DESCRIPTION

CA SMA M /SMA M RG174/U



UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE IN INCHES [mm]
OVERALL CABLE LENGTH TOLERANCE:
≤12 [305] = +1 [25] / -0
>12 [305] ≤60 [1524] = +2 [51] / -0
>60 [1524] ≤120 [3048] = +4 [102] / -0
>120 [3048] ≤176 [4426] = +4 [102] / -0
>176 [4426] ≤330 [8382] = +5 [127] / -0
ALL OTHER DIMENSIONAL TOLERANCES:
.X = ± .2
.XX = ± .02
.XXX = ± .005

APPROVALS

DATE

DRAWN BY
D.CASTRO
12/3/07

CHECKED BY
D.FRISIELLO
12/4/07

APPROVED BY
D.DOLCE
12/4/07

CONFIGURATION DETAILS OF
UNDIMENSIONED FEATURES
MAY VARY

COLOR VARIATIONS
MAY OCCUR

SIZE

FSCM NO.

DWG. NO.

REV.

A

43321

CC174S

B

SCALE: NONE

CAD FILE: CC174S.DDDRW

SHEET 1 OF 1

6

5

4

3

2

1