
chanhvinh.com

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.


RoHS Compliant

REVISIONS

REV	DESCRIPTION	DATE	APPROVED
J	ECN 4422: ADDED 4 METER LENGTH AND NEW FORMAT	12/3/09	D.FRISIELLO
K	ECN 5868: ADDED LENGTHS 03 M, 075 M, REVISED PACKAGING NOTE	12/8/11	D.FRISIELLO
L	ECN6237: ADDED CONTACT PLATING NOTE. UPDATED FORMAT.	09/14/12	DFP



WIRING DIAGRAM



MODEL NUMBER	LENGTH METERS [FEET]
CSMUAA-03M	0.3 [.98]
CSMUAA-05M	0.5 [1.64]
CSMUAA-075M	0.75 [2.46]
CSMUAA-1M	1.0 [3.28]
CSMUAA-2M	2.0 [6.56]
CSMUAA-3M	3.0 [9.84]
CSMUAA-4M	4.0 [13.12]
CSMUAA-5M	5.0 [16.40]

NOTES:

1. CABLE ASSEMBLY SHALL HAVE 360Á SHIELD TERMINATION.
2. CABLE ASSEMBLY SHALL MEET USB 2.0 REQUIREMENTS.
3. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
4. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE IN INCHES [mm]
OVERALL CABLE LENGTH TOLERANCE:
012 [305] = +1 [25] / -0
>12 [305] 060 [1524] = +2 [51] / -0
>60 [1524] 0120 [3048] = +4 [102] / -0
>120 [3048] 0300 [7620] = +6 [152] / -0
>300 [7620] = +5% / -0%
ALL OTHER DIMENSIONAL TOLERANCES:
.X = Ñ .2
.XX = Ñ .02
.XXX = Ñ.005

PROJECTION

APPROVALS	DATE
DRAWN BY C.MCCORMICK	01/04/2001
CHECKED BY TJC	05/16/2001
APPROVED BY RC	05/16/2001

CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY

COLOR VARIATIONS MAY OCCUR

L-COM Global Connectivity
45 BEECHWOOD DRIVE
NORTH ANDOVER, MA
01845

CATEGORY: USB

PRODUCT DESCRIPTION: CABLE, USB SERIES A/A

SIZE	FSCM NO.	DWG. NO.	REV.
A	43321	CSMUAA	L

SCALE: NONE | CAD FILE: CSMUAA.SLDDRW | SHEET 1 OF 1