
chanhvinh.com


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS

REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	5/10/13	D.GRIFFIN
B	ECN 8854: UPDATE FEMALE END AS AS SHORTER SIZE MOLDING	07/14/17	S.LI



MODEL NUMBER	LENGTH METERS [FEET]
ECUSBAX-03M	0.3 [.98]
ECUSBAX-05M	0.5 [1.64]
ECUSBAX-075M	0.75 [2.46]
ECUSBAX-1M	1.0 [3.28]
ECUSBAX-2M	2.0 [6.56]
ECUSBAX-3M	3.0 [9.84]



NOTES:

1. CABLE ASSEMBLY SHALL HAVE 360° SHIELD TERMINATION.
2. CABLE ASSEMBLY SHALL MEET USB 2.0 REQUIREMENTS.
3. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
4. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

REGULATORY COMPLIANCE:
CE2011/65/EU(RoHS DIRECTIVE)

UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE IN INCHES [mm]
OVERALL CABLE LENGTH TOLERANCE:
≤12 [305] = +1 [25] / -0
>12 [305] ≤60 [1524] = +2 [51] / -0
>60 [1524] ≤120 [3048] = +4 [102] / -0
>120 [3048] ≤300 [7620] = +6 [152] / -0
>300 [7620] = +5% / -0%
ALL OTHER DIMENSIONAL TOLERANCES:
.X = ± .2 [5.08]
.XX = ± .02 [.51]
.XXX = ±.005 [.13]
PROJECTION

APPROVALS	DATE
DRAWN BY D.FRISIELLO	5/7/13
CHECKED BY R.SCOTT	5/7/13
APPROVED BY S.SMITH	5/7/13

CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY
COLOR VARIATIONS MAY OCCUR
REF

L-COM Global Connectivity
50 HIGH STREET
NORTH ANDOVER, MA
01845

CATEGORY
USB

PRODUCT DESCRIPTION
CBL USB DX TYPE A M/F

SIZE	FSCM NO.	DWG. NO.	REV.
A	43321	ECUSBAX	B

SCALE: NONE | CAD FILE: ECUSBAX.SLDDRW | SHEET 1 OF 1