chanhvinh.com

HyperLink Wireless 900 MHz 3 dBi RP-SMA Plug High Performance "Rubber Duck" Wireless LAN Antenna - Model: HG903RD-RSP



Applications and Features

Applications:

- 900MHz ISM Band
- 900MHz Cellular Band Applications
- 900MHz Digital Spread Spectrum Radios
- 900MHz Telemetry Products
- GSM
- RFID
- Wireless Video Transmitters and Receivers
- Multipoint and Mobile Applications

Features:

- Better performance then most stock AP antennas
- Flexible "Rubber Duck" antenna
- Tilt and swivel design
- Reverse Polarity SMA-Plug (RP-SMA) Connector
- RoHS Compliant

RoHS Compliant

Description

This high performance 900MHz Omnidirectional "rubber-duck" antenna provides broad coverage and 3 dBi gain. It is a coaxial sleeve design with an omni-directional pattern. It is ideally suited for 900MHz ISM band applications as well as 900MHz cellular applications.

Measuring 8.62" long, this flexible antenna features a tilt-and-swivel Reverse Polarity SMA-Plug (RP-SMA) connector, allowing them to be used vertically, at a right angle, or any angle in-between. It is suitable as a replacement RF antenna for 900MHz radios that are equipped with RP-SMA connectors such as wireless video transmitters and receivers, 900MHz digital spread spectrum radios and more.

Specifications

Electrical Specifications

Frequency	860-960 MHz
Gain	3 dBi
Horizontal Beam Width	360°
Impedance	50 Ohm
Max. Power	50W
VSWR	< 2.0
Lightning Protection	DC Ground


© L-com, Inc. All Rights Reserved. L-com Global Connectivity and the L-com logo are registered marks.

chanhvinh.com


Mechanical Specifications

Weight	1.6 oz. (45 g)
Length	8.62" (219 mm)
Max. Diameter	0.66" (16.7 mm)
Finish	Matte Black
Connector	RP-SMA Plug
Operating Temperature	-40° C to 60° C (-40° F to 140° F)
Polarization	Vertical
Flame Rating	UL 94HB
RoHS Compliant	Yes

Dimensions



RF Antenna Patterns



Guaranteed Quality

This product is backed by L-Com's Limited Warranty

L-com, Inc. 50 High St., West Mill, 3rd Floor, Suite #30 North Andover, MA 01845
www.L-com.com E-mail: sales@L-com.com Phone: 1-800-343-1455 Fax: 1-978-689-9484
© L-com, Inc. All Rights Reserved. L-com Global Connectivity and the L-com logo are registered marks.