chanhvinh.com

U.I. Lapp GmbH	PRODUCT INFORMATION	LAPP GROUP
	ETHERLINE® Cat.6A + Cat.7	**29.11.2013**

Fixed installation
Industrial Ethernet cable Cat.6A or Cat.7 for fixed installation; halogenfree, PVC or PUR outer sheath, design 4x2xAWG22/1



Automation

Industrial machinery and plant engineering

Mechanical resistance

Interference signals

UV-resistant

Info
Industrial Ethernet cable
For PROFINET applications with 4 pairs
CAT.6Aand Cat.7 qualified for 10Gbit/s

Application range
for industrial secondary and tertiary cabling according to EN 50173-3 ISO/IEC 24702
Fixed installation
Can be used in dry or damp rooms
For PROFINET applications type A

Benefits
Screened against interference
Industrial use
Can be used for Industrial Ethernet in harsh industrial environments

Design
Solid bare copper wire AWG22
Core insulation made of polyethylene (PE)
S/FTP: copper braid as overall screening and pair screening with aluminium compound foil
Colour: green (based on RAL 6018)

PN 0486/01_03.10
©2012 Lapp Group - Technical changes reserved
Photographs are not to scale and do not represent detailed images of the respective products.

chanhvinh.com

Product features

PUR outer sheath is highly resistant to mineral oils and abrasion
Robust, halogen-free outer sheath
PVC sheath
High-quality, double screening ensures high transmission reliability in areas with electromagnetic interference

Remark

Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
PROFINET® is a registered trademark of the PNO (PROFIBUS user organisation)
Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

Peak operating voltage:	(not for power applications) 125 V
Minimum bending radius:	Fixed installation: see data sheet
Temperature range:	See data sheet
Characteristic impedance:	100 ohm at 1 - 100 MHz

PN 0486/01_03.10
©2012 Lapp Group - Technical changes reserved
Photographs are not to scale and do not represent detailed images of the respective products.

chanhvinh.com

Part number	Article designation	Number of pairs and AWG per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
Outer sheath: halogen-free, flame-retardant compound					
2170466	ETHERLINE® Cat.6A H	4 x 2 x AWG22/1	8,7	53.0	99
2170476	ETHERLINE® CAT.7 H	4 x 2 x AWG22/1	8,7	53.0	99
Outer sheath: PUR, halogen-free					
2170465	ETHERLINE®CAT.6A P	4 x 2 x AWG22/1	8,7	53.0	91
2170475	ETHERLINE® Cat.7 P	4 x 2 x AWG22/1	8,7	53.0	91
Outer sheath: PVC					
2170464	ETHERLINE® Cat.6A Y	4 x 2 x AWG22/1	8,7	53.0	98
2170474	ETHERLINE® Cat.7 Y	4 x 2 x AWG22/1	8,7	53.0	98

PN 0486/01_03.10
©2012 Lapp Group - Technical changes reserved
Photographs are not to scale and do not represent detailed images of the respective products.