chanhvinh.com

381166916	DATA SHEET	LAPP
Valid from: 06.11.2024	EPIC® POWER M12 FEKF5F-0.5-M16	

Description



- Panel mount socket for power transmission, M12 screw connection, 5-pole, K-coding
- Front/screw mounting with M16 thread, 0.5m conductors, 5 x 14AWG

General characteristics

Design	Panel mount socket M12
Connection	Screw connection
Coding	K-Coding
Number of poles	5-pole (4+PE)
Product standard	DIN EN 61076-2-111
Protection class	IP 67
Temperature rating (operation)	-25 up to +85 °C (-13 up to +185 °F)
Mating cycles	≥ 100
Tightening torque, connector	0.4 up to 0.6 Nm
Tightening torque, locknut	3 up to 4 Nm

Electrical properties, connector

Rating voltage	630 V
Rating current	12 A
Overvoltage category	II
Pollution degree	3
Insulation resistance	≥ 100 MΩ
Contact resistance of connector	≤ 5 mΩ

Materials, connector

Contacts	Brass, gold plated
Contact holder	TPU GF
Connector shell	Brass, nickel plated
Locknut	Brass, nickel plated
Inner overmold	Epoxide resin
Seal	FPM/FKM

Single cores


AWM style	1015
Material of conductor	Stranded copper wire, stripped section tinned
Material of core insulation	PVC
Conductor cross-section	14AWG
Color of cores	Black (BK), Green/Yellow (GN/YE)

We reserve all rights according to DIN ISO 16016.


chanhvinh.com

381166916	DATA SHEET	LAPP
Valid from: 06.11.2024	EPIC® POWER M12 FEKF5F-0.5-M16	


Technical drawings




Pin diagram



Wire list



Panel cut-out



Maximum wall thickness is 7 mm

Application range

Connection of enclosures and cabinets.

Note

The photographs are not to scale and are not detailed images of the respective products.

We reserve all rights according to DIN ISO 16016.