chanhvinh.com

381166924	DATA SHEET	LAPP
Valid from: 06.11.2024	EPIC® M12 FEAF4.5F-0.5-M16	

Description

- Sensor/Actuator flush-type socket, M12 screw connection, 5-pole, A-coding
- Front/screw mounting with M16 thread, 0.5m conductors, 5 x 22AWG



General characteristics

Design	Panel mount M12, female contacts
Connection	Screw connection
Coding	A-Coding
Number of poles	5
Product standard	DIN EN 61076-2-101
Protection class	IP 67
Temperature rating (operation)	-25 up to +85 °C (-13 up to +185 °F)
Mating cycles	≥ 100
Tightening torque, connector	0.4 up to 0.6 Nm
Tightening torque, counter-nut	3 up to 4 Nm

Electrical properties, connector

Rating voltage	60 V
Rating current	4 A
Overvoltage category	II
Pollution degree	3
Insulation resistance	≥ 100 MΩ
Contact resistance of connector	≤ 5 mΩ

Materials, connector

Contacts	Brass, gold plated
Contact holder	TPU GF
Connector shell	Zinc die-cast, nickel plated
Counter-nut M16x1,5	Brass, nickel plated
Inner overmold	Epoxi resin
Seal	FPM/FKM

Single core


AWM style	1569
Material of conductor	Stranded copper wire, stripped zone tin plated
Material of core insulation	PVC
Conductor cross-section	22AWG
Color of cores	Brown (BN), White (WH), Blue (BU), Black (BK), Grey (GY)

We reserve all rights according to DIN ISO 16016.


chanhvinh.com

381166924	DATA SHEET	LAPP
Valid from: 06.11.2024	EPIC® M12 FEAF4.5F-0.5-M16	


Technical drawings




Pin diagram



Wire list



Panel cut-out



Maximum wall thickness is 3,5mm

Application range

Connection of enclosures and cabinets.

Note

The photographs are not to scale and are not detailed images of the respective products..

We reserve all rights according to DIN ISO 16016.