chanhvinh.com

EN 420 | EN 388 4X43D | EN 407 X1XXXX

EU regulation 2016/425 attest n°0075/057/162/09/19/2774 delivered by CTC, notified body n°0075

SPHINX/VIZ

CUT PROTECTION GLOVE - LEVEL D



PPE Category II

EN 388	EN388:2016
	Levels:
Resistance to abrasion:	●●●●
Blade cut resistance:	X
Tear resistance:	●●●●
Puncture resistance:	●●●○
Blade Cut resistance according to ISO13997:	D

EN 407	EN407
	Levels:
Burning behaviour :	X
Contact heat :	●○○○
Convective heat :	X
Radiant heat :	X
Small splashes of molten metal :	X
Large splashes of molten metal :	X

Sizes	Packaging
6 – 7 – 8 – 9 – 10 -11	12 per packet - 120 per box

Seamless knitted glove, 13 gauge, in 100% high density polyethylene filament, mineral filament and 100% yellow texturized polyamide with elastane. Black nitrile foam coating on palm and fingertips. Elastic wrist.

THE + PRODUCT

- **GRIP**
- **RESISTANCE**
- **SEALING**

RELEVANT SECTORS

- Automotive manufacturing and supply industry
- Engineering industry and industrial maintenance
- Metal manufacturing and processing industry
- Rubber manufacturing and processing industry
- Building and public works
- Assembly works
- Glass manufacturing and processing industry

LEBON International S.à.r.l
Immeuble Laccolith
20, rue Eugène Ruppert L-2453 Luxembourg
Website : www.lebonprotection.com
TEL : +352 26 49 36 07
FAX : +352 26 49 35 35