chanhvinh.com


Series 26 - Brass/Steel

Nominal Diameter
7.2 = 40 mm²



Universal brass coupling with European standard industrial profile. Coupling system with single-hand operation and standard-valve. Small mass size. The ergonomic sleeve design prevents entering dirt on the valve body.

- Available on request:
  - in brass material with nickel plating
  - with additional end connections
  - other seals for different temperature ranges and fluids



Euro Profile

KA Single Shut-Off

Working Pressure*:
up to 35 bar
Material:
- **Coupling:** Brass
- **Plug:** Brass
- **Seals:** NBR

Working Temperature:
-20°C up to +100°C (NBR)
Flow Rate Air:
1.070 l/min.
inlet pressure 6 bar, pressure drop 0.5 bar
Flow Rate Water:
18 l/min.
pressure drop 0.5 bar

KB Double Shut-Off

Working Pressure*:
up to 35 bar
Material:
- **Coupling:** Brass
- **Plug:** Brass
- **Seals:** NBR

Working Temperature:
-20°C up to +100°C (NBR)
Flow Rate Air:
950 l/min.
inlet pressure 6 bar, pressure drop 0.5 bar
Flow Rate Water:
8.8 l/min.
pressure drop 0.5 bar


* maximum static working pressure with design factor 4 to 1.

Single Shut-Off

26KAA Coupler with valve, Male Thread

Brass, NBR






A			HEX	L	L1	D	Version
G1/8	26KAAW10MPX		22	43	9	25	Brass
G1/8	26KAAW10MPN	9101 26 10	22	43	9	25	Nickel-plated brass
G1/4	26KAAW13MPX		22	39	9	25	Brass
G1/4	26KAAW13MPN	9101 26 13	22	39	9	25	Nickel-plated brass
G3/8	26KAAW17MPX		22	41	9	25	Brass
G3/8	26KAAW17MPN	9101 26 17	22	41	9	25	Nickel-plated brass
G1/2	26KAAW21MPX		22	44	12	25	Brass
G1/2	26KAAW21MPN	9101 26 21	22	44	12	25	Nickel-plated brass
G1/2	26KAAW21MPXS_36		24	44	12	25	Brass
M14 x 1.5	26KAAD14MPX		22	43	10	25	Brass
M16 x 1.5	26KAAD16MPX		22	43	11	25	Brass
M18 x 1.5	26KAAD18MPX		22	43	11	25	Brass

Single Shut-Off

26KAI Coupler with valve, Female Thread

Brass, NBR






A			HEX	L	L1	D	Version
G1/8	26KAIW10MPX		22	41	8	25	Brass
G1/4	26KAIW13MPX		22	41	9	25	Brass
G1/4	26KAIW13MPN	9114 26 13	22	41	9	25	Nickel-plated brass
G3/8	26KAIW17MPX		22	41	9	25	Brass
G3/8	26KAIW17MPN	9114 26 17	22	41	9	25	Nickel-plated brass
G1/2	26KAIW21MPX		24	44	10	25	Brass
G1/2	26KAIW21MPN	9114 26 21	24	44	10	25	Nickel-plated brass
M14 x 1.5	26KAIM14MPX		22	41	9	25	Brass
M16 x 1.5	26KAIM16MPX		22	41	9	25	Brass
M18 x 1.5	26KAIM18MPX		22	44	9	25	Brass


Series 26 - Brass/Steel

Single Shut-Off

26KAT Coupler with valve, Hose Barb

Brass, NBR






A		HEX	L	L1	D
6	26KATF06MPX	21	58	25	25
8	26KATF08MPX	21	58	25	25
9	26KATF09MPX	21	58	25	25
10	26KATF10MPX	21	58	25	25
13	26KATF13MPX	21	58	25	25
6 Push-Lok	26KATP06MPX	21	58	20.5	25
10 Push-Lok	26KATP10MPX	21	58	24	25
13 Push-Lok	26KATP13MPX	21	58	28	25

26KAKO Coupler with valve, with Plastic Hose Connection

Brass, NBR






A		HEX	G	L	L1	L2	D
4 x 6	26KAKO06MPX	21	M10x1	58	7	6	25
6 x 8	26KAKO08MPX	21	M12x1	45	7	6	25
8 x 10	26KAKO10MPX	21	M16x1	49	9	8	25
9 x 12	26KAKO12MPX	21	M16x1	49	9	8	25

26KATS Coupler with valve, Panel Mount with Hose Barb

Brass, NBR






A		HEX	HEX1	B	G	L	L1	L2	D
6	26KATS06MPX	21	17	4	M12x1	60	17	10	25
10	26KATS10MPX	21	17	4	G1/4	72	25	14	25

Single Shut-Off

26KAKK Coupler with valve, Plastic Hose Connection with Spring Guard

Brass, NBR






A		HEX	G	L	L1	L2	D
4 x 6	26KAKK06MPX	21	M10x1	120	7	6	25
6 x 8	26KAKK08MPX	21	M12x1	132	7	6	25
8 x 10	26KAKK10MPX	21	M16x1	143	9	8	25
9 x 12	26KAKK12MPX	21	M16x1	150	9	8	25

26SFA Plug without valve, Male Thread

Brass






A		HEX	L	L1
G1/8	26SFAW10MXX	14	31	7
G1/4	26SFAW13MXX	17	33	9
G3/8	26SFAW17MXX	19	33	9
G1/2	26SFAW21MXX	24	38	12
M14 x 1.5	26SFAD14MXX	17	35	10
M16 x 1.5	26SFAD16MXX	19	36	11
M18 x 1.5	26SFAD18MXX	22	37	11

26SFI Plug without valve, Female Thread

Brass






A		HEX	L	L1
G1/8	26SFIW10MXX	14	30	7
G1/4	26SFIW13MXX	17	33	10
G3/8	26SFIW17MXX	19	33	10
G1/2	26SFIW21MXX	24	35	12
M14 x 1.5	26SFIM14MXX	17	33	10
M16 x 1.5	26SFIM16MXX	19	33	10

Single Shut-Off

26SFT Plug without valve, Hose Barb

Brass






A		L	L1	D
4	26SFTF04MXX	48	25	12
6	26SFTF06MXX	48	25	12
8	26SFTF08MXX	48	25	12
9	26SFTF09MXX	48	25	12
10	26SFTF10MXX	48	25	12
13	26SFTF13MXX	48	25	15
6 Push-Lok	26SFTP06MXX	43	20.5	16
10 Push-Lok	26SFTP10MXX	46	24	22
13 Push-Lok	26SFTP13MXX	50	28	24

26SFK0 Plug without valve, with Plastic Hose Connection

Brass






A		HEX	G	L	L1	L2	D
4 x 6	26SFK006MXX		M10x1	34	7	6	12
6 x 8	26SFK008MXX		M12x1	34	7	6	12
8 x 10	26SFK010MXX	17	M16x1	42	9	6	
9 x 12	26SFK012MXX	17	M16x1	42	9	8	

26SFTS Plug without valve, Panel Mount with Hose Barb

Brass






A		HEX	HEX1	B	G	L	L1	L2
10	26SFTS10MXX	17	19	4	M14x1	56	17	14

Single Shut-Off

26SFKK Plug without valve, Plastic Hose Connection with Spring Guard

Brass







A		HEX	G	L	L1	L2	D
4 x 6	26SFKK06MXX		M10x1	120	7	6	12
6 x 8	26SFKK08MXX		M12x1	127	7	6	12
8 x 10	26SFKK10MXX	17	M16x1	135	9	8	
9 x 12	26SFKK12MXX	17	M16x1	142	9	8	

26SRTF Plug without valve, Recoil Eliminator with Hose Barb

Brass






A		HEX	L	L1
6	26SRTF06MXX	21	60	25
8	26SRTF08MXX	21	60	25
9	26SRTF09MXX	21	60	25
10	26SRTF10MXX	21	60	25
13	26SRTF13MXX	21	60	25

Double Shut-off

26KBA Coupler with valve, Male Thread

Brass, NBR





A		HEX	L	L1	D
G1/8	26KBAW10MPX	22	43	9	25
G1/4	26KBAW13MPX	22	39	9	25
G3/8	26KBAW17MPX	22	41	9	25
G1/2	26KBAW21MPX	24	44	10	25
M14 x 1.5	26KBAD14MPX	22	43	10	25
M16 x 1.5	26KBAD16MPX	22	43	11	25
M18 x 1.5	26KBAD18MPX	22	43	11	25


Series 26 - Brass/Steel

Double Shut-off

26KBI Coupler with valve, Female Thread

Brass, NBR







A		HEX	L	L1	D
G1/8	26KBIW10MPX	22	41	8	25
G1/4	26KBIW13MPX	22	41	9	25
G3/8	26KBIW17MPX	22	41	9	25
G1/2	26KBIW21MPX	24	44	10	25
M14 x 1.5	26KBIM14MPX	22	41	9	25
M16 x 1.5	26KBIM16MPX	22	41	9	25
M18 x 1.5	26KBIM18MPX	22	41	9	25

26KBT Coupler with valve, Hose Barb

Brass, NBR






A		HEX	L	L1	D
6	26KBTF06MPX	21	58	25	25
8	26KBTF08MPX	21	58	25	25
9	26KBTF09MPX	21	58	25	25
10	26KBTF10MPX	21	58	25	25
13	26KBTF13MPX	21	58	25	25
6 Push-Lok	26KBTP06MPX	21	58	20.5	25
10 Push-Lok	26KBTP10MPX	21	58	24	25
13 Push-Lok	26KBTP13MPX	21	58	28	25

26KBKO Coupler with valve, with Plastic Hose Connection

Brass, NBR






A		HEX	G	L	L1	L2	D
4 x 6	26KBKO06MPX	21	M10x1	45	7	6	25
6 x 8	26KBKO08MPX	21	M12x1	45	7	6	25
8 x 10	26KBKO10MPX	21	M16x1	49	9	8	25
9 x 12	26KBKO12MPX	21	M16x1	49	9	8	25

Double Shut-off

26KBTS Coupler with valve, Panel Mount with Hose Barb

Brass, NBR






A		HEX	HEX1	B	G	L	L1	L2	D
6	26KBTS06MPX	21	17	4	M12x1	60	17	10	25
10	26KBTS10MPX	21	17	4	G1/4	72	25	14	25

26KBKK Coupler with valve, Plastic Hose Connection with Spring Guard

Brass, NBR





A		HEX	G	L	L1	L2	D
6 x 8	26KBKK08MPX	21	M12x1	132	7	6	25
8 x 10	26KBKK10MPX	21	M16x1	143	9	8	25
9 x 12	26KBKK12MPX	21	M16x1	150	9	8	25

Plugs for Series 26KB can be found with Series 25, on pages 247.