chanhvinh.com

EGG.1T.314.CLL

MECHANICAL DETAILS

Shell Style Model EG* : Fixed receptacle nut fixing


Keying

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Cable Fixing 0 - 0 mm

Variant 2 :

		A	B	e	E	L	M	N
Mm.		15.5	10.6	M12x1.0	6	23	1.8	21.5
In.		0.61	0.42		0.24	0.91	0.07	0.85



PERFORMANCE DETAIL

Insert :

Insulator

Specifications

Contact Type: Solder



OTHER CHARACTERISTICS

Shell Style/Model	Libellé
Temp (min)	-55?C
Temp (max)	+200?C
Humidity (max):	<=95% [at 60 deg C /140 F]
Vibration:	15 g [10 Hz - 2000 Hz]
Shock Resistance:	100 g [6 ms]
Salt Spray	>144 hr
Climatical	50/175/21
Shielding (min):	75 dB (10 MHz)
Shielding (min):	40 dB (1 GHz)
IP Rating	68

Available Download

T_series_en.pdf

Related links

- Contact
- Quote Request
- Catalogs Downloads
- Catalogs Requests
- Sample Request
- 3D drawings