chanhvinh.com

Lovato electric
ENERGY AND AUTOMATION

HR602CD024

INDUSTRIAL RELAY WITH LED STATE INDICATOR AND MECHANICAL ACTUATOR, 24VDC, 7A, 2 C/O CONTACT. FITTING ON SOCKET HR6XS2...



Contact characteristics			
Contact configuration			2 C/O
Rated insulation voltage Ui IEC/EN		V	500
Rated impulse withstand voltage Uimp		kV	4
IEC Conventional free air thermal current Ith ≤ 40°C		A	7
Rated current (In)		A	7
Max contrallable power in			
	AC-1	W	7
Rated operating power AC-1			
		VA	1750
Rated operating power AC-15			
	230 VAC	VA	150
Single-phase motor control			
	230VAC	kW	0.37
Rated operating current DC-1			
	30V	A	12
	110V	A	0.3
	220V	A	0.1
Minimum switching load		V / mA	5 / 100
Contact impedance		mΩ	100
Contact material			Ag/Ni
Operating times			
Closing		ms	<25
Opening		ms	<25
Operations			
Mechanical life		cycles	20000000
Electrical life AC1		cycles	100000
Coil characteristics			
Relay control voltage		V	24VDC
Average coil consumption AC at 20°C		VA	1.7
Average coil consumption DC at 20°C		W	1.1
Operating range			
	Closing	% Un	75…110
	Opening	% Un	10…30
Maximum cycle frequency		cycles/h	3600
Mechanical features			
Max socket terminal tightening torque		Nm	0.6
Socket screw tightening tool (cross / flat blade)			PH1 / 4.5mm
Conductor section			
AWG/Kcmil			
	min		20
	max		14
IEC			
	min	mm²	0.5
	max	mm²	2.5

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

chanhvinh.com

Lovato electric
ENERGY AND AUTOMATION

HR602CD024

INDUSTRIAL RELAY WITH LED STATE INDICATOR AND MECHANICAL ACTUATOR, 24VDC, 7A, 2 C/O CONTACT. FITTING ON SOCKET HR6XS2...

Operating position			
	normal		Any
Fixing			On 35mm DIN rail and with screw

Ambient conditions


Temperature			
Operating temperature			
	min	°C	-40
	max	°C	+70
Storage temperature			
	min	°C	-40
	max	°C	+80

Other features


Indication	Yes
Mechanical contact position indicator	Yes
Mechanical test actuator	Yes

Dimensions


HR60 2C... with socket HR6XS21 - HR6XS22



HR60 4C... with socket HR6XS41 - HR6XS42



HR60 2C... - HR60 4C... with socket HR6XS21S - HR6XS41S



Wiring diagrams


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding


chanhvinh.com

Lovato electric
ENERGY AND AUTOMATION

HR602CD024

INDUSTRIAL RELAY WITH LED STATE INDICATOR AND MECHANICAL ACTUATOR, 24VDC, 7A, 2 C/O CONTACT. FITTING ON SOCKET HR6XS2...





Certifications and compliance

Compliance

	IEC/EN 61810

Certificates

	CSA
	cURus
	EAC
	VDE

ETIM classification

ETIM 8.0	EC001437 - Switching relay

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding