chanhvinh.com

Lovato electric
ENERGY AND AUTOMATION

HR703CD024

11-PIN INDUSTRIAL RELAY WITH LED STATE INDICATOR AND MECHANICAL ACTUATOR, 24VDC, 10A, 3 C/O CONTACTS, FITTING ON SOCKET HR7XS2



Contact characteristics			
Contact configuration			3 C/O
Rated insulation voltage Ui IEC/EN		V	250
Rated impulse withstand voltage Uimp		kV	6
IEC Conventional free air thermal current Ith ≤ 40°C		A	10
Rated current (In)		A	10
Rated operating power AC-1		VA	2500
Rated operating power AC-15	230 VAC	VA	500
Single-phase motor control	230VAC	kW	1.2
Rated operating current DC-1	30V	A	10
Minimum switching load		V / mA	5 / 100
Contact impedance		mΩ	100
Contact material			Ag/Ni
Operating times			
Closing		ms	<30
Opening		ms	<30
Operations			
Mechanical life		cycles	5000000
Electrical life AC1		cycles	100000
Coil characteristics			
Relay control voltage		V	24VDC
Average coil consumption AC at 20°C		VA	3
Average coil consumption DC at 20°C		W	1.5
Operating range	Closing	% Un	75…110
	Opening	% Un	10…30
Maximum cycle frequency		cycles/h	3600
Mechanical features			
Max socket terminal tightening torque		Nm	0.6
Socket screw tightening tool (cross / flat blade)			PH1 / 4.5mm
Conductor section			
AWG/Kcmil	min		20
	max		14
IEC			
	min	mm²	0.5
	max	mm²	2.5
Operating position	normal		Any

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

chanhvinh.com

Lovato electric
ENERGY AND AUTOMATION

HR703CD024

11-PIN INDUSTRIAL RELAY WITH LED STATE INDICATOR AND MECHANICAL ACTUATOR, 24VDC, 10A, 3 C/O CONTACTS, FITTING ON SOCKET HR7XS2

Fixing			On 35mm DIN rail and with screw


Ambient conditions

Temperature			
	Operating temperature		
		min °C	-40
		max °C	+55
	Storage temperature		
		min °C	-40
		max °C	+70


Other features


Indication	Yes
Mechanical contact position indicator	Yes
Mechanical test actuator	Yes

Dimensions



Wiring diagrams





Certifications and compliance

Compliance

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

chanhvinh.com

	IEC/EN 61810
Certificates	
	CSA
	cURus
	EAC

ETIM classification

ETIM 8.0	EC001437 - Switching relay

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding