chanhvinh.com

LPCB2102

PUSHBUTTON ACTUATOR, SPRING RETURN, WITH SYMBOL Ø22MM PLATINUM SERIES CHROMED PLASTIC, EXTENDED, 0/BLACK



General characteristics

Colour			Black
Type of positions			Extended pushbutton
Material			Polyamide
IEC degree of protection			IP66, IP67 and IP69K

Mechanical features

Operating force		kg-lb	<0.5Kg / 1.1lb
Mechanical life		cycles	5000000
Fixing			Without mounting adapter
Mounting adapter			LPXAU120
Weight		g	27

UL technical data


UL degree of protection			Type1, 2, 3R, 4, 4X, 12, 12K

Ambient conditions

Temperature

Operating temperature			
	min	°C	-25
	max	°C	+70
Storage temperature			
	min	°C	-40
	max	°C	+85

Dimensions



Certifications and compliance

Compliance

CSA C22.2 n° 14
IEC/EN/BS 60947-1
IEC/EN/BS 60947-5-1
UL508

Certificates

CCC
cULus

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

chanhvinh.com

LPCB2102

PUSHBUTTON ACTUATOR, SPRING RETURN, WITH SYMBOL Ø22MM PLATINUM SERIES CHROMED PLASTIC, EXTENDED, 0/BLACK

EAC

RINA

ETIM classification

ETIM 8.0	EC000221 - Front element for push button

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding