chanhvinh.com

Lovato electric
ENERGY AND AUTOMATION

DCTLA4000500

Thyristor module, 50kvar at 400VAC, rated operating voltage 400VAC, with current control



Product designation			Thyristor modules
Product type designation			DCTL
General characteristics			
Rated voltage		V	400
Operating voltage range			340…440
Rated frequency		Hz	50/60
Operating frequency range		Hz	45…65
Rated current (Ie)		A	72
Step power at			
	400VAC	kvar	50
Peak inverse voltage (PIV)		VAC	1800
Number of controlled phases		Nr.	2
Control circuit			12-24VDC input or free-voltage input or via RS485 serial port (with optional card EXC1042 in combination with controller DCRG8F + EXP1012)
Auxiliary supply			
Rated auxiliary supply voltage Us AC			
	min	VAC	100
	Max	VAC	240
Auxiliary rated frequency		Hz	50/60
Power consumption Max		VA	14.1
Power dissipation Max		W	5.8
Control input			
Terminals			CONTROL +/-
Rated voltage			12-24VDC
Operating range			8…30VDC
Digital inputs			
Terminals			C-IN1
Applied voltage at contact (internal)			5VDC
Input current		mA	≤10
Low input signal		VDC	≤0.8
High input signal		VDC	≥3.2
Input signal delay		ms	≥50
NTC probe input			
Terminals			NTC-NTC
Sensor type			NTC (ordering code NTC01)

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

chanhvinh.com

Lovato electric
ENERGY AND AUTOMATION

DCTLA4000500

Thyristor module, 50kvar at 400VAC, rated operating voltage 400VAC, with current control

Measuring range		°C	-25…+85
Maximum connection lenght		mt	3
Fan power supply			
Terminals			FAN +/-
Supply voltage (internal)			5VDC (provided by DCTL)
Fan type			2 built-in fans type EXP8004
Relay outputs			
Number of relay output		Nr.	1
Contact arrangement			1 C/O-SPDT
Rated current			NO contact: AC1 5A 250VAC / 5A 30VDC NC contact: AC1 3A 250VAC / 3A 30VDC
UL/CSA and IEC/EN 60947-5-1 designation			D300
Maximum switching voltage		VAC	250
Electrical life (with rated load)		cycles	NO contact: 10x103 NC contact: 20x103
Mechanical life		cycles	107
Insulations			
Rated insulation voltage Ui IEC/EN		V	480
Rated impulse withstand voltage Uimp		kV	4
Connections - power terminals			
Type of terminal			Fixed - double lock clamp
Conductor cross section			
	min	mm²	2 x 2.5
	Max	mm²	2 x 35
	min	AWG	2 x 18
	Max	AWG	2 x 2
Tightening torque (Max)			
		Nm	5.5-6.5
		lbin/lbft	4.06-4.79 lbft
Connections - relay output			
Type of terminal			Screw
Conductor cross section			
	min	mm²	0.2
	Max	mm²	4
	min	AWG	26
	Max	AWG	10
Tightening torque (Max)			
		Nm	0.8
		lbin	7
Connections - fan and digital input			
Type of terminal			Screw
Conductor cross section			
	min	mm²	0.2
	Max	mm²	2.5
	min	AWG	24
	Max	AWG	12

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

chanhvinh.com

Lovato electric
ENERGY AND AUTOMATION

DCTLA4000500

Thyristor module, 50kvar at 400VAC, rated operating voltage 400VAC, with current control

Tightening torque (Max)				
			Nm	0.44
			lbin	4
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-20
		max	°C	+45°C without derating (up to 55°C with derating)
	Storage temperature			
		min	°C	-30
		max	°C	+80
Relative humidity			%	<80%
Maximum Pollution degree				2
Overvoltage category				III
Max altitude			m	2000m wihtout derating
Climatic sequence				Z/ABDM (IEC/EN 60068-2-61)
Shock resistance				15g (IEC/EN 60068-2-27)
Vibration resistance				0.7g (IEC/EN 60068-2-6)
Housing				
Execution				Internal panel version
Material				Polycarbonate
Mounting				Screw fixing or DIN-rail (IEC/EN 60715) with optional accessory EXP8003
Degree of protection				IP00
Dimensions (W x H x D)			mm	95 x 226 x 182
Weight			g	2840
Dimensions				


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

chanhvinh.com

Lovato electric
ENERGY AND AUTOMATION


DCTLA4000500

Thyristor module, 50kvar at 400VAC, rated operating voltage 400VAC, with current control



Wiring diagrams

DCTL



Certifications and compliance

Compliance

IEC/EN 60947-4-3
IEC/EN 61000-6-2
IEC/EN 61000-6-4

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

chanhvinh.com

DCTLA4000500

Thyristor module, 50kvar at 400VAC, rated operating voltage 400VAC, with current control

Certificates

cULus

ETIM classification

ETIM 8.0	EC002055 - Solid state relay

chanhvinh.com

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding