chanhvinh.com

Chemical protection

# ALTO 285

Prolonged contact (or immersion) | short wear

## Good mechanical performance for long-lasting chemical protection



CHEMICAL PROTECTION
**TYPE A**

| EN388 | EN ISO 374-1 | EN ISO 374-5 |
|---|---|---|
| 2131X | TYPE A ABKMPT | |

CATEGORY 3

CE

0334

DEXTERITY

EN420: 5/5

## SPECIFIC ADVANTAGES

### Cut protection

- A long cuff for a better protection of the forearm

### Durability

- Longer service life and good impact protection, due to the thickness of the material

### Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

## INDUSTRIES

- Mechanical industry
- Other industries

## APPLICATIONS

- Maintenance in wet environments (water, oil, greases, hydrocarbons)
- Maintenance in wet environments

Edit 10/10/2024

chanhvinh.com

Chemical protection

# ALTO 285

Prolonged contact (or immersion) | short wear

## LEGENDS

EN388 — MECHANICAL HAZARDS

PERFORMANCE LEVELS (X = NOT TESTED)

| 2 | 1 | 3 | 1 | X | |
|---|---|---|---|---|---|
| 0-4 | 0-5 | 0-4 | 0-4 | A-F | P |

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN ISO 374-1 — TYPE A — CHEMICAL RISKS

A: Methanol
B: Acetone
K: Sodium hydroxide 40%
M: Nitric acid 65%
P: Hydrogen peroxide 30%
T: Formaldehyde 37%

EN ISO 374-5 — MICRO-ORGANISMS

Protection against bacteria and fungi

## PRODUCT DETAILS

| | |
|---|---|
| Interior finish | Chlorinated |
| Exterior finish | Reinforced grip |
| Material | Natural latex |
| Cuff characteristic | Rolled Cuff |
| Colour.s | Yellow Beige |
| Length (cm) | 60 |
| Thickness (mm) | 1.0 |
| European sizes | 8 9 10 |
| Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity) | 1.1E+11 Ω |
| Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity) | 2.8E+11 Ω |

## LOGISTIC DETAILS

| | |
|---|---|
| Packaging | 1 pair/bag<br>30 pairs/carton |

## LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/01652
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Edit 10/10/2024