chanhvinh.com


MEDER electronic
Products for tomorrow...


Europe: +49 / 7731 8399 0 | Email: info@meder.com
USA: +1 / 508 295 0771 | Email: salesusa@meder.com
Asia: +852 / 2955 1682 | Email: salesasia@meder.com

Item No.:
1912169114
Item:
H12-1A69

Dimensions mm[inch]


tolerances acc. to DIN ISO 2768-m
Toleranzen gem. DIN ISO 2768-m





Isometric

Scale 1:2
Maßstab 1:2




Cable

Cu-Sn wire 0,6 mm,
silicon tube blue
Cu-Sn Draht 0,6 mm
Silikonschlauch blau


Layout

Top view
Draufsicht



Marking

according to EN60062/factory code
gem. EN60062/Fertigungsstätte



Coil Data at 20 °C	Conditions	Min	Typ	Max	Unit
Coil resistance		207	230	253	Ohm
Coil voltage			12		VDC
Rated power			620		mW
Coil current			52		mA
Thermal resistance	max. Relay temperature = operating temperature + self heating		32		K/W
Inductance			240		mH
Pull-In voltage				8,4	VDC
Drop-Out voltage		1			VDC

Contact data 69	Conditions	Min	Typ	Max	Unit
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			50	W
Switching voltage	DC or Peak AC			10.000	V
Switching current	DC or Peak AC			3	A
Carry current	DC or Peak AC			5	A
Contact resistance static	Measured with 40% overdrive Start Value			150	mOhm
Insulation resistance	RH <45 %, 100 V test voltage	10			TOhm
Breakdown voltage	according to IEC 255-5	15.000			VDC
Operate time incl. bounce	measured with 40% overdrive			3	ms
Release time	measured with no coil excitation			1,5	ms
Capacitance	@ 10 kHz across open switch		0,2		pF

Special Product Data	Conditions	Min	Typ	Max	Unit
Number of contacts		1			
Contact - form		A - NO			
Dielectric Strength Coil/Contact	according to IEC 255-5	15			kV DC
Insulation resistance Coil/Contact	RH <45%, 100 VDC test voltage	10			TOhm
Capacity Coil/Contact	@ 10 kHz		1,2		pF
Case colour		nature			
Housing material		Crastin,SK 645FR,rated 94V-0,140°C,E.I. Dupont			
Connection pins		FeNi-alloy tin plated			
Magnetic Shield		no			
Reach / RoHS conformity		yes			

chanhvinh.com

MEDER electronic
Products for tomorrow...

Europe: +49 / 7731 8399 0 | Email: info@meder.com
USA: +1 / 508 295 0771 | Email: salesusa@meder.com
Asia: +852 / 2955 1682 | Email: salesasia@meder.com

Item No.:
1912169114
Item:
H12-1A69

Environmental data	Conditions	Min	Typ	Max	Unit
Shock	1/2 sine wave duration 11ms			50	g
Vibration	from 10 - 2000 Hz			20	g
Operating temperature		-20		70	°C
Storage temperature		-20		90	°C
Soldering temperature	wave soldering max. 5 sec.			260	°C
Washability		fully sealed			

General data	Conditions	Min	Typ	Max	Unit
Total weigth			28		g
Packaging		carton box 10 pcs./each			

chanhvinh.com