chanhvinh.com

Fuses 5x20 - Time-lag - 5ST

IEC MINIATURE FUSES

5X20



FEATURES & BENEFITS

- 5x20
- Timed fusion
- Safe protection system

APPLICATIONS

- For the protection of motors

STANDARDS

- IEC 60127-2 sheet 3

Mersen's 5ST miniature fuses cover a range including multiple amperages for 250VAC, for the protection of electrical distribution circuits and other industrial applications.

5ST miniature fuses are time-delay fuses that protect your electrical equipment while withstanding the high, sudden, short current that allows a motor to start.

All our technology and processes are defined to ensure the best technical performance.

TECHNICAL DATA OVERVIEW

Voltage AC	250 VAC
Ratings (A)	0,063 A to 20 A
Speed/Characteristic	Time-lag
I.R. AC (IEC/UL)	35 A
Body Material	Glass
Construction	Without extinguishing agent
Contact caps	Brass, nickel plated

© 2025 Mersen. All rights reserved. Mersen reserves the right to change, adapt, limit or discontinue its products. Therefore the data provided herein are for information only and are not contractually binding. To ensure that Mersen provides the best solution to your needs, please contact and provide Mersen with all relevant technical specifications and conditions.

Fuses 5x20 - Time-lag - 5ST

PRODUCT RANGE

5X20 Action Semi-Timed 5ST - Set of 100

Catalog number	Item number	Size	Rated voltage	Rated current I_n	Pre-arcing I^2t	Breaking capacity @ Nominal current	Watt Loss @ 100% In	Max. voltage drop
MI5ST25V0.063/100	D090531Q	5x20	250 V	0,063 A	0.022 A²s	35 A	0.27 W	1.54 V
MI5ST25V0.08/100	E090532Q	5x20	250 V	0,08 A	0.023 A²s	35 A	0.4 W	1.61 V
MI5ST25V0.1/100	F090533Q	5x20	250 V	0,1 A	0.048 A²s	35 A	0.32 W	1.19 V
MI5ST25V0.125/100	G090534Q	5x20	250 V	0,125 A	0.063 A²s	35 A	0.34 W	0.91 V
MI5ST25V0.16/100	H090535Q	5x20	250 V	0,16 A	0.096 A²s	35 A	0.36 W	0.76 V
MI5ST25V0.2/100	J090536Q	5x20	250 V	0,2 A	0.099 A²s	35 A	0.33 W	0.5 V
MI5ST25V0.25/100	K090537Q	5x20	250 V	0,25 A	0.51 A²s	35 A	0.22 W	0.33 V
MI5ST25V0.315/100	L090538Q	5x20	250 V	0,315 A	0.35 A²s	35 A	0.09 W	0.12 V
MI5ST25V0.4/100	M090539Q	5x20	250 V	0,4 A	0.75 A²s	35 A	0.11 W	0.1 V
MI5ST25V0.5/100	N090540Q	5x20	250 V	0,5 A	0.95 A²s	35 A	0.13 W	0.12 V
MI5ST25V0.63/100	P090541Q	5x20	250 V	0,63 A	1.52 A²s	35 A	0.19 W	0.1 V
MI5ST25V0.8/100	Q090542Q	5x20	250 V	0,8 A	3.43 A²s	35 A	0.19 W	0.09 V
MI5ST25V1/100	R090543Q	5x20	250 V	1 A	6.35 A²s	35 A	0.21 W	0.08 V
MI5ST25V1.25/100	S090544Q	5x20	250 V	1,25 A	12.2 A²s	35 A	0.23 W	0.07 V
MI5ST25V1.6/100	T090545Q	5x20	250 V	1,6 A	23.1 A²s	35 A	0.27 W	0.06 V
MI5ST25V2/100	V090546Q	5x20	250 V	2 A	31.9 A²s	35 A	0.4 W	0.07 V
MI5ST25V2.5/100	W090547Q	5x20	250 V	2,5 A	61.2 A²s	35 A	0.45 W	0.07 V
MI5ST25V3.15/100	X090548Q	5x20	250 V	3,15 A	91.5 A²s	35 A	0.58 W	0.08 V
MI5ST25V4/100	Y090549Q	5x20	250 V	4 A	173.5 A²s	35 A	0.64 W	0.06 V
MI5ST25V5/100	Z090550Q	5x20	250 V	5 A	124.2 A²s	35 A	0.75 W	0.06 V
MI5ST25V6.3/100	A090551Q	5x20	250 V	6,3 A	143 A²s	35 A	1.21 W	0.07 V
MI5ST25V8/100	P206070Q	5x20	250 V	8 A [1]	248.2 A²s	35 A	1.76 W	0.08 V
MI5ST25V10/100	Q206071Q	5x20	250 V	10 A [1]	395 A²s	35 A	2.21 W	0.08 V
MI5ST25V12.5/100	Z233449Q	5x20	250 V	12,5 A [2]	422 A²s	300 A	-	0.13 V
MI5ST25V16/100	A233450Q	5x20	250 V	16 A [2]	1582 A²s	300 A	-	0.1 V
MI5ST25V20/100	B233451Q	5x20	250 V	20 A [2]	3580 A²s	300 A	-	0.1 V

[1] No VDE Approval
[2] No standard rating

© 2025 Mersen. All rights reserved. Mersen reserves the right to change, adapt, limit or discontinue its products. Therefore the data provided herein are for information only and are not contractually binding. To ensure that Mersen provides the best solution to your needs, please contact and provide Mersen with all relevant technical specifications and conditions.

Fuses 5x20 - Time-lag - 5ST

PRODUCT RANGE

5X20 Action Semi-Timed 5ST - Set of 1000

Catalog number	Item number	Size	Rated voltage	Rated current I_n	Pre-arcing I^2t	Breaking capacity @ Nominal current	Watt Loss @ 100% In	Max. voltage drop
MI5ST25V0.1/1000	F090533T	5x20	250 V	0,1 A	0.048 A²s	35 A	0.32 W	1.19 V
MI5ST25V0.125/1000	G090534T	5x20	250 V	0,125 A	0.063 A²s	35 A	0.34 W	0.91 V
MI5ST25V0.16/1000	H090535T	5x20	250 V	0,16 A	0.096 A²s	35 A	0.36 W	0.76 V
MI5ST25V0.2/1000	J090536T	5x20	250 V	0,2 A	0.099 A²s	35 A	0.33 W	0.5 V
MI5ST25V0.25/1000	K090537T	5x20	250 V	0,25 A	0.51 A²s	35 A	0.22 W	0.33 V
MI5ST25V0.315/1000	L090538T	5x20	250 V	0,315 A	0.35 A²s	35 A	0.09 W	0.12 V
MI5ST25V0.4/1000	M090539T	5x20	250 V	0,4 A	0.75 A²s	35 A	0.11 W	0.1 V
MI5ST25V0.5/1000	N090540T	5x20	250 V	0,5 A	0.95 A²s	35 A	0.13 W	0.12 V
MI5ST25V0.63/1000	P090541T	5x20	250 V	0,63 A	1.52 A²s	35 A	0.19 W	0.1 V
MI5ST25V0.8/1000	Q090542T	5x20	250 V	0,8 A	3.43 A²s	35 A	0.19 W	0.09 V
MI5ST25V1/1000	R090543T	5x20	250 V	1 A	6.35 A²s	35 A	0.21 W	0.08 V
MI5ST25V1.25/1000	S090544T	5x20	250 V	1,25 A	12.2 A²s	35 A	0.23 W	0.07 V
MI5ST25V1.6/1000	T090545T	5x20	250 V	1,6 A	23.1 A²s	35 A	0.27 W	0.06 V
MI5ST25V2/1000	V090546T	5x20	250 V	2 A	31.9 A²s	35 A	0.4 W	0.07 V
MI5ST25V2.5/1000	W090547T	5x20	250 V	2,5 A	61.2 A²s	35 A	0.45 W	0.07 V
MI5ST25V3.15/1000	X090548T	5x20	250 V	3,15 A	91.5 A²s	35 A	0.58 W	0.08 V
MI5ST25V4/1000	Y090549T	5x20	250 V	4 A	173.5 A²s	35 A	0.64 W	0.06 V
MI5ST25V5/1000	Z090550T	5x20	250 V	5 A	124.2 A²s	35 A	0.75 W	0.06 V
MI5ST25V6.3/1000	A090551T	5x20	250 V	6,3 A	143 A²s	35 A	1.21 W	0.07 V
MI5ST25V10/1000	Q206071T	5x20	250 V	10 A [1]	395 A²s	35 A	2.21 W	0.08 V

[1] No VDE Approval

5X20 Action Semi-Timed 5ST - Assortment Box

Catalog number	Item number	Size	Rated voltage	Rated current I_n
MIBOX5ST	H203764	5x20	250 V	0,1 A to 6,3 A

Composition of the box


Catalog number	Item number	Size	Rated voltage	Rated current I_n	Pre-arcing I^2t	Breaking capacity @ Nominal current	Watt Loss @ 100% In	Max. voltage drop
MI5ST25V0.1	F090533	5x20	250 V	0,1 A	0.048 A²s	35 A	0.32 W	1.19 V
MI5ST25V0.125	G090534	5x20	250 V	0,125 A	0.063 A²s	35 A	0.34 W	0.91 V
MI5ST25V0.16	H090535	5x20	250 V	0,16 A	0.096 A²s	35 A	0.36 W	0.76 V
MI5ST25V0.2	J090536	5x20	250 V	0,2 A	0.099 A²s	35 A	0.33 W	0.5 V
MI5ST25V0.25	K090537	5x20	250 V	0,25 A	0.51 A²s	35 A	0.22 W	0.33 V
MI5ST25V0.315	L090538	5x20	250 V	0,315 A	0.35 A²s	35 A	0.09 W	0.12 V
MI5ST25V0.4	M090539	5x20	250 V	0,4 A	0.75 A²s	35 A	0.11 W	0.1 V
MI5ST25V0.5	N090540	5x20	250 V	0,5 A	0.95 A²s	35 A	0.13 W	0.12 V
MI5ST25V0.63	P090541	5x20	250 V	0,63 A	1.52 A²s	35 A	0.19 W	0.1 V
MI5ST25V0.8	Q090542	5x20	250 V	0,8 A	3.43 A²s	35 A	0.19 W	0.09 V
MI5ST25V1	R090543	5x20	250 V	1 A	6.35 A²s	35 A	0.21 W	0.08 V
MI5ST25V1.25	S090544	5x20	250 V	1,25 A	12.2 A²s	35 A	0.23 W	0.07 V
MI5ST25V1.6	T090545	5x20	250 V	1,6 A	23.1 A²s	35 A	0.27 W	0.06 V
MI5ST25V2	V090546	5x20	250 V	2 A	31.9 A²s	35 A	0.4 W	0.07 V
MI5ST25V2.5	W090547	5x20	250 V	2,5 A	61.2 A²s	35 A	0.45 W	0.07 V
MI5ST25V3.15	X090548	5x20	250 V	3,15 A	91.5 A²s	35 A	0.58 W	0.08 V
MI5ST25V4	Y090549	5x20	250 V	4 A	173.5 A²s	35 A	0.64 W	0.06 V
MI5ST25V6.3	A090551	5x20	250 V	6,3 A	143 A²s	35 A	1.21 W	0.07 V

© 2025 Mersen. All rights reserved. Mersen reserves the right to change, adapt, limit or discontinue its products. Therefore the data provided herein are for information only and are not contractually binding. To ensure that Mersen provides the best solution to your needs, please contact and provide Mersen with all relevant technical specifications and conditions.

chanhvinh.com

Fuses 5x20 - Time-lag - 5ST

TIME CURRENT CHARACTERISTIC CURVES



© 2025 Mersen. All rights reserved. Mersen reserves the right to change, adapt, limit or discontinue its products. Therefore the data provided herein are for information only and are not contractually binding. To ensure that Mersen provides the best solution to your needs, please contact and provide Mersen with all relevant technical specifications and conditions.

Fuses 5x20 - Time-lag - 5ST

TECHNICAL CHARACTERISTICS

In - t characteristics

Rated current factor		Melting time		
		32 mA - 100mA	125mA - 12,5A	12,5A - 20A
1,5 - In	tmin	60 min	60 min	60 min
	tmax	-	-	-
2,1 - In	tmin	0	0	0
	tmax	2 min	2 min	30 min
2,75 - In	tmin	200 ms	600 ms	-
	tmax	10 s	10 s	-
4 - In	tmin	40 ms	150 ms	200 ms
	tmax	3 s	3 s	2 s
10 - In	tmin	10 ms	20 ms	20 ms
	tmax	300 ms	300 ms	200 ms

© 2025 Mersen. All rights reserved. Mersen reserves the right to change, adapt, limit or discontinue its products. Therefore the data provided herein are for information only and are not contractually binding. To ensure that Mersen provides the best solution to your needs, please contact and provide Mersen with all relevant technical specifications and conditions.