chanhvinh.com

32/64-Kbit SPI Serial EEPROM, Industrial Grade

AT25320B/AT25640B

Features

- Serial Peripheral Interface (SPI) Compatible
- Supports SPI Modes 0 (0,0) and 3 (1,1):
  - Data sheet describes mode 0 operation
- Low-Voltage and Standard-Voltage Operation:
  - 1.8V (V_{CC} = 1.8V to 5.5V)
- Industrial Temperature Range: -40°C to +85°C
- 20 MHz Clock Rate (5V)
- 32-Byte Page Mode
- Block Write Protection:
  - Protect 1/4, 1/2 or entire array
- Write-Protect ($\overline{WP}$) Pin and Write Disable Instructions for Both Hardware and Software Data Protection
- Self-Timed Write Cycle within 5 ms Maximum
- High Reliability:
  - Endurance: 1,000,000 write cycles
  - Data retention: 100 years
- RoHS Compliant Package Options
- Die Sale Options: Wafer Form and Bumped Wafers

Packages

- 8-Lead SOIC, 8-Lead TSSOP, 8-Pad UDFN and 8-Ball VFBGA

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

Table of Contents

Features ... 1

Packages ... 1

1. Package Types (not to scale) ... 3

2. Pin Description ... 4
   - 2.1. Chip Select ($\overline{CS}$) ... 4
   - 2.2. Serial Data Output (SO) ... 4
   - 2.3. Write-Protect ($\overline{WP}$) ... 4
   - 2.4. Ground (GND) ... 4
   - 2.5. Serial Data Input (SI) ... 4
   - 2.6. Serial Data Clock (SCK) ... 5
   - 2.7. Suspends Serial Input ($\overline{HOLD}$) ... 5
   - 2.8. Device Power Supply (V_{CC}) ... 5

3. Description ... 6
   - 3.1. Block Diagram ... 6

4. Electrical Characteristics ... 7
   - 4.1. Absolute Maximum Ratings ... 7
   - 4.2. DC and AC Operating Range ... 7
   - 4.3. DC Characteristics ... 7
   - 4.4. AC Characteristics ... 8
   - 4.5. Electrical Specifications ... 9

5. Serial Interface Description ... 11

6. Functional Description ... 12

7. Timing Diagrams ... 15

8. Packaging Information ... 18
   - 8.1. Package Marking Information ... 18

9. Revision History ... 29


Microchip Information ... 30
- The Microchip Website ... 30
- Product Change Notification Service ... 30
- Customer Support ... 30
- Product Identification System ... 31
- Microchip Devices Code Protection Feature ... 31
- Legal Notice ... 32
- Trademarks ... 32
- Quality Management System ... 33
- Worldwide Sales and Service ... 34

© 2018-2024 Microchip Technology Inc. and its subsidiaries


chanhvinh.com

1. Package Types (not to scale)


8-Lead SOIC/TSSOP
(Top View)



8-Pad UDFN(1)
(Top View)



8-Ball VFBGA
(Top View)



Note 1: The exposed pad on UDFN packages can be connected to Vss or left floating.

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

2. Pin Description

The descriptions of the pins are listed in Table 2-1.

Table 2-1. Pin Function Table

Name	8-Lead SOIC	8-Lead TSSOP	8-Pad UDFN(1)	8-Ball VFBGA	Function
$\overline{CS}$	1	1	1	1	Chip Select
SO	2	2	2	2	Serial Data Output
$\overline{WP}$(2)	3	3	3	3	Write-Protect
GND	4	4	4	4	Ground
SI	5	5	5	5	Serial Data Input
SCK	6	6	6	6	Serial Data Clock
$\overline{HOLD}$(2)	7	7	7	7	Suspends Serial Input
V_{CC}	8	8	8	8	Device Power Supply

Notes:

1. The exposed pad on this package can be connected to GND or left floating.
2. The Write-Protect ($\overline{WP}$) and Hold ($\overline{HOLD}$) pins should be driven high or low as appropriate.

2.1 Chip Select ($\overline{CS}$)

The AT25320B/AT25640B is selected when the Chip Select ($\overline{CS}$) pin is low. When the device is not selected, data will not be accepted via the Serial Data Input (SI) pin, and the Serial Output (SO) pin will remain in a high-impedance state.

To ensure robust operation, the $\overline{CS}$ pin should follow V_{CC} upon power-up. It is, therefore, recommended to connect $\overline{CS}$ to V_{CC} using a pull-up resistor (less than or equal to 10 kΩ). After power-up, a low level on $\overline{CS}$ is required prior to any sequence being initiated.

2.2 Serial Data Output (SO)

The Serial Data Output (SO) pin is used to transfer data out of the AT25320B/AT25640B. During a read sequence, data are shifted out on this pin after the falling edge of the Serial Data Clock (SCK).

2.3 Write-Protect ($\overline{WP}$)

The Write-Protect ($\overline{WP}$) pin will allow normal read/write operations when held high. When the $\overline{WP}$ pin is brought low and the WPEN bit is set to a logic '1', all write operations to the STATUS register are inhibited. $\overline{WP}$ going low while $\overline{CS}$ is still low will interrupt a write operation to the STATUS register. If the internal write cycle has already been initiated, $\overline{WP}$ going low will have no effect on any write operation to the STATUS register. The $\overline{WP}$ pin function is blocked when the WPEN bit in the STATUS register is set to a logic '0'. This will allow the user to install the AT25320B/AT25640B in a system with the $\overline{WP}$ pin tied to ground and still be able to write to the STATUS register. All $\overline{WP}$ pin functions are enabled when the WPEN bit is set to a logic '1'.

2.4 Ground (GND)

The ground reference for the Device Power Supply (V_{CC}). The Ground (GND) pin should be connected to the system ground.

2.5 Serial Data Input (SI)

The Serial Data Input (SI) pin is used to transfer data into the device. It receives instructions, addresses and data. Data are latched on the rising edge of the Serial Data Clock (SCK).

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

2.6 Serial Data Clock (SCK)

The Serial Data Clock (SCK) pin is used to synchronize the communication between a host and the AT25320B/AT25640B. Instructions, addresses or data present on the Serial Data Input (SI) pin are latched in on the rising edge of SCK, while output on the Serial Data Output (SO) pin is clocked out on the falling edge of SCK.

2.7 Suspends Serial Input ($\overline{HOLD}$)

The $\overline{HOLD}$ pin is used in conjunction with the $\overline{CS}$ pin to pause the AT25320B/AT25640B. When the device is selected and a serial sequence is underway, $\overline{HOLD}$ can be used to pause the serial communication with the host device without resetting the serial sequence. To pause, the $\overline{HOLD}$ pin must be brought low while the SCK pin is low. To resume serial communication, the $\overline{HOLD}$ pin is brought high while the SCK pin is low (SCK may still toggle during $\overline{HOLD}$). Inputs to the SI pin will be ignored while the SO pin is in the high-impedance state.

2.8 Device Power Supply (V_{CC})

The Device Power Supply (V_{CC}) pin is used to supply the source voltage to the device. Operations at invalid V_{CC} voltages may produce spurious results and should not be attempted.

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com


3. Description

The AT25320B/AT25640B provides 32,768/65,536 bits of Serial Electrically Erasable Programmable Read-Only Memory (EEPROM) organized as 4,096/8,192 words of 8 bits each. The device is optimized for use in many industrial and commercial applications where low-power and low-voltage operation are essential.

The AT25320B/AT25640B is enabled through the Chip Select ($\overline{CS}$) pin and accessed via a three-wire interface consisting of Serial Data Input (SI), Serial Data Output (SO) and Serial Clock (SCK). All programming cycles are completely self-timed, and no separate erase cycle is required before write.

Block write protection is enabled by programming the STATUS register with one of four blocks of write protection. Separate Program Enable and Program Disable instructions are provided for additional data protection. Hardware data protection is provided via the $\overline{WP}$ pin to protect against inadvertent write attempts to the STATUS register. The $\overline{HOLD}$ pin may be used to suspend any serial communication without resetting the serial sequence.

3.1 Block Diagram



© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

4. Electrical Characteristics

4.1 Absolute Maximum Ratings

Temperature under bias	-55°C to +125°C
Storage temperature	-65°C to +150°C
V_{CC}	6.25V
Voltage on any pin with respect to ground	-1.0V to +7.0V
DC output current	5.0 mA
ESD protection	2 kV

Note: Stresses above those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress rating only, and functional operation of the device at these or any other conditions above those indicated in the operation listings of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

4.2 DC and AC Operating Range

Table 4-1. DC and AC Operating Range

AT25320B/AT25640B		
Operating Temperature (Case)	Industrial Temperature Range	-40°C to +85°C
V_{CC} Power Supply	Low-Voltage Grade	1.8V to 5.5V

4.3 DC Characteristics

Table 4-2. DC Characteristics [1]

Parameter	Symbol	Minimum	Maximum	Units	Conditions	
Supply Voltage	V_{CC1}	1.8	5.5	V		
Supply Voltage	V_{CC2}	2.5	5.5	V		
Supply Voltage	V_{CC3}	4.5	5.5	V		
Supply Current	I_{CC1}	—	10.0	mA	V_{CC} = 5.0V at 20 MHz, SO = Open, Read	
Supply Current	I_{CC2}	—	10.0	mA	V_{CC} = 5.0V at 20 MHz, SO = Open, Read, Write	
Supply Current	I_{CC3}	—	6.0	mA	V_{CC} = 5.0V at 5 MHz, SO = Open, Read, Write	
Standby Current	I_{SB1}	—	6.0[2]	µA	V_{CC} = 1.8V, $\overline{CS}$ = V_{CC}, V_{in} = V_{CC} or V_{SS}	
Standby Current	I_{SB2}	—	7.0[2]	µA	V_{CC} = 2.5V, $\overline{CS}$ = V_{CC}, V_{in} = V_{CC} or V_{SS}	
Standby Current	I_{SB3}	—	10.0[2]	µA	V_{CC} = 5.0V, $\overline{CS}$ = V_{CC}, V_{in} = V_{CC} or V_{SS}	
Input Leakage	I_{IL}	-3.0	3.0	µA	V_{IN} = 0V to V_{CC}	
Output Leakage	I_{OL}	-3.0	3.0	µA	V_{IN} = 0V to V_{CC}, T_{AC} = 0°C to +70°C	
Input Low-Voltage	V_{IL}[3]	-0.6	V_{CC} x 0.3	V		
Input High-Voltage	V_{IH}[3]	V_{CC} x 0.7	V_{CC} + 0.5	V		
Output Low-Voltage	V_{OL1}	—	0.4	V	3.6V ≤ V_{CC} ≤ 5.5V	I_{OL} = 3.0 mA
Output High-Voltage	V_{OH1}	V_{CC} - 0.8	—	V	3.6V ≤ V_{CC} ≤ 5.5V	I_{OH} = -1.6 mA
Output Low-Voltage	V_{OL2}	—	0.2	V	1.8V ≤ V_{CC} ≤ 3.6V	I_{OL} = 0.15 mA
Output High-Voltage	V_{OH2}	V_{CC} - 0.2	—	V	1.8V ≤ V_{CC} ≤ 3.6V	I_{OH} = -100 µA

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

Notes:

1. Applicable over recommended operating range from: T_A = -40°C to +85°C, V_{CC} = 1.8V to 5.5V (unless otherwise noted).
2. Worst case measured at 85°C.
3. V_{IL} min and V_{IH} max are reference only and are not tested.

4.4 AC Characteristics

Table 4-3. AC Characteristics[1]

Parameter	Symbol	Minimum	Maximum	Units	Conditions
SCK Clock Frequency	f_{SCK}	0	20	MHz	V_{CC} = 4.5V to 5.5V
		0	10	MHz	V_{CC} = 2.5V to 5.5V
		0	5	MHz	V_{CC} = 1.8V to 5.5V
Input Rise Time	t_{RI}	—	2	µs	V_{CC} = 4.5V to 5.5V
		—	2	µs	V_{CC} = 2.5V to 5.5V
		—	2	µs	V_{CC} = 1.8V to 5.5V
Input Fall Time	t_{FI}	—	2	µs	V_{CC} = 4.5V to 5.5V
		—	2	µs	V_{CC} = 2.5V to 5.5V
		—	2	µs	V_{CC} = 1.8V to 5.5V
SCK High Time	t_{WH}	20	—	ns	V_{CC} = 4.5V to 5.5V
		40	—	ns	V_{CC} = 2.5V to 5.5V
		80	—	ns	V_{CC} = 1.8V to 5.5V
SCK Low Time	t_{WL}	20	—	ns	V_{CC} = 4.5V to 5.5V
		40	—	ns	V_{CC} = 2.5V to 5.5V
		80	—	ns	V_{CC} = 1.8V to 5.5V
$\overline{CS}$ High Time	t_{CS}	25	—	ns	V_{CC} = 4.5V to 5.5V
		50	—	ns	V_{CC} = 2.5V to 5.5V
		100	—	ns	V_{CC} = 1.8V to 5.5V
$\overline{CS}$ Setup Time	t_{CSS}	25	—	ns	V_{CC} = 4.5V to 5.5V
		50	—	ns	V_{CC} = 2.5V to 5.5V
		100	—	ns	V_{CC} = 1.8V to 5.5V
$\overline{CS}$ Hold Time	t_{CSH}	25	—	ns	V_{CC} = 4.5V to 5.5V
		50	—	ns	V_{CC} = 2.5V to 5.5V
		100	—	ns	V_{CC} = 1.8V to 5.5V
Data In Setup Time	t_{SU}	5	—	ns	V_{CC} = 4.5V to 5.5V
		10	—	ns	V_{CC} = 2.5V to 5.5V
		20	—	ns	V_{CC} = 1.8V to 5.5V
Data In Hold Time	t_H	5	—	ns	V_{CC} = 4.5V to 5.5V
		10	—	ns	V_{CC} = 2.5V to 5.5V
		20	—	ns	V_{CC} = 1.8V to 5.5V
$\overline{HOLD}$ Setup Time	t_{HD}	5	—	ns	V_{CC} = 4.5V to 5.5V
		10	—	ns	V_{CC} = 2.5V to 5.5V
		20	—	ns	V_{CC} = 1.8V to 5.5V
$\overline{HOLD}$ Hold Time	t_{CD}	5	—	ns	V_{CC} = 4.5V to 5.5V
		10	—	ns	V_{CC} = 2.5V to 5.5V
		20	—	ns	V_{CC} = 1.8V to 5.5V

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

.....continued					
Parameter	**Symbol**	**Minimum**	**Maximum**	**Units**	**Conditions**
Output Valid	t_V	0	20	ns	V_{CC} = 4.5V to 5.5V
		0	40	ns	V_{CC} = 2.5V to 5.5V
		0	80	ns	V_{CC} = 1.8V to 5.5V
Output Hold Time	t_{HO}	0	—	ns	V_{CC} = 4.5V to 5.5V
		0	—	ns	V_{CC} = 2.5V to 5.5V
		0	—	ns	V_{CC} = 1.8V to 5.5V
$\overline{HOLD}$ to Output Low Z	t_{LZ}	0	25	ns	V_{CC} = 4.5V to 5.5V
		0	50	ns	V_{CC} = 2.5V to 5.5V
		0	100	ns	V_{CC} = 1.8V to 5.5V
$\overline{HOLD}$ to Output High Z	t_{HZ}	—	40	ns	V_{CC} = 4.5V to 5.5V
		—	80	ns	V_{CC} = 2.5V to 5.5V
		—	200	ns	V_{CC} = 1.8V to 5.5V
Output Disable Time	t_{DIS}	—	40	ns	V_{CC} = 4.5V to 5.5V
		—	80	ns	V_{CC} = 2.5V to 5.5V
		—	200	ns	V_{CC} = 1.8V to 5.5V
Write Cycle Time	t_{WC}	—	5	ms	V_{CC} = 4.5V to 5.5V
		—	5	ms	V_{CC} = 2.5V to 5.5V
		—	5	ms	V_{CC} = 1.8V to 5.5V

Note:

1. Applicable over recommended operating range from T_A = -40°C to +85°C, V_{CC} = As Specified, C_L = 1 TTL Gate and 30 pF (unless otherwise noted).

4.5 Electrical Specifications

4.5.1 Power-Up Requirements and Reset Behavior

During a power-up sequence, the V_{CC} supplied to the AT25320B/AT25640B should monotonically rise from GND to the minimum V_{CC} level (as specified in Table 4-1), with a slew rate no faster than 0.1 V/µs.

4.5.1.1 Device Reset

To prevent inadvertent write operations or any other spurious events from occurring during a power-up sequence, the AT25320B/AT25640B includes a Power-on Reset (POR) circuit. Upon power-up, the device will not respond to any instructions until the V_{CC} level crosses the internal voltage threshold (V_{POR}) that brings the device out of Reset and into Standby mode.

The system designer must ensure the instructions are not sent to the device until the V_{CC} supply has reached a stable value greater than or equal to the minimum V_{CC} level. Additionally, once the V_{CC} is greater than or equal to the minimum V_{CC} level, the bus host must wait at least t_{PUP} before sending the first instruction to the device. See Table 4-4 for the values associated with these power-up parameters.

Table 4-4. Power-Up Conditions[1]

Symbol	Parameter	Min.	Max.	Units
t_{PUP}	Time required after V_{CC} is stable before the device can accept instructions	100	—	µs
V_{POR}	Power-on Reset Threshold Voltage	—	1.5	V
t_{POFF}	Minimum time at V_{CC} = 0V between power cycles	500	—	ms

Note:

1. These parameters are characterized, but they are not 100% tested in production.

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

If an event occurs in the system where the V_{CC} level supplied to the AT25320B/AT25640B drops below the maximum V_{POR} level specified, it is recommended that a full-power cycle sequence be performed by first driving the V_{CC} pin to GND in less than 1 ms, waiting at least the minimum t_{POFF} time and then performing a new power-up sequence in compliance with the requirements defined in this section.

4.5.2 Pin Capacitance

Table 4-5. Pin Capacitance[1,2]

Symbol	Test Condition	Max.	Units	Conditions
C_{OUT}	Output Capacitance (SO)	8	pF	V_{OUT} = 0V
C_{IN}	Input Capacitance ($\overline{CS}$, SCK, SI, $\overline{WP}$, $\overline{HOLD}$)	6	pF	V_{IN} = 0V

Notes:

1. This parameter is characterized but is not 100% tested in production.
2. Applicable over recommended operating ranges: T_A = 25°C, f_{SCK} = 1.0 MHz, V_{CC} = 5.0V (unless otherwise noted).

4.5.3 EEPROM Cell Performance Characteristics

Table 4-6. EEPROM Cell Performance Characteristics

Operation	Test Condition	Min.	Max.	Units
Write Endurance[1, 2]	T_A = 25°C, V_{CC} = 3.3V	1,000,000	—	Write Cycles
Data Retention[1]	T_A = 55°C	100	—	Years

Notes:

1. Performance is determined through characterization and the qualification process.
2. Due to the memory array architecture, the Write Cycle Endurance is specified for writes in groups of four data bytes. The beginning of any 4-byte boundaries can be determined by multiplying any integer (N) by four (i.e., 4*N). The end address can be found by adding three to the beginning value (i.e., 4*N+3).


© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

5. Serial Interface Description

Host:	The device that generates the serial clock.
Client:	Because the Serial Clock (SCK) pin is always an input, the AT25320B/AT25640B always operates as a client.
Transmitter/ receiver:	The AT25320B/AT25640B has separate pins designated for data transmission (SO) and reception (SI).
MSb:	The Most Significant bit (MSb) is the first bit transmitted and received.
Serial Opcode:	After the device is selected with $\overline{CS}$ going low, the first byte will be received. This byte contains the opcode that defines the operations to be performed.
Invalid Opcode:	If an invalid opcode is received, no data will be shifted into the AT25320B/AT25640B, and the Serial Output (SO) pin will remain in a high-impedance state until the falling edge of $\overline{CS}$ is detected again. This will reinitialize the serial communication.

Figure 5-1. SPI Serial Interface



© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

6. Functional Description

The AT25320B/AT25640B is designed to interface directly with the synchronous Serial Peripheral Interface (SPI) of the 6805 and 68HC11 series of microcontrollers.

The AT25320B/AT25640B utilizes an 8-bit instruction register. The list of instructions and their operation codes are contained in Table 6-1. All instructions, addresses and data are transferred with the MSb first and start with a high-to-low $\overline{CS}$ transition.

Table 6-1. Instruction Set

Instruction Name	Instruction Format	Operation
WREN	0000 X110	Set Write Enable Latch
WRDI	0000 X100	Reset Write Enable Latch
RDSR	0000 X101	Read STATUS Register
WRSR	0000 X001	Write STATUS Register
READ	0000 X011	Read Data from Memory Array
WRITE	0000 X010	Write Data to Memory Array

Write Enable (WREN): The device will power-up in the Write Disable state when V_{CC} is applied. All programming instructions must, therefore, be preceded by a Write Enable instruction.

Write Disable (WRDI): To protect the device against inadvertent writes, the Write Disable instruction disables all programming modes. The WRDI instruction is independent of the status of the $\overline{WP}$ pin.

Read STATUS Register (RDSR): The Read STATUS Register instruction provides access to the STATUS register. The $\overline{Ready}$/Busy and Write Enable status of the device can be determined by the RDSR instruction. Similarly, the Block Write Protection bits indicate the extent of protection employed. These bits are set by using the WRSR instruction.

Table 6-2. STATUS Register Format

Bit 7	Bit 6	Bit 5	Bit 4	Bit 3	Bit 2	Bit 1	Bit 0
WPEN	X	X	X	BP1	BP0	WEN	$\overline{RDY}$

Table 6-3. Read STATUS Register Bit Definition

Bit	Definition
Bit 0 ($\overline{RDY}$)	Bit 0 = 0 ($\overline{RDY}$) indicates the device is READY. Bit 0 = 1 indicates the write cycle is in progress.
Bit 1 (WEN)	Bit 1= 0 indicates the device is not write enabled. Bit 1 = 1 indicates the device is write enabled.
Bit 2 (BP0)	See Table 6-4.
Bit 3 (BP1)	See Table 6-4.
Bits 4 – 6 are zeros when device is not in an internal write cycle.	
Bit 7 (WPEN)	See Table 6-5.
Bits 0 – 7 are ones during an internal write cycle.	

Write STATUS Register (WRSR): The WRSR instruction allows the user to select one of four levels of protection. The AT25320B/AT25640B is divided into four array segments. One-quarter, one-half or all of the memory segments can be protected. Data within any selected segment will, therefore, be read-only. The Block Write Protection levels and corresponding STATUS register control bits are shown in Table 6-4.

The three bits BP0, BP1 and WPEN are nonvolatile cells that have the same properties and functions as the regular memory cells (e.g., WREN, t_{WC}, RDSR).

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

Table 6-4. Block Write-Protect Bits

Level	STATUS Register Bits		Array Addresses Protected	
	BP1	BP0	AT25320B	AT25640B
0	0	0	None	None
1(1/4)	0	1	0C00-0FFF	1800-1FFF
2(1/2)	1	0	0800-0FFF	1000-1FFF
3(All)	1	1	0000-0FFF	0000-1FFF

The WRSR instruction also allows the user to enable or disable the Write-Protect ($\overline{WP}$) pin through the use of the Write-Protect Enable (WPEN) bit. Hardware Write Protection is enabled when the $\overline{WP}$ pin is low and the WPEN bit is set to a logic '1'. Hardware Write Protection is disabled when either the $\overline{WP}$ pin is high or the WPEN bit is set to a logic '0'. When the device is Hardware Write-Protected, writes to the STATUS register, including the Block Protect bits and the WPEN bit, and the block-protected sections in the memory array are disabled. Writes are only allowed to sections of the memory that are not block-protected.

Note: When the WPEN bit is Hardware Write-Protected, it cannot be set back to a logic '0' as long as the $\overline{WP}$ pin is held low.

Table 6-5. WPEN Operation

WPEN	$\overline{WP}$	WEN	Protected Blocks	Unprotected Blocks	STATUS Register
0	x	0	Protected	Protected	Protected
0	x	1	Protected	Writeable	Writeable
1	Low	0	Protected	Protected	Protected
1	Low	1	Protected	Writeable	Protected
x	High	0	Protected	Protected	Protected
x	High	1	Protected	Writeable	Writeable

Read Sequence (READ):

Reading the AT25320B/AT25640B via the Serial Output (SO) pin requires the following sequence. After the $\overline{CS}$ line is pulled low to select a device, the READ instruction is transmitted via the SI line followed by the byte address to be read (A15 – A0, see Table 6-6). Upon completion, any data on the SI line will be ignored. The data (D7 – D0) at the specified address is then shifted out onto the SO line. If only one byte is to be read, the $\overline{CS}$ line should be driven high after the data comes out. The read sequence can be continued since the byte address is automatically incremented and data will continue to be shifted out. When the highest address is reached, the address counter will roll over to the lowest address allowing the entire memory to be read in one continuous read cycle.

Write Sequence (WRITE):

In order to program the AT25320B/AT25640B, two separate instructions must be executed. First, the device ***must be write enabled*** via the WREN instruction. Then, a WRITE instruction may be executed. Also, the address of the memory location(s) to be programmed must be outside the protected address field location selected by the Block Write Protection level. During an internal write cycle, all instructions will be ignored except the RDSR instruction.

A WRITE instruction requires the following sequence. After the $\overline{CS}$ line is pulled low to select the device, the WRITE instruction is transmitted via the SI line followed by the byte address (A15 – A0) and the data (D7 – D0) to be programmed (see Table 6-6). Programming will start after the $\overline{CS}$ pin is brought high. The low-to-high transition of the $\overline{CS}$ pin must occur during the SCK low-time immediately after clocking in the D0 (LSb) data bit.

The $\overline{Ready}$/Busy status of the device can be determined by initiating a Read STATUS Register (RDSR) instruction. If Bit 0 = 1, the write cycle is still in progress. If Bit 0 =

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

0, the write cycle has ended. Only the RDSR instruction is enabled during the write programming cycle.

The AT25320B/AT25640B is capable of a 32-byte page write operation. After each byte of data is received, the five low-order address bits are internally incremented by one; the high-order bits of the address will remain constant. If more than 32 bytes of data are transmitted, the address counter will roll over and the previously written data will be overwritten. The AT25320B/AT25640B is automatically returned to the write disable state at the completion of a write cycle.

Note: If the device is not write enabled, it will ignore the WRITE instruction and will return to the Standby state when $\overline{CS}$ is brought high. A new $\overline{CS}$ falling edge is required to reinitiate the serial communication.

Table 6-6. Address Key

Address	AT25320B	AT25640B
A_N	A_{11}–A_0	A_{12}–A_0
Don't Care Bits	A_{15}–A_{12}	A_{15}–A_{13}

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

7. Timing Diagrams

Figure 7-1. Synchronous Data Timing (for Mode 0)




Figure 7-2. WREN Timing





Figure 7-3. WRDI Timing



© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

Figure 7-4. RDSR Timing






Figure 7-5. WRSR Timing



Note: This instruction initiates a self-timed internal write cycle (t_{WC}) on the rising edge of $\overline{CS}$ after a valid sequence.


Figure 7-6. Read Timing



© 2018-2024 Microchip Technology Inc. and its subsidiaries


chanhvinh.com

Figure 7-7. Write Timing



Note: This instruction initiates a self-timed internal write cycle (t_{WC}) on the rising edge of $\overline{CS}$ after a valid sequence.

Figure 7-8. $\overline{HOLD}$ Timing




© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

8. Packaging Information

8.1 Package Marking Information

AT25320B and AT25640B: Package Marking Information

8-lead SOIC	8-lead TSSOP
	
8-pad UDFN	**8-ball VFBGA**
2.0 x 3.0 mm Body 	2.35 x 3.73 mm Body 

Note 1: ● designates pin 1
Note 2: Package drawings are not to scale

Catalog Number Truncation	
AT25320B	Truncation Code ###: 5BB
AT25640B	Truncation Code ###: 5CB


Date Codes		**Voltages**
Y = Year		% = Minimum Voltage
Y = Year code (last digit of calendar year) YY = Year code (last 2 digits of calendar year) WW = Week code (week of January 1 is week '01')		L: 1.8V min
Country of Origin	**Device Grade**	**Atmel Truncation**
CO = Country of Origin	H or U: Industrial Grade	AT: Atmel ATM: Atmel ATML: Atmel
Lot Number or Trace Code		
NNN = Alphanumeric Trace Code (2 Characters for Small Packages)		

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

8-Lead Plastic Small Outline (SN) - Narrow, 3.90 mm (.150 In.) Body [SOIC]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging




Microchip Technology Drawing No. C04-057-SN Rev K Sheet 1 of 2

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

8-Lead Plastic Small Outline (SN) - Narrow, 3.90 mm (.150 In.) Body [SOIC]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Pins	N		8	
Pitch	e		1.27 BSC	
Overall Height	A	–	–	1.75
Molded Package Thickness	A2	1.25	–	-
Standoff §	A1	0.10	–	0.25
Overall Width	E		6.00 BSC	
Molded Package Width	E1		3.90 BSC	
Overall Length	D		4.90 BSC	
Chamfer (Optional)	h	0.25	–	0.50
Foot Length	L	0.40	–	1.27
Footprint	L1		1.04 REF	
Lead Thickness	c	0.17	–	0.25
Lead Width	b	0.31	–	0.51
Lead Bend Radius	R	0.07	–	–
Lead Bend Radius	R1	0.07	–	–
Foot Angle	θ	0°	–	8°
Mold Draft Angle	θ1	5°	–	15°
Lead Angle	θ2	0°	–	–

Notes:

1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. § Significant Characteristic
3. Dimensions D and E1 do not include mold flash or protrusions. Mold flash or protrusions shall not exceed 0.15mm per side.
4. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. Theoretically exact value shown without tolerances.
   REF: Reference Dimension, usually without tolerance, for information purposes only.
5. Datums A & B to be determined at Datum H.


Microchip Technology Drawing No. C04-057-SN Rev K Sheet 2 of 2

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

8-Lead Plastic Small Outline (SN) - Narrow, 3.90 mm (.150 In.) Body [SOIC]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E		1.27 BSC	
Contact Pad Spacing	C		5.40	
Contact Pad Width (X8)	X1			0.60
Contact Pad Length (X8)	Y1			1.55

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. Theoretically exact value shown without tolerances.


Microchip Technology Drawing C04-2057-SN Rev K

© 2018-2024 Microchip Technology Inc. and its subsidiaries


chanhvinh.com

8-Lead Plastic Thin Shrink Small Outline (ST) - 4.4 mm Body [TSSOP]


Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



TOP VIEW



SIDE VIEW



VIEW A-A


Microchip Technology Drawing C04-086 Rev C Sheet 1 of 2

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

8-Lead Plastic Thin Shrink Small Outline (ST) - 4.4 mm Body [TSSOP]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Pins	N		8	
Pitch	e		0.65 BSC	
Overall Height	A	-	-	1.20
Molded Package Thickness	A2	0.80	1.00	1.05
Standoff	A1	0.05	-	-
Overall Width	E		6.40 BSC	
Molded Package Width	E1	4.30	4.40	4.50
Overall Length	D	2.90	3.00	3.10
Foot Length	L	0.45	0.60	0.75
Footprint	L1		1.00 REF	
Lead Thickness	c	0.09	-	0.25
Foot Angle	φ	0°	4°	8°
Lead Width	b	0.19	-	0.30

Notes:

1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. Dimensions D and E1 do not include mold flash or protrusions. Mold flash or protrusions shall not exceed 0.20mm per side.
3. Dimensioning and tolerancing per ASME Y14.5M

   BSC: Basic Dimension. Theoretically exact value shown without tolerances.

   REF: Reference Dimension, usually without tolerance, for information purposes only.


Microchip Technology Drawing C04-086 Rev C Sheet 2 of 2

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

8-Lead Plastic Thin Shrink Small Outline (ST) - 4.4 mm Body [TSSOP]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E		0.65 BSC	
Contact Pad Spacing	C		5.80	
Contact Pad Width (X8)	X1			0.45
Contact Pad Length (X8)	Y1			1.50
Contact Pad to Center Pad (X6)	G1	0.20		

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. Theoretically exact value shown without tolerances.
2. For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process


Microchip Technology Drawing C04-2086 Rev B

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

8-Lead Ultra Thin Plastic Dual Flat, No Lead Package (Q4B) - 2x3 mm Body [UDFN]
Atmel Legacy Global Package Code YNZ

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging




Microchip Technology Drawing C04-21355-Q4B Rev C Sheet 1 of 2

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

8-Lead Ultra Thin Plastic Dual Flat, No Lead Package (Q4B) - 2x3 mm Body [UDFN]
Atmel Legacy Global Package Code YNZ

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N		8	
Pitch	e		0.50 BSC	
Overall Height	A	0.50	0.55	0.60
Standoff	A1	0.00	0.02	0.05
Terminal Thickness	A3		0.152 REF	
Overall Length	D		2.00 BSC	
Exposed Pad Length	D2	1.40	1.50	1.60
Overall Width	E		3.00 BSC	
Exposed Pad Width	E2	1.20	1.30	1.40
Terminal Width	b	0.18	0.25	0.30
Terminal Length	L	0.25	0.35	0.45
Terminal-to-Exposed-Pad	K	0.20	-	-

Notes:

1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. Package is saw singulated
3. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.
REF: Reference Dimension, usually without tolerance, for information purposes only.


Microchip Technology Drawing C04-21355-Q4B Rev C Sheet 2 of 2

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

8-Lead Ultra Thin Plastic Dual Flat, No Lead Package (Q4B) - 2x3 mm Body [UDFN]
Atmel Legacy Global Package Code YNZ

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E		0.50 BSC	
Optional Center Pad Width	X2			1.60
Optional Center Pad Length	Y2			1.40
Contact Pad Spacing	C		2.90	
Contact Pad Width (X8)	X1			0.30
Contact Pad Length (X8)	Y1			0.85
Contact Pad to Center Pad (X8)	G1	0.33		
Contact Pad to Contact Pad (X6)	G2	0.20		
Thermal Via Diameter	V		0.30	
Thermal Via Pitch	EV		1.00	

Notes:


1. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. Theoretically exact value shown without tolerances.
2. For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-23355-Q4B Rev C

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

8-ball, 2.35 x 3.73 mm Body, 0.75 mm pitch,Very Thin, Fine-Pitch Ball Grid Array Package (VFBGA)



TOP VIEW SIDE VIEW BOTTOM VIEW

8 SOLDER BALLS

COMMON DIMENSIONS
(Unit of Measure = mm)

SYMBOL	MIN	NOM	MAX	NOTE
A	0.81	0.91	1.00	
A1	0.15	0.20	0.25	
A2	0.40	0.45	0.50	
b	0.25	0.30	0.35	
D	2.35 BSC			
E	3.73 BSC			
e	0.75 BSC			
e1	0.74 REF			
d	0.75 BSC			
d1	0.80 REF			

Notes:

1. This drawing is for general
2. Dimension 'b' is measured at the maximum solder ball diameter.
3. Solder ball composition shall be 95.5Sn-4.0Ag-.5Cu.

6/11/13

	TITLE	GPC	DRAWING NO.	REV.
	8U2-1, 8-ball, 2.35 x 3.73 mm Body, 0.75 mm pitch, Very Thin, Fine-Pitch Ball Grid Array Package (VFBGA)	GWW	8U2-1	G

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

9. Revision History

Revision C (August 2024)
Updated DC Characteristics table. Minor editorial updates throughout the document.

Revision B (July 2021)
Added note to table 4-6 that explains the array architecture and how endurance is specified. Replaced terminology "Master" and "Slave" with "Host" and "Client" respectively. Removed XDFN package option. Updated SOIC, TSSOP and UDFN package drawings.

Revision A (June 2018)
Updated to the Microchip template. Microchip DS20005993A replaces Atmel document 8535. Updated Part Marking Information. Added ESD rating. Removed lead finish designation. Added POR recommendations section. Updated trace code format in package markings. Updated section content throughout for clarification. Updated the SOIC, TSSOP, and UDFN package drawings to the Microchip equivalents.

Atmel Document 8535 Revision H (January 2015)
Added the UDFN Expanded Quantity Option. Updated the 8X, 8MA2, and 8ME1 package outline drawings and the ordering information.

Atmel Document 8535 Revision G (November 2012)
Updated part markings to single page part marking. Updated package drawings. Replaced 8A2 package with 8X package. Update template and Atmel logos.

Atmel Document 8535 Revision F (June 2010)
Updated 8A2 and 8S1 package drawings. Remove Preliminary.

Atmel Document 8535 Revision E (April 2010)
Updated Ordering Code Detail, Ordering Information, template.

Atmel Document 8535 Revision D (August 2009)
Changed Catalog Numbering. Added new Part Marking Information.

Atmel Document 8535 Revision C (May 2009)
Added Part Marking information; changed to Preliminary status.

Atmel Document 8535 Revision B (July 2008)
Modified ‘Endurance’ parameter on page 6.

Atmel Document 8535 Revision A (April 2008)
Initial document release.

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

Microchip Information

The Microchip Website

Microchip provides online support via our website at www.microchip.com/. This website is used to make files and information easily available to customers. Some of the content available includes:

- **Product Support** – Data sheets and errata, application notes and sample programs, design resources, user's guides and hardware support documents, latest software releases and archived software
- **General Technical Support** – Frequently Asked Questions (FAQs), technical support requests, online discussion groups, Microchip design partner program member listing
- **Business of Microchip** – Product selector and ordering guides, latest Microchip press releases, listing of seminars and events, listings of Microchip sales offices, distributors and factory representatives

Product Change Notification Service

Microchip's product change notification service helps keep customers current on Microchip products. Subscribers will receive email notification whenever there are changes, updates, revisions or errata related to a specified product family or development tool of interest.

To register, go to www.microchip.com/pcn and follow the registration instructions.

Customer Support

Users of Microchip products can receive assistance through several channels:

- Distributor or Representative
- Local Sales Office
- Embedded Solutions Engineer (ESE)
- Technical Support

Customers should contact their distributor, representative or ESE for support. Local sales offices are also available to help customers. A listing of sales offices and locations is included in this document.


Technical support is available through the website at: www.microchip.com/support

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

Product Identification System

To order or obtain information, e.g., on pricing or delivery, refer to the factory or the listed sales office.



Note: Refer to the automotive data sheet for automotive grade ordering information.

Examples:

Device	Package	Package Drawing Code	Package Option	Shipping Carrier Option	Device Grade
AT25320B-SSHL-B	SOIC	SN	SS	Bulk (Tubes)	Industrial Temperature (-40°C to 85°C)
AT25640B-SSHL-B	SOIC	SN	SS	Bulk (Tubes)	
AT25320B-SSHL-T	SOIC	SN	SS	Tape and Reel	
AT25640B-SSHL-T	SOIC	SN	SS	Tape and Reel	
AT25320B-XHL-B	TSSOP	ST	X	Bulk (Tubes)	
AT25640B-XHL-B	TSSOP	ST	X	Bulk (Tubes)	
AT25640B-XHL-T	TSSOP	ST	X	Tape and Reel	
AT25320B-XHL-T	TSSOP	ST	X	Tape and Reel	
AT25320B-MAHL-T	UDFN	Q4B	MA	Tape and Reel	
AT25320B-MAHL-E	UDFN	Q4B	MA	Tape and Reel	
AT25640B-MAHL-T	UDFN	Q4B	MA	Tape and Reel	
AT25640B-MAHL-E	UDFN	Q4B	MA	Tape and Reel	
AT25640B-CUL-T	VFBGA	8U2-1	C	Tape and Reel	

Microchip Devices Code Protection Feature

Note the following details of the code protection feature on Microchip products:

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is secure when used in the intended manner, within operating specifications, and under normal conditions.

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

- Microchip values and aggressively protects its intellectual property rights. Attempts to breach the code protection features of Microchip product is strictly prohibited and may violate the Digital Millennium Copyright Act.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not mean that we are guaranteeing the product is “unbreakable”. Code protection is constantly evolving. Microchip is committed to continuously improving the code protection features of our products.

Legal Notice

This publication and the information herein may be used only with Microchip products, including to design, test, and integrate Microchip products with your application. Use of this information in any other manner violates these terms. Information regarding device applications is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. Contact your local Microchip sales office for additional support or, obtain additional support at www.microchip.com/en-us/support/design-help/client-support-services.

THIS INFORMATION IS PROVIDED BY MICROCHIP “AS IS”. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP’S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION.

Use of Microchip devices in life support and/or safety applications is entirely at the buyer’s risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

Trademarks

The Microchip name and logo, the Microchip logo, Adaptec, AVR, AVR logo, AVR Freaks, BesTime, BitCloud, CryptoMemory, CryptoRF, dsPIC, flexPWR, HELDO, IGLOO, JukeBlox, KeeLoq, Kleer, LANCheck, LinkMD, maXStylus, maXTouch, MediaLB, megaAVR, Microsemi, Microsemi logo, MOST, MOST logo, MPLAB, OptoLyzer, PIC, picoPower, PICSTART, PIC32 logo, PolarFire, Prochip Designer, QTouch, SAM-BA, SenGenuity, SpyNIC, SST, SST Logo, SuperFlash, Symmetricom, SyncServer, Tachyon, TimeSource, tinyAVR, UNI/O, Vectron, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

AgileSwitch, ClockWorks, The Embedded Control Solutions Company, EtherSynch, Flashtec, Hyper Speed Control, HyperLight Load, Libero, motorBench, mTouch, Powermite 3, Precision Edge, ProASIC, ProASIC Plus, ProASIC Plus logo, Quiet-Wire, SmartFusion, SyncWorld, TimeCesium, TimeHub, TimePictra, TimeProvider, and ZL are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, Augmented Switching, BlueSky, BodyCom, Clockstudio, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, Espresso T1S, EtherGREEN, EyeOpen, GridTime, IdealBridge, IGaT, In-Circuit Serial Programming, ICSP, INICnet, Intelligent Paralleling, IntelliMOS, Inter-Chip Connectivity, JitterBlocker, Knob-on-Display, MarginLink, maxCrypto, maxView, memBrain, Mindi,

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

MiWi, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, mSiC, MultiTRAK, NetDetach, Omniscient Code Generation, PICDEM, PICDEM.net, PICkit, PICtail, Power MOS IV, Power MOS 7, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, RTAX, RTG4, SAM-ICE, Serial Quad I/O, simpleMAP, SimpliPHY, SmartBuffer, SmartHLS, SMART-I.S., storClad, SQI, SuperSwitcher, SuperSwitcher II, Switchtec, SynchroPHY, Total Endurance, Trusted Time, TSHARC, Turing, USBCheck, VariSense, VectorBlox, VeriPHY, ViewSpan, WiperLock, XpressConnect, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

The Adaptec logo, Frequency on Demand, Silicon Storage Technology, and Symmcom are registered trademarks of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2018-2024, Microchip Technology Incorporated and its subsidiaries. All Rights Reserved.

ISBN: 978-1-6683-0007-7

AMBA, Arm, Arm7, Arm7TDMI, Arm9, Arm11, Artisan, big.LITTLE, Cordio, CoreLink, CoreSight, Cortex, DesignStart, DynamIQ, Jazelle, Keil, Mali, Mbed, Mbed Enabled, NEON, POP, RealView, SecurCore, Socrates, Thumb, TrustZone, ULINK, ULINK2, ULINK-ME, ULINK-PLUS, ULINKpro, µVision, Versatile are trademarks or registered trademarks of Arm Limited (or its subsidiaries) in the US and/or elsewhere.

Quality Management System

For information regarding Microchip's Quality Management Systems, please visit www.microchip.com/quality.

© 2018-2024 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

Worldwide Sales and Service

AMERICAS	ASIA/PACIFIC	ASIA/PACIFIC	EUROPE
Corporate Office 2355 West Chandler Blvd. Chandler, AZ 85224-6199 Tel: 480-792-7200 Fax: 480-792-7277 Technical Support: www.microchip.com/support Web Address: www.microchip.com	**Australia - Sydney** Tel: 61-2-9868-6733	**India - Bangalore** Tel: 91-80-3090-4444	**Austria - Wels** Tel: 43-7242-2244-39 Fax: 43-7242-2244-393
Atlanta Duluth, GA Tel: 678-957-9614 Fax: 678-957-1455	**China - Beijing** Tel: 86-10-8569-7000	**India - New Delhi** Tel: 91-11-4160-8631	**Denmark - Copenhagen** Tel: 45-4485-5910 Fax: 45-4485-2829
Austin, TX Tel: 512-257-3370	**China - Chengdu** Tel: 86-28-8665-5511	**India - Pune** Tel: 91-20-4121-0141	**Finland - Espoo** Tel: 358-9-4520-820
Boston Westborough, MA Tel: 774-760-0087 Fax: 774-760-0088	**China - Chongqing** Tel: 86-23-8980-9588	**Japan - Osaka** Tel: 81-6-6152-7160	**France - Paris** Tel: 33-1-69-53-63-20 Fax: 33-1-69-30-90-79
Chicago Itasca, IL Tel: 630-285-0071 Fax: 630-285-0075	**China - Dongguan** Tel: 86-769-8702-9880	**Japan - Tokyo** Tel: 81-3-6880- 3770	**Germany - Garching** Tel: 49-8931-9700
Dallas Addison, TX Tel: 972-818-7423 Fax: 972-818-2924	**China - Guangzhou** Tel: 86-20-8755-8029	**Korea - Daegu** Tel: 82-53-744-4301	**Germany - Haan** Tel: 49-2129-3766400
Detroit Novi, MI Tel: 248-848-4000	**China - Hangzhou** Tel: 86-571-8792-8115	**Korea - Seoul** Tel: 82-2-554-7200	**Germany - Heilbronn** Tel: 49-7131-72400
Houston, TX Tel: 281-894-5983	**China - Hong Kong SAR** Tel: 852-2943-5100	**Malaysia - Kuala Lumpur** Tel: 60-3-7651-7906	**Germany - Karlsruhe** Tel: 49-721-625370
Indianapolis Noblesville, IN Tel: 317-773-8323 Fax: 317-773-5453 Tel: 317-536-2380	**China - Nanjing** Tel: 86-25-8473-2460	**Malaysia - Penang** Tel: 60-4-227-8870	**Germany - Munich** Tel: 49-89-627-144-0 Fax: 49-89-627-144-44
Los Angeles Mission Viejo, CA Tel: 949-462-9523 Fax: 949-462-9608 Tel: 951-273-7800	**China - Qingdao** Tel: 86-532-8502-7355	**Philippines - Manila** Tel: 63-2-634-9065	**Germany - Rosenheim** Tel: 49-8031-354-560
Raleigh, NC Tel: 919-844-7510	**China - Shanghai** Tel: 86-21-3326-8000	**Singapore** Tel: 65-6334-8870	**Israel - Hod Hasharon** Tel: 972-9-775-5100
New York, NY Tel: 631-435-6000	**China - Shenyang** Tel: 86-24-2334-2829	**Taiwan - Hsin Chu** Tel: 886-3-577-8366	**Italy - Milan** Tel: 39-0331-742611 Fax: 39-0331-466781
San Jose, CA Tel: 408-735-9110 Tel: 408-436-4270	**China - Shenzhen** Tel: 86-755-8864-2200	**Taiwan - Kaohsiung** Tel: 886-7-213-7830	**Italy - Padova** Tel: 39-049-7625286
Canada - Toronto Tel: 905-695-1980 Fax: 905-695-2078	**China - Suzhou** Tel: 86-186-6233-1526	**Taiwan - Taipei** Tel: 886-2-2508-8600	**Netherlands - Drunen** Tel: 31-416-690399 Fax: 31-416-690340
	China - Wuhan Tel: 86-27-5980-5300	**Thailand - Bangkok** Tel: 66-2-694-1351	**Norway - Trondheim** Tel: 47-72884388
	China - Xian Tel: 86-29-8833-7252	**Vietnam - Ho Chi Minh** Tel: 84-28-5448-2100	**Poland - Warsaw** Tel: 48-22-3325737
	China - Xiamen Tel: 86-592-2388138		**Romania - Bucharest** Tel: 40-21-407-87-50
	China - Zhuhai Tel: 86-756-3210040		**Spain - Madrid** Tel: 34-91-708-08-90 Fax: 34-91-708-08-91
			Sweden - Gothenberg Tel: 46-31-704-60-40
			Sweden - Stockholm Tel: 46-8-5090-4654
			UK - Wokingham Tel: 44-118-921-5800 Fax: 44-118-921-5820

© 2018-2024 Microchip Technology Inc. and its subsidiaries