chanhvinh.com

DSA61XX

Ultra-Small, Low Power MEMS Oscillator for Automotive

Features

- Automotive AEC-Q100 Qualified
- Wide Frequency Range: 3.5 kHz to 100 MHz
- Ultra-Low Power Consumption: 3 mA/1 µA (Active/Standby)
- Ultra-Small Footprints
  - 1.6 mm x 1.2 mm VFLGA
  - 2.0 mm x 1.6 mm VFLGA
  - 2.5 mm x 2.0 mm VLGA
  - 3.2 mm x 2.5 mm VDFN
  - 5.0 mm x 3.2 mm VDFN
  - 7.0 mm x 5.0 mm VDFN
- Frequency Select Input Supports Two Pre-Defined Frequencies
- Various Drive Strengths Available
- High Stability: ±20 ppm, ±25 ppm, ±50 ppm
- Wide Temperature Range
  - Automotive Grade 1: –40°C to +125°C
  - Automotive Grade 2: –40°C to +105°C
  - Automotive Grade 3: –40°C to +85°C
- Excellent Shock and Vibration Immunity
  - Qualified to MIL-STD-883
- High Reliability
  - 20x Better MTF Than Quartz Oscillators
- Supply Range of 1.71V to 3.63V
- Short Sample Lead Time: <1 week
- Lead Free & RoHS Compliant

Applications

- Automotive Infotainment
- Automotive ADAS, Surround View Cameras
- In-Vehicle Networking, CAN bus, Ethernet
- 10BASE-T1S


General Description

The DSA61xx family of MEMS oscillators combines the industry leading low power consumption and ultra-small packages with exceptional frequency stability and jitter performance over temperature. The single-output DSA61xx MEMS oscillators are excellent choices for use as clock references in automotive applications in which small size, low power consumption, and long-term reliability are paramount. The family of devices are AEC-Q100 qualified.


The DSA61xx family is available in 1.6 mm x 1.2 mm & 2.0 mm x 1.6 mm VFLGA, 7.0 mm x 5.0 mm, 5.0 mm x 3.2 mm & 3.2 mm x 2.5 mm VDFN, and 2.5 mm x 2.0 mm VLGA packages. These packages are “drop-in” replacements for standard 4-pin CMOS quartz crystal oscillators.

Package Types

DSA61xx
7.0 mm x 5.0 mm VDFN
(Top View)




DSA61xx
5.0 mm x 3.2 mm VDFN
3.2 mm x 2.5 mm VDFN
2.5 mm x 2.0 mm VLGA
2.0 mm x 1.6 mm VFLGA
1.6 mm x 1.2 mm VFLGA
(Top View)



© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

Block Diagram



© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

1.0 ELECTRICAL CHARACTERISTICS

Absolute Maximum Ratings

Supply Voltage ..... –0.3V to +4.0V
Input Voltage (V_{IN}) ..... –0.3V to V_{DD}+0.3V
ESD Protection ..... 4 kV HBM, 400V MM, 2 kV CDM

ELECTRICAL CHARACTERISTICS

Electrical Characteristics: Unless otherwise indicated, V_{DD} = 1.8V –5% to 3.3V +10%, T_A = –40°C to +125°C.

Parameters	Sym.	Min.	Typ.	Max.	Units	Conditions
Supply Voltage	V_{DD}	1.71	—	3.63	V	Note 1
Power Supply Ramp	t_{PU}	0.1	—	100	ms	Note 8
Active Supply Current	I_{DD}	—	3.0	—	mA	f_{OUT} = 27 MHz, V_{DD} = 1.8V, No Load
Standby Supply Current	I_{STBY}	—	1	—	µA	V_{DD} = 1.8/2.5V, Note 2
		—	1.5	—		V_{DD} = 3.3V, Note 2
Output Duty Cycle	SYM	45	—	55	%	—
Frequency	f_0	0.0035	—	100	MHz	Standard and High drive strength
		0.0035	—	60	MHz	Low drive strength
Frequency Stability	Δf	—	—	±20 ±25 ±50	ppm	All temp ranges, Note 3
Aging	Δf	—	—	±5	ppm	1st year @ 25°C
		—	—	±1		Per year after first year
Startup Time	t_{SU}	—	—	1.5	ms	From 90% V_{DD} to valid clock output, T = 25°C
Input Logic Levels	V_{IH}	0.7 x V_{DD}	—	—	V	Input Logic High, Note 4
	V_{IL}	—	—	0.3 x V_{DD}	V	Input Logic Low, Note 4
Output Disable Time	t_{DA}	—	—	200 + 2 Periods	ns	Note 5
Output Enable Time	t_{EN}	—	—	1	µs	Note 6
Enable Pull-up Resistor	—	—	—	300	—	kΩ	If configured, Note 7

Note 1: Pin 4 V_{DD} should be filtered with 0.1 µF capacitor.
2: Not including current through pull-up resistor on EN pin (if configured). Higher standby current seen at >3.3V V_{DD}.
3: Includes frequency variations due to initial tolerance, temp. and power supply voltage.
4: Input waveform must be monotonic with rise/fall time < 10 ms
5: Output Disable time takes up to two periods of the output waveform + 200 ns.
6: For parts configured with OE, not Standby.
7: Output is enabled if pad is floated or not connected.
8: Time to reach 90% of target V_{DD}. Power ramp rise must be monotonic.

© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

ELECTRICAL CHARACTERISTICS (CONTINUED)

Electrical Characteristics: Unless otherwise indicated, V_{DD} = 1.8V –5% to 3.3V +10%, T_A = –40°C to +125°C.

Parameters	Sym.	Min.	Typ.	Max.	Units	Conditions	
Output Logic Levels	V_{OH}	0.8 x V_{DD}	—	—	V	Output Logic High, I = –1 mA, Low Drive	
						Output Logic High, I = –3 mA, Std. Drive	
						Output Logic High, I = –6 mA, High Drive	
	V_{OL}	—	—	0.2 x V_{DD}	V	Output Logic Low, I = 1 mA, Low Drive	
						Output Logic Low, I = 3 mA, Std. Drive	
						Output Logic Low, I = 6 mA, High Drive	
Output Transition Time Rise Time/Fall Time	t_{RX}/t_{FX}	—	3.2	5.4	ns	DSA61x3 Low Drive, 20% to 80% C_L = 5 pF	V_{DD} = 1.8V
		—	2.0	3.3	ns		V_{DD} = 2.5V/3.3V
	t_{RY}/t_{FY}	—	1	1.5	ns	DSA61x2 High Drive, 20% to 80% C_L = 15 pF	V_{DD} = 1.8V
		—	0.5	1.0	ns		V_{DD} = 2.5V/3.3V
		—	1.2	2.0	ns	DSA61x1 Std Drive, 20% to 80% C_L = 10 pF	V_{DD} = 1.8V
		—	0.6	1.2	ns		V_{DD} = 2.5V/3.3V
Period Jitter, RMS	J_{PER}	—	8.5	—	ps_{RMS}	Std. and High Drive, f_{OUT} = 27 MHz	V_{DD} = 1.8V
		—	7	—			V_{DD} = 2.5V/3.3V
		—	26	—		Low Drive, f_{OUT} = 27 MHz	V_{DD} = 1.8V
		—	13	—			V_{DD} = 2.5V/3.3V

Note 1: Pin 4 V_{DD} should be filtered with 0.1 µF capacitor.

2: Not including current through pull-up resistor on EN pin (if configured). Higher standby current seen at >3.3V V_{DD}.

3: Includes frequency variations due to initial tolerance, temp. and power supply voltage.

4: Input waveform must be monotonic with rise/fall time < 10 ms

5: Output Disable time takes up to two periods of the output waveform + 200 ns.

6: For parts configured with OE, not Standby.

7: Output is enabled if pad is floated or not connected.

8: Time to reach 90% of target V_{DD}. Power ramp rise must be monotonic.

© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

ELECTRICAL CHARACTERISTICS (CONTINUED)

Electrical Characteristics: Unless otherwise indicated, V_{DD} = 1.8V –5% to 3.3V +10%, T_A = –40°C to +125°C.

Parameters	Sym.	Min.	Typ.	Max.	Units	Conditions	
Cycle-to-Cycle Jitter (Peak)	J_{Cy-Cy}	—	50	70	ps	Std. and High Drive, f_{OUT} = 27 MHz	V_{DD} = 1.8V
		—	35	60			V_{DD} = 2.5V/3.3V
		—	180	300		Low Drive, f_{OUT} = 27 MHz	V_{DD} = 1.8V
		—	90	150			V_{DD} = 2.5V/3.3V
Period Jitter (Peak-to-Peak)	J_{PP}	—	70	—	ps	Std. and High Drive, f_{OUT} = 27 MHz	V_{DD} = 1.8V
		—	60	—			V_{DD} = 2.5V/3.3V
		—	200	—		Low Drive, f_{OUT} = 27 MHz	V_{DD} = 1.8V
		—	100	—			V_{DD} = 2.5V/3.3V

Note 1: Pin 4 V_{DD} should be filtered with 0.1 µF capacitor.

2: Not including current through pull-up resistor on EN pin (if configured). Higher standby current seen at >3.3V V_{DD}.

3: Includes frequency variations due to initial tolerance, temp. and power supply voltage.

4: Input waveform must be monotonic with rise/fall time < 10 ms

5: Output Disable time takes up to two periods of the output waveform + 200 ns.

6: For parts configured with OE, not Standby.

7: Output is enabled if pad is floated or not connected.

8: Time to reach 90% of target V_{DD}. Power ramp rise must be monotonic.

TEMPERATURE SPECIFICATIONS (Note 1)

Parameters	Sym.	Min.	Typ.	Max.	Units	Conditions
Temperature Ranges						
Junction Operating Temperature	T_J	–40	—	+150	°C	—
Storage Ambient Temperature Range	T_A	–55	—	+150	°C	—
Soldering Temperature	T_S	—	+260	—	°C	40 sec. max.

Note 1: The maximum allowable power dissipation is a function of ambient temperature, the maximum allowable junction temperature and the thermal resistance from junction to air (i.e., T_A, T_J, θ_{JA}). Exceeding the maximum allowable power dissipation will cause the device operating junction temperature to exceed the maximum +125°C rating. Sustained junction temperatures above +125°C can impact the device reliability.

© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

2.0 PIN DESCRIPTIONS

The DSA61xx is a highly configurable device and can be factory programmed in many different ways to meet the customer's needs. Microchip's ClockWorks® Configurator http://clockworks.microchip.com/Timing/ must be used to choose the necessary options, create the final part number, data sheet, and order samples. The descriptions of the pins are listed in Table 2-1.

TABLE 2-1: DSA61XX PIN FUNCTION TABLE

Pin Number	Pin Name	Description
1 (Note 1)	OE	Output Enable: H = Active, L = Disabled (High Impedance).
	$\overline{\text{STDBY}}$	Standby: H = Device is active, L = Device is in standby (Low Power Mode).
	FS	Frequency Select: H = Output Frequency 1, L = Output Frequency 2.
2	GND	Ground.
3	Output	Oscillator clock output.
4	VDD	Power supply: 1.71V to 3.63V.

Note 1: DSA610xB/1xB/3xB has a 300 kΩ internal pull-up resistor on pin 1. DSA614xB/5xB/7xB has no internal pull-up resistor on pin 1 and needs an external pull-up or to be driven by another chip.

An explanation of the different options listed in Table 2-1 follows.

2.1 Pin 1

This is a control pin and may be configured to fulfill one of three different functions. If not actively driven, a 10 kΩ pull-up resistor is recommended.

2.1.1 OUTPUT ENABLE (OE)

Pin 1 may be configured as OE. Oscillator output may be turned on and off according to the state of this pin.

2.1.2 $\overline{\text{STDBY}}$

Pin 1 may be configured as Standby. When the pin is low, both output buffer and PLL will be off and the device will enter a low power mode.

2.1.3 FREQUENCY SELECT (FS)

Pin 1 may be configured as FS. The output may be set to one of two pre-programmed frequencies. The output clock frequencies can only be set to either kHz or MHz. A combination of kHz and MHz cannot be set.

2.2 Pins 2 through 4

Pins 2 and 4 are the supply terminals, GND and VDD respectively. Pin 3 is the clock output that can be selected to have Low, Standard, or High drive strength setting using the ClockWorks® Configurator to customize your device on the Microchip website.

2.3 Output Buffer Options

The DSA61xx family is available with a number of output driver options.

The low-drive (61x3), standard-drive (61x1), and high-drive (61x2) deliver respective output currents of greater than 1 mA, 3 mA, and 6 mA at 20%/80% of the supply voltage. For heavy loads of 15 pF or higher, the high-drive option is recommended.

© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

3.0 DIAGRAMS




FIGURE 3-1: *Output Waveform.*




FIGURE 3-2: *Test Circuit.*




FIGURE 3-3: *Recommended Board Layout.*

© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

4.0 SOLDER REFLOW PROFILE




FIGURE 4-1: *Solder Reflow Profile.*

MSL 1 @ 260°C refer to JSTD-020C	
Ramp-Up Rate (200°C to Peak Temp)	3°C/sec. max.
Preheat Time 150°C to 200°C	60 to 180 sec.
Time maintained above 217°C	60 to 150 sec.
Peak Temperature	255°C to 260°C
Time within 5°C of actual Peak	20 to 40 sec.
Ramp-Down Rate	6°C/sec. max.
Time 25°C to Peak Temperature	8 minutes max.


© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com


5.0 PACKAGING INFORMATION

5.1 Package Marking Information


4-Lead
7.0mm x 5.0mm VDFN*
5.0mm x 3.2mm VDFN*
3.2mm x 2.5mm VDFN*
2.5mm x 2.0mm VLGA*




Example



4-Lead VFLGA*
2.0mm x 1.6mm
1.6mm x 1.2mm



Example




Legend:	XX...X	Product code or customer-specific information
	Y	Year code (last digit of calendar year)
	YY	Year code (last 2 digits of calendar year)
	WW	Week code (week of January 1 is week ‘01’)
	SSS	Alphanumeric traceability code
	(e3)	Pb-free JEDEC® designator for Matte Tin (Sn)
	*	This package is Pb-free. The Pb-free JEDEC designator ((e3)) can be found on the outer packaging for this package.
	●, ▲, ▼	Pin one index is identified by a dot, delta up, or delta down (triangle mark).
Note:		In the event the full Microchip part number cannot be marked on one line, it will be carried over to the next line, thus limiting the number of available characters for customer-specific information. Package may or may not include the corporate logo. Underbar (_) and/or Overbar (¯) symbol may not be to scale.

chanhvinh.com

4-Lead Very Thin Dual Flatpack, No Lead Package (JZA) - 7x5x0.9 mm Body [VDFN] With 2.2x3.5 mm Exposed Pad

Note:	For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging




© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

4-Lead Very Thin Dual Flatpack, No Lead Package (JZA) - 7x5x0.9 mm Body [VDFN] With 2.2x3.5 mm Exposed Pad

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N		004	
Pitch	e		5.08 Ref	
Overall Height	A	0.80	0.85	0.90
Standoff	A1	0.00	-	0.05
Terminal Thickness	A3		0.203 Ref	
Overall Length	D	6.90	7.00	7.10
Exposed Pad Length	D2	2.10	2.20	2.30
Overall Width	E	4.90	5.00	5.10
Exposed Pad Width	E2	3.40	3.50	3.60
Terminal Width	b	1.35	1.40	1.45
Terminal Length	L	1.10	1.20	1.30

Notes:

1. Pin 1 visual index feature may vary, but must be located within the pin 1 area.
2. Package is saw singulated
3. Dimensioning and tolerancing per ASME Y14.5M

   BSC: Basic Dimension. Theoretically exact value shown without tolerances.


   REF: Reference Dimension, usually without tolerance, for information purposes only.

© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

4-Lead Very Thin Dual Flatpack, No Lead Package [JZA] - 7x5x0.9 mm Body [VDFN] With 2.2x3.5 mm Exposed Pad

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Optional Center Pad Width	X2			2.30
Optional Center Pad Length	Y2			3.60
Contact Pad Spacing	C1		5.08	
Contact Pad Spacing	C2		3.90	
Contact Pad Width (Xnn)	X1			1.50
Contact Pad Length (Xnn)	Y1			1.30
Contact Pad to Center Pad (Xnn)	G1	0.69		
Thermal Via Diameter	V		0.33	
Thermal Via Pitch	EV		1.20	

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. Theoretically exact value shown without tolerances.
2. For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process


Microchip Technology Drawing C04-3025-JZA Rev B

© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

4-Lead Very Thin Plastic Dual Flat, No Lead Package (H6A) - 5x3.2 mm Body [VDFN]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging




Microchip Technology Drawing C04-1008-H6A Rev C Sheet 1 of 2

chanhvinh.com

4-Lead Very Thin Plastic Dual Flat, No Lead Package (H6A) - 5x3.2 mm Body [VDFN]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N		4	
Pitch	e		2.54 BSC	
Overall Height	A	0.80	0.85	0.90
Standoff	A1	0.00	0.02	0.05
Terminal Thickness	A3		0.20 REF	
Overall Length	D		5.00 BSC	
Overall Width	E		3.20 BSC	
Terminal Width	b	1.15	1.20	1.25
Terminal 1 Tab	b1		0.10 REF	
Terminal Length	L	0.80	0.90	1.00
Terminal Pull Back	L1		0.10 REF	
Terminal 1 Tab	L2		0.20 REF	
Terminal 1 Chamfer	CH		0.25 REF	
Terminal Spacing	K		1.20 REF	

Notes:

1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. Package is saw singulated
3. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. Theoretically exact value shown without tolerances.
   REF: Reference Dimension, usually without tolerance, for information purposes only.


Microchip Technology Drawing C04-1008-H6A Rev C Sheet 2 of 2

© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

4-Lead Very Thin Plastic Dual Flat, No Lead Package (H6A) - 5x3.2 mm Body [VDFN]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E		2.54	
Contact Pad Spacing	C		2.00	
Contact Pad Width (X4)	X1			1.40
Contact Pad Length (X4)	Y1			
Contact Pad to Center Pad (X2)	G1	1.00		1.10
Contact Pad to Contact Pad (X2)	G2	1.14		
Terminal 1 Contact Pad Chamfer	CH		0.30	

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.


Microchip Technology Drawing C04-3008 Rev C

© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

4-Lead Very Thin Plastic Dual Flatpack No-Lead (H4A) - 3.2x2.5 mm Body [VDFN]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging




Microchip Technology Drawing C04-1006 Rev B Sheet 1 of 2

© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

4-Lead Very Thin Plastic Dual Flatpack No-Lead (H4A) - 3.2x2.5 mm Body [VDFN]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N		4	
Pitch	e		2.10 BSC	
Overall Height	A	0.80	0.85	0.90
Standoff	A1	0.00	0.02	0.05
Overall Length	D		3.20 BSC	
Overall Width	E		2.50 BSC	
Terminal Width	b	0.85	0.90	0.95
Terminal Length	L	0.70	0.80	0.90
Terminal 1 Index Chamfer	CH		0.25 REF	

Notes:

1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. Package is saw singulated
3. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. Theoretically exact value shown without tolerances.
   REF: Reference Dimension, usually without tolerance, for information purposes only.


Microchip Technology Drawing C04-1006 Rev B Sheet 2 of 2

© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

4-Lead Very Thin Plastic Dual Flatpack No-Lead (H4A) - 3.2x2.5 mm Body [VDFN]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E	2.10 BSC		
Contact Pad Spacing	C		1.80	
Contact Pad Width (Xnn)	X			0.90
Contact Pad Length (Xnn)	Y			1.00
Contact Pad Length (Xnn)	CH	0.20 REF		

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M

   BSC: Basic Dimension. Theoretically exact value shown without tolerances.
   REF: Reference Dimension, usually without tolerance, for information purposes only.


Microchip Technology Drawing C04-3006 Rev B

© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

4-Lead Very Thin Land Grid Array (AUA) - 2.5x2.0 mm Body [VLGA]

Note:	For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging




Microchip Technology Drawing C04-1202B Sheet 1 of 2

© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

4-Lead Very Thin Land Grid Array (AUA) - 2.5x2.0 mm Body [VLGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N		4	
Terminal Pitch	e		1.65 BSC	
Terminal Pitch	e1		1.25 BSC	
Overall Height	A	0.79	0.84	0.89
Standoff	A1	0.00	0.02	0.05
Substrate Thickness (with Terminals)	A3		0.20 REF	
Overall Length	D		2.50 BSC	
Overall Width	E		2.00 BSC	
Terminal Width	b1	0.60	0.65	0.70
Terminal Length	L	0.60	0.65	0.70
Terminal 1 Index Chamfer	CH	-	0.225	-

Notes:

1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. Package is saw singulated
3. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.
REF: Reference Dimension, usually without tolerance, for information purposes only.


Microchip Technology Drawing C04-1202B Sheet 2 of 2

© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

4-Lead Very Thin Land Grid Array (AUA) - 2.5x2.0 mm Body [VLGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E	1.65 BSC		
Contact Spacing	C		1.25	
Contact Width (X4)	X			0.70
Contact Pad Length (X4)	Y			0.80
Space Between Contacts (X2)	G1	0.95		
Space Between Contacts (X2)	G2	0.45		
Contact 1 Index Chamfer	CH	0.13 X 45° REF		

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. Theoretically exact value shown without tolerances.


Microchip Technology Drawing C04-3202B


© 2019 - 2026 Microchip Technology Inc. and its subsidiaries


chanhvinh.com

4-Lead Very Thin Fine Pitch Land Grid Array (ASA) - 2.0x1.6 mm Body [VFLGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging








Microchip Technology Drawing C04-1200 Rev D Sheet 1 of 2

© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

4-Lead Very Thin Fine Pitch Land Grid Array (ASA) - 2.0x1.6 mm Body [VFLGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N		4	
Terminal Pitch	e		1.55 BSC	
Terminal Pitch	e1		0.95 BSC	
Overall Height	A	0.79	0.84	0.89
Standoff	A1	0.00	0.02	0.05
Substrate Thickness (with Terminals)	A3		0.20 REF	
Overall Length	D		2.00 BSC	
Overall Width	E		1.60 BSC	
Terminal Width	b1	0.30	0.35	0.40
Terminal Width	b2	0.40	0.45	0.50
Terminal Length	L	0.50	0.55	0.60
Terminal 1 Index Chamfer	CH	-	0.15	-

Notes:

1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. Package is saw singulated
3. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.
REF: Reference Dimension, usually without tolerance, for information purposes only.


Microchip Technology Drawing C04-1200 Rev D Sheet 2 of 2

chanhvinh.com

chanhvinh.com

4-Lead Very Thin Fine Pitch Land Grid Array (ASA) - 2.0x1.6 mm Body [VFLGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E		1.55 BSC	
Contact Spacing	C		0.95	
Contact Width	X1			0.50
Contact Width (X3)	X2			0.40
Contact Pad Length (X4)	Y			0.70
Space Between Contacts	G1	1.05		
Space Between Contacts (X2)	G2	0.25		
Space Between Contacts	G3	1.15		
Contact 1 Index Chamfer	CH		0.13 X 45° REF	

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. Theoretically exact value shown without tolerances.
2. The value in parenthesis, next to the item description is a unit multiplier.


Microchip Technology Drawing C04-3200 Rev D


© 2019 - 2026 Microchip Technology Inc. and its subsidiaries


chanhvinh.com

4-Lead Very Thin Fine Pitch Land Grid Array (ARA) - 1.6x1.2 mm Body [VFLGA]

Note:	For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging








Microchip Technology Drawing C04-1199B Sheet 1 of 2

chanhvinh.com

4-Lead Very Thin Fine Pitch Land Grid Array (ARA) - 1.6x1.2 mm Body [VFLGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N		4	
Terminal Pitch	e		1.20 BSC	
Terminal Pitch	e1		0.75 BSC	
Overall Height	A	0.79	0.84	0.89
Standoff	A1	0.00	0.02	0.05
Substrate Thickness (with Terminals)	A3		0.20 REF	
Overall Length	D		1.60 BSC	
Overall Width	E		1.20 BSC	
Terminal Width	b1	0.25	0.30	0.35
Terminal Width	b2	0.325	0.375	0.425
Terminal Length	L	0.30	0.35	0.40
Terminal 1 Index Chamfer	CH	-	0.125	-

Notes:

1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. Package is saw singulated
3. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.

REF: Reference Dimension, usually without tolerance, for information purposes only.


Microchip Technology Drawing C04-1199B Sheet 2 of 2

© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

4-Lead Very Thin Fine Pitch Land Grid Array (ARA) - 1.6x1.2 mm Body [VFLGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E1		1.20 BSC	
Contact Pitch	E2		1.16 BSC	
Contact Spacing	C		0.75	
Contact Width (X3)	X1			0.35
Contact Width	X2			0.43
Contact Pad Length (X4)	Y			0.50
Space Between Contacts	G1	0.85		
Space Between Contacts (X2)	G2	0.25		
Space Between Contacts	G3	0.77		
Contact 1 Index Chamfer	CH		0.13 X 45° REF	

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. Theoretically exact value shown without tolerances.
2. The value in parenthesis, next to the item description is a unit multiplier.

Microchip Technology Drawing C04-3199B

© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

NOTES:

chanhvinh.com

© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

APPENDIX A: REVISION HISTORY

Revision A (June 2019)

- Initial creation of DSA61xx Microchip data sheet DS20006222A.

Revision B (November 2022)

- Added the 7.0 mm x 5.0 mm VDFN, 5.0 mm x 3.2 mm VDFN and 3.2 mm x 2.5 mm VDFN package options throughout the document.
- Updated the previously existing package outline drawings to their most current versions.

Revision C (April 2026)

- Added one bullet each to the Features and Applications sections.
- Added Low drive strength information to the Electrical Characteristics table.
- Added Low drive strength information to **Section 2.2 “Pins 2 through 4”** and **Section 2.3 “Output Buffer Options”**.
- Updated the Package Marking Information drawing and the Product Identification System section.

chanhvinh.com

chanhvinh.com

NOTES:

chanhvinh.com

© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

PRODUCT IDENTIFICATION SYSTEM

To order or obtain information, e.g., on pricing or delivery, contact your local Microchip representative or sales office.

PART NO.	X	X	X	X	X	X	-XXX.XXXX	X	XXX
Device	Pin 1 Definition	Output Drive Strength	Package	Temperature Range	Frequency Stability	Revision	Frequency	Media Type	Automotive Suffix

Device: DSA61: Ultra-Small, Low Power MEMS Oscillator

Pin 1 Definition:

Selection	Pin 1	Internal Pull-Up Register
0	OE	Pull-up
1	$\overline{\text{STDBY}}$	Pull-up
2	FS	Pull-up
4	OE	None
5	$\overline{\text{STDBY}}$	None
6	FS	None

Output Drive Strength:
1 = Standard
2 = High
3 = Low

Package:
A = 4-Lead 7.0 mm x 5.0 mm VDFN
B = 4-Lead 5.0 mm x 3.2 mm VDFN
C = 4-Lead 3.2 mm x 2.5 mm VDFN
J = 4-Lead 2.5 mm x 2.0 mm VLGA
M = 4-Lead 2.0 mm x 1.6 mm VFLGA
H = 4-Lead 1.6 mm x 1.2 mm VFLGA

Temperature Range:
A = –40°C to +125°C (Automotive Grade 1)
L = –40°C to +105°C (Automotive Grade 2)
I = –40°C to +85°C (Automotive Grade 3)

Frequency Stability:
1 = ± 50 ppm
2 = ± 25 ppm
3 = ± 20 ppm

Revision: B = Revision B

Frequency:
xxx.xxxx = User-Defined Frequency between 001.0000 MHz and 80.0000 MHz
xxxKxxx = User-Defined Frequency between 002.000 kHz and 999.999 kHz
xxxx = Frequency configuration code when pin 1 = FS. Configure the part online through ClockWorks® configurator.

Media Type:
<blank>= 50/Tube, 100 pce. min. (A Package Option)
<blank>= 72/Tube, 144 pce. min. (B Package Option)
<blank>= 110/Tube (C Package Option)
<blank>= 140/Tube (J Package Option)
<blank>= 100/Bag (M & H Package Options)
T = 1,000/Reel
B = 3,000/Reel

Automotive Suffix: Vxx = The “xx” is assigned by Microchip.

Examples:

a) DSA6112JI2B-100.0000VAO:

Ultra-Small, Low Power MEMS Oscillator, Pin 1 = STDBY with Internal Pull-Up, High Drive Strength, 4-Lead 2.5 mm x 2.0 mm VLGA, Automotive Grade 3 Temperature, ±25 ppm Stability, Revision B, 100 MHz Frequency, 140/Tube

b) DSA6101HL1B-016.0000TVAO:

Ultra-Small, Low Power MEMS Oscillator, Pin 1 = OE with Internal Pull–Up, Standard Drive Strength, 4-Lead 1.6 mm x 1.2 mm VFLGA, Automotive Grade 2 Temperature, ±50 ppm Stability, Revision B, 16 MHz Frequency, 1,000/Reel

c) DSA6123MA2B-0101BVAO:

Ultra-Small, Low Power MEMS Oscillator, Pin 1 = Freq. Select with Internal Pull-Up, Low Drive Strength, 4-Lead 2.0 mm x 1.6 mm VFLGA, Automotive Grade 1 Temperature, ±25 ppm Stability, Revision B, Two Frequencies Configured through ClockWorks, 3,000/Reel

Note 1: Tape and Reel identifier only appears in the catalog part number description. This identifier is used for ordering purposes and is not printed on the device package. Check with your Microchip Sales Office for package availability with the Tape and Reel option.

Note 1: Please visit Microchip ClockWorks® Configurator Website to configure the part number for customized frequency. http://clockworks.microchip.com/timing/.

© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

NOTES:

© 2019 - 2026 Microchip Technology Inc. and its subsidiaries

chanhvinh.com

Microchip Information

Trademarks

The “Microchip” name and logo, the “M” logo, and other names, logos, and brands are registered and unregistered trademarks of Microchip Technology Incorporated or its affiliates and/or subsidiaries in the United States and/or other countries (“Microchip Trademarks”). Information regarding Microchip Trademarks can be found at https://www.microchip.com/en-us/about/legalinformation/microchip-trademarks.

ISBN: 979-8-3371-3119-1

Legal Notice

This publication and the information herein may be used only with Microchip products, including to design, test, and integrate Microchip products with your application. Use of this information in any other manner violates these terms. Information regarding device applications is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. Contact your local Microchip sales office for additional support or, obtain additional support at www.microchip.com/en-us/support/design-help/client-support-services.

THIS INFORMATION IS PROVIDED BY MICROCHIP "AS IS". MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP'S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION.

Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

Microchip Devices Code Protection Feature

Note the following details of the code protection feature on Microchip products:

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is secure when used in the intended manner, within operating specifications, and under normal conditions.
- Microchip values and aggressively protects its intellectual property rights. Attempts to breach the code protection features of Microchip product is strictly prohibited and may violate the Digital Millennium Copyright Act.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not mean that we are guaranteeing the product is “unbreakable”. Code protection is constantly evolving. Microchip is committed to continuously improving the code protection features of our products.