chanhvinh.com

MIC5283

120 V_{IN}, 150 mA, Ultra-Low I_Q, High-PSRR Linear Regulator

Features

- Wide Input Voltage Range: 6V to 120V DC
- Ultra-Low Quiescent Current: 8 µA
- 150 mA Guaranteed Output Current
- Adjustable Output from 1.22V to 5.5V
- Stable with Ceramic Capacitors
- Ultra-High PSRR (75 dB at 10 kHz)
- Ultra-High Line Rejection (Load Dump)
- High Output Accuracy
  - ±3% Initial Accuracy
- Thermal-Shutdown and Current-Limit Protection
- Thermally-Efficient, 8-Lead ePad SOIC Package
- Very Low-Profile 3 mm × 3 mm VDFN Package

Applications

- Industrial Applications
- Remote Keyless Entry Power Supply
- Telecom Applications
- Off-Line Power Supplies

General Description

The MIC5283 high-performance linear regulator offers a very-wide input operating voltage range, up to 120V DC, and supplies an output current of up to 150 mA.

Ideal for high input voltage applications such as industrial and telecom, the MIC5283 offers ±3% initial accuracy, extremely high-power supply rejection ratio (75 dB at 10 kHz) and an ultra-low quiescent current of 8 µA. The MIC5283 is optimized for high-voltage line transients, making it ideal for harsh environment applications.


The MIC5283 is offered in both fixed output voltage (3.3V or 5.0V) and adjustable output voltage (1.22V to 5.5V) options.

The MIC5283 operates over a −40°C to +125°C temperature range and is available in lead-free, RoHS compliant, ePad SOIC-8 and 3 mm × 3 mm VDFN packages

Package Types


MIC5283YME

8-Lead SOIC | Fixed Voltages




MIC5283YML

8-Lead VDFN | Fixed Voltages




MIC5283-x.xYME

8-Lead SOIC | Adjustable Voltages



MIC5283-x.xYML

8-Lead VDFN | Adjustable Voltages




© 2023 Microchip Technology Inc.


chanhvinh.com

Typical Application Circuits

MIC5283YME



MIC5283-5.0YME




© 2023 Microchip Technology Inc.


chanhvinh.com

Functional Block Diagram

MIC5283 Fixed Version



MIC5283 Adjustable Version



chanhvinh.com

1.0 ELECTRICAL CHARACTERISTICS

Absolute Maximum Ratings †

VIN to GND..... –0.3V to +125V
VCPSRR to GND.....–0.3 to +14V
VFB, VSNS, VOUT to GND..... –0.3V to +6V
HBM ESD Ratings (Note 1).....2 kV
MM ESD Ratings (Note 1).....200V

Operating Ratings ‡

V_{IN} ..... +6V to +120V
V_{OUT} Adjust Range ..... +1.22V to +5.5V
Power Dissipation (P_D)..... Internally Limited (Note 2)

† Notice: Stresses above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at those or any other conditions above those indicated in the operational sections of this specification is not intended. Exposure to maximum rating conditions for extended periods may affect device reliability.

‡ Notice: The device is not guaranteed to function outside its operating ratings.

Note 1: Devices are ESD sensitive; use proper handling precautions.

2: The maximum allowable power dissipation at any T_A (ambient temperature) is $P_{D(max)} = (T_{J(max)} – T_A) / \theta_{JA}$. Exceeding the maximum allowable power dissipation results in excessive die temperature, and causes the regulator to enter thermal shutdown.

ELECTRICAL CHARACTERISTICS

V_{IN} = 12V, C_{IN} = 1.0 µF, C_{PSRR} = 0.1 µF, C_{OUT} = 10 µF, V_{OUT} = 5.0V or 3.3V, I_{OUT} = 100 µA, T_A = 25°C, **bold** values indicate –40°C ≤ T_J ≤ +125°C, unless noted. (Note 1)

Parameters	Sym.	Min.	Typ.	Max.	Units	Conditions
Power Supply Input						
Input Voltage Range	V_{IN}	6	—	120	V	—
Quiescent Supply Current	I_Q	—	8	**14**	µA	I_{OUT} = 0
Output Voltage						
Output Voltage Accuracy	ΔV_{OUT}	–3	—	+3	%	Variation from nominal VOUT 100 µA ≤ I_{OUT} ≤ 150 mA
		–5	—	**+5**	%	
Line Regulation (Note 2)	$\Delta V_{OUT}/V_{OUT}$	**–0.5**	0.04	**+0.5**	%/V	10V ≤ V_{IN} ≤ 120V
Feedback Input (Adjustable)						
Feedback Voltage	V_{FB}	1.183	1.220	1.256	V	100 µA ≤ I_{OUT} ≤ 150 mA
		1.159	1.220	**1.281**	V	
Feedback Current	I_{FB}	—	3.2	—	nA	V_{FB} = 1.22V
Current Limit						
Current Limit	I_{LIMIT}	**180**	300	**500**	mA	V_{OUT} = 0V
Ripple Rejection						
Power Supply Rejection Ratio (I_{OUT} = 50 mA)	PSRR	—	70	—	dB	100 Hz ≤ f ≤ 1 kHz
		—	75	—	dB	1 kHz < f ≤ 30 kHz
		—	65	—	dB	30 kHz < f ≤ 100 kHz

Note 1: Specifications are for packaged products only.

2: Line regulation is a percentage of V_{OUT}.

© 2023 Microchip Technology Inc.

chanhvinh.com

ELECTRICAL CHARACTERISTICS (CONTINUED)

V_{IN} = 12V, C_{IN} = 1.0 µF, C_{PSRR} = 0.1 µF, C_{OUT} = 10 µF, V_{OUT} = 5.0V or 3.3V, I_{OUT} = 100 µA, T_A = 25°C, **bold** values indicate –40°C ≤ T_J ≤ +125°C, unless noted. (Note 1)

Parameters	Sym.	Min.	Typ.	Max.	Units	Conditions
Power Dropout Voltage						
Dropout Voltage	$V_{IN} - V_{OUT}$	—	1.8	**2.8**	V	I_{OUT} = 150 mA
Thermal Protection						
Thermal-Shutdown Temperature	T_{SHDN}	—	155	—	°C	TJ rising
Thermal-Shutdown Hysteresis	T_{SHDN_HYS}	—	15	—	°C	—

Note 1: Specifications are for packaged products only.

2: Line regulation is a percentage of V_{OUT}.

TEMPERATURE SPECIFICATIONS

Parameters	Sym.	Min.	Typ.	Max.	Units	Conditions
Operating Junction Temperature Range	T_J	–40	—	+125	°C	—
Storage Temperature Range	T_A	–65	—	+150	°C	—
Lead Temperature	—	—	—	+260	°C	Soldering, 10 seconds
Thermal Resistance 8-Lead VDFN	θ_{JA}	—	60	—	°C/W	Note 1
Thermal Resistance 8-Lead SOIC	θ_{JA}	—	41	—	°C/W	

Note 1: The maximum allowable power dissipation at any T_A (ambient temperature) is $P_{D(max)} = (T_{J(max)} - T_A) / \theta_{JA}$. Exceeding the maximum allowable power dissipation results in excessive die temperature, and causes the regulator to enter thermal shutdown.

© 2023 Microchip Technology Inc.

chanhvinh.com

2.0 TYPICAL PERFORMANCE CURVES

Note: The graphs and tables provided following this note are a statistical summary based on a limited number of samples and are provided for informational purposes only. The performance characteristics listed herein are not tested or guaranteed. In some graphs or tables, the data presented may be outside the specified operating range (e.g., outside specified power supply range) and therefore outside the warranted range.




FIGURE 2-1: *Quiescent Supply Current vs. Input Voltage.*




FIGURE 2-4: *Output Voltage vs. Output Current.*




FIGURE 2-2: *Quiescent Supply Current vs. Temperature.*




FIGURE 2-5: *Output Voltage vs. Temperature.*




FIGURE 2-3: *.Output Voltage vs. Input Voltage.*




FIGURE 2-6: *Dropout Voltage vs. Output Current.*

© 2023 Microchip Technology Inc.

chanhvinh.com




FIGURE 2-7: *Dropout Voltage vs. Temperature.*




FIGURE 2-10: *Feedback Pin Voltage vs. Temperature.*




FIGURE 2-8: *Feedback Pin Current vs. Temperature.*




FIGURE 2-11: *Feedback Pin Voltage vs. Output Current.*




FIGURE 2-9: *Feedback Pin Current vs. Input Voltage.*




FIGURE 2-12: *Current Limit vs. Temperature.*

chanhvinh.com




FIGURE 2-13: *Line Regulation vs. Temperature.*




FIGURE 2-16: *Case Temperature (ME) vs. Output Current. (Please see Note.)*




FIGURE 2-14: *Case Temperature (ML) vs. Output Current. (Please see Note.)*




FIGURE 2-17: *Power Dissipation (ME) vs. Output Current.*




FIGURE 2-15: *Power Dissipation (ML) vs. Output Current.*




FIGURE 2-18: *PSRR vs. Frequency.*

Note: The temperature measurement was taken at the hottest point on the MIC5283 case mounte don a 2.25 square-inch PCB at an ambient temperature of 25°C; see “Thermal Measurement” section. Actual results will depend upon the size of the PCB, ambient temperature, and proximity to other heat-emitting components.

© 2023 Microchip Technology Inc.

chanhvinh.com




FIGURE 2-19: *Soft Turn-On into Full Load.*




FIGURE 2-22: *Fast Turn-Off.*




FIGURE 2-20: *Soft Turn-Off.*




FIGURE 2-23: *V_{IN} ULVO Threshold.*




FIGURE 2-21: *Fast Turn-On.*




FIGURE 2-24: *Current Limit.*

chanhvinh.com




FIGURE 2-25: *Thermal Shutdown Response.*




FIGURE 2-28: *Inrush Current Response.*




FIGURE 2-26: *V_{OUT} Recovery from Thermal Shutdown.*




FIGURE 2-29: *Load Transient Response.*




FIGURE 2-27: *Turn-On into Short Circuit.*




FIGURE 2-30: *Line Transient Response.*

© 2023 Microchip Technology Inc.

chanhvinh.com

3.0 PIN DESCRIPTIONS

The descriptions of the pins are listed in Table 3-1.

TABLE 3-1: PIN FUNCTION TABLE

Pin Number (Fixed)	Pin Number (Adj.)	Pin Name	Description
1	1	VIN	Supply Voltage Input. Connect 1µF capacitor from VIN to GND.
2, 3, 7	2, 3, 7	NC	Not internally connected. Connect NC to GND or leave unconnected.
4	4	CPSRR	Bypass Capacitor Connection. Connect 0.1µF capacitor from CPSRR to GND.
5	5	GND	Ground.
	6	FB	Feedback Connection. For external resistor divider to set V_{OUT}.
6		SNS	Sense input. Connect SNS to VOUT.
8	8	VOUT	Regulator Output. Connect 10µF capacitor from VOUT to GND.
EP	EP	EP	Exposed Pad (ePad) for Thermal Dissipation. Connect EP to GND.

chanhvinh.com

chanhvinh.com

4.0 APPLICATION INFORMATION

The MIC5283 voltage regulator accepts a 6V to 120V input voltage and has an ultra-low 8 µA typical quiescent current while offering an excellent line transient response and PSRR. These features make it ideal for harsh, noisy environments. All options offer 150 mA of output current.

The MIC5283YML and MIC5283YME options offer adjustable output voltage from 1.22V to 5.5V. The MIC5283-3.3YML and MIC5283-3.3YME offer fixed 3.3V outputs and the MIC5283-5.0YML and MIC5283-5.0YME offer fixed 5.0V outputs. The YME packaged devices feature a heat slug to more effectively remove heat from the die.

4.1 Thermal Protection

The MIC5283 has internal thermal shutdown to protect it from excessive heating of the die. When the junction temperature exceeds approximately +155°C, the output is disabled and the device begins to cool down. The device turns back on when the junction temperature cools by 15°C. This will result in a cycled output during continuous thermal-overload conditions.

4.2 Current Limit

The MIC5283 features output current-limit protection. The output sustains a continuous short circuit to GND without damage to the device, but thermal shutdown often results. The typical value for the current limit of the MIC5283 is 300 mA.

4.3 Input Capacitor

Connect a 1.0 µF capacitor from VIN to GND. Microchip recommends the C5750X7R2E105M, 1.0 µF, 250V capacitor made by TDK. When using a different capacitor, assure that the voltage rating of the capacitor has adequate headroom to withstand any potential transient.

4.4 CPSRR Capacitor

To maintain high power supply rejection, connect a 0.1 µF capacitor from CPSRR to GND. The voltage rating of the capacitor must be at least 14V.

4.5 Output Capacitor

Connect a 10 µF capacitor from VOUT to GND. Assure that the voltage rating of the capacitor exceeds the designed output voltage of the MIC5283.

4.6 Output Voltage Setting

For the MIC5283YML and MIC5283YME, VOUT is programmable from 1.22V to 5.5V using an external resistive divider. VOUT is set using the following equation:

EQUATION 4-1:

$$V_{OUT} = V_{REF} \times \left(\frac{R1}{R2} + 1\right)$$

where V_{REF} = 1.22V, and R1 and R2 form the feedback voltage divider from VOUT to GND.




FIGURE 4-1: *Output Voltage Setting for the MIC5283YME.*

4.7 Thermal Measurements

It is always prudent to measure an IC's case temperature to make sure that it is within operating limits, but it is easy to get erroneous results. The standard thermocouple that comes with many voltage meters uses a large wire gauge that behaves like a heat-sink, resulting in artificially low case temperature measurements.

Use a thermocouple of 36-gauge wire or smaller, such as the Omega (5SC-TT-K-36-36), to minimize the heat-sinking effect. Also, apply a thermal compound to maximize heat transfer between the IC and the thermocouple.

One recommended alternative to consider is an infrared thermometer. The IR thermometer from Optris has a 1 mm spot size, ideal for monitoring small surface mount packages. Also, the optional stand makes it easy to keep the beam on the IC for long periods of time.


© 2023 Microchip Technology Inc.

chanhvinh.com


5.0 PACKAGING INFORMATION

5.1 Package Marking Information


8-Lead SOIC (Fixed)




Example




8-Lead SOIC (Adj.)




Example



8-Lead VDFN (All)



Example



ORDERING INFORMATION

Part Number	Output Voltage	Top Mark	Temperature Range	Package	Lead Finish
MIC5283YME	Adjustable	5283YME	–40°C to +125°C	8-Lead ePad SOIC	Pb-Free
MIC5283-3.3YME	3.3V	5283-33YME	–40°C to +125°C	8-Lead ePad SOIC	Pb-Free
MIC5283-5.0YME	5.0V	5283-50YME	–40°C to +125°C	8-Lead ePad SOIC	Pb-Free
MIC5283YML	Adjustable	A83	–40°C to +125°C	8-Lead 3 mm × 3 mm VDFN	Pb-Free
MIC5283-3.3YML	3.3V	8S3	–40°C to +125°C	8-Lead 3 mm × 3 mm VDFN	Pb-Free
MIC5283-5.0YML	5.0V	583	–40°C to +125°C	8-Lead 3 mm × 3 mm VDFN	Pb-Free

Legend:

XX...X	Product code or customer-specific information
Y	Year code (last digit of calendar year)
YY	Year code (last 2 digits of calendar year)
WW	Week code (week of January 1 is week ‘01’)
NNN	Alphanumeric traceability code
(e3)	Pb-free JEDEC® designator for Matte Tin (Sn)
*	This package is Pb-free. The Pb-free JEDEC designator (e3) can be found on the outer packaging for this package.
●, ▲, ▼	Pin one index is identified by a dot, delta up, or delta down (triangle mark).

Note: In the event the full Microchip part number cannot be marked on one line, it will be carried over to the next line, thus limiting the number of available characters for customer-specific information. Package may or may not include the corporate logo.


Underbar (_) and/or Overbar (¯) symbol may not be to scale.

Note: If the full seven-character YYWWNNN code cannot fit on the package, the following truncated codes are used based on the available marking space: 6 Characters = YWWNNN; 5 Characters = WWNNN; 4 Characters = WNNN; 3 Characters = NNN; 2 Characters = NN; 1 Character = N.

chanhvinh.com

8-Lead 3 mm × 3 mm × 0.9 mm VDFN Package Outline and Recommended Land Pattern

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging




Microchip Technology Drawing C04-1021 A Sheet 1 of 2

© 2023 Microchip Technology Inc.

chanhvinh.com

8-Lead 3 mm × 3 mm × 0.9 mm VDFN Package Outline and Recommended Land Pattern

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N		8	
Pitch	e		0.65 BSC	
Overall Height	A	0.80	0.85	0.90
Standoff	A1	0.00	0.02	0.05
Terminal Thickness	A3		0.203 REF	
Overall Length	D		3.00 BSC	
Exposed Pad Length	D2	2.25	2.30	2.35
Overall Width	E		3.00 BSC	
Exposed Pad Width	E2	1.50	1.55	1.60
Terminal Width	b	0.20	0.25	0.30
Terminal Length	L	0.35	0.40	0.45
Terminal-to-Exposed-Pad	K	0.20	-	-

Notes:

1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. Package is saw singulated
3. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. Theoretically exact value shown without tolerances.
   REF: Reference Dimension, usually without tolerance, for information purposes only.


Microchip Technology Drawing C04-1021 A Sheet 1 of 2

© 2023 Microchip Technology Inc.

chanhvinh.com

8-Lead 3 mm × 3 mm × 0.9 mm VDFN Package Outline and Recommended Land Pattern

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E		0.65 BSC	
Optional Center Pad Width	X2			2.35
Optional Center Pad Length	Y2			1.60
Contact Pad Spacing	C		2.90	
Contact Pad Width (X8)	X1			0.30
Contact Pad Length (X8)	Y1			0.85
Contact Pad to Center Pad (X8)	G1	0.23		
Contact Pad to Contact Pad (X6)	G2	0.35		
Thermal Via Diameter	V		0.30	
Thermal Via Pitch	EV		1.00	

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. Theoretically exact value shown without tolerances.
2. For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process


Microchip Technology Drawing C04-3021 Rev A

© 2023 Microchip Technology Inc.

chanhvinh.com

8-Lead 3.9 mm SOIC with 3.1 mm × 2.41 mm ePad Package Outline and Recommended Land Pattern

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging




Microchip Technology Drawing C04-1136 Rev B Sheet 1 of 2

chanhvinh.com

8-Lead 3.9 mm SOIC with 3.1 mm × 2.41 mm ePad Package Outline and Recommended Land Pattern

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N		8	
Pitch	e		1.27 BSC	
Overall Height	A	1.43	1.55	1.68
Standoff	A1	0.00	0.05	0.10
Molded Package Thickness	A2	1.25	-	-
Overall Length	D		4.89 BSC	
Exposed Pad Length	D1	-	3.10	-
Overall Width	E		6.02 BSC	
Molded Package Width	E1		3.90 BSC	
Exposed Pad Width	E2	-	2.41	-
Terminal Width	b	0.35	0.41	0.49
Lead Thickness	c	0.19	0.20	0.25
Terminal Length	L	0.41	0.64	0.89
Footprint	L1		1.04 REF	
Foot Angle	Θ	0°	5°	8°
Lead Bend Radius	R1	0.07	-	-
Lead Bend Radius	R2	0.07	-	-
Mold Draft Angle	α	5°	-	15°
Mold Draft Angle	β	5°	-	15°

Notes:

1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. Package is saw singulated
3. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. Theoretically exact value shown without tolerances.
   REF: Reference Dimension, usually without tolerance, for information purposes only.


Microchip Technology Drawing C04-1136 Rev B Sheet 2 of 2

© 2023 Microchip Technology Inc.

chanhvinh.com

8-Lead 3.9 mm SOIC with 3.1 mm × 2.41 mm ePad Package Outline and Recommended Land Pattern

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E		1.27 BSC	
Optional Center Pad Width	X2			3.15
Optional Center Pad Length	Y2			2.45
Contact Pad Spacing	C		5.40	
Contact Pad Width (X8)	X1			0.60
Contact Pad Length (X8)	Y1			1.60
Contact Pad to Center Pad (X8)	G1	0.68		
Contact Pad to Contact Pad (X6)	G2	0.67		
Thermal Via Diameter	V		0.30	
Thermal Via Pitch	EV		1.00	

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. Theoretically exact value shown without tolerances.
2. For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-1136 Rev B

chanhvinh.com

NOTES:

chanhvinh.com

© 2023 Microchip Technology Inc.

chanhvinh.com

APPENDIX A: REVISION HISTORY

Revision A (May 2023)

- Converted Micrel document MIC5283 to Microchip data sheet DS20006761A.
- Minor text changes throughout.

chanhvinh.com

chanhvinh.com

NOTES:

chanhvinh.com

© 2023 Microchip Technology Inc.

chanhvinh.com

PRODUCT IDENTIFICATION SYSTEM

To order or obtain information, e.g., on pricing or delivery, contact your local Microchip representative or sales office.

PART No.	-X.XX	X	XX	-XX
Device	Output Voltage	Junction Temp. Range	Package	Media Type

Device:	MIC5283:	500 mA-Peak Output LDO Regulator
Output Voltage:	<blank>=	Adjustable Voltage
	-3.3 =	3.3V
	-5.0 =	5.0V
Junction Temperature Range:	Y =	–40°C to +125°C
Package:	ML =	8-Lead VDFN
	ME =	8-Lead ePad SOIC
Media Type:	<blank>=	95/Tube (SOIC option only)
	-TR =	2500/Reel (SOIC option only)
	-TR =	5000/Reel (VDFN option only)
	-T5 =	500/Reel

Note 1: Tape and Reel identifier only appears in the catalog part number description. This identifier is used for ordering purposes and is not printed on the device package. Check with your Microchip Sales Office for package availability with the Tape and Reel option.

Examples:

a) MIC5283YME: MIC5283, Adjustable Output Voltage, –40°C to +125°C Temp. Range, 8-Lead ePad SOIC, 95/Tube

b) MIC5283-3.3YME: MIC5283, 3.3V Output Voltage, –40°C to +125°C Temp. Range, 8-Lead ePad SOIC, 95/Tube

c) MIC5283-5.0YME-TR: MIC5283, 5.0V Output Voltage, –40°C to +125°C Temp. Range, 8-Lead ePad SOIC, 2500/Reel

b) MIC5283YML: MIC5283, Adjustable Output Voltage, –40°C to +125°C Temp. Range, 8-Lead VDFN, 95/Tube

c) MIC5283-3.3YML-TR: MIC5283, 3.3V Output Voltage, –40°C to +125°C Temp. Range, 8-Lead VDFN, 5000/Reel

b) MIC5283-5.0YML-T5: MIC5283, 5.0V Output Voltage, –40°C to +125°C Temp. Range, 8-Lead VDFN, 500/Reel

© 2023 Microchip Technology Inc.

chanhvinh.com

NOTES:

chanhvinh.com

© 2023 Microchip Technology Inc.

chanhvinh.com

Note the following details of the code protection feature on Microchip products:

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is secure when used in the intended manner, within operating specifications, and under normal conditions.
- Microchip values and aggressively protects its intellectual property rights. Attempts to breach the code protection features of Microchip product is strictly prohibited and may violate the Digital Millennium Copyright Act.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not mean that we are guaranteeing the product is "unbreakable" Code protection is constantly evolving. Microchip is committed to continuously improving the code protection features of our products.

This publication and the information herein may be used only with Microchip products, including to design, test, and integrate Microchip products with your application. Use of this information in any other manner violates these terms. Information regarding device applications is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. Contact your local Microchip sales office for additional support or, obtain additional support at https://www.microchip.com/en-us/support/design-help/client-support-services.

THIS INFORMATION IS PROVIDED BY MICROCHIP "AS IS". MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP'S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION.

Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

For information regarding Microchip's Quality Management Systems, please visit www.microchip.com/quality.

Trademarks

The Microchip name and logo, the Microchip logo, Adaptec, AVR, AVR logo, AVR Freaks, BesTime, BitCloud, CryptoMemory, CryptoRF, dsPIC, flexPWR, HELDO, IGLOO, JukeBlox, KeeLoq, Kleer, LANCheck, LinkMD, maXStylus, maXTouch, MediaLB, megaAVR, Microsemi, Microsemi logo, MOST, MOST logo, MPLAB, OptoLyzer, PIC, picoPower, PICSTART, PIC32 logo, PolarFire, Prochip Designer, QTouch, SAM-BA, SenGenuity, SpyNIC, SST, SST Logo, SuperFlash, Symmetricom, SyncServer, Tachyon, TimeSource, tinyAVR, UNI/O, Vectron, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

AgileSwitch, APT, ClockWorks, The Embedded Control Solutions Company, EtherSynch, Flashtec, Hyper Speed Control, HyperLight Load, Libero, motorBench, mTouch, Powermite 3, Precision Edge, ProASIC, ProASIC Plus, ProASIC Plus logo, Quiet- Wire, SmartFusion, SyncWorld, Temux, TimeCesium, TimeHub, TimePictra, TimeProvider, TrueTime, and ZL are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, Augmented Switching, BlueSky, BodyCom, Clockstudio, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, Espresso T1S, EtherGREEN, GridTime, IdealBridge, In-Circuit Serial Programming, ICSP, INICnet, Intelligent Paralleling, IntelliMOS, Inter-Chip Connectivity, JitterBlocker, Knob-on-Display, KoD, maxCrypto, maxView, memBrain, Mindi, MiWi, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, Omniscient Code Generation, PICDEM, PICDEM.net, PICkit, PICtail, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, RTAX, RTG4, SAM-ICE, Serial Quad I/O, simpleMAP, SimpliPHY, SmartBuffer, SmartHLS, SMART-I.S., storClad, SQI, SuperSwitcher, SuperSwitcher II, Switchtec, SynchroPHY, Total Endurance, Trusted Time, TSHARC, USBCheck, VariSense, VectorBlox, VeriPHY, ViewSpan, WiperLock, XpressConnect, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

The Adaptec logo, Frequency on Demand, Silicon Storage Technology, and Symmcom are registered trademarks of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2023, Microchip Technology Incorporated and its subsidiaries.

All Rights Reserved.

ISBN: 978-1-6683-2446-2

chanhvinh.com

Worldwide Sales and Service

AMERICAS

Corporate Office
2355 West Chandler Blvd.
Chandler, AZ 85224-6199
Tel: 480-792-7200
Fax: 480-792-7277
Technical Support:
http://www.microchip.com/support
Web Address:
www.microchip.com

Atlanta
Duluth, GA
Tel: 678-957-9614
Fax: 678-957-1455

Austin, TX
Tel: 512-257-3370

Boston
Westborough, MA
Tel: 774-760-0087
Fax: 774-760-0088

Chicago
Itasca, IL
Tel: 630-285-0071
Fax: 630-285-0075

Dallas
Addison, TX
Tel: 972-818-7423
Fax: 972-818-2924

Detroit
Novi, MI
Tel: 248-848-4000

Houston, TX
Tel: 281-894-5983

Indianapolis
Noblesville, IN
Tel: 317-773-8323
Fax: 317-773-5453
Tel: 317-536-2380

Los Angeles
Mission Viejo, CA
Tel: 949-462-9523
Fax: 949-462-9608
Tel: 951-273-7800

Raleigh, NC
Tel: 919-844-7510

New York, NY
Tel: 631-435-6000

San Jose, CA
Tel: 408-735-9110
Tel: 408-436-4270

Canada - Toronto
Tel: 905-695-1980
Fax: 905-695-2078

ASIA/PACIFIC

Australia - Sydney
Tel: 61-2-9868-6733

China - Beijing
Tel: 86-10-8569-7000

China - Chengdu
Tel: 86-28-8665-5511

China - Chongqing
Tel: 86-23-8980-9588

China - Dongguan
Tel: 86-769-8702-9880

China - Guangzhou
Tel: 86-20-8755-8029

China - Hangzhou
Tel: 86-571-8792-8115

China - Hong Kong SAR
Tel: 852-2943-5100

China - Nanjing
Tel: 86-25-8473-2460

China - Qingdao
Tel: 86-532-8502-7355

China - Shanghai
Tel: 86-21-3326-8000

China - Shenyang
Tel: 86-24-2334-2829

China - Shenzhen
Tel: 86-755-8864-2200

China - Suzhou
Tel: 86-186-6233-1526

China - Wuhan
Tel: 86-27-5980-5300

China - Xian
Tel: 86-29-8833-7252

China - Xiamen
Tel: 86-592-2388138

China - Zhuhai
Tel: 86-756-3210040

ASIA/PACIFIC

India - Bangalore
Tel: 91-80-3090-4444

India - New Delhi
Tel: 91-11-4160-8631

India - Pune
Tel: 91-20-4121-0141

Japan - Osaka
Tel: 81-6-6152-7160

Japan - Tokyo
Tel: 81-3-6880- 3770

Korea - Daegu
Tel: 82-53-744-4301

Korea - Seoul
Tel: 82-2-554-7200

Malaysia - Kuala Lumpur
Tel: 60-3-7651-7906

Malaysia - Penang
Tel: 60-4-227-8870

Philippines - Manila
Tel: 63-2-634-9065

Singapore
Tel: 65-6334-8870

Taiwan - Hsin Chu
Tel: 886-3-577-8366

Taiwan - Kaohsiung
Tel: 886-7-213-7830

Taiwan - Taipei
Tel: 886-2-2508-8600

Thailand - Bangkok
Tel: 66-2-694-1351

Vietnam - Ho Chi Minh
Tel: 84-28-5448-2100

EUROPE

Austria - Wels
Tel: 43-7242-2244-39
Fax: 43-7242-2244-393

Denmark - Copenhagen
Tel: 45-4485-5910
Fax: 45-4485-2829

Finland - Espoo
Tel: 358-9-4520-820

France - Paris
Tel: 33-1-69-53-63-20
Fax: 33-1-69-30-90-79

Germany - Garching
Tel: 49-8931-9700

Germany - Haan
Tel: 49-2129-3766400

Germany - Heilbronn
Tel: 49-7131-72400

Germany - Karlsruhe
Tel: 49-721-625370

Germany - Munich
Tel: 49-89-627-144-0
Fax: 49-89-627-144-44

Germany - Rosenheim
Tel: 49-8031-354-560

Israel - Ra'anana
Tel: 972-9-744-7705

Italy - Milan
Tel: 39-0331-742611
Fax: 39-0331-466781

Italy - Padova
Tel: 39-049-7625286

Netherlands - Drunen
Tel: 31-416-690399
Fax: 31-416-690340

Norway - Trondheim
Tel: 47-7288-4388

Poland - Warsaw
Tel: 48-22-3325737

Romania - Bucharest
Tel: 40-21-407-87-50

Spain - Madrid
Tel: 34-91-708-08-90
Fax: 34-91-708-08-91

Sweden - Gothenberg
Tel: 46-31-704-60-40

Sweden - Stockholm
Tel: 46-8-5090-4654

UK - Wokingham
Tel: 44-118-921-5800
Fax: 44-118-921-5820

© 2023 Microchip Technology Inc. and its subsidiaries.