chanhvinh.com

molex

Part Number : 2196761121
Product Description : Pre-Crimped Lead Mini-SPOX Female-to-Mini-SPOX Female, Tin (Sn) Plating,  75.00mm Length, 22 AWG, Black
Series Number : 219676
Status : Active
Product Category : Power and Signal Cable Assemblies



## Documents & Resources

### Drawings
2196761121_sd.pdf

## Product Environment Compliance

### Compliance

| | |
|---|---|
| GADSL/IMDS | Not Relevant |
| China RoHS | |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2024)4144-DC (27 June 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements
- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

# Part Details

## General

| | |
|---|---|
| Status | Active |
| Category | Power and Signal Cable Assemblies |
| Series | 219676 |
| Description | Pre-Crimped Lead Mini-SPOX Female-to-Mini-SPOX Female, Tin (Sn) Plating, 75.00mm Length, 22 AWG, Black |
| Application | Signal, Wire-to-Board |
| Assembly Configuration | Pre-crimped Lead Only |
| Connector to Connector | Mini-SPOX Crimp Terminals |
| Product Family | Off-the-Shelf Pre-Crimped Leads |
| Product Name | Mini-SPOX |
| UPC | 195842853140 |

## Electrical

| | |
|---|---|
| Current - Maximum per Contact | 3.0A |
| Voltage - Maximum | 250V AC (RMS)/DC |

## Physical

| | |
|---|---|
| Cable Length | 75.00mm |
| Circuits (Loaded) | 1 |
| Circuits (maximum) | 1 |
| Color - Resin | Black |
| Gender | Female-Female |
| Material - Metal | Phosphor Bronze |
| Material - Plating Mating | Tin |
| Material - Plating Termination | Tin |
| Material - Resin | PVC |
| Net Weight | 0.555/g |
| Number of Rows | 1 |
| Packaging Type | Bag |
| Plating min - Mating | 0.889µm |
| Plating min - Termination | 0.914µm |

chanhvinh.com

| | |
|---|---|
| Single Ended | No |
| Termination Interface Style | Crimp or Compression |
| Wire/Cable Type | UL 1569 |
| Wire Insulation Diameter | 1.90mm  max. |
| Wire Size (AWG) | 22 |

## Use with Part(s)

| Description | Part Number |
|---|---|
| Mini-SPOX Single Row Receptacle Housings | 5264 |

This document was generated on Oct 17, 2024