
chanhvinh.com



BC856BS

65 V, 100 mA PNP/PNP general-purpose transistor

Rev. 01 — 11 August 2009 Product data sheet

1. Product profile

1.1 General description

PNP/PNP general-purpose transistor pair in a very small Surface-Mounted Device (SMD) plastic package.

Table 1. Product overview

Type number	Package		NPN/NPN complement	NPN/PNP complement
	NXP	JEITA		
BC856BS	SOT363	SC-88	BC846BS	BC846BPN

1.2 Features

- Low collector capacitance
- Low collector-emitter saturation voltage
- Closely matched current gain
- Reduces number of components and board space
- No mutual interference between the transistors
- AEC-Q101 qualified

1.3 Applications

- General-purpose switching and amplification

1.4 Quick reference data

Table 2. Quick reference data

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Per transistor						
V_{CEO}	collector-emitter voltage	open base	-	-	–65	V
I_C	collector current		-	-	–100	mA
h_{FE}	DC current gain	V_{CE} = –5 V; I_C = –2 mA	200	290	450	



chanhvinh.com

NXP founded by Philips

chanhvinh.com

2. Pinning information

Table 3. Pinning

Pin	Description	Simplified outline	Graphic symbol
1	emitter TR1		
2	base TR1		
3	collector TR2		
4	emitter TR2		
5	base TR2		
6	collector TR1		

sym018

3. Ordering information

Table 4. Ordering information

Type number	Package		
	Name	Description	Version
BC856BS	SC-88	plastic surface-mounted package; 6 leads	SOT363

4. Marking

Table 5. Marking codes

Type number	Marking code[1]
BC856BS	*E6

[1] * = -: made in Hong Kong
* = p: made in Hong Kong
* = t: made in Malaysia
* = W: made in China

© NXP B.V. 2009. All rights reserved.

chanhvinh.com


5. Limiting values

Table 6. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions		Min	Max	Unit
Per transistor						
V_{CBO}	collector-base voltage	open emitter		-	–80	V
V_{CEO}	collector-emitter voltage	open base		-	–65	V
V_{EBO}	emitter-base voltage	open collector		-	–6	V
I_C	collector current			-	–100	mA
I_{CM}	peak collector current	single pulse; $t_p \leq 1$ ms		-	–200	mA
I_{BM}	peak base current	single pulse; $t_p \leq 1$ ms		-	–200	mA
P_{tot}	total power dissipation	$T_{amb} \leq 25$ °C	[1]	-	200	mW
Per device						
P_{tot}	total power dissipation	$T_{amb} \leq 25$ °C	[1]	-	300	mW
T_j	junction temperature			-	150	°C
T_{amb}	ambient temperature			–55	+150	°C
T_{stg}	storage temperature			–65	+150	°C

[1] Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper, tin-plated and standard footprint.



FR4 PCB, standard footprint

Fig 1. Per device: Power derating curve SOT363 (SC-88)

© NXP B.V. 2009. All rights reserved.


chanhvinh.com

6. Thermal characteristics

Table 7. Thermal characteristics

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
Per transistor							
$R_{th(j-a)}$	thermal resistance from junction to ambient	in free air	[1]	-	-	625	K/W
$R_{th(j-sp)}$	thermal resistance from junction to solder point			-	-	230	K/W
Per device							
$R_{th(j-a)}$	thermal resistance from junction to ambient	in free air	[1]	-	-	416	K/W

[1] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.



FR4 PCB, standard footprint

Fig 2. Per transistor: Transient thermal impedance from junction to ambient as a function of pulse duration; typical values

© NXP B.V. 2009. All rights reserved.

chanhvinh.com

7. Characteristics


Table 8. Characteristics

T_{amb} = 25 °C unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Per transistor						
I_{CBO}	collector-base cut-off current	V_{CB} = –50 V; I_E = 0 A	-	-	–15	nA
		V_{CB} = –30 V; I_E = 0 A; T_j = 150 °C	-	-	–5	µA
I_{EBO}	emitter-base cut-off current	V_{EB} = –6 V; I_C = 0 A	-	-	–100	nA
h_{FE}	DC current gain	V_{CE} = –5 V				
		I_C = –10 µA	-	270	-	
		I_C = –2 mA	200	290	450	
V_{CEsat}	collector-emitter saturation voltage	I_C = –10 mA; I_B = –0.5 mA	-	–55	–100	mV
		I_C = –100 mA; I_B = –5 mA	-	–200	–300	mV
V_{BEsat}	base-emitter saturation voltage	I_C = –10 mA; I_B = –0.5 mA	-	–755	–850	mV
		I_C = –100 mA; I_B = –5 mA	-	–900	-	mV
V_{BE}	base-emitter voltage	V_{CE} = –5 V				
		I_C = –2 mA	–600	–650	–750	mV
		I_C = –10 mA	-	-	–820	mV
C_c	collector capacitance	V_{CB} = –10 V; I_E = i_e = 0 A; f = 1 MHz	-	2.3	-	pF
C_e	emitter capacitance	V_{EB} = –0.5 V; I_C = i_c = 0 A; f = 1 MHz	-	10	-	pF
f_T	transition frequency	V_{CE} = –5 V; I_C = –10 mA; f = 100 MHz	100	-	-	MHz
NF	noise figure	V_{CE} = –5 V; I_C = –0.2 mA; R_S = 2 kΩ; f = 10 Hz to 15.7 kHz	-	1.6	-	dB
		V_{CE} = –5 V; I_C = –0.2 mA; R_S = 2 kΩ; f = 1 kHz; B = 200 Hz	-	2.9	-	dB

© NXP B.V. 2009. All rights reserved.

chanhvinh.com




V_{CE} = −5 V

(1) T_{amb} = 100 °C

(2) T_{amb} = 25 °C


(3) T_{amb} = −55 °C

Fig 3. Per transistor: DC current gain as a function of collector current; typical values




T_{amb} = 25 °C

Fig 4. Per transistor: Collector current as a function of collector-emitter voltage; typical values



V_{CE} = −5 V; T_{amb} = 25 °C

Fig 5. Per transistor: Base-emitter voltage as a function of collector current; typical values



I_C/I_B = 20

(1) T_{amb} = −55 °C


(2) T_{amb} = 25 °C

(3) T_{amb} = 100 °C

Fig 6. Per transistor: Base-emitter saturation voltage as a function of collector current; typical values

© NXP B.V. 2009. All rights reserved.

chanhvinh.com




I_C/I_B = 20

(1) T_{amb} = 100 °C

(2) T_{amb} = 25 °C


(3) T_{amb} = −55 °C

Fig 7. Per transistor: Collector-emitter saturation voltage as a function of collector current; typical values




V_{CE} = −5 V; T_{amb} = 25 °C

Fig 8. Per transistor: Transition frequency as a function of collector current; typical values



f = 1 MHz; T_{amb} = 25 °C

Fig 9. Per transistor: Collector capacitance as a function of collector-base voltage; typical values



f = 1 MHz; T_{amb} = 25 °C

Fig 10. Per transistor: Emitter capacitance as a function of emitter-base voltage; typical values

© NXP B.V. 2009. All rights reserved.

chanhvinh.com

8. Test information

8.1 Quality information

This product has been qualified in accordance with the Automotive Electronics Council (AEC) standard *Q101 - Stress test qualification for discrete semiconductors*, and is suitable for use in automotive applications.

9. Package outline




Fig 11. Package outline SOT363 (SC-88)

10. Packing information

Table 9. Packing methods

The indicated -xxx are the last three digits of the 12NC ordering code.[1]

Type number	Package	Description		Packing quantity	
				3000	10000
BC856BS	SOT363	4 mm pitch, 8 mm tape and reel; T1	[2]	-115	-135
		4 mm pitch, 8 mm tape and reel; T2	[3]	-125	-165

[1] For further information and the availability of packing methods, see Section 14.

[2] T1: normal taping

[3] T2: reverse taping

© NXP B.V. 2009. All rights reserved.

chanhvinh.com

11. Soldering




Fig 12. Reflow soldering footprint SOT363 (SC-88)




Fig 13. Wave soldering footprint SOT363 (SC-88)

© NXP B.V. 2009. All rights reserved.

chanhvinh.com

12. Revision history

Table 10. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
BC856BS_1	20090811	Product data sheet	-	-

chanhvinh.com

© NXP B.V. 2009. All rights reserved.

chanhvinh.com

13. Legal information

13.1 Data sheet status

Document status[1][2]	Product status[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL http://www.nxp.com.

13.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

13.3 Disclaimers

General — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

Terms and conditions of sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at http://www.nxp.com/profile/terms, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by NXP Semiconductors. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

Quick reference data — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

13.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

14. Contact information

For more information, please visit: **http://www.nxp.com**

For sales office addresses, please send an email to: **salesaddresses@nxp.com**

© NXP B.V. 2009. All rights reserved.

chanhvinh.com

15. Contents

1 Product profile 1
1.1 General description 1
1.2 Features 1
1.3 Applications 1
1.4 Quick reference data 1
2 Pinning information 2
3 Ordering information 2
4 Marking 2
5 Limiting values 3
6 Thermal characteristics 4
7 Characteristics 5
8 Test information 8
8.1 Quality information 8
9 Package outline 8
10 Packing information 8
11 Soldering 9
12 Revision history 10
13 Legal information 11
13.1 Data sheet status 11
13.2 Definitions 11
13.3 Disclaimers 11
13.4 Trademarks 11
14 Contact information 11
15 Contents 12

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

© NXP B.V. 2009. All rights reserved.

For more information, please visit: http://www.nxp.com
For sales office addresses, please send an email to: salesaddresses@nxp.com

Date of release: 11 August 2009
Document identifier: BC856BS_1

founded by
PHILIPS