chanhvinh.com

858-878Mhz 8dBi Fiberglass Antenna
OKdo SKU:

Product Details

This outdoor rated fiberglass antenna will help achieve optimal transmission and reception when attached to IoT equipment. The slim pole design can easily be attached to multiple surfaces using the clamp set included in the kit that fits around the grooves in the metal end of the aerial.
Typically used at the gateway side of a network link, this range of OKdo antennas could also be used with remote devices if dimensions are suitable.



Features and Benefits

The outdoor antenna is manufactured from robust fiberglass which is naturally resistant to corrosion and weather deterioration with minimal degradation on the transmitted or received signal.

Kit Contents

Fiberglass antenna, grey colour, N Male connector	X 1
Fitting kit	X 1
Cables	Sold separately


Technical Specifications

Electrical Specifications	
Frequency Rang	858-878MHz
Polarization	Vertical
Gain	8 ± 1d Bi
Horizontal Beam width	360°
Vertical Beam width	18°
VSWR	≤1.8
Nominal Impedance	50Ω
Maximum Power	50W
Mechanical Specifications	
Connector	N-J
Max. Wind Velocity	210km/h
Mounting Mast size	Φ30-50mm
Dimensions	Φ20x1300mm
Weight	1.5KG
Operating Temperature	-40～+60℃

chanhvinh.com

Internal

Gain



Installation guide

This example shows how to attach the antenna to a pole



The antenna passes through the clip and is fixed on the holding pole with U-shaped clamp.

Technical Drawings

