
chanhvinh.com

OMRON

Emergency Stop Pushbutton Switches

A22NE-PD/A22NE-P/A22E Series



Basic:
Screw Terminal Block Types
A22E Series

Vibration-resistant:
Push-In Plus Terminal Block Types
A22NE-P Series

NEW
Push-In Plus Terminal Block +
Lock-lever-linked Contact Types
A22NE-PD Series

chanhvinh.com

Machines Are Designed to Stop Without Fail.

An emergency stop pushbutton switch stops machine equipment in an emergency to protect the safety of workers. However, if the switch does not function properly due to human error, malfunction, defective wiring or other reasons, it will lead to a major accident. That is why Omron has focused on stopping machines without fail and produced a lineup of emergency stop switches with enhanced functionality.



chanhvinh.com

» Three Functions to Enhance Reliability




Stops machines when a Switch is improperly mounted.

- Cuts off the current when the lock lever is off.
- Instantly detects work errors and lever damage.

Lock-lever-linked Contacts

Refer to page 4 for details.



Reduces loose and detached wiring.

- Wires are resistant to vibration and do not come off easily.
- Reduces work for wiring and maintenance.

Push-In Plus Terminal Block

Refer to page 5 for details.



Stable operation in harsh environments.

- Usable up to 80°C and pressures of 80 to 100 BAR.
- Spray-resistant on the front and sides.

Optional IP69K

Refer to page 5 for details.

A Lineup That Allows You to Choose According to Your Needs

Fully-loaded with Three Functions	Easy and Reliable Push-In Plus Terminal Block	Basic Screw Terminal Block
A22NE-PD Series Page 7	**A22NE-P** Series Page 21	**A22E** Series Page 37
		


chanhvinh.com

Accident Prevention/Stable Operation

Suppress Malfunctions Throughly with Functions for Various Applications.

Lock-lever-linked Contacts


A22NE-PD Series



Detects Improper Installations for Zero Malfunction Problems During Emergencies

If the sliding operation of the lock lever is insufficient, the operation unit may not function properly when needed, even if pushed. With the lock-lever-linked contact function, if the sliding operation of the lock lever is insufficient, the original NC contact will turn to a NO state when the operation unit is not pushed, making it possible to detect errors from the state of the contact.

Lock lever OFF



The contact* opens and the current is cutoff.

Machine equipment stops.

Lock lever ON




The contact* closes and the current flows.

Machine equipment operates.

* The example shows an NC contact. However, all contacts are interlocked with the lock lever, and the statuses of NO contacts are also switched.

For machine equipment that can cause major accidents


Ensures additional safety for machine equipment that cannot afford a slight delay.



chanhvinh.com

Push-In Plus Terminal Block

A22NE-PD/A22NE-P Series



Prevents Loose and Detached Wiring Caused by Vibration During Operation

In addition to preventing unexpected stoppages caused by disconnection, it is also possible to reduce maintenance efforts.

Also help reduce the wiring work



Just insert wires like you would into an earphone jack. No tools are required. They help reduce the time and work involved in wiring.



IEC standard (Cable diameter)	Push-In Plus Terminal Block	Screw Terminal Block
20 N min (AWG20, 0.5 mm²)	125 N	112 N

* Information for Push-In Plus Terminal Blocks and screw terminal blocks is based on OMRON's actual measurement value data for the XW2R.

Optional IP69K

A22NE-PD/A22NE-P Series

High-level Sealing that Is Resistant to Harsh Environments

Conventional OMRON emergency stop pushbutton switches were made to IP65 standards, but the unique technology used for our rubber-designed covers achieves IP69K specifications that can withstand high-temperature and high-pressure sprays from any direction.



For sites that demand high-level sanitation control

Withstands high-temperature and high-pressure sprays without the need for an additional waterproof cover, allowing for worry-free installation in sites where cleaning with high-pressure washing machines is performed.



chanhvinh.com

Emergency Stop Pushbutton Switches (22-dia. or 25-dia.)
A22NE-PD/A22NE-P/A22E

Install in 22-dia. or 25-dia. Panel Cutout (When Using a Ring)

- Direct opening mechanism to open the circuit when the contact welds.
- With a latching mechanism to prevent operating errors.
- Lock lever for easily mounting and removing the Unit.
- Use 25-dia. ring to install in 25-dia. panel cutouts. ✻
- In a model equipped with Lock-lever-linked contact function, the improper installation of the Switch Unit can be detected. (A22NE-PD)

✻ Switches with an IP69K degree of protection do not support the 25-dia.

⚠ Be sure to read the "*Safety Precautions*" on pages 18, 33, 50, and 56.

Push-in Plus Terminal Block Types

With Lock-lever-linked contact function
A22NE-PD Page 7




Without Lock-lever-linked contact function
A22NE-P Page 21



Screw Terminal Block Types

Without Lock-lever-linked contact function
A22E Page 37



chanhvinh.com

Emergency Stop Pushbutton Switches (22-dia. or 25-dia.) Push-in Plus Terminal Block Models With Lock-lever-linked Contact Function

A22NE-PD

Install in 22-dia. or 25-dia. Panel Cutout

(When Using a Ring)

- The small size of the control panel is realized by conserving space and changing the direction of the wiring.
- Since there is no looseness in the wiring, there is a reduction in the maintenance efforts.
- A maximum of up to four contact points can be combined together in the contact-point configuration.
- Oil-resistant to IP65 (non-lighted models) / IP65 (lighted models) / IP69K high-temperature, high-pressure cleaning (pull-reset models).
- Whether or not the Operation Unit and the Switch Unit have been properly mounted can be detected from the open/closed state of the contact (Lock-lever-linked contact function). ✻

✻ All contacts are interlocked with the lock lever.
(The statuses of both NC contacts and NO contacts are switched.)



For the most recent information on models that have been certified for safety standards, refer to your OMRON website.

⚠ Be sure to read the "*Safety Precautions*" on pages 18 and 56.

Model Number Structure

Model Number Legend (Completely Assembled)

.....Shipped as a set which includes the Operation Unit, LED Lamp (lighted models only), and Switch Block.

A22NE- 1 2 - 3 4 5 - 6 - 7

1. Operation Unit size (diameter)

Code	Description
S	30 dia.
M	40 dia.
L	60 dia.

2. Reset function

Code	Description
None	Turn-reset
P	Pull-reset ✻

✻ The pull-reset type is only available on the 40 dia. Operation Unit, non-lighted type. Not available on lighted types.

3. Terminal specification

Code	Description
P	Push-in plus terminal block

4. Lock lever function

Code	Description
D	Lock-lever-linked contact function

5. Contacts

Code	Number of Contacts	Contacts	
		NO	NC
01	one contact	0	1
02	two contacts	0	2
11		1	1
03	three contacts	0	3
21		2	1
12		1	2
22	four contacts	2	2
13		1	3
04		0	4

Note. NO: 1a-contact NC: 1b-contact

6. LED lamp voltage

Code	Description
N	Non-lighted
C	24 VAC/VDC

✻ Lighting color is red.

7. Others (Degree of Protection)

Code	Description
None	IP65
69K	IP69K ✻

✻ IP69K is supported only by the Pull-reset models.

chanhvinh.com

A22NE-PD

Ordering Information

List of Models (Completely Assembled)

Non-lighted Models (Without EMO/EMS Indication)

Appearance	Operation	Degree of Protection	Contact configuration ✻	Set Model	Color of cap
	40-dia. head Medium Pull-reset A22NE-MP-PD□□-N	IP65 oil-resistant models	2NC	**A22NE-MP-PD02-N**	Red
			2NC, 1NO	**A22NE-MP-PD12-N**	
			3NC	**A22NE-MP-PD03-N**	
			2NC, 2NO	**A22NE-MP-PD22-N**	
			3NC, 1NO	**A22NE-MP-PD13-N**	
			4NC	**A22NE-MP-PD04-N**	
	40-dia. head Medium Pull-reset A22NE-MP-PD□□-N-69K	IP69K	2NC	**A22NE-MP-PD02-N-69K**	
			2NC, 1NO	**A22NE-MP-PD12-N-69K**	
			3NC	**A22NE-MP-PD03-N-69K**	
			2NC, 2NO	**A22NE-MP-PD22-N-69K**	
			3NC, 1NO	**A22NE-MP-PD13-N-69K**	
			4NC	**A22NE-MP-PD04-N-69K**	
	30-dia. head Small Turn-reset A22NE-S-PD□□-N	IP65 oil-resistant models	2NC	**A22NE-S-PD02-N**	
			2NC, 1NO	**A22NE-S-PD12-N**	
			3NC	**A22NE-S-PD03-N**	
			2NC, 2NO	**A22NE-S-PD22-N**	
			3NC, 1NO	**A22NE-S-PD13-N**	
			4NC	**A22NE-S-PD04-N**	
	40-dia. head Medium Turn-reset A22NE-M-PD□□-N	IP65 oil-resistant models	2NC	**A22NE-M-PD02-N**	
			2NC, 1NO	**A22NE-M-PD12-N**	
			3NC	**A22NE-M-PD03-N**	
			2NC, 2NO	**A22NE-M-PD22-N**	
			3NC, 1NO	**A22NE-M-PD13-N**	
			4NC	**A22NE-M-PD04-N**	
	60-dia. head Large Turn-reset A22NE-L-PD□□-N	IP65 oil-resistant models	2NC	**A22NE-L-PD02-N**	
			2NC, 1NO	**A22NE-L-PD12-N**	
			3NC	**A22NE-L-PD03-N**	
			2NC, 2NO	**A22NE-L-PD22-N**	
			3NC, 1NO	**A22NE-L-PD13-N**	
			4NC	**A22NE-L-PD04-N**	

✻ In addition to the above, we also provide the following contact configurations: [1NC], [1NC, 1NO], and [1NC, 2NO]. Ask your OMRON representative for details.

Lighted Model (Without EMO/EMS Indication)

Appearance	Operation	Degree of Protection	Contact configuration ✻	LED lamp voltage	Set Model	Color of cap
	40-dia. head Medium Turn-reset A22NE-M-PD□□-C	IP65	2NC	24 V AC/DC	**A22NE-M-PD02-C**	Red
			2NC, 1NO		**A22NE-M-PD12-C**	
			3NC		**A22NE-M-PD03-C**	
			2NC, 2NO		**A22NE-M-PD22-C**	
			3NC, 1NO		**A22NE-M-PD13-C**	
			4NC		**A22NE-M-PD04-C**	

✻ In addition to the above, we also provide the following contact configurations: [1NC], [1NC, 1NO], and [1NC, 2NO]. Ask your OMRON representative for details.

chanhvinh.com

Accessories (Order Separately)

Operation Unit

Non-lighted

Function	Degree of protection \ Size	Small (30 dia.)	Medium (40 dia.)	Large (60-dia.)
		Single item order model		
Pull-reset	IP65 oil-resistant models	---	A22NE-MP-N 	---
	IP69K	---	A22NE-MP-N-69K 	---
Turn-reset	IP65 oil-resistant models	A22NE-S-N 	A22NE-M-N 	A22NE-L-N 
			A22NE-MRO-N A22NE-MRO-N-RD 	
			A22NE-MRS-N A22NE-MRS-N-RD 	

Lighted

Function	Sealing capability \ Size	Medium (40 dia.)
		Single item order model
Turn-reset	IP65	A22NE-M-L 


chanhvinh.com

A22NE-PD

LED lamp

Appearance	LED light	Rated voltage	Model	Remarks
	Red	24 V AC/DC	**A22NZ-L-RC**	These are provided with the completely assembled set of lighted models. Order LED Lamps only when replacing them.

Control Box

Item	Appearance	Model	Remarks
Control Box	 One hole, yellow box	**A22NZ-A-B101Y**	Material: Polycarbonate resin. For 22.3-mm panel hole diameter.

Note: For details on the accessories common to the screw terminal block models and push-in plus terminal block models, refer to *"Common Accessories and Tools (Order Separately)"* on page 51.

chanhvinh.com

Specifications

Certified Standard Ratings

- UL508 (File No. E76675), CSA C22.2 No.14
  5 A at 125 VAC, 3 A at 250 VAC B300
- TÜV (EN60947-5-1) - Certified direct opening - (EN60947-5-5)
  AC-15 3 A at 125 VAC
  DC-13 1 A at 30 VDC
- CCC (GB14048.5)
  AC-15 3 A at 125 VAC
  DC-13 1 A at 30 VDC

Applicable Standards

UL1059, UL486E

Note: Use a 10 A fuse type gI or gG that conforms to IEC60269 as a short-circuit protection device. This fuse is not provided in the main unit.

Ratings

Contacts (Standard Load)

Rated insulation voltage (V)	Rated carry current (A)	Rated voltage (V)	Rated current (A)			
			AC15 (Inductive load)	AC12 (Resistive load)	DC13 (Inductive load)	DC12 (Resistive load)
250	5	30 VAC	---	---	---	---
		125 VAC	3 A	5 A	---	---
		250 VAC	1.5 A	3 A	---	---
		30 VDC	---	---	1 A	2 A
		125 VDC	---	---	0.22 A	0.4 A
		250 VDC	---	---	0.1 A	0.2 A

Note: 1. The above ratings were obtained by conducting tests under the following conditions.
(1) Ambient temperature: 20°±2°C
(2) Ambient humidity: 65±5%
(3) Operating frequency: 20 operations/minute

2. Minimum applicable load: 1 mA at 5 VDC (Resistive load)
The operating range may vary depending on the usage conditions and type of load.

Certified Standards

Certification body	Standards	File No.
UL ✻	UL508, C22.2 No.14	E76675
TÜV SÜD	EN60947-5-1 (Certified direct opening), EN60947-5-5	Consult your OMRON representative for details.
CQC (CCC)	GB14048.5	Consult your OMRON representative for details.

Note: Only models with NC contacts have a direct opening mechanism.
✻ UL-certification for CSA C22.2 No. 14 has been obtained.

LED Lamp (A22NZ-L-RC)

Rated voltage	Operating voltage	Current value
24 VAC/VDC	24 VAC/VDC ± 10%	Approx. 12 mA

chanhvinh.com

A22NE-PD

Characteristics

Item		Operation	Turn-reset		Pull-reset	
			Non-lighted model	Lighted Model	Non-lighted model	Non-lighted model (Models with IP69K)
			A22NE-□-PD□□-N-□	A22NE-M-PD□□-C-□	A22NE-MP-PD□□-N-□	A22NE-MP-PD□□-N-69K
Allowable operating frequency	Mechanical		30 operations/minute or less (One operation consists of set and reset operations.)			
	Electrical		30 operations/minute or less (One operation consists of set and reset operations.)			
Insulation resistance ∗1			100 MΩ min. (at 500 VDC)			
Contact resistance			100 mΩ max. (initial value)			
Dielectric strength	Between terminals of same polarity*1		2,000 VAC, 50/60 Hz 1 minute (initial value)			
	Between terminals of different polarity		2,000 VAC, 50/60 Hz 1 minute (initial value)			
	Between each terminal and ground		2,000 VAC, 50/60 Hz 1 minute (initial value)			
Vibration resistance	Malfunction		10 to 55 Hz, 1.5 mm double amplitude (contact separation within 1 ms)			
Shock resistance	Malfunction		250 m/s^2 max. (contact separation within 1 ms)			
Durability	Mechanical		300,000 operations min. (One operation consists of set and reset operations.)			100,000 operations min. (One operation consists of set and reset operations.)
	Electrical (100 mA at 24 VAC (Resistive load))		250,000 operations min. (One operation consists of set and reset operations.)			100,000 operations min. (One operation consists of set and reset operations.)
	Electrical (3 mA at 250 VAC (Resistive load))		100,000 operations min. (One operation consists of set and reset operations.)			
Ambient operating temperature ∗2			-20 to +70°C	-20 to +55°C	-20 to +70°C	-20 to +70°C ∗3
Ambient operating humidity			35 to 85% RH			
Ambient storage temperature ∗2			-40 to +70°C			
Degree of protection ∗4			IP65 oil-resistant models	IP65	IP65 oil-resistant models	IP69K
Electric shock protection class			Class II			
PTI (tracking characteristic)			175			
Degree of contamination			3 (EN 60947-5-1)			
Minimum direct opening stroke			11 mm			
Minimum direct opening force			45 N			
Conditional short-circuit current			100 A (EN 60947-5-1)			
Wight (for a 40-dia. head 2NC/2NO Operation Unit)			Approx. 95 g	Approx. 95 g	Approx. 125 g	Approx. 135 g

∗1. State when an LED is not added between terminals of the same polarity on a lighting unit.
∗2. With no icing or condensation.
∗3. Capable of operation at up to 80°C under IP□9K testing conditions per JIS D 5020.
∗4. The degree of protection from the front of the panel.

Operating Characteristics


Item	Turn-reset	Pull-reset	
	Lighted / non-lighted models	Non-lighted model	Non-lighted model (Models with IP69K)
Total travel force (TTF)	45 N max.	60 N max.	70 N max.
Return force (RF)	0.25N·m max. ∗	60 N max.	70 N max.
Total travel (TT)	10 ±1 mm	5.5 ±1 mm	

∗ Rotation torque value.


chanhvinh.com

Terminal Arrangement (BOTTOM VIEW)

Non-lighted




One contact (1NC) | Two contacts (2NC) | Two contacts (1NC + 1NO)




Three contacts (3NC) | Three contacts (2NC + 1NO) | Four contacts (3NC + 1NO) | Four contacts (4NC)

Lighted

The switch terminal is same as that in the non-lighted models.
Indicates the terminals for lighting (X1-X2).
(Example: Four contacts (4NC) Lighted models)



Terminal arrangement



Terminal Arrangement

Type	Terminal Arrangement (BOTTOM VIEW)			
	1NC, 1NO (two contacts)	2NC, 2NO (four contacts)	3NC, 1NO (four contacts)	4NC (four contacts)
Non-lighted	NO 14–13 NC 12–11	NO 24–23, NO 14–13 NC 22–21, NC 12–11	NC 32–31, NO 14–13 NC 22–21, NC 12–11	NC 32–31, NC 42–41 NC 22–21, NC 12–11
Lighted	NO 14–13 X2 — X1 NC 12–11	NO 24–23, NO 14–13 X2 — X1 NC 22–21, NC 12–11	NC 32–31, NO 14–13 X2 — X1 NC 22–21, NC 12–11	NC 32–31, NC 42–41 X2 — X1 NC 22–21, NC 12–11

Note: The terminal arrangement shows the representative. It depends on the number of contacts in the series.

chanhvinh.com

A22NE-PD


Structure and Nomenclature



Operation Unit

Color: Red


Non-lighted
LED lighting



Lamp

Light source

- LED Lamp



Switch

Mounting Latches
Switch Blocks
Lighting unit

Contact Ratings

3 A at 250 VAC
5 A at 125 VAC

Lighting Method

Non-lighted
Lighted (LED)

chanhvinh.com


Dimensions

(Unit: mm)

Non-lighted Models


A22NE-MP-PD□□-N
Pull-reset (40-dia.) Degree of Protection: IP65 oil-resistant models






A22NE-MP-PD□□-N-69K
Pull-reset (40-dia.) Degree of Protection: IP69K






A22NE-S-PD□□-N
Small Turn-reset (30-dia.) Degree of Protection:
IP65 oil-resistant models





A22NE-M-PD□□-N
Medium Turn-reset (40-dia.) Degree of Protection:
IP65 oil-resistant models






Note: The dimensions the same even if the Operation Unit is replaced with the A22NE-MR□-N or the A22NE-MR□-N-RD.

A22NE-L-PD□□-N
Large Turn-reset (60-dia.) Degree of Protection:
IP65 oil-resistant models






Lighted Model

A22NE-M-PD□□-C
Medium Turn-reset (40-dia.) Degree of Protection: IP65







Note: Unless otherwise specified, a tolerance of ±0.8mm applies to all dimensions.

Accessories (Order Separately)

LED Lamp
A22NZ-L-RC





Note: For details on the accessories common to the screw terminal block types and push-in plus terminal block types, refer to *"Common Accessories and Tools (Order Separately)"* on page 51.

chanhvinh.com

A22NE-PD

Application


Mounting to the Panel

(1) Preparing the Panel


Panel hole dimension and panel thickness

- If outer surface treatment such as coating is performed for the panel, the panel dimensions after outer surface treatment must meet the specified panel dimensions.

Panel hole dimension	Panel thickness
22.3 dia.	1 to 5 mm




When using a A22Z-3360 (Order Separately) Lock Ring



For 25-dia.

- Use the A22Z-R25 (Order Separately) rubber ring.

✻ Switches with an IP69K degree of protection do not support the 25-dia.




(2) Minimum mounting pitch (Dimension A, Dimension B)

Minimum mounting pitch

Type of operation unit	Dimension A (mm) min.	Dimension B (mm) min.
30-dia., 40-dia. models	50 ✻1	50
60-dia. model	70	70

✻1. If the Switch Unit lock levers all face the same direction at the minimum mounting pitch, be sure to note the order the Switch Units are attached to the Operation Unit.
✻2. When using each accessory (Order Separately), set the A and B dimensions in view of the dimensions of the accessories.
✻3. Make sure the mounting pitch does not hinder the operation.

Panel Hole Dimensions for 22.3 Diameter




(3) Mounting the Operation Unit on the Panel

- Do not tighten the Tightening Nut more than necessary using tools such as pointed-nose pliers.
- Doing so will damage the Tightening Nut.
  (The tightening torque of the Tightening Nut is 1.0 to 2.0 N·m.)
  Tightening Wrench: A22Z-3905


Panel Hole of 22.3-mm Diameter

- Insert the Operation Unit from the front of the panel, insert the Lock Ring and Tightening Nut from the back of the panel, and tighten the Tightening Nut. Before tightening, check that the rubber washer is present between the Operation Unit and the panel.



When the A22Z-3360 Lock Ring (Order Separately) is used

- Take note of the direction when mounting the Lock Ring.




Panel Hole of 25-mm Diameter


- Insert the A22Z-R25 (Order Separately) between the Operation Unit and Panel, and tighten the Tightening Nut.
  Before tightening, check that the rubber washer supplied with the Operation Unit is present between the Operation Unit and the 25-dia. Ring.

Panel Hole of 30-mm Diameter

- Insert the A22Z-A30 (Order Separately) between the Operation Unit and Panel, and tighten the Tightening Nut.
  Before tightening, check that the supplied rubber washer is present between the Operation Unit and the panel, and between the 30-dia. Resin Attachment and the panel.

✻ Switches with an IP69K degree of protection do not support the 30-dia.






Panel Cutouts	Panel thickness
25 mm dia.	1 to 5 mm
30 mm dia.	1 to 3 mm

chanhvinh.com


Removing the Switch Unit

When the Switch Unit is to be Removed

Slowly push the release port (concave part) of the lock lever with a screwdriver to release the lock. The lock lever moves to the release position.



<Lock lever position>




When the lock lever is at the released position in this Switch, the NO and NC contact operation is reversed.

Set the lock lever to the locked position when using the Switch.

Installing the LED Lamp (Lighted Models)

When the LED Lamp is to be Installed

Insert the protrusions on the LED Lamp into the guides on the Switch Unit in direction (1), and then turn the LED Lamp in direction (2) to lock it in place.



chanhvinh.com

A22NE-PD

Safety Precautions

Be sure to read the precautions **for All PushButton Switches** in the website at: http://www.ia.omron.com/.

Indication and Meaning for Safe Use

⚠ Warning	**Indicates a potentially hazardous situation that, if not avoided, could result in serious injury or death. Additionally there may be significant property damage.**
Precautions for Safe Use	**Comments on what to do or avoid doing, to use the product safely.**
Precautions for Correct Use	**Supplementary comments on what to do or avoid doing to use the product safely and prevent its malfunctioning or an adverse effect on its performance or functions.**

⚠ WARNING


Do not perform wiring with power supplied to the Switch/Indicator. Do not touch the terminals or other charged parts while power is being supplied. Doing so may result in electric shock.




Precautions for Safe Use

- Make sure the Operation Unit and the Switch Unit are properly assembled.

<Assembling the Operation Unit and Switch Unit>
(1) Assembling the Operation Unit and Switch Unit
Align the TOP indication (the mark ⇩) on the Operation Unit with the TOP indication on the Switch Unit, and insert the Operation Unit while keeping the bottom A pressed.
(2) Locking the lock lever
With a screwdriver inserted in the lock hole of the lock lever, bring the screwdriver in contact with the convex part of the case, and turn the lock lever until a clicking sound is heard.



<Lock lever position>



Release position Locked position

When the lock lever is at the released position in this Switch, the NO and NC contact operation is reversed.
Set the lock lever to the locked position when using the Switch.

- When transition wiring is performed, make sure the switching current inside the Switch and the current based on the transition wiring is below the rated current of the Switch.
If a current value higher than the rated current flows, it could result in emission of heat, or damage and deformation of the Switch, which could cause fire and locking of the contact, and thus a loss of safety.
- Do not disassemble or modify the Switch/Indicator under any circumstances.
- Doing so may prevent the Switch/Indicator from functioning to its full capability. Do not drop the Switch/Indicator. Do not apply pressure that may deform or alter the Switch/Indicator.
- The durability of the Switch varies considerably depending on the switching conditions. Always test the Switch/Indicator under actual working conditions before application and use the Switch/Indicator only for the number of switching operations allowed.
- Do not allow the load voltage and current to exceed the rated value. This may damage or burn out the Switch/Indicator.
- Do not use the Switch/Indicator in locations where explosive or flammable gases or liquid may be present or scattered. The electric ark or the heat caused by switching contacts may cause a fire or explosion.
- Do not use the Switch/Indicator in locations where toxic gases, such as H_2S, SO_2, NH_3, HNO_3, and Cl_2, may be present, or in locations subject to high temperature or humidity. Doing so may damage the Switch/Indicator due to contact failure or corrosion.
- Do not use the Switch/Indicator submersed in oil or water, or in locations continuously subject to splashes of oil or water. Doing so may result in oil or water entering and damaging the Switch/Indicator.
- Do not use or keep the Switch/Indicator under the following conditions:
  - Subject to severe temperature changes.
  - Subject to high humidity or condensation.
  - Subject to severe vibration or shock.
  - Where direct rays of the sun strike.
  - Where sea breeze may be present.
- Make sure that a rubber washer is present between the Operation Unit and the panel. In models with IP69K, make sure the rubber bush of the Operation Unit is properly attached.
Otherwise, the specifications of the protective structure may not be satisfied.
- Do not apply excessive force to the Switch or wirings. Damage or deformation of the Switch Unit could result in an improper contact or a loss of safety.
- Use an appropriate wiring and crimp terminals (hereinafter, called ferrule terminals).
- Exercise caution to avoid wiring errors when connecting the terminals.
- To prevent wiring materials from smoking or ignition, confirm wire ratings and use the wiring materials given in the following table.

Wire Type	Wire material	Recommended Wire	Wire coating peeling amount
Solid wire/ Stranded Wire	Copper	0.25 to 1.5 mm^2 AWG 24 to 16	Ferrules used: 10 to 12 mm (Varies depending on the recommended ferrule conductor length) Ferrules not used: 8 mm

Use wiring crimp terminals and ferrule terminals of the specified size.

chanhvinh.com


- After storing the product for a long time exceeding 1 year, perform, at a minimum, inspections of the operating characteristics, contact resistance, insulation resistance, and dielectric strength as well as evaluate the product under the working conditions.
- This product is intended for indoor use only. Using the product outdoors will result in failure.
- Do not wire anything to the release holes.
- Do not tilt or twist a flat-blade screwdriver while it is inserted into a release hole on the terminal block. The terminal block may be damaged.
- Insert a flat-blade screwdriver into the release holes at an angle. The terminal block may be damaged if you insert the screwdriver straight in.
- Do not allow the flat-blade screwdriver to fall out while it is inserted into a release hole.
- Do not bend a wire past its natural bending radius or pull on it with excessive force.
  Doing so may cause the wire disconnection.
- Do not insert more than one wire into each terminal insertion hole.
- When mounting on a device with high airtightness, test operation in advance. There is a risk that the negative pressure will prevent the Operation Unit of from returning.
- Although the contacts of an A22NE-PD can be used with both the standard loads and microloads, once a contact has opened or closed under a load, you cannot again connect a small-capacity load. Doing so could roughen the contact surface, and result in loss of contact reliability.
- In the case of loads where an inrush current occurs when the contact is opened or closed, the durability may reduce due to extreme wear on the contacts.
  If necessary, insert a contact protection circuit.
- If a contact weld, the lock lever might not return to the release position, and contact inversion might not occur. In such a case, move the lock lever to the release position, and remove the Switch Unit from the Operation Unit.

Precautions for Correct Use

Wiring


1. Connecting Wires to the Push-In Plus Terminal Block

Part Names of the Terminal Block



Connecting Wires with Ferrules and Solid Wires


- Insert the solid wire or ferrule straight into the terminal block until the end strikes the terminal block.
- If a wire is difficult to connect because it is too thin, use a flat-blade screwdriver in the same way as when connecting stranded wires.



Connecting Stranded Wires

Use the following procedure to connect the wires to the terminal block.

1. Hold a flat-blade screwdriver at an angle and insert it into the release hole. The angle should be appropriately 10 to 15°. If the flat-blade screwdriver is inserted correctly, you will feel the spring in the release hole.
2. With the flat-blade screwdriver still inserted into the release hole, insert the wire into the terminal hole until the end strikes the terminal block.
3. Remove the flat-blade screwdriver from the release hole.



chanhvinh.com


Checking Connections

- After the insertion, pull gently on the wire to make sure that it will not come off and it is securely fastened to the terminal block.
- If you use a ferrule with a conductor length of 10 mm, part of the conductor may be visible after the ferrule is inserted into the terminal block, but the product insulation distance will still be satisfied.

2. Removing Wires from the Push-In Plus Terminal Block

Use the following procedure to remove wires from the terminal block.
The same method is used to remove stranded wires, solid wires, and ferrules.

1. Hold a flat-blade screwdriver at an angle and insert it into the release hole. The angle should be appropriately 10 to 15°.
2. With the flat-blade screwdriver still inserted into the release hole, remove the wire from the terminal insertion hole.
3. Remove the flat-blade screwdriver from the release hole.



3. Recommended Ferrules and Crimp Tools

Coating peeling amount


Recommend Wire Type	Stripping length (Ferrules not used)
0.25 to 1.5 mm²/AWG 24 to AWG 16	8 mm

Recommended ferrules

Applicable wire		Ferrule conductor length (mm)	Stripping length (mm) (Ferrules not used)	Recommended ferrules		
(mm²)	(AWG)			Phoenix Contact product	Weidmuller product	Wago product
0.25	24	8	10	AI 0, 25-8	H0.25/12	216-301
		10	12	AI 0, 25-10	---	---
0.34	22	8	10	AI 0, 34-8	H0.34/12	216-302
		10	12	AI 0, 34-10	---	---
0.5	20	8	10	AI 0, 5-8	H0.5/14	216-201
		10	12	AI 0, 5-10	H0.5/16	216-241
0.75	18	8	10	AI 0, 75-8	H0.75/14	216-202
		10	12	AI 0, 75-10	H0.75/16	216-242
1/1.25	18/17	8	10	AI 1-8	H1.0/14	216-203
		10	12	AI 1-10	H1.0/16	216-243
1.25/1.5	17/16	8	10	AI 1, 5-8	H1.5/14	216-204
		10	12	AI 1, 5-10	H1.5/16	216-244
Recommended Crimp Tools				CRIMPFOX6 CRIMPFOX6T-F CRIMPFOX10S	PZ6 roto	Variocri mp4


Note: 1. Make sure that the outer diameter of the wire coating is smaller than the inner diameter of the insulation sleeve of the recommended ferrule.

2. Make sure that the ferrule processing dimensions conform to the following figures.



Recommended Flat-Blade Screwdrivers

Use a flat-blade screwdriver to connect and remove wires.
Use one of the following flat-blade screwdrivers.
The following table shows manufacturers and models as of 2015/Dec.



Model	Manufacture
ESD 0,40 × 2,5	Wera
SZS 0,4 × 2,5 SZF 0-0,4 × 2,5 ✻	Phoenix Contact
0.4 × 2.5 × 75 302	Wiha
AEF.2,5 × 75	Facom
210-719	Wago
SDI 0,4 × 2,5 × 75	Weidmuller

✻ The SZF 0-0,4 × 2,5 (manufactured by Phoenix Contact) can be procured through an OMRON exclusive purchase form (XW4Z-00B).


- After wiring the Switch/Indicator, provide a sufficient insulation distance.

LED Lamps

- A current-limiting resistor is built in the LED lamp, so the installation of an external resistance is not required.
- Lighting malfunction of the LED lamp
  A micro-current of approximately 0.1 mA or less is sufficient to turn on the LED lamps. Take a countermeasure like adding a resistor to prevent mis-lighting in parallel to the LED lamp.
  The micro-current varies with the machine (leak current or stray capacity between cables, etc.). Select resistance value and allowable power consumption that meet the actual current.

(Example of lighting malfunction prevention circuit)

When using a 24 VAC/DC Lighted Model



Be sure to read the *"Safety Precautions"* on page 56.

chanhvinh.com


Emergency Stop Pushbutton Switches (22-dia. or 25-dia.) Push-in Plus Terminal Block Models

A22NE-P

Install in 22-dia. or 25-dia. Panel Cutout

(When Using a Ring)

- The small size of the control panel is realized by conserving space and changing the direction of the wiring.
- Since there is no looseness in the wiring, there is a reduction in the maintenance efforts.
- A lock lever mechanism that can be easily operated is adopted.
- A maximum of up to six contact points can be combined together in the contact-point configuration.
- Oil-resistant to IP65 (non-lighted models) / IP65 (lighted models) / Supports IP69K high-temperature, high-pressure cleaning (pull-reset models).



For the most recent information on models that have been certified for safety standards, refer to your OMRON website.

⚠ Be sure to read the "*Safety Precautions*" on pages 33 and 56.

Model Number Structure

Model Number Legend (Completely Assembled)

.....Shipped as a set which includes the Operation Unit, LED Lamp (lighted model only), Mounting Latches, Lighting Units (lighted model only), and Switch Block.

A22NE- [1] [2] - [3] [4] - [5] - [6] **(Example: A22NE-M-P102-N)**

1. Operation Unit size (diameter)

Code	Description
S	30 dia.
M	40 dia.
L	60 dia.

2. Reset function

Code	Description
None	Turn-reset
P	Pull-reset ✻

✻ The pull-reset type is only available on the 40 dia. Operation Unit, non-lighted type. Not available on lighted types.


3. Contact specification/Terminal specification

Code	Description
P	Standard load/Push-in plus terminal block

4. Contacts

Code	Number of Switch Blocks		Unit position					
			Non-lighted			Lighted		
	NO	NC	1	2	3	1	2	3
002	0	1	---	---	NC	---	Lighting unit	NC
102	1	1	NO	---	NC	NO	Lighting unit	NC
202	0	2	NC	---	NC	NC	Lighting unit	NC
212	1	2	NC	NO	NC	---		
222	0	3	NC	NC	NC			

Note 1. NO: 1a-contact NC: 1b-contact
2. For details on the unit position, refer to the figure below.



5. LED lamp voltage

Code	Description	LED Lamp Voltage
N	Non-lighted	---
A	Lighted (LED) ✻	6 VAC/DC
B		12 VAC/DC
C		24 VAC/DC
D		100/110/120 VAC
E		200/220/230/240 VAC

✻ Lighting color is red.

6. Others (Degree of Protection/Control box)

Code	Configuration
None	IP65
69K	IP69K
B ✻	Built-in control box

✻ One-contact unit type.

chanhvinh.com

A22NE-P

Ordering Information

List of Models (Completely Assembled)

Non-lighted Models

Appearance	Operation	Degree of Protection	Contact configuration ✻	Set Model	Color of cap
	40-dia. head Medium Pull-reset A22NE-MP-P□□2-N	IP65 oil-resistant models	1NC (1)	**A22NE-MP-P002-N**	Red
			1NC, 1NO (2)	**A22NE-MP-P102-N**	
			2NC (2)	**A22NE-MP-P202-N**	
			2NC, 1NO (3)	**A22NE-MP-P212-N**	
			3NC (3)	**A22NE-MP-P222-N**	
	40-dia. head Medium Pull-reset A22NE-MP-P□□2-N-69K	IP69K	1NC (1)	**A22NE-MP-P002-N-69K**	
			1NC, 1NO (2)	**A22NE-MP-P102-N-69K**	
			2NC (2)	**A22NE-MP-P202-N-69K**	
			2NC, 1NO (3)	**A22NE-MP-P212-N-69K**	
			3NC (3)	**A22NE-MP-P222-N-69K**	
	30-dia. head Small Turn-reset A22NE-S-P□□2-N	IP65 oil-resistant models	1NC (1)	**A22NE-S-P002-N**	
			1NC, 1NO (2)	**A22NE-S-P102-N**	
			2NC (2)	**A22NE-S-P202-N**	
			2NC, 1NO (3)	**A22NE-S-P212-N**	
			3NC (3)	**A22NE-S-P222-N**	
	40-dia. head Medium Turn-reset A22NE-M-P□□2-N		1NC (1)	**A22NE-M-P002-N**	
			1NC, 1NO (2)	**A22NE-M-P102-N**	
			2NC (2)	**A22NE-M-P202-N**	
			2NC, 1NO (3)	**A22NE-M-P212-N**	
			3NC (3)	**A22NE-M-P222-N**	
	60-dia. head Large Turn-reset A22NE-L-P□□2-N		1NC (1)	**A22NE-L-P002-N**	
			1NC, 1NO (2)	**A22NE-L-P102-N**	
			2NC (2)	**A22NE-L-P202-N**	
			2NC, 1NO (3)	**A22NE-L-P212-N**	
			3NC (3)	**A22NE-L-P222-N**	

✻ The number in parentheses ( ) indicates the number of switch units.

Lighted Model

Appearance	Operation	Degree of Protection	Contact configuration ✻	LED lamp voltage	Set Model	Color of cap
	40-dia. head Medium Turn-reset A22NE-M-P□□2-A	IP65	1NC (1)	6 VAC/VDC	**A22NE-M-P002-A**	Red
			1NC, 1NO (2)		**A22NE-M-P102-A**	
			2NC (2)		**A22NE-M-P202-A**	
	40-dia. head Medium Turn-reset A22NE-M-P□□2-B		1NC (1)	12 VAC/VDC	**A22NE-M-P002-B**	
			1NC, 1NO (2)		**A22NE-M-P102-B**	
			2NC (2)		**A22NE-M-P202-B**	
	40-dia. head Medium Turn-reset A22NE-M-P□□2-C		1NC (1)	24 VAC/VDC	**A22NE-M-P002-C**	
			1NC, 1NO (2)		**A22NE-M-P102-C**	
			2NC (2)		**A22NE-M-P202-C**	
	40-dia. head Medium Turn-reset A22NE-M-P□□2-D		1NC (1)	100, 110, 120 VAC	**A22NE-M-P002-D**	
			1NC, 1NO (2)		**A22NE-M-P102-D**	
			2NC (2)		**A22NE-M-P202-D**	
	40-dia. head Medium Turn-reset A22NE-M-P□□2-E		1NC (1)	220, 230, 240 VAC	**A22NE-M-P002-E**	
			1NC, 1NO (2)		**A22NE-M-P102-E**	
			2NC (2)		**A22NE-M-P202-E**	

✻ The number in parentheses ( ) indicates the number of switch units.

Switch with Integrated Control Box

Appearance	Contact configuration (Number of switch blocks)	Model
	1NC (1)	**A22NE-M-P002-N-B**
	1NC, 1NO (2)	**A22NE-M-P102-N-B**
	2NC (2)	**A22NE-M-P202-N-B**

chanhvinh.com

Subassembled..... The Operation Unit, LED Lamp, Mounting Latches, Switch Blocks, and Lighting Unit can be ordered separately. Use them in combination for models that are not available as assembled Units. These can also be used as inventory for maintenance parts.

Non-lighted

Operation Unit



Lighted

Operation Unit



Mounting Latches




LED Lamp



Switch Blocks ✻

Push-in Plus Terminal Block



Switch Blocks + Lighting Unit

Push-in Plus Terminal Block



✻ Up to three Switch Blocks can be mounted.

chanhvinh.com

A22NE-P

Operation Unit

Non-lighted

Function	Sealing capability	Size: Small (30 dia.)	Medium (40 dia.)	Large (60-dia.)
		Single item order model		
Pull-reset	IP65 oil-resistant models	---	A22NE-MP-N 	---
	IP69K	---	A22NE-MP-N-69K 	---
Turn-reset	IP65 oil-resistant models	A22NE-S-N 	A22NE-M-N 	A22NE-L-N 
			A22NE-MRO-N A22NE-MRO-N-RD 	
			A22NE-MRS-N A22NE-MRS-N-RD 	

Lighted



Function	Sealing capability	Size: Medium (40 dia.)
		Single item order model
Turn-reset	IP65	A22NE-M-L 

LED lamp

Appearance	LED light	Rated voltage	Model	Remarks
	Red	6 VAC/VDC	**A22NZ-L-RA**	These LED lamps are for exclusive use with the A22N and the A22NE-P. These are provided with the completely assembled set of lighted models. Order LED lamps only when replacing them.
		12 VAC/VDC	**A22NZ-L-RB**	
		24 VAC/VDC	**A22NZ-L-RC**	
		100, 110, 120 VAC	**A22NZ-L-RD**	
		200, 220, 230, 240 VAC	**A22NZ-L-RE**	

chanhvinh.com

Accessories (Order Separately)

Item	Appearance	Contact specifications		Model	Remarks
Switch Blocks (one contact)		1NO (Blue)	Standard load	**A22NZ-S-P1A**	Provided as standard. Order Switch Blocks only when adding or replacing them.
		1NC (Red)	Standard load	**A22NZ-S-P1B**	
Switch Blocks (two contacts)		2NO (Blue)	Standard load	**A22NZ-S-P2A**	Order Switch Blocks only when adding or replacing them.
		2NC (Red)	Standard load	**A22NZ-S-P2B**	
		1NO/1NC (White)	Standard load	**A22NZ-S-P2C**	
Lighting unit		6 VAC/VDC		**A22NZ-T-AP**	These are provided with the completely assembled set of lighted models. Order Lighting Units only when replacing them.
		12 VAC/VDC		**A22NZ-T-BP**	
		24 VAC/VDC		**A22NZ-T-CP**	
		100, 110, 120 VAC		**A22NZ-T-DP**	
		200, 220, 230, 240 VAC		**A22NZ-T-EP**	
Mounting Latches		---		**A22NZ-H-02**	This Mounting Latch is for exclusive use with the A22NE-P. It is provided with the completely assembled set. Order Mounting Latches only when mounting Switch Blocks or Lighting Units that are purchased individually.
Control Boxes (Enclosures)		One hole, yellow box		**A22NZ-A-B101Y**	Can be combined with 2-contact Switch Blocks.
				A22NZ-A-B01Y	Cannot be combined with 2-contact Switch Blocks. ✻

Note: For details on the accessories common to the screw terminal block types and push-in plus terminal block types, refer to *"Common Accessories and Tools (Order Separately)"* on page 51.

✻ The A22NZ-A-B01Y Control Box cannot be used in combination with the A22Z-3476-1 90-dia. Legend Plates for Emergency Stop or the A22Z-EG□ E-stop Shrouds.

chanhvinh.com

A22NE-P

Specifications

Certified Standard Ratings

- UL508 (File No. E76675), CSA C22.2 No.14
  6 A at 240 VAC, 10 A at 120 VAC
- TÜV (EN60947-5-1) - Certified direct opening - (EN60947-5-5)
  AC-15 3 A at 240 VAC
  DC-13 4 A at 24 VDC
- CCC (GB14048.5)
  AC-15 3 A at 240 VAC
  DC-13 4 A at 24 VDC

Applicable Standards

UL1059, UL486E (Push-in Plus Terminal Block Types)

Note: Use a 10 A fuse type gI or gG that conforms to IEC60269 as a short-circuit protection device. This fuse is not provided in the main unit.

Ratings

Contacts (Standard Load)

Rated insulation voltage (V)	Rated carry current (A)	Rated voltage (V)	Rated current (A)			
			AC15 (Inductive load)	AC12 (Resistive load)	DC13 (Inductive load)	DC12 (Resistive load)
600	10	24 VAC	10	10	---	---
		120 VAC	6	10		
		240 VAC	3	6		
		380 VAC	1.9	2		
		440 VAC	1.6	2		
		24 VDC	---	---	4	8
		120 VDC			1.1	2.2
		240 VDC			0.55	1.1

Note: 1. The above ratings were obtained by conducting tests under the following conditions.
(1) Ambient temperature: 20°±2°C
(2) Ambient humidity: 65±5%
(3) Operating frequency: 20 operations/minute

2. Minimum applicable load: 10 mA at 5 VDC (Resistive load)
The operating range may vary depending on the usage conditions and type of load.

Certified Standards

Certification body	Standards	File No.
UL ✻	UL508, C22.2 No.14	E76675
TÜV SÜD	EN60947-5-1 (Certified direct opening), EN60947-5-5	Consult your OMRON representative for details.
CQC (CCC)	GB14048.5	2017010305959182

Note: Only models with NC contacts have a direct opening mechanism.
✻ UL-certification for CSA C22.2 No. 14 has been obtained.

LED Lamp

Rated voltage	Operating voltage	Current value
6 VAC/VDC	6 VAC/VDC ± 10%	Approx. 11 mA
12 VAC/VDC	12 VAC/VDC ± 10%	Approx. 12 mA
24 VAC/VDC	24 VAC/VDC ± 10%	Approx. 12 mA
100 VAC	100 VAC ± 10%	Approx. 12 mA
110 VAC	110 VAC ± 10%	
120 VAC	100 VAC to 130 VAC	
200 VAC	200 VAC ± 10%	Approx. 12 mA
220 VAC	220 VAC ± 10%	
230 VAC	230 VAC ± 10%	
240 VAC	220 VAC to 250 VAC	

chanhvinh.com

Characteristics

Item		Operation	Turn-reset		Pull-reset	
			Non-lighted model	Lighted Model	Non-lighted model	
			A22NE-□-P□□□-N	A22NE-M-P□□□-□	A22NE-MP-P□□□-N	A22NE-MP-P□□□-N-69K
Allowable operating frequency	Mechanical		30 operations/minute or less (One operation consists of set and reset operations.)			
	Electrical		30 operations/minute or less (One operation consists of set and reset operations.)			
Insulation resistance ∗1			100 MΩ min. (at 500 VDC)			
Contact resistance			100 mΩ max. (initial value)			
Dielectric strength	Between terminals of same polarity*1		2,500 VAC, 50/60 Hz 1 minute (initial value)			
	Between each terminal and ground		2,500 VAC, 50/60 Hz 1 minute (initial value)			
Vibration resistance	Malfunction		10 to 55 Hz, 1.5 mm double amplitude (contact separation within 1 ms)			
Shock resistance	Malfunction		250 m/s^2 max. (contact separation within 1 ms)			
Durability	Mechanical		300,000 operations min. (One operation consists of set and reset operations.)			100,000 operations min. (One operation consists of set and reset operations.)
	Electrical		300,000 operations min. (One operation consists of set and reset operations.)			100,000 operations min. (One operation consists of set and reset operations.)
Ambient operating temperature ∗2			-20 to +70°C	-20 to +55°C	-20 to +70°C	-20 to +70°C ∗3
Ambient operating humidity			35 to 85% RH			
Ambient storage temperature ∗2			-40 to +70°C			
Degree of protection ∗4			IP65 oil-resistant models ∗5	IP65	IP65 oil-resistant models ∗5	IP69K
Electric shock protection class			Class II			
PTI (tracking characteristic)			175			
Degree of contamination			3 (EN 60947-5-1)			
Minimum direct opening stroke			11 mm			
Minimum direct opening force			45 N			
Conditional short-circuit current			100 A (EN 60947-5-1)			
Wight (for a 40-dia. head 1NC/1NO Operation Unit)			Approx. 55g	Approx. 60g	Approx. 85 g	Approx. 115 g




∗1. State when an LED is not added between terminals of the same polarity on a lighting unit. Does not apply to lighted-type 100 to 200 V lighting units.
∗2. With no icing or condensation.
∗3. Capable of operation at up to 80°C under IP□9K testing conditions per JIS D 5020.
∗4. The degree of protection from the front of the panel.
∗5. The degree of protection is IP65 even with an integrated control box, but the system is not oil resistant.

Operating Characteristics

Item	Turn-reset	Pull-reset	
	Lighted / non-lighted models	Non-lighted model	Non-lighted model (Models with IP69K)
Total travel force (TTF)	45 N max.	60 N max.	70 N max.
Return force (RF)	0.25N·m ✻ max.	60 N max.	70 N max.
Total travel (TT)	10 ±1 mm	5.5 ±1 mm	5.5 ±1 mm

✻ Rotation torque value.







Terminal Arrangement (BOTTOM VIEW)

Non-lighted (two contacts)	Non-lighted (three contacts)	Lighted (two contacts)
		

chanhvinh.com


A22NE-P

Terminal connection

Type	Terminal Connection (BOTTOM VIEW)			
	1NC, 1NO (two contacts)	2NC (two contacts)	2NC, 1NO (three contacts)	3NC (three contacts)
Non-lighted				
Lighted				


Note: The above terminal connection diagrams are examples for 1NO, 1NC (two contacts), or 2NC (two contacts).

Terminal wiring drawings of two-contact Switch Units



Type	Terminal Connection (BOTTOM VIEW)	
	2NC (two contacts)	1NC, 1NO (two contacts)
A		
B		

Structure and Nomenclature



Operation Unit

Color: Red

Non-lighted
LED lighting

Lamp

Light source

- LED Lamp





Switch

Mounting Latches
Switch Blocks
Lighting unit

Contact Ratings

6 A at 240 VAC
10 A at 120 VAC

Lighting Method

Non-lighted
Lighted (LED)

chanhvinh.com


Dimensions


(Unit: mm)

Non-lighted Models

A22NE-MP-P□□2-N


Pull-reset (40-dia.) Degree of Protection: IP65 oil-resistant models






A22NE-MP-P□□2-N-69K


Pull-reset (40-dia.) Degree of Protection: IP69K






A22NE-S-P□□2-N


Small Turn-reset (30-dia.) Degree of Protection:
IP65 oil-resistant models






A22NE-M-P□□2-N

Medium Turn-reset (40-dia.) Degree of Protection:
IP65 oil-resistant models







Note: The dimensions the same even if the Operation Unit is replaced with the A22NE-MR□-N or the A22NE-MR□-N-RD.

A22NE-L-P□□2-N

Large Turn-reset (60-dia.) Degree of Protection:
IP65 oil-resistant models







Lighted Model


A22NE-M-P□□2-□

Medium Turn-reset (40-dia.) Degree of Protection: IP65





Dimensions when a two-contact Switch Block is attached



Note: Unless otherwise specified, a tolerance of ±0.8 mm applies to all dimensions.


chanhvinh.com


A22NE-P

Accessories (Order Separately)


Switch Block with Push-In Plus technology


Switch Block (one contact)
A22NZ-S-P1□







Switch Block (two contacts)
A22NZ-S-P2□







Lighting unit
A22NZ-T-□P







Mounting Latches
A22NZ-H-02







LED Lamp
A22NZ-L-□□







Control Box
A22NZ-A-B01Y





Control Box
A22NZ-A-B101Y





Note: For details on the accessories common to the screw terminal block types and push-in plus terminal block types, refer to *"Common Accessories and Tools (Order Separately)"* on page 51.

chanhvinh.com

Application


Mounting to the Panel

(1) Preparing the Panel


Panel hole dimension and panel thickness

- If outer surface treatment such as coating is performed for the panel, the panel dimensions after outer surface treatment must meet the specified panel dimensions.

Panel hole dimension	Panel thickness
22.3 dia.	1 to 5 mm




When using a A22Z-3360 (Order Separately) Lock Ring



For 25-dia.

- Use the A22Z-R25 (Order Separately) rubber ring.

✻Switches with an IP69K degree of protection do not support the 25-dia.




(2) Minimum mounting pitch (Dimension A, Dimension B)

Minimum mounting pitch

Type of operation unit	Dimension A (mm) min.	Dimension B (mm) min.
30-dia., 40-dia. models	50 ✻1	50
60-dia. model	70	70

✻1. If the Mounting Collar lock levers all face the same direction at the minimum mounting pitch, be sure to note the order the mounting collars are attached to the Operation Unit.
✻2. When using each accessory (Order Separately), set the A and B dimensions in view of the dimensions of the accessories.
✻3. Make sure the mounting pitch does not hinder the operation.

Panel Hole Dimensions for 22.3 Diameter




(3) Mounting the Operation Unit on the Panel

- Do not tighten the Tightening Nut more than necessary using tools such as pointed-nose pliers.
- Doing so will damage the Tightening Nut.
  (The tightening torque of the Tightening Nut is 1.0 to 2.0 N·m.)
  Tightening Wrench: A22Z-3905


Panel Hole of 22.3-mm Diameter

- Insert the Operation Unit from the front of the panel, insert the Lock Ring and Tightening Nut from the back of the panel, and tighten the Tightening Nut. Before tightening, check that the rubber washer is present between the Operation Unit and the panel.




When the A22Z-3360 Lock Ring (Order Separately) is used

- Take note of the direction when mounting the Lock Ring.



Panel Hole of 25-mm Diameter


- Insert the A22Z-R25 (Order Separately) between the Operation Unit and Panel, and tighten the Tightening Nut. Before tightening, check that the rubber washer supplied with the Operation Unit is present between the Operation Unit and the 25-dia. Ring.



Panel Hole of 30-mm Diameter

- Insert the A22Z-A30 (Order Separately) between the Operation Unit and Panel, and tighten the Tightening Nut. Before tightening, check that the supplied rubber washer is present between the Operation Unit and the panel, and between the 30-dia. Resin Attachment and the panel.

✻ Switches with an IP69K degree of protection do not support the 30-dia.




Panel Cutouts	Panel thickness
25 mm dia.	1 to 5 mm
30 mm dia.	1 to 3 mm

chanhvinh.com

Removing the Mounting Latch

When the Mounting Latch is to be Removed


- Press the lock lever in from the back side to release the lock, and then hook the Mounting Collar with a screwdriver, move it in the direction indicated at (2), and remove it. Turn the lever all of the way until it clicks into place.



Switch Blocks and Lighting Unit


(1) Installing the Switch Blocks and Lighting Unit

- Catch the projection on the opposite side of the Mounting Collar from the lever side and press the Switch Block in the direction indicated at (1).



(2) Removing the Switch Blocks and Lighting Units


- Insert a screwdriver into the gap between the Mounting Collar and Switch Block and press it inward in the direction shown at (2).



Attaching the LED Lamp to the Lighting Unit

When the LED Lamp is to be Installed

- Insert the protrusions on the LED Lamp into the guides on the Lighting Unit and then turn the LED Lamp in direction (2) to lock it in place.




Control Box

(1) Mounting the Switch


Mount the Switch in the same way as for a standard panel.

The tightening torque of the Box screws is 1.4 to 2.0 N·m.




(2) Creating a Cable Hole

To open a cable hole, leave the cover attached, place the tip of a screwdriver in the grooves at four locations around the cable hole, and strike the screwdriver with a hammer to open the hole.



(3) Securing the Connector Cable

1. Insert the connector into the cable port hole in the Box and secure with the fixing ring inside the box.
2. Pass the tightening cap through the cable, insert the cable into the connector, and tighten the tightening cap to secure the cable.



Cable diameter (mm)	Connector
7 to 9 dia.	A22Z-3500-1
9 to 11 dia.	A22Z-3500-2

chanhvinh.com

Safety Precautions

Be sure to read the precautions **for All PushButton Switches** in the website at: http://www.ia.omron.com/.

Indication and Meaning for Safe Use

Warning	**Indicates a potentially hazardous situation that, if not avoided, could result in serious injury or death. Additionally there may be significant property damage.**
Precautions for Safe Use	**Comments on what to do or avoid doing, to use the product safely.**
Precautions for Correct Use	**Supplementary comments on what to do or avoid doing to use the product safely and prevent its malfunctioning or an adverse effect on its performance or functions.**

⚠ WARNING


Do not perform wiring with power supplied to the Switch/Indicator. Do not touch the terminals or other charged parts while power is being supplied. Doing so may result in electric shock.




Precautions for Safe Use

- If the Operation Unit is separated from the Switch Units, the equipment will not stop, resulting in a hazardous situation. Make sure the Operation Unit, Mounting Latches, and the Switch Units are properly assembled.

  <Assembling the Operation Unit and the Mounting Latches>
  Align the TOP indication (the ⇩ mark) on the Operation Unit with the TOP indication on the Mounting Latches to fit it properly, and turn the lock lever on the Mounting Latch in the direction shown in the figure below until a clicking sound is heard.



  <Assembling the Mounting Latches and Switch Blocks>
  Make sure the hooking part (convex part) on the Mounting Latches is perfectly latched into the hooking part (concave part) on the Switch Block.



- When transition wiring is performed, make sure the switching current inside the Switch and the current based on the transition wiring is below the rated current of the Switch.
  If a current value higher than the rated current flows, it could result in emission of heat, or damage and deformation of the Switch, which could cause fire and locking of the contact, and thus a loss of safety.
- Do not disassemble or modify the Switch/Indicator under any circumstances.
- Doing so may prevent the Switch/Indicator from functioning to its full capability. Do not drop the Switch/Indicator. Do not apply pressure that may deform or alter the Switch/Indicator.
- The durability of the Switch varies considerably depending on the switching conditions. Always test the Switch/Indicator under actual working conditions before application and use the Switch/Indicator only for the number of switching operations allowed.
- Do not allow the load voltage and current to exceed the rated value. This may damage or burn out the Switch/Indicator.
- Do not use the Switch/Indicator in locations where explosive or flammable gases or liquid may be present or scattered. The electric ark or the heat caused by switching contacts may cause a fire or explosion.
- Do not use the Switch/Indicator in locations where toxic gases, such as H_2S, SO_2, NH_3, HNO_3, and Cl_2, may be present, or in locations subject to high temperature or humidity. Doing so may damage the Switch/Indicator due to contact failure or corrosion.
- Do not use the Switch/Indicator submersed in oil or water, or in locations continuously subject to splashes of oil or water. Doing so may result in oil or water entering and damaging the Switch/Indicator.
- Do not use or keep the Switch/Indicator under the following conditions:
  - Subject to severe temperature changes.
  - Subject to high humidity or condensation.
  - Subject to severe vibration or shock.
  - Where direct rays of the sun strike.
  - Where sea breeze may be present.
- Make sure that a rubber washer is present between the Operation Unit and the panel. In models with IP69K, make sure the rubber bush of the Operation Unit is properly attached.
  Otherwise, the specifications of the protective structure may not be satisfied.
- Do not apply excessive force to the Switch or wirings. Damage or deformation of the Switch Block could cause an improper contact or a loss of safety.
- Use an appropriate wiring and crimp terminals (hereinafter, called ferrule terminals).
- Exercise caution to avoid wiring errors when connecting the terminals.
- To prevent wiring materials from smoking or ignition, confirm wire ratings and use the wiring materials given in the following table.

Wire Type	Wire material	Recommended Wire	Wire coating peeling amount
Solid wire/ Stranded Wire	Copper	0.25 to 1.5 mm^2 AWG 24 to 16	Ferrules used: 10 to 12 mm (Varies depending on the recommended ferrule conductor length) Ferrules not used: 8 mm

  Use wiring crimp terminals and ferrule terminals of the specified size.
- After storing the product for a long time exceeding 1 year, perform, at a minimum, inspections of the operating characteristics, contact resistance, insulation resistance, and dielectric strength as well as evaluate the product under the working conditions.
- This Switch/Indicator is intended for indoor use only.
  Using the Switch/Indicator outdoors may result in failure.
- Do not wire anything to the release holes.
- Do not tilt or twist a flat-blade screwdriver while it is inserted into a release hole on the terminal block. The terminal block may be damaged.
- Insert a flat-blade screwdriver into the release holes at an angle. The terminal block may be damaged if you insert the screwdriver straight in.
- Do not allow the flat-blade screwdriver to fall out while it is inserted into a release hole.
- Do not bend a wire past its natural bending radius or pull on it with excessive force.
  Doing so may cause the wire disconnection.

chanhvinh.com


- Do not insert more than one wire into each terminal insertion hole.
- Do not mount A22N-P or A22NE-P Push-In Plus terminal switch blocks on A22N screw terminal blocks. Doing so may result in unsatisfactory performance.
- When mounting on a device with high airtightness, test operation in advance. There is a risk that the negative pressure will prevent the Operation Unit of from returning.
- In the case of loads where an inrush current occurs when the contact is opened or closed, the durability may reduce due to extreme wear on the contacts.
  If necessary, insert a contact protection circuit.

Precautions for Correct Use

Wiring


1. Connecting Wires to the Push-In Plus Terminal Block

Part Names of the Terminal Block



Connecting Wires with Ferrules and Solid Wires

- Insert the solid wire or ferrule straight into the terminal block until the end strikes the terminal block. The angle should be approximately 6°.
- If a wire is difficult to connect because it is too thin, use a flat-blade screwdriver in the same way as when connecting stranded wires.




The wiring for the Lighting Unit and Switch Block (2 contacts) are the same as for the Switch Block (1 contact) shown in the above illustration.

chanhvinh.com

Connecting Stranded Wires

Use the following procedure to connect the wires to the terminal block.

1. Hold a flat-blade screwdriver at an angle and insert it into the release hole.
   The angle should be approximately 6°. If the flat-blade screwdriver is inserted correctly, you will feel the spring in the release hole.
2. With the flat-blade screwdriver still inserted into the release hole, insert the wire into the terminal hole until the end strikes the terminal block.
3. Remove the flat-blade screwdriver from the release hole.



The wiring and screwdriver angles for the Lighting Unit and Switch Block (2 contacts) are the same as for the Switch Block (1 contact) shown in the above illustration.


Checking Connections

- After the insertion, pull gently on the wire to make sure that it will not come off and it is securely fastened to the terminal block.
- If you use a ferrule with a conductor length of 10 mm, part of the conductor may be visible after the ferrule is inserted into the terminal block, but the product insulation distance will still be satisfied.

2. Removing Wires from the Push-In Plus Terminal Block

Use the following procedure to remove wires from the terminal block. The same method is used to remove stranded wires, solid wires, and ferrules.

1. Hold a flat-blade screwdriver at an angle and insert it into the release hole. The angle should be approximately 6°.
2. With the flat-blade screwdriver still inserted into the release hole, remove the wire from the terminal insertion hole.
3. Remove the flat-blade screwdriver from the release hole.



The wiring and screwdriver angles for the Lighting Unit and Switch Block (2 contacts) are the same as for the Switch Block (1 contact) shown in the above illustration.

3. Recommended Ferrules and Crimp Tools

Coating peeling amount


Recommend Wire Type	Stripping length (Ferrules not used)
0.25 to 1.5 mm²/AWG 24 to AWG 16	8 mm

Recommended ferrules

Applicable wire		Ferrule conductor length (mm)	Stripping length (mm) (Ferrules not used)	Recommended ferrules		
(mm²)	(AWG)			Phoenix Contact product	Weidmuller product	Wago product
0.25	24	8	10	AI 0, 25-8	H0.25/12	216-301
		10	12	AI 0, 25-10	---	---
0.34	22	8	10	AI 0, 34-8	H0.34/12	216-302
		10	12	AI 0, 34-10	---	---
0.5	20	8	10	AI 0, 5-8	H0.5/14	216-201
		10	12	AI 0, 5-10	H0.5/16	216-241
0.75	18	8	10	AI 0, 75-8	H0.75/14	216-202
		10	12	AI 0, 75-10	H0.75/16	216-242
1/1.25	18/17	8	10	AI 1-8	H1.0/14	216-203
		10	12	AI 1-10	H1.0/16	216-243
1.25/1.5	17/16	8	10	AI 1, 5-8	H1.5/14	216-204
		10	12	AI 1, 5-10	H1.5/16	216-244
Recommended Crimp Tools				CRIMPFOX6 CRIMPFOX6T-F CRIMPFOX10S	PZ6 roto	Variocrimp4


Note: 1. Make sure that the outer diameter of the wire coating is smaller than the inner diameter of the insulation sleeve of the recommended ferrule.

2. Make sure that the ferrule processing dimensions conform to the following figures.



Recommended Flat-Blade Screwdrivers

Use a flat-blade screwdriver to connect and remove wires.
Use one of the following flat-blade screwdrivers.
The following table shows manufacturers and models as of 2015/Dec.



Model	Manufacture
ESD 0,40 × 2,5	Wera
SZS 0,4 × 2,5 SZF 0-0,4 × 2,5 ✻	Phoenix Contact
0.4 × 2.5 × 75 302	Wiha
AEF.2,5 × 75	Facom
210-719	Wago
SDI 0,4 × 2,5 × 75	Weidmuller

✻ The SZF 0-0,4 × 2,5 (manufactured by Phoenix Contact) can be procured through an OMRON exclusive purchase form (XW4Z-00B).

- After wiring the Switch/Indicator, provide a sufficient insulation distance.


chanhvinh.com

LED Lamps

- A current-limiting resistor is built in the LED lamp, so the installation of an external resistance is not required.
- Lighting malfunction of the LED lamp
  A micro-current of approximately 0.1 mA or less is sufficient to turn on the LED lamps. Take a countermeasure like adding a resistor to prevent mis-lighting in parallel to the LED lamp.
  The micro-current varies with the machine (leak current or stray capacity between cables, etc.). Select resistance value and allowable power consumption that meet the actual current.

(Example of lighting malfunction prevention circuit)

When using a 24-VAC/VDC lighted unit



Be sure to read the *"Safety Precautions"* on page 56.

chanhvinh.com

Emergency Stop Pushbutton Switches (22-dia. or 25-dia.) Screw Terminal Block types


A22E

Install in 22-dia. or 25-dia. Panel Cutout

(When Using a Ring)

- Increase wiring efficiency with three-row mounting of Switch Units. (with non-lighted Switch Blocks, three Units can be mounted for multiple contacts).
- Mounted using either open-type (fork-type) or closed-type (round-type) crimp terminals.
- Oil-resistant to IP65 (non-lighted models) / IP65 (lighted models).
- A lock plate is provided as a standard feature to ensure that the control box and switch are not easily separated.

⚠ Be sure to read the "*Safety Precautions*" on pages 50 and 56.



For the most recent information on models that have been certified for safety standards, refer to your OMRON website.

Model Number Structure

Model Number Legend (Completely Assembled)

.....Shipped as a set which includes the Operation Unit, LED Lamp (lighted model only), Mounting Latches, Switch Block, and Lock Plate

A22E □ - □ - □ - □ - □ - □ (Example: A22EL-M-24A-01)

(1 2 3 4 5 6)

1. Lighted/Non-lighted

Code	Description
None	Non-lighted
L	Lighted ✻

✻ Lighted Emergency Stop Switches are available only for the medium (M). turn-reset models.

2. Operation Unit size (diameter)/Reset function

Code	Size	Description
MP	40 dia.	Pull-reset
S	30 dia.	Turn-reset
M	40 dia.	
L	60 dia.	

3. LED Lamp voltage

Lighting unit (Direct lighting)

Code	Description	Operating Voltage
None	Non-lighted	---
6 A	Lighted (LED) ✻	6 VAC/DC
12 A		12 VAC/DC
24 A		24 VAC/DC

Lighting unit (Voltage-reduction lighting)


Code	Description	Operating Voltage
T1	Lighted (LED) ✻	100 VAC
T2		200 VAC

✻ Equipped with 24-VAC/DC LED.

4. Contacts

Code	Number of Switch Blocks		Unit position					
			Non-lighted			Lighted		
	NO	NC	1	2	3	1	2	3
01	0	1	NC	---	---	NC	---	Lighting unit
11	1	1	NC	NO	---	NC	NO	Lighting unit
02	0	2	NC	NC	---	NC	NC	Lighting unit
12	1	2	NC	NO	NC	---		
03	0	3	NC	NC	NC			

Note 1. NO: 1a-contact NC: 1b-contact
2. For details on the unit position, refer to the figure below.



5. Configuration

Code	Configuration
None	Switch only
B	Switch with Integrated Control Box

6. Configuration

Code	Configuration
None	Neither "EMO" nor "EMS" printed, arrows engraved in red.
EMO	"EMO" and arrows printed in white.
EMO-RD	"EMO" printed in white, arrows engraved in red.
EMS	"EMS" and arrows printed in white.
EMS-RD	"EMS" printed in white, arrows engraved in red.

chanhvinh.com

A22E

Ordering Information

List of Models (Completely Assembled)

Non-lighted Models (Without EMO/EMS Indication)

Appearance	Operation	Degree of Protection	Contact configuration ✻1	Set Model	Color of cap
	40-dia. head Medium Pull-reset A22E-MP	IP65 oil-resistant models	1NC (1)	**A22E-MP-01**	Red
			1NC, 1NO (2)	**A22E-MP-11**	
			2NC (2)	**A22E-MP-02**	
	30-dia. head Small Turn-reset A22E-S		1NC (1)	**A22E-S-01** ✻2	
			1NC, 1NO (2)	**A22E-S-11** ✻2	
			2NC (2)	**A22E-S-02** ✻2	
			2NC, 1NO (3)	**A22E-S-12** ✻2	
			3NC (3)	**A22E-S-03** ✻2	
	40-dia. head Medium Turn-reset A22E-M		1NC (1)	**A22E-M-01** ✻2	
			1NC, 1NO (2)	**A22E-M-11** ✻2	
			2NC (2)	**A22E-M-02** ✻2	
			2NC, 1NO (3)	**A22E-M-12** ✻2	
			3NC (3)	**A22E-M-03** ✻2	
	60-dia. head Large Turn-reset A22E-L		1NC (1)	**A22E-L-01** ✻2	
			1NC, 1NO (2)	**A22E-L-11** ✻2	
			2NC (2)	**A22E-L-02** ✻2	

✻1. The number in parentheses ( ) indicates the number of switch units.
✻2. Models with Korean S-mark certification
Note: Yellow cap models are also available (not for emergency stop use). Contact your OMRON representative.

Non-lighted Models (With EMO/EMS Indication)

Appearance	Operation	Degree of Protection	Contact configuration ✻1	Set Model	Color of cap
	40-dia. head Medium Turn-reset With EMO Indication	IP65 oil-resistant models	1NC (1)	**A22E-M-01-EMO** ✻2	Red
				A22E-M-01-EMO-RD	
			1NC, 1NO (2)	**A22E-M-11-EMO** ✻2	
				A22E-M-11-EMO-RD	
			2NC (2)	**A22E-M-02-EMO** ✻2	
				A22E-M-02-EMO-RD	
			2NC, 1NO (3)	**A22E-M-12-EMO** ✻2	
				A22E-M-12-EMO-RD	
			3NC (3)	**A22E-M-03-EMO** ✻2	
				A22E-M-03-EMO-RD	
	40-dia. head Medium Turn-reset With EMS Indication		1NC (1)	**A22E-M-01-EMS** ✻2	
				A22E-M-01-EMS-RD	
			1NC, 1NO (2)	**A22E-M-11-EMS** ✻2	
				A22E-M-11-EMS-RD	
			2NC (2)	**A22E-M-02-EMS** ✻2	
				A22E-M-02-EMS-RD	
			2NC, 1NO (3)	**A22E-M-12-EMS** ✻2	
				A22E-M-12-EMS-RD	
			3NC (3)	**A22E-M-03-EMS** ✻2	
				A22E-M-03-EMS-RD	

✻1. The number in parentheses ( ) indicates the number of switch units.
✻2. Models with Korean S-mark certification
Note: The colors of switch blocks are as follows:
NO (a-contact): Black
NC (b-contact): Red
The above illustration shows the 2NC (2b-contact) configuration.

chanhvinh.com

Lighted Models

Appearance	Operation	Degree of Protection	Contact configuration ✻1	LED Lamp voltage	Set Model	Color of cap
	40-dia. head Push-lock Turn-reset Lighting unit (Direct lighting) A22E	IP65	1NC (1)	6 VAC/VDC	**A22EL-M-6A-01 ✻2**	Red
				12 VAC/VDC	**A22EL-M-12A-01 ✻2**	
				24 VAC/VDC	**A22EL-M-24A-01 ✻2**	
			1NC, 1NO (2)	6 VAC/VDC	**A22EL-M-6A-11 ✻2**	
				12 VAC/VDC	**A22EL-M-12A-11 ✻2**	
				24 VAC/VDC	**A22EL-M-24A-11 ✻2**	
			2NC (2)	6 VAC/VDC	**A22EL-M-6A-02 ✻2**	
				12 VAC/VDC	**A22EL-M-12A-02 ✻2**	
				24 VAC/VDC	**A22EL-M-24A-02 ✻2**	
	40-dia. head Push-lock Turn-reset Lighting unit (Voltage-reduction lighting) A22E		1NC (1)	100 VAC	**A22EL-M-T1-01**	
				200 VAC	**A22EL-M-T2-01**	
			1NC, 1NO (2)	100 VAC	**A22EL-M-T1-11**	
				200 VAC	**A22EL-M-T2-11**	
			2NC (2)	100 VAC	**A22EL-M-T1-02**	
				200 VAC	**A22EL-M-T2-02**	

✻1. The number in parentheses ( ) indicates the number of switch units.
✻2. Models with Korean S-mark certification

Switch with Integrated Control Box

Appearance	Contact configuration (Number of switch blocks)	Model
	1NC (1)	**A22E-M-01B ✻**
	1NC, 1NO (2)	**A22E-M-11B ✻**
	2NC (2)	**A22E-M-02B ✻**

Note: The A22Z-B101Y Control Box is used.
✻ Models with Korean S-mark certification

chanhvinh.com

A22E

Subassembled .... The Operation Unit, LED Lamp, Mounting Latches, and Switch Blocks can be ordered separately. Use them in combination for models that are not available as assembled Units. These can also be used as inventory for maintenance parts.

Non-lighted

Operation Unit




Lighted

Operation Unit



Mounting Latches




LED Lamp

LED




Switch Blocks ✻

Screw Terminal Block



Switch Blocks + Lighting unit

Screw Terminal Block



Lock Plate



Lock Plate



✻ Up to three Switch Blocks can be mounted.

chanhvinh.com

Operation Unit
Non-lighted

Function	Sealing capability	Size	Small (30 dia.)	Medium (40 dia.)	Large (60 dia.)
			Single item order model		
Pull-reset	IP65 oil-resistant models		---	A22E-MP 	---
Turn-reset	IP65 oil-resistant models		A22E-S 	A22E-M 	A22E-L 
				A22E-M-EMO A22E-M-EMO-RD 	
				A22E-M-EMS A22E-M-EMS-RD 	

Lighted

Function	Sealing capability	Size	Medium (40 dia.)
			Single item order model
Turn-reset	IP65		A22EL-M 

LED lamp



Appearance	LED light		Rated voltage	Model
	Red	Standard	6 VAC/VDC	**A22-6AR**
			12 VAC/VDC	**A22-12AR**
			24 VAC/VDC	**A22-24AR**

Note: For a model with a Lighting unit (Voltage-reduction lighting), use the A22-24AR.



chanhvinh.com

A22E

Switch
Non-lighted / Direct lighting

Classification		Non-lighted	Direct lighting
Appearance			
Contact specifications/ Configuration (Number of switch blocks)		Model	Model
For Standard loads	1NC (1)	A22-01M	A22L-01M
	1NC, 1NO (2)	A22-11M	A22L-11M
	2NC (2)	A22-02M	A22L-02M



Voltage-reduction lighting (100 VAC, 200 VAC)

Classification		100 VAC, Lighted	200 VAC, Lighted
Appearance			
Contact specifications/ Configuration (Number of switch blocks)		Model	Model
For Standard loads	1NC (1)	A22L-01M-T1	A22L-01M-T2
	1NC, 1NO (2)	A22L-11M-T1	A22L-11M-T2
	2NC (2)	A22L-02M-T1	A22L-02M-T2

Note: For a model with a Lighting unit (Voltage-reduction lighting), use the A22-24AR.

chanhvinh.com

Accessories (Order Separately)

Item	Appearance	Contact specifications		Model	Remarks
Switch Blocks (one contact)		1NO (Black)	Standard load	**A22-10**	Provided as standard. Order Switch Blocks only when adding or replacing them.
			Microload	**A22-10S**	
		1NC (Red)	Standard load	**A22-01**	
			Microload	**A22-01S**	
Switch Blocks (two contacts)		2NO (Black)	Standard load	**A22-20**	Order Switch Blocks only when adding or replacing them.
			Microload	**A22-20S**	
		2NC (Red)	Standard load	**A22-02**	
			Microload	**A22-02S**	
		1NC + 1NO Contact (Black/ Red)	Standard load	**A22-11**	
			Microload	**A22-11S**	
Lighting unit		Direct lighting		**A22-TN**	Used when changing the lighting method.
		Voltage-reduction lighting	100 VAC	**A22-T1**	
			200 VAC	**A22-T2**	
Mounting Latches		---		**A22-3200**	Provided as standard. Order Mounting Latches only when mounting Switch Blocks or Lighting Units that are purchased individually.
Lock Plate		---		**A22Z-3380**	Use to fix the lever on the Switch.
Control Boxes (Enclosures)		One hole, yellow box		**A22Z-B101Y**	Material: Polycarbonate resin. When using a Control Box, 2NO, 2NC, or 1NC + 1NO two-contact Switch Blocks are not supported. ✻
				A22Z-B201Y	

Note: For details on the accessories common to the screw terminal block types and push-in plus terminal block types, refer to *"Common Accessories and Tools (Order Separately)"* on page 51.

✻ The A22NZ-B101Y and A22NZ-B201Y Control Box cannot be used in combination with the A22Z-3476-1 90-dia. Legend Plates for Emergency Stop or the A22Z-EG□ E-stop Shrouds.

chanhvinh.com

A22E

Specifications

Certified Standard Ratings

- UL, cUL (File No. E41515)
  6 A at 220 VAC, 10 A at 110 VAC
- TÜV (EN60947-5-1) (Low Voltage Directive)
  3 A at 220 VAC
- CCC (GB14048.5)
  3 A at 240 VAC, 1.5 A at 24 VDC

Certified Standards

Certification body	Standards	File No.
UL ✻1	UL508, C22.2 No.14	E41515
TÜV SÜD	EN60947-5-1 (Certified direct opening), EN60947-5-5	Consult your OMRON representative for details.
CQC (CCC)	GB14048.5	2003010303070635
KOSHA ✻2	EN60947-5-1	Consult your OMRON representative for details.

Note: 1. Only models with NC contacts have a direct opening mechanism.
2. A fuse is not provided.

✻1. UL-certification for CSA C22.2 No. 14 has been obtained. Certification has been obtained for individual Switch Blocks and Lighting Units.

✻2. Some models have been certified.

Ratings

Contacts (Standard Load)

Rated carry current (A)	Rated voltage (V)	Rated current (A)			
		AC15 (Inductive load)	AC12 (Resistive load)	DC13 (Inductive load)	DC12 (Resistive load)
10	24 VAC	10	10	---	---
	110 VAC	5	10		
	220 VAC	3	6		
	380 VAC	2	3		
	440 VAC	1	2		
	24 VDC	---	---	1.5	10
	110 VDC			0.5	2
	220 VDC			0.2	0.6
	380 VDC			0.1	0.2

Note: 1. Rated current values are determined according to the testing conditions. The above ratings were obtained by conducting tests under the following conditions.
(1) Ambient temperature: 20°±2°C
(2) Ambient humidity: 65±5%
(3) Operating frequency: 20 operations/minute
2. Minimum applicable load: 10 mA at 5 VDC

Contacts (Microload)

Rated applicable load	100 mA at 30 VDC (Resistive load)
Minimum applicable load	1 mA at 5 VDC

LED Lamp

Rated voltage	Operating voltage	Current value
6 VAC/VDC	6 VAC/VDC ± 5%	Approx. 8 mA
12 VAC/VDC	12 VAC/VDC ± 5%	
24 VAC/VDC	24 VAC/VDC ± 5%	

Voltage-reduction lighting

Rated voltage	Operating voltage	Rated current	Applicable lamp (BA9S/Base: 13)
110 VAC	100 VAC (95 to 115 V)	Approx. 8 mA	LED lamp A22-24A□
220 VAC	200 VAC (190 to 230 V)		

Characteristics

Item	Type	Turn-reset		Pull-reset
		Non-lighted model	Lighted model	Non-lighted model
Allowable operating frequency	Mechanical	30 operations/minute (One operation consists of set and reset operations.)		
	Electrical	30 operations/minute (One operation consists of set and reset operations.)		
Insulation resistance		100 MΩ min. (at 500 VDC)		
Contact resistance		100 mΩ max. (initial value)		
Dielectric strength	Between terminals of same polarity	2,500 VAC, 50/60 Hz for 1 min.		
	Between each terminal and ground	2,500 VAC, 50/60 Hz for 1 min.		
Vibration resistance		10 to 55 Hz, 1.5-mm double amplitude (contact separation within 1 ms)		
Shock resistance	Destruction	1000 m/s^2		
	Malfunction	250 m/s^2 max. (contact separation within 1 ms)		
Durability	Mechanical	300,000 operations min. (One operation consists of set and reset operations.)		
	Electrical	300,000 operations min. (One operation consists of set and reset operations.)		
Ambient operating temperature ✻1		-20 to +70°C	-20 to +55°C	-20 to +70°C
Ambient operating humidity		35 to 85% RH		
Ambient storage temperature		-40 to +70°C		
Degree of protection		IP65 oil-resistant models ✻2 ✻3	IP65 ✻2	IP65 oil-resistant models ✻2 ✻3
Electric shock protection class		Class II		
PTI (tracking characteristic)		175		
Degree of contamination		3 (EN60947-5-1)		
Minimum direct opening stroke		11 mm		
Minimum direct opening force		45 N		
Conditional short-circuit current		100 A (EN 60947-5-1)		
Weight (for a 40-dia. head 1NC/1NO Operation Unit)		Approx. 65 g	Approx. 80 g	Approx. 100 g

✻1. With no icing or condensation.
✻2. The degree of protection from the front of the panel.
✻3. The degree of protection is IP65 even with an integrated control box, but the system is not oil resistant.




chanhvinh.com

Operating Characteristics









Item	Turn-reset	Pull-reset
Total travel force (TTF)	44.1 N max.	58.8 N max.
Return force (RF)	0.25 N·m max. ✻	58.8 N max.
Total travel (TT)	10 ±1 mm	5.5 ±1 mm

✻ Rotation torque value.

Terminal Arrangement (BOTTOM VIEW)


Non-lighted (two contacts)	Non-lighted (three contacts)	Lighted (two contacts)
		

Terminal connection

Type	Terminal Connection (BOTTOM VIEW)			
	1NC, 1NO (two contacts)	2NC (two contacts)	2NC, 1NO (three contacts)	3NC (three contacts)
Non-lighted				
Lighted with Direct lighting				
Lighted with Voltage-reduction lighting				

Note: The above terminal connection diagrams are examples of the number of contacts.

Terminal wiring drawings of two-contact Switch Units




Type	Terminal Connection (BOTTOM VIEW)		
	2NC (two contacts)	2NO (two contacts)	1NC, 1NO (two contacts)
A			
B			

chanhvinh.com

A22E

Structure and Nomenclature



Operation Unit

Color: Red


Non-lighted
LED lighting



Lamp

Light source

- LED Lamp



Switch


Mounting Latches
Switch Blocks
Lighting unit

Contact Ratings

10 A at 100 VAC (resistive load)
10 A at 24 VDC (resistive load)

Lighting Method

Non-lighted
Lighted (Direct lighting)
Lighted (Voltage-reduction lighting)



Lock Plate (Attached with the Operation Unit)

(Refer to the *"Mounting the Lock Plate"* on page 50 for use.)


Dimensions


(Unit: mm)

Non-lighted Models

A22E-MP

Medium Pull-reset (40-dia.) Degree of Protection:
IP65 oil-resistant models






A22E-S


Small Turn-reset (30-dia.) Degree of Protection:
IP65 oil-resistant models






A22E-M

Medium Turn-reset (40-dia.) Degree of Protection:
IP65 oil-resistant models






Note: The dimensions are the same as for EMO/EMS indication models.

A22E-L

Large Turn-reset (60-dia.)Degree of Protection:
IP65 oil-resistant models






Note: Unless otherwise specified, a tolerance of ±0.8 mm applies to all dimensions.


chanhvinh.com

Lighted Model

A22EL-M
Medium Turn-reset (40-dia.) Degree of Protection:
IP65 oil-resistant models



Switch dimensions when mounted to a 2NO (2NC) one-piece switch block




Note: The operation unit is an example for the A22E-M.

Note: Unless otherwise specified, a tolerance of ±0.8 mm applies to all dimensions.

Accessories (Order Separately)


LED Lamp

A22-6□, 12□, 24□




Control Box


A22Z-B101Y (1-hole)



Cable Draw-out Hole (Top View)




Mounting Hole




Control Box


A22Z-B201Y (1-hole)



Cable Draw-out Hole (Top View)



Mounting Hole



Note: For details on the accessories common to the screw terminal block types and push-in plus terminal block types, refer to *"Common Accessories and Tools (Order Separately)"* on page 51.

chanhvinh.com


A22E

Installation

Mounting to the Panel

(1) Preparing the Panel

- The panel dimensions are shown below.
- The panel thickness must be 1 to 5 mm.




With Lock Ring **Without Lock Ring**

- Always use a 25-mm-dia. A22Z-R25 Lock Ring for a 25-mm-dia. hole. IP65 degree of protection will be lost if the 25-mm-dia. Lock Ring is not used because of the larger size of a 25-mm-dia. hole.
- When painting or coating the panel, make sure that the specified panel dimensions apply to the panel after painting or coating.


(3) Mounting the Switch on the Operation Unit

- Insert the Operation Unit into the Switch Unit, aligning the arrow mark inscribed on the Case with the lever on the Switch Blocks, then move the lever in the direction indicated by the arrow in the following figure.




(4) Removing the Switch

- Move the lever in the direction indicated by the arrow in the following figure, then pull the Operation Unit or the Switch Blocks.
  Since the lever has a hole with an inside diameter of 6.5 mm, the lever can be moved in the specified direction by inserting a screwdriver into the hole and then moving the screwdriver.




(2) Mounting the Operation Unit on the Panel


- Insert the Operation Unit from the front surface of the panel, insert the Lock Ring and the Tightening Nut from the terminal side, then tighten the Ring. Before tightening, check that the rubber washer is present between the Operation Unit and the panel.
- Align the Lock Ring with the groove in the casing, then insert the Lock Ring so that its edge is located on the panel side.
- Tighten the Tightening Nut at a torque of 1.0 to 2.0 N·m.
- When using a Lock Ring, replace with the supplied Lock Ring, insert the projecting part into the lock slot, and then tighten the Tightening Nut.



1. When the panel cutout dimension is 25 dia., remove the supplied rubber washer and mount the 25-dia. Ring as shown below. (Since the A22Z-R25 is not attached to the main body, order separately.) When using a Legend Plate (Order Separately), do not remove the rubber washer.




2. When the panel cutout dimension is 30 dia., use resin attachment A22Z-A30. Since it is not attached to the main body, order separately.



Assembling the Cap

Emergency Stop Switch

- Insert the protrusion of the Tightening Wrench (A22Z-3905) into the Cap slot and then turn to remove the Cap.




chanhvinh.com

Installing/Replacing the LED Lamp

Installing/Replacing on the Switch


• Grip the lamp with your fingers, then rotate the lamp while pressing it against the Switch.



Control Box (Enclosure)


(1) Mounting the Switch

The Standard-size Legend Plate Frame can be mounted.
Mount the Frame as shown in the following diagram. Mount the Switch in the same way as for an ordinary panel.




(2) Creating a Cable Port Hole

Place the tip of a screwdriver on the surface where the cable port hole is to be created with the cover attached and strike the screwdriver to punch a hole.
Attempts to punch a hole on the other side of the case will damage the Box.



(3) Securing the Connector Cable

1. Insert the connector into the cable port hole in the Box and secure with the Mounting Ring inside the box.
2. Pass the tightening cap through the cable, insert the cable into the connector, and tighten the tightening cap to secure the cable.




Cable diameter (mm)	Connector
7 to 9 dia.	**A22Z-3500-1**
9 to 11 dia.	**A22Z-3500-2**

Installing/Removing the Switch Blocks


(1) Installing the Switch Blocks

• Hook the small protrusion on the Mounting Latch into the groove on the other side of the lever, then push up the Switch Block in the direction indicated by the arrow in the figure below.



(2) Removing the Switch Blocks

• Insert a screwdriver between the Mounting Latch and the Switch Block, then push down the screwdriver in the direction indicated by the arrow in the following figure.



Use either of the following screwdrivers.


⊖ Flat-head screwdriver 3 to 6 mm

⊕ Phillips screwdriver 3 to 6 mm dia.

Wiring

Wiring Round Crimp Terminals

• Loosen the terminal screw from the Switch Unit until it completely comes off the groove, insert a screwdriver as shown in the following figure, then push up the washer in the direction indicated by the arrow to temporarily secure it.
Now, a round crimp terminal can be connected. After inserting the terminal, tighten the screws to complete wiring.



chanhvinh.com

A22E

Safety Precautions

Be sure to read the precautions **for All PushButton Switches** in the website at:http://www.ia.omron.com/.

Indication and Meaning for Safe Use

⚠ Warning	**Indicates a potentially hazardous situation that, if not avoided, could result in serious injury or death. Additionally there may be significant property damage.**
⚠ CAUTION	**Indicates a potentially hazardous situation which, if not avoided, may result in minor or moderate injury or in property damage.**
Precautions for Safe Use	**Supplementary comments on what to do or avoid doing, to use the product safely.**

⚠ WARNING

Do not perform wiring with power supplied to the Switch/ Indicator. Do not touch the terminals or other charged parts while power is being supplied. Doing so may result in electric shock.



⚠ Caution


If the Operation Unit is separated from the Socket Unit, the equipment will not stop, creating a hazardous condition. Secure the lever on the Socket Unit by using the A22Z-3380 Lock Plate so that the Operation Unit cannot be easily separated from the Socket Unit.
(Refer to "*Mounting the Lock Plate*" at the below.)



Precautions for Correct Use

Mounting the Lock Plate


1. Confirm that the lever on the Mounting Latch is on the side where the Operation Unit is secured and then insert the protrusion on the Lock Plate into the hole in the lever on the Mounting Latch.
2. Press the hole on the Lock Plate onto the protrusion on the Mounting Latch until it clicks into place.




Wiring

- Terminal screws must be Phillips or slotted M3.5 screws with a square washer.
- The tightening torque is 1.08 to 1.27 N·m.
- Single wires, stranded wires, and crimp terminals can be connected to the Switch.
- Applicable Wiring Materials:
  Twisted strands: 2 mm² max.
  Solid wire: 1.6 mm dia. max.

Naked Crimp Terminals



Crimp Terminals with Insulating Sheaths




- After wiring the Switch, maintain an appropriate clearance and creepage distance.

LED Lamps

- The LED current-limiting resistor is built-in, so internal resistance is not required.
- If commercially available LEDs are used, select the ones that meet the following conditions:
  Base: BA9S/13
  Overall length: 26 mm max.
  Power consumption: 2.6 W max.
  When DC-specific LEDs are used, wire the Switch so that the X1 terminal is positive.
- Mis-lighting of the LED
  The LED lights with approx. 0.1 mA or less of micro-current. Take a countermeasure like adding a resistor to prevent mis-lighting in parallel to the LED.
  The micro-current varies with the machine (leak current or stray capacity between cables, etc.). Select resistance value and allowable power consumption that meet the actual current.

(Circuit example)


In case of using 24 VAC/VDC, Direct lighting



- Do not use a lamp that does not satisfy the rating.

Using the Microload

Contact failure may occur if a Switch designed for a standard load is used to switch a microload. Use Switches within the application ranges shown in the following graph. Even within the application range, insert a contact protection circuit, if necessary, to prevent the reduction of life expectancy due to extreme wear on the contacts caused by loads where inrush current occurs when the contact is opened and closed.
The minimum applicable load is the N-level reference value. This value indicates the malfunction reference level for the reliability level of 60% (λ_{60}) (conforming to JIS C5003).
The equation, $\lambda_{60} = 0.5 \times 10^{-6}$/time indicates that the estimated malfunction rate is less than 1/2,000,000 with a reliability level of 60%.



Be sure to read the *"Safety Precautions"* on page 56.

chanhvinh.com

Common Accessories and Tools (Order Separately)

Ordering Information

Common to Push-in Plus Terminal Block types (A22NE-PD/A22NE-P)/Screw Terminal Block types (A22E)

Item	Appearance	Classification		Model	Remarks
Legend Plates for Emergency Stop		60-dia. black letters on yellow back-ground		A22Z-3466-1	Used in combination with the rubber packing when the level of protection is to be met between panels. ✻1
		90-dia. black letters on yellow back-ground		A22Z-3476-1	Used in combination with the rubber packing when the level of protection is to be met between panels. ✻1 ✻3
		60-dia. black letters on yellow background		A22Z-3466-2	Used in combination with the rubber packing when the level of protection is to be met between panels. ✻1
Hole Plug		Round		A22Z-3530	Used for covering the panel cutouts for future panel expansion. Black color.
Connectors		Applicable cable diameter	7 to 9 dia.	A22Z-3500-1	Plastic connector used to extend a cable from the Switch Box. (Refer to page 16, 32, and 49).
			9 to 11 dia.	A22Z-3500-2	
25-dia. Ring		---		A22Z-R25	Use when mounting to a panel with a 25-dia. hole. (Refer to page 16, 31, and 48). Material: Rubber, Level of protection: IP65
30-dia. Resin Attachment		---		A22Z-A30	Use when mounting to a panel with a 30-dia. hole. (Refer to page 16, 31, and 48). A rubber packing is provided with the product.
Lock Ring		---		A22Z-3360	The body is equipped with a Lock Ring. This Lock Ring is used when a more secure lock feature is required. (Refer to page 16 and 31).
Tightening Tool		---		A22Z-3905	Used for tightening the tightening nut from the back side of the panel, and for removing the cap in lighted models.
E-stop Shroud for EMO, Yellow		---		A22Z-EG1	Provides SEMI-S2/SEMATECH APPLICATION GUIDE FOR SEMI-S2 compatibility. The SEMI-S2-compatible Shroud and legend plate for EMERGENCY OFF come as a set. Use with an A22E Emergency Stop Switch (for emergency shutoff) ✻2 ✻3
E-stop Shroud for EMO, Yellow		Legend plate for EMERGENCY OFF is not included.		A22Z-EG10	Provides SEMI-S2/SEMATECH APPLICATION GUIDE FOR SEMI S2 compatibility. Use with an A22E with EMO indication. (for emergency off) ✻3
E-stop Shroud for EMS, White		---		A22Z-EG1-W	Provides SEMI-S2/SEMATECH APPLICATION GUIDE FOR SEMI-S2 compatibility. The SEMI-S2-compatible Shroud and legend plate for EMERGENCY STOP come as a set. Use with an A22E Emergency Stop Switch. (for emergency stop) ✻2 ✻3
E-stop Shroud for EMS, White		Legend plate for EMERGENCY STOP is not included.		A22Z-EG10-W	Provides SEMI-S2/SEMATECH APPLICATION GUIDE FOR SEMI S2 compatibility. Use with an A22E with EMS indication. (for emergency stop) ✻3
E-stop Shroud, Yellow		Spacer Unit is not included.		A22Z-EG2	SEMI-S2/SEMATECH APPLICATION GUIDE FOR SEMI S2-compatible Shroud. (for emergency shutoff) ✻2 ✻3 Use together with an A22E Emergency Stop Switch.
		One Spacer Unit is included.		A22Z-EG21	
		Two Spacer Units are included.		A22Z-EG22	
E-stop Shroud for EMO, Yellow		---		A22Z-EG3	Provides SEMI-S2/SEMATECH APPLICATION GUIDE FOR SEMI-S2 compatibility. The SEMI-S2-compatible Shroud and legend plate for EMERGENCY OFF come as a set. Use with an A22E Emergency Stop Switch.(for emergency shutoff) ✻2 ✻3
Rubber Packing		-		A22Z-R	Used together with accessories. Contains 10 packings.

✻1. If you use Legend Plates for Emergency Stop, set the thickness of the panels between 1 to 4 mm.
✻2. These Shrouds are for use with the equipment only that conforms to SEMI standards. Do not use them for any other applications (e.g. emergency stop switches for machines or devices such as Machine tools, Printing presses, Industrial machinery, etc).
✻3. The Control Boxes cannot be used in combination with the A22Z-3476-1 Legend Plates for Emergency Stop or the A22Z-EG□ E-stop Shrouds.

Note: 1. Accessories for A22Z-EG1: one “EMERGENCY OFF” label, two rubber packings, and one lock ring
2. Accessories for A22Z-EG10: one rubber packing and one lock ring (without label)

chanhvinh.com

A22NE-PD/A22NE-P/A22E


Dimensions

(Unit: mm)


Screw Terminal Block Type/Push-in Plus Terminal Block Type


Hole Plug
Round A22Z-3530





30-dia. Resin Attachment
A22Z-A30







Legend Plates for Emergency Stop




A22Z-3476-1 (90 dia.)




A22Z-3466-1 (60 dia.)




A22Z-3466-2 (60 dia.)



Lock Ring
A22Z-3360







Material: Nickel plated on iron

25-dia. Ring
A22Z-R25










Material: NBR (black)


Tightening Tool
A22Z-3905






Rubber Packing
A22Z-R






Connector
A22Z-3500









chanhvinh.com

Common E-stop Shrouds
A22Z-EG1, A22Z-EG1-W, A22Z-EG10, A22Z-EG10-W






Note: 1. The dimensions of the Shroud conform to the specifications of the SEMATECH Application Guide for SEMI S2-93.
2. The Shroud is not provided with the Switch.




"EMERGENCY STOP" is indicated on A22Z-EG1-W.
Legend plate is not provided with A22Z-EG10 and A22Z-EG10-W.


Screw Terminal Block type Mounting a 1-pole Switch Unit




Push-in Plus Terminal Block type Mounting a 1-pole Switch Unit




Push-in Plus Terminal Block type Mounting a 2-pole Switch Unit



Panel Cutout Dimensions





Model	Allowable panel thickness [mm]
A22NE-PD series	1 to 1.8
A22NE-P series	1 to 2.0
A22E series	




chanhvinh.com


E-stop Shrouds
A22Z-EG2, A22Z-EG21, A22Z-EG22









During spacer attachment






Note: 1. The dimensions of the Shroud conform to the specifications of the SEMATECH *Application Guide for SEMI S2-93.*
2. The Shroud is not provided with the Switch.
3. Tighten to a torque of 1.96 to 2.94 N·m.
4. The allowable panel thicknesses are as follows:
Without Spacers: t=1.3 to 22.5 mm
With 1 Spacer: t=1.3 to 12.5 mm
With 2 Spacers: t=1.3 to 2.5 mm


Screw Terminal Block Type Mounting a 1-pole Switch Unit ✻




Screw Terminal Block Type Mounting a 2-pole Switch Unit ✻



Push-in Plus Terminal Block Type Mounting a 1-pole Switch Unit ✻



Push-in Plus Terminal Block Type Mounting a 2-pole Switch Unit ✻




✻ These are the dimension from the front of the panel when the Switch Unit is attached.


chanhvinh.com

E-stop Shroud
A22Z-EG3







Screw Terminal Block Type Mounting a 1-pole Switch Unit




Screw Terminal Block Type Mounting a 2-pole Switch Unit




Push-in Plus Terminal Block Type Mounting a 1-pole Switch Unit




Push-in Plus Terminal Block Type Mounting a 2-pole Switch Unit







Panel Cutout Dimensions



Model	Allowable panel thickness [mm]
A22NE-PD series	1 to 1.8
A22NE-P series	1 to 2.0
A22E series	

Note: 1. The dimensions of the Shroud conform to the specifications of the SEMATECH *Application Guide for SEMI S2-93.*

2. The Shroud is not provided with the Switch.

chanhvinh.com

A22E/A22NE-P

Safety Precautions

Be sure to read the precautions **for All PushButton Switches** in the website at:http://www.ia.omron.com/.

Indication and Meaning for Safe Use

Precautions for Safe Use	**Supplementary comments on what to do or avoid doing, to use the product safely.**

Precautions for Correct Use

Mounting


- Always make sure that the power is turned OFF before wiring the Switch. Also, do not touch the terminals or other current-carrying ports while power is being supplied. Electric shock may occur.
- Do not tighten the tightening nut more than necessary by using tools such as pointed-nose pliers. Doing so could damage the tightening nut. (The tightening torque is 1.0 to 2.0 N·m.)
- Recommended panel thickness: 1 to 5 mm.
- When mounting the caps after changing the LED or the caps, tighten the caps at a tightening torque of 0.49 to 0.78 N·m.

Operating Environment

- This model is designed with a protective structure so that it will not sustain damage if it is subjected to water from any direction to the front of the panel.
- The Switch is intended for indoor use only. Using the Switch outdoor may cause it to fail.

Others

- If the panel is to be coated, make sure that the panel meets the specified dimensions after coating.
- Due to the structure of the Switch, severe shock or vibration may cause malfunctions or damage to the Switch.
  Also, most Switches are made from resin and will be damaged if they come into contact with sharp objects. Particularly scratches on the Operation Unit may create visual and operational obtrusions.
  Handle the Switches with care, and do not throw or drop them.



chanhvinh.com

Terms and Conditions Agreement

Read and understand this catalog.

Please read and understand this catalog before purchasing the products. Please consult your OMRON representative if you have any questions or comments.

Warranties.

(a) Exclusive Warranty. Omron's exclusive warranty is that the Products will be free from defects in materials and workmanship for a period of twelve months from the date of sale by Omron (or such other period expressed in writing by Omron). Omron disclaims all other warranties, express or implied.

(b) Limitations. OMRON MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, ABOUT NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OF THE PRODUCTS. BUYER ACKNOWLEDGES THAT IT ALONE HAS DETERMINED THAT THE PRODUCTS WILL SUITABLY MEET THE REQUIREMENTS OF THEIR INTENDED USE.

Omron further disclaims all warranties and responsibility of any type for claims or expenses based on infringement by the Products or otherwise of any intellectual property right. (c) Buyer Remedy. Omron's sole obligation hereunder shall be, at Omron's election, to (i) replace (in the form originally shipped with Buyer responsible for labor charges for removal or replacement thereof) the non-complying Product, (ii) repair the non-complying Product, or (iii) repay or credit Buyer an amount equal to the purchase price of the non-complying Product; provided that in no event shall Omron be responsible for warranty, repair, indemnity or any other claims or expenses regarding the Products unless Omron's analysis confirms that the Products were properly handled, stored, installed and maintained and not subject to contamination, abuse, misuse or inappropriate modification. Return of any Products by Buyer must be approved in writing by Omron before shipment. Omron Companies shall not be liable for the suitability or unsuitability or the results from the use of Products in combination with any electrical or electronic components, circuits, system assemblies or any other materials or substances or environments. Any advice, recommendations or information given orally or in writing, are not to be construed as an amendment or addition to the above warranty.

See http://www.omron.com/global/ or contact your Omron representative for published information.

Limitation on Liability; Etc.

OMRON COMPANIES SHALL NOT BE LIABLE FOR SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS OR PRODUCTION OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED IN CONTRACT, WARRANTY, NEGLIGENCE OR STRICT LIABILITY.

Further, in no event shall liability of Omron Companies exceed the individual price of the Product on which liability is asserted.

Suitability of Use.

Omron Companies shall not be responsible for conformity with any standards, codes or regulations which apply to the combination of the Product in the Buyer's application or use of the Product. At Buyer's request, Omron will provide applicable third party certification documents identifying ratings and limitations of use which apply to the Product. This information by itself is not sufficient for a complete determination of the suitability of the Product in combination with the end product, machine, system, or other application or use. Buyer shall be solely responsible for determining appropriateness of the particular Product with respect to Buyer's application, product or system. Buyer shall take application responsibility in all cases.

NEVER USE THE PRODUCT FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY OR IN LARGE QUANTITIES WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO ADDRESS THE RISKS, AND THAT THE OMRON PRODUCT(S) IS PROPERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM.

Programmable Products.

Omron Companies shall not be responsible for the user's programming of a programmable Product, or any consequence thereof.

Performance Data.

Data presented in Omron Company websites, catalogs and other materials is provided as a guide for the user in determining suitability and does not constitute a warranty. It may represent the result of Omron's test conditions, and the user must correlate it to actual application requirements. Actual performance is subject to the Omron's Warranty and Limitations of Liability.

Change in Specifications.

Product specifications and accessories may be changed at any time based on improvements and other reasons. It is our practice to change part numbers when published ratings or features are changed, or when significant construction changes are made. However, some specifications of the Product may be changed without any notice. When in doubt, special part numbers may be assigned to fix or establish key specifications for your application. Please consult with your Omron's representative at any time to confirm actual specifications of purchased Product.

Errors and Omissions.

Information presented by Omron Companies has been checked and is believed to be accurate; however, no responsibility is assumed for clerical, typographical or proofreading errors or omissions.

chanhvinh.com

OMRON Corporation **Industrial Automation Company**
Kyoto, JAPAN
Contact: www.ia.omron.com

Regional Headquarters
OMRON EUROPE B.V.
Wegalaan 67-69, 2132 JD Hoofddorp
The Netherlands
Tel: (31)2356-81-300/Fax: (31)2356-81-388

OMRON SCIENTIFIC TECHNOLOGIES INC.
6550 Dumbarton Circle Fremont
CA 94555 U.S.A.
Tel: (1) 510-608-3400/Fax: (1) 510-744-1442

OMRON ASIA PACIFIC PTE. LTD.
No. 438A Alexandra Road # 05-05/08 (Lobby 2),
Alexandra Technopark,
Singapore 119967
Tel: (65) 6835-3011/Fax: (65) 6835-2711

OMRON (CHINA) CO., LTD.
Room 2211, Bank of China Tower,
200 Yin Cheng Zhong Road,
PuDong New Area, Shanghai, 200120, China
Tel: (86) 21-5037-2222/Fax: (86) 21-5037-2200

Authorized Distributor:

© OMRON Corporation 2018-2021 All Rights Reserved.
In the interest of product improvement,
specifications are subject to change without notice.

CSM_20_15
Cat. No. A263-E1-09 1021(0917)