chanhvinh.com

OMRON Industrial Automation



E2E-X6B1TL12-M1

Proximity sensor, inductive, nickel-brass, long body, M12, shielded, 6 mm, DC, 3-wire, PNP NO, IO-Link COM3, M12 connector

Specifications

Size	M12
Mounting type	Quasi-flush
Sensing distance	6 mm
Overall length of sensor	70 mm
Thread length	54 mm
Material housing	Brass, nickel plated
Output type	IO-Link, PNP
Operation mode	NO
Connection method	Connector M12
Cable specifications	-
IO-Link function	✔
IO-Link baud rate	COM3 (230.4 kbps)
Degree of protection (IP)	IP67/IP69K

Related products



M12 Connectors & Cordsets
Industrial connectors & cordsets for any application

chanhvinh.com

Downloads


CAD Library



E2E NEXT

Datasheet


EN PDF 38.9 MB



E2E(Q) - Basic Models

Index list

EN PDF 719 KB



E2E(Q) - Premium Models

Index list

EN PDF 719 KB



E2E[Q]-XxBxxxx

IO-Link IODD file

EN ZIP 1.35 MB



EAC Mark removal

Discontinuation Notice

EN PDF 221 KB



IO-Link Series

Brochure

EN PDF 7.5 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 17 January, 2025. Click here for terms of use.

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU