chanhvinh.com

# G5Q
PCB Power Relay

## A Miniature Power Relay with 1-pole 10A Switching Capacity



- Compact single pole relay.
- Excellent switching performance for a variety of loads.
- Small, yet provide 8-kV impulse withstand voltage (between coil and contacts).
- Low coil power consumption (SPST-NO: 200 mW, SPDT: 400 mW)
- Coil insulation system: Class F (UL1446).
- IEC/EN 60335-1 conformed. (-HA Model)

**RoHS Compliant**

## ■Model Number Legend

G5Q-□□□-□-□-□
1 2 3 4 5 6

**1. Number of Poles**
1 : 1-pole

**2. Contact Form**
None : SPDT (1c)
A : SPST-NO (1a)

**3. Enclosure rating**
None : Flux protection
4 : Sealed

**4. Classification**
None : Standard
EU : High-capacity

**5. Market Code**
None : General purpose
HA : Home Appliance according to IEC/EN60335-1

**6. Coil Holding Voltage**
None : Not supported
PW : Supported

## ■Application Examples

- Ideal for output applications of control equipments.

## ■Ordering Information

| Terminal Shape | Market Code | Classification | Contact form | Enclosure rating | Model | Rated coil voltage | Minimum packing unit |
|---|---|---|---|---|---|---|---|
| PCB terminals | General purpose | Standard | SPST-NO(1a) | Flux protection | G5Q-1A | 5VDC<br>9VDC<br>12VDC<br>24VDC | 100 pcs/tray |
| | | | | Sealed | G5Q-1A4 | | |
| | | | SPDT(1c) | Flux protection | G5Q-1 | | |
| | | | | | G5Q-1-PW | 5VDC<br>12VDC<br>24VDC | |
| | | | | Sealed | G5Q-14 | 5VDC<br>9VDC<br>12VDC<br>24VDC | |
| | | High-capacity | SPST-NO(1a) | Flux protection | G5Q-1A-EU | 5VDC<br>12VDC<br>24VDC | |
| | | | | Sealed | G5Q-1A4-EU | | |
| | | | SPDT(1c) | Flux protection | G5Q-1-EU | | |
| | | | | Sealed | G5Q-14-EU | | |
| | Home Appliance | Standard | SPST-NO(1a) | Flux protection | G5Q-1A-HA | | |
| | | High-capacity | | | G5Q-1A-EU-HA | 12VDC<br>24VDC | |
| | | Standard | SPDT(1c) | | G5Q-1-HA | 5VDC<br>12VDC<br>24VDC | |
| | | | | | G5Q-1-HA-PW | | |
| | | High-capacity | | | G5Q-1-EU-HA | 12VDC<br>24VDC | |

Note 1. When ordering, add the rated coil voltage to the model number.
Example: G5Q-1A DC5
Rated coil voltage
Note 2. Contact your OMRON sales representative for tube packing models (40 pcs/tube).

chanhvinh.com



# G5Q

## PCB Power Relay

## ■Ratings

### ●Coil

| Contact form | Rated voltage | Rated current (mA) | Coil resistance (Ω) | Must operate voltage (V) | Must release voltage (V) | Max. voltage (V) | Power consumption (mW) |
|---|---|---|---|---|---|---|---|
| SPST-NO (1a) | 5 VDC | 40 | 125 | 75% max. | 5% min. | 190% (at 23°C) | Approx. 200 |
| | 9 VDC | 22.2 | 405 | | | | |
| | 12 VDC | 16.7 | 720 | | | | |
| | 24 VDC | 8.3 | 2880 | | | | |
| SPDT (1c) | 5 VDC | 80 | 63 | | 5% min. 5 to 25%* | | Approx. 400 Approx. 36* |
| | 9 VDC | 44.4 | 202 | | | | |
| | 12 VDC | 33.3 | 360 | | | | |
| | 24 VDC | 16.7 | 1440 | | | | |

Note 1. The rated current and coil resistance are measured at a coil temperature of 23°C with a tolerance of ±10%.
Note 2. The operating characteristics are measured at a coil temperature of 23°C.
Note 3. The “Max. voltage” is the maximum voltage that can be applied to the relay coil.
* Power consumption with Holding Voltage is 36mW. Please confirm the detail in page 6 Coil Voltage Reduction (Holding Voltage).

### ●Contacts

| Load / Item | Resistive load | | | |
|---|---|---|---|---|
| | SPST-NO (1a) | | SPDT (1c) | |
| | Standard | High-capacity | Standard | High-capacity |
| Contact Type | Single | | | |
| Contact material | Ag-Alloy (Cd free) | | | |
| Rated load (resistive) | 10 A at 125 VAC<br>3 A at 125 VAC<br>5 A at 250 VAC<br>3 A at 250 VAC<br>5 A at 30 VDC | 10 A at 250 VAC<br>3 A at 125 VAC<br>5 A at 250 VAC<br>3 A at 250 VAC<br>5 A at 30 VDC | 10 A at 125 VAC (NO)<br>3 A at 125 VAC (NO)<br>5 A at 250 VAC (NO)<br>3 A at 250 VAC (NO)<br>5 A at 30 VDC (NO)<br>3 A at 125 VAC (NC)<br>3 A at 250 VAC (NC)<br>3 A at 30 VDC (NC) | 10 A at 250 VAC (NO)<br>3 A at 125 VAC (NO)<br>5 A at 250 VAC (NO)<br>3 A at 250 VAC (NO)<br>5 A at 30 VDC (NO)<br>3 A at 125 VAC (NC)<br>3 A at 250 VAC (NC)<br>3 A at 30 VDC (NC) |
| Rated carry current | 10 A (NO)/3 A (NC) | | | |
| Max. switching voltage | 277 VAC, 30 VDC | | | |
| Max. switching current | AC: 10 A (NO)/3 A (NC)<br>DC: 5 A (NO)/3 A (NC) | | | |

chanhvinh.com



## ■Characteristics

| Item | Classification | Standard model |
|---|---|---|
| Contact resistance *1 | | 100 mΩ max. |
| Operate time | | 10 ms max. |
| Release time | | 5 ms max. |
| Insulation resistance *2 | | 1,000 MΩ min. |
| Dielectric strength | Between coil and contacts | 4,000 VAC, 50/60 Hz for 1 min |
| | Between contacts of the same polarity | 1,000 VAC, 50/60 Hz for 1 min |
| Impulse withstand voltage (between coil and contacts) | | 8 kV (1.2 x 50 μs) |
| Vibration resistance | Destruction | 10 to 55 to 10 Hz, 0.75 mm single amplitude (1.5 mm double amplitude) |
| | Malfunction | 10 to 55 to 10 Hz, 0.75 mm single amplitude (1.5 mm double amplitude) |
| Shock resistance | Destruction | 1,000 m/s² |
| | Malfunction | 100 m/s² |
| Durability | Mechanical | 10,000,000 operations (18,000 operations per hour) |
| | Electrical | • NO<br>25,000 operations: 10 A at 250 VAC resistive load<br>(operation: ON for 1 sec, OFF for 3 sec) <High-capacity type><br>50,000 operations: 10 A at 125 VAC resistive load<br>(operation: ON for 1 sec, OFF for 3 sec)<br>200,000 operations: 3 A at 125 VAC resistive load<br>(operation: ON for 1 sec, OFF for 1 sec)<br>50,000 operations: 5 A at 250 VAC resistive load<br>(operation: ON for 1 sec, OFF for 1 sec)<br>100,000 operations: 3 A at 250 VAC resistive load<br>(operation: ON for 1 sec, OFF for 1 sec)<br>100,000 operations: 5 A at 30 VDC resistive load<br>(operation: ON for 1 sec, OFF for 1 sec)<br>• NC<br>200,000 operations: 3 A at 125 VAC resistive load<br>(operation: ON for 1 sec, OFF for 1 sec)<br>100,000 operations: 3 A at 250 VAC resistive load<br>(operation: ON for 1 sec, OFF for 1 sec)<br>100,000 operations: 3 A at 30 VDC resistive load<br>(operation: ON for 1 sec, OFF for 1 sec) |
| Failure rate (P level) (reference *3) | | 10 mA at 5 VDC |
| Ambient operating temperature | | -40°C to 105°C (with no icing or condensation)<br>-40°C to 85°C (with no icing or condensation) <High-capacity type> |
| Ambient operating humidity | | 5% to 85% |
| Weight | | Approx. 6.5 g |

Note. Note. Values in the above table are the initial values at 23°C.

*1. The contact resistance is possible with 1 A applied at 5 VDC using a fall-of-potential method.

*2. Testing conditions: The insulation resistance was measured with a 500 VDC megohmmeter at the same locations as the dielectric strength was measured.

*3. This value was measured at a switching frequency of 120 operations/min.


chanhvinh.com




# ■Engineering Data

## ●Maximum Switching Capacity

Standard





High-capacity(-EU)





## ●Ambient Temperature VS. Maximum Coil Voltage

Standard





High-capacity(-EU)





Note. The Maximum coil voltage refers to the maximum value in a varying range of operating power voltage, not a continuous voltage.

## ●Shock Malfunction




Sample: G5Q-14 12 VDC
Number of Relays: 5 pcs
Test conditions: Shock is applied in ±X, ±Y, and ±Z directions three times each with and without energizing the Relays to check the number of malfunctions. The energized voltage is 100% of the rated voltage.
Requirement: None malfuction
100 m/s²






# ■Dimensions

(Unit: mm)

## G5Q-1A(4)(-EU)(-HA)











* Average value

**PCB Mounting Holes**
(Bottom View)
Tolerance: ±0.1 mm





**Terminal Arrangement/ Internal Connections**
(Bottom View)





(No coil polarity)

## G5Q-1(4)(-EU)(-HA)(-PW)











* Average value

**PCB Mounting Holes**
(Bottom View)
Tolerance: ±0.1 mm




**Terminal Arrangement/ Internal Connections**
(Bottom View)




(No coil polarity)

chanhvinh.com



## ■Approved Standards

**UL Recognized: (File No. E41515)**

**CSA Certified: (File No. LR31928)**

| Model | Contact form | Coil ratings | Contact ratings | Number of test operations |
|---|---|---|---|---|
| G5Q-1A(4)(-EU)(-HA)<br>G5Q-1(4)(-EU)(-HA)(-PW) | SPST-NO (1a)<br>SPDT (1c) | 5 to 48 VDC | 10 A 250 VAC N.O. only (Resistive) 40°C | 6,000 |
| | | | 10 A 30 VDC N.O. only (Resistive) 40°C | |
| | | | 4 A 120 VAC N.O. only (Resistive) 40°C | 100,000 |
| | | | 3 A 250 VAC N.C. only (Resistive) 40°C | 6,000 |
| | | | 3 A 30 VDC N.C. only (Resistive) 40°C | |

**EN/IEC, VDE (Certified/No.40009467)**

| Model | Contact form | Coil ratings | Contact ratings | Number of test operations |
|---|---|---|---|---|
| G5Q-1(4)(-HA)(-PW)<br>G5Q-1A(4)(-HA) | SPST-NO (1a)<br>SPDT (1c) | 5 to 48 VDC | 10 A making and 0 A breaking, 250 VAC (cosϕ=1) 105°C<br>5 A marking and 3 A breaking, 30 VDC (0 ms) 105°C | 10,000 |
| | | | 5 A 250 VAC (cosϕ=1) (N.O.) 105°C | 75,000 |
| G5Q-1A(4)-EU(-HA)<br>G5Q-1(4)-EU(-HA) | | | 10 A 250 VAC (cosϕ=1) (N.O.) 65°C<br>5 A 30 VDC (0 ms) (N.O.) 65°C<br>3 A 30 VDC (0 ms) (N.C.) 65°C | 10,000 |
| | | | 4 A 250 VAC (cosϕ=1) (N.O.) 85°C | 100,000 |

| | |
|---|---|
| Creepage distance | 6.4 mm min. |
| Clearance distance | 5.5 mm min. |
| Insulation material group | IIIa |
| Type of insulation coil-contact circuit<br>open contact circuit | Basic (Rated voltage 400 V) / Reinforced (Rated voltage 250 V)<br>Micro disconnection |
| Rated Insulation voltage | 250 V |
| Pollution degree | 2 |
| Rated voltage system | 250 V / 400 V (EU flux type only) |
| Over voltage category | III |
| Category of protection according to IEC 61810-1 | RT II (Flux protection) / RT III (Sealed) |
| Glow wire according to IEC 60335-1 | <HA Models only><br>GWT 750°C min. (IEC 60695-2-11) / GWFI 850°C min. (IEC 60695-2-12) |
| Tracking Index of relay base | PTI 250 V min. (housing parts) |
| Flammability class according to UL94 | V-0 |
| Coil Insulation system | F Class (UL 1446) |

chanhvinh.com




## ■Precautions

●Please refer to “PCB Relays Common Precautions” for correct use.

### Correct Use

●Coil Voltage Reduction (Holding Voltage) after Relay operation

- If the coil voltage is reduced to the holding voltage after Relay operation, first apply the rated voltage to the coil for at least 100 ms, as shown below.
- A voltage of at least 30% of the rated voltage is required for the coil holding voltage. Do not allow voltage fluctuations to cause the coil holding voltage to fall below this level.




| | Applied coil voltage | Coil resistance* | Power consumption |
|---|---|---|---|
| Rated voltage | 100% | 63Ω (5 VDC)<br>360Ω (12 VDC)<br>1440Ω (24 VDC) | Approx. 400 mW |
| Holding voltage | 30% | | Approx. 36 mW |

* The coil resistance were measured at a coil temperature of 23°C with tolerances of ±10%.



Please check each region's Terms & Conditions by region website.

**OMRON Corporation**
**Electronic and Mechanical Components Company**

**Regional Contact**

**Americas**
https://www.components.omron.com/

**Europe**
http://components.omron.eu/

**Asia-Pacific**
https://ecb.omron.com.sg/

**China**
https://www.ecb.omron.com.cn/

**Korea**
https://www.omron-ecb.co.kr/

**Japan**
https://www.omron.co.jp/ecb/

© OMRON Corporation 2007-2019 All Rights Reserved.
In the interest of product improvement, specifications are subject to change without notice.

**Cat. No. J155-E1-13**
0919(0207)(O)