chanhvinh.com

FAIRCHILD SEMICONDUCTOR®

June 2009

FXLH42245
Low-Voltage, Dual-Supply, 8-Bit, Signal Translator with Configurable Voltage Supplies, Bushold Data Inputs, 3-State Outputs and 26Ω Series Resistors in the B-Port Outputs

Features

- Bi-Directional Interface between Two Levels from 1.1V to 3.6V
- Fully Configurable, Inputs Track V_{CC} Level
- Non-Preferential Power-up; Either V_{CC} May Be Powered-up First
- Outputs Remain in 3-State until Active V_{CC} Level is Reached
- Outputs Switch to 3-State if Either V_{CC} is at GND
- Bushold on Data Inputs Eliminates the need for External Pull-Up / Pull-Down Resistors
- 26W Output Series Resistors on the B Port to Reduce Line Noise
- Power-Off Protection
- Control Inputs (T/$\overline{R}$, $\overline{OE}$) Levels are Referenced To V_{CCA} Voltage
- Packaged in 24-Pin MLP
- ESD Protection Exceeds:
  - 4kV Human Body Model (per JESD22-A114 & Mil Std 883e 3015.7)
  - 8kV Human Body Model I/O to GND (per JESD22-A114 & Mil Std 883e 3015.7)
  - 1kV Charge Device Model (per ESD STM 5.3)
  - 200V Machine Model (per JESD22-A115 & ESD STM5.2)

Description

The FXLH42245 is a configurable dual-voltage-supply translator designed for bi-directional voltage translation of signals between two voltage levels. The device allows translation between voltages as high as 3.6V to as low as 1.1V. The A port tracks the V_{CCA} level and the B port tracks the V_{CCB} level. Both ports are designed to accept supply voltage levels from 1.1V to 3.6V. This allows for bi-directional voltage translation over a variety of voltage levels: 1.2V, 1.5V, 1.8V, 2.5V, and 3.3V.

The device remains in 3-state until both V_{CC}s reach active levels, allowing either V_{CC} to be powered-up first. The device also contains power-down control circuits that place the device in 3-state if either V_{CC} is removed.

The Transmit/Receive (T/$\overline{R}$) input determines the direction of data flow through the device. The $\overline{OE}$ input, when HIGH, disables both the A and B ports by placing them in a 3-state condition. The FXLH42245 is designed with the control pins (T/$\overline{R}$ and $\overline{OE}$) supplied by V_{CCA}.

Ordering Information

Part Number	Eco Status	Package	Packing Method
FXLH42245MPX	Green	24-Pin Molded Leadless Package (MLP), JEDEC MO-220, 3.5 x 4.5mm	Tape and Reel

For Fairchild's definition of Eco Status, please visit: http://www.fairchildsemi.com/company/green/rohs_green.html.

© 2004 Fairchild Semiconductor Corporation

chanhvinh.com

Pin Configuration



Figure 1. Pin Configuration (Top Through View)

Pin Definitions

Pin #	Name	Description
1	V_{CCA}	Side-A Power Supply
2	$\overline{T/R}$	Transmit / Receive Input
3, 4, 5, 6, 7, 8, 9, 10	A_0, A_1, A_2, A_3, A_4, A_5, A_6, A_7	Side-A Inputs or 3-State Outputs
11, 12, 13	GND	Ground
14, 15, 16, 17, 18, 19, 20, 21	B_7, B_6, B_5, B_4, B_3, B_2, B_1, B_0	Side-B Inputs or 3-State Outputs
22	$\overline{OE}$	Output Enable Input
23, 24	V_{CCB}	Side-B Power Supply

Truth Table

Inputs		Description
$\overline{OE}$	$\overline{T/R}$	
LOW Voltage Level	LOW Voltage Level	Bus B Data to Bus A
LOW Voltage Level	HIGH Voltage Level	Bus A Data to Bus B
HIGH Voltage Level	Don't Care	3-State

© 2004 Fairchild Semiconductor Corporation

chanhvinh.com

Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

Symbol	Parameter	Conditions		Min.	Max.	Unit
V_{CCA}	Supply Voltage			-0.5	4.6	V
V_{CCB}				-0.5	4.6	
V_I	DC Input Voltage	I/O Port A		-0.5 to V_{CCA}	0.5	V
		I/O Port B		-0.5 to V_{CCB}	0.5	
		Control Inputs ($\overline{T}/R$, $\overline{OE}$)		-0.5	0.5	
V_O	Output Voltage[1]	Output 3-State		-0.5	4.6	V
		Output Active (A_n)		-0.5 to V_{CCA}	0.5	
		Output Active (B_n)		-0.5 to V_{CCB}	0.5	
I_{IK}	DC Input Diode Current	V_I < 0V			-50	mA
I_{OK}	DC Output Diode Current	V_O < 0V			-50	mA
		V_O > V_{CC}			50	
I_{OH}/I_{OL}	DC Output Source/Sink Current				±50	mA
I_{CC}	DC V_{CC} or Ground Current per Supply Pin				±100	mA
T_{STG}	Storage Temperature Range			-65	+150	°C
ESD	Electrostatic Discharge Capability	Human Body Model, JESD22-A114, Mil Std 883e 3015.7			4	kV
			I/O to GND		8	
		Charged Device Model, JESD22-C101,STM 5.3			1	
		Machine Model, JESD22-A115,STM 5.2			200	V

Note:

1. I/O absolute maximum ratings must be observed.

Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. Fairchild does not recommend exceeding them or designing to Absolute Maximum Ratings.

Symbol	Parameter	Conditions		Min.	Max.	Unit
V_{CC}	Power Supply	Operating V_{CCA} or V_{CCB}		1.1	3.6	V
V_I	Input Voltage	Port A		0	V_{CCA}	V
		Port B		0	V_{CCB}	
		Control Inputs ($\overline{T}/R$, $\overline{OE}$)		0	V_{CCA}	
I_{OH}/I_{OL}	Output Current	Port A V_{CCA}	3.0V to 3.6V		±24	mA
			2.3V to 2.7V		±18	
			1.65V to 1.95V		±6	
			1.40V to 1.65V		±2	
			1.1V to 1.4V		±0.5	
		Port B V_{CCB} Resistor Outputs	3.0V to 3.6V		±14	
			2.3V to 2.7V		±8	
			1.65V to 1.95V		±3	
			1.40V to 1.65V		±1	
			1.1V to 1.4V		±0.25	
T_A	Operating Temperature, Free Air			-40	+85	°C
$\Delta V/\Delta t$	Minimum Input Edge Rate	$V_{CCA/B}$ =1.1V to 3.6V			10	ns/V

Note:

2. All unused inputs must be held at V_{CCI} or GND.

© 2004 Fairchild Semiconductor Corporation

chanhvinh.com

Electrical Characteristics

Symbol	Parameter	Conditions	V_{CCI} (V)	V_{CCO} (V)	Min.	Max.	Units
V_{IH}	HIGH Level Input(3)	Data Inputs A_n, B_n	2.70 to 3.60	1.1 to 3.6	2.0		V
			2.30 to 2.70		1.6		
			1.65 to 2.30		0.65 x V_{CCI}		
			1.40 to 1.65		0.65 x V_{CCI}		
			1.10 to 1.40		0.9 x V_{CCI}		
		Control Pins $\overline{OE}$, T/$\overline{R}$ (Referenced to V_{CCA})	2.70 to 3.6	1.1 to 3.6	2.0		
			2.30 to 2.70		1.6		
			1.65 to 2.30		0.65 x V_{CCA}		
			1.40 to 1.65		0.65 x V_{CCA}		
			1.10 to 1.40		0.9 x V_{CCA}		
V_{IL}	LOW Level Input(3)	Data Inputs A_n, B_n	2.70 to 3.60	1.1 to 3.6		0.8	V
			2.30 to 2.70			0.7	
			1.65 to 2.30			0.35 x V_{CCI}	
			1.40 to 1.65			0.35 x V_{CCI}	
			1.10 to 1.40			0.10 x V_{CCI}	
		Control Pins /$\overline{OE}$, T/$\overline{R}$ (Referenced to V_{CCA})	2.70 to 3.60	1.1 to 3.6		0.8	
			2.30 to 2.70			0.7	
			1.65 to 2.30			0.35 x V_{CCA}	
			1.40 to 1.65			0.35 x V_{CCA}	
			1.10 to 1.40			0.10 x V_{CCA}	
V_{OH}	HIGH Level Output(4) B Port	I_{OH} = -100µA	1.1 to 3.6	1.1 to 3.6	V_{CC0} to 0.2		V
		I_{OH} = -6mA	2.7	2.7	2.2		
		I_{OH} = -8mA	3.0	3.0	2.4		
		I_{OH} = -12mA	3.0	3.0	2.2		
		I_{OH} = -4mA	2.3	2.3	2.0		
		I_{OH} = -6mA	2.3	2.3	1.8		
		I_{OH} = -8mA	2.3	2.3	1.7		
		I_{OH} = -3mA	1.65	1.65	1.25		
		I_{OH} = -1mA	1.4	1.4	1.05		
		I_{OH} = -0.25mA	1.1	1.1	0.75 x V_{CC0}		
	HIGH Level Output(4) A Port	I_{OH} = -100µA	1.1 to 3.6	1.1 to 3.6	V_{CC0} to 0.2		
		I_{OH} = -12mA	2.7	2.7	2.2		
		I_{OH} = -18mA	3.0	3.0	2.4		
		I_{OH} = -24mA	3.0	3.0	2.2		
		I_{OH} = -6mA	2.3	2.3	2.0		
		I_{OH} = -12mA	2.3	2.3	1.8		
		I_{OH} = -18mA	2.3	2.3	1.7		
		I_{OH} = -6mA	1.65	1.65	1.25		
		I_{OH} = -2mA	1.4	1.4	1.05		
		I_{OH} = -0.5mA	1.1	1.1	0.75 x V_{CC0}		

Continued on the following page

© 2004 Fairchild Semiconductor Corporation

chanhvinh.com

Electrical Characteristics (Continued)

Symbol	Parameter	Conditions	V_{CCI} (V)	V_{CCO} (V)	Min.	Max.	Units
V_{OL}	LOW Level Output[4] B Port	I_{OL} = 100µA	1.1 to 3.6	1.1 to 3.6		0.2	V
		I_{OL} = 6mA	2.7	2.7		0.4	
		I_{OL} = 8mA	3.0	3.0		0.55	
		I_{OL} = 12mA	3.0	3.0		0.80	
		I_{OL} = 6mA	2.3	2.3		0.4	
		I_{OL} = 8mA	2.3	2.3		0.6	
		I_{OL} = 3mA	1.65	1.65		0.3	
		I_{OL} = 1mA	1.4	1.4		0.35	
		I_{OL} = 0.25mA	1.1	1.1		0.3 x V_{CC0}	
	LOW Level Output[4] A Port	I_{OL} = 100µA	1.1 to 3.6	1.1 to 3.6		0.2	
		I_{OL} = 12mA	2.7	2.7		0.4	
		I_{OL} = 18mA	3.0	3.0		0.4	
		I_{OL} = 24mA	3.0	3.0		0.55	
		I_{OL} = 12mA	2.3	2.3		0.4	
		I_{OL} = 18mA	2.3	2.3		0.6	
		I_{OL} = 6mA	1.65	1.65		0.3	
		I_{OL} = 2mA	1.4	1.4		0.35	
		I_{OL} = 0.5mA	1.1	1.1		0.3 x V_{CC0}	
I_L	Input Leakage Current, Control Pins	V_I=V_{CCA} or GND	1.1 to 3.6	3.6		±1.0	µA
$I_{I(HOLD)}$	Bushold Input Minimum Drive Current	V_{IN}=0.8	3.0	3.0	75		µA
		V_{IN}=2.0	3.0	3.0	-75		
		V_{IN}=0.7	2.3	2.3	45		
		V_{IN}=1.6	2.3	2.3	-45		
		V_{IN}=0.57	1.65	1.65	25		
		V_{IN}=10.7	1.65	1.65	-25		
		V_{IN}=0.49	1.4	1.4	11		
		V_{IN}=0.91	1.4	1.4	-11		
		V_{IN}=0.11	1.1	1.1		4	
		V_{IN}=0.99	1.1	1.1		-4	
$I_{I(OD)}$	Bushold Input Over-Drive Current-to-Current State	Note 5	3.6	3.6	450		µA
		Note 6	3.6	3.6	-450		
		Note 5	2.7	2.7	300		
		Note 6	2.7	2.7	-300		
		Note 5	1.95	1.95	200		
		Note 6	1.95	1.95	-200		
		Note 5	1.6	1.6	120		
		Note 6	1.6	1.6	-120		
		Note 5	1.4	1.4	80		
		Note 6	1.4	1.4	-80		

Continued on the following page

© 2004 Fairchild Semiconductor Corporation

chanhvinh.com

Electrical Characteristics (Continued)

Symbol	Parameter	Conditions	V_{CCI} (V)	V_{CCO} (V)	Min.	Max.	Units
I_{OFF}	Power Off Leakage Current	A_n, V_I or V_O=0V to 3.6V	0	3.6		±10	µA
		B_n, V_I or V_O=0V to 3.6V	3.6	0		±10	
I_{OZ}	3-State Output Leakage (V_O, V_{CC} or GND V_I=V_{IH} or V_{IL})	A_n, B_n, $\overline{OE}$=V_{IH}	3.6	3.6		±10	µA
		B_n, $\overline{OE}$= Don't Care(7)	0	3.6		±10	
		A_n, $\overline{OE}$= Don't Care(7)	3.6	0		±10	
$I_{CCA/B}$	Quiescent Supply Current(8)	V_I=V_{CCI} or GND; I_O=0	1.1 to 3.6	1.1 to 3.6		20	µA
I_{CCZ}			1.1 to 3.6	1.1 to 3.6		20	
I_{CCA}		V_I=V_{CCA} or GND; I_O=0	0	1.1 to 3.6		-10	
			1.1 to 3.6	0		10	
I_{CCB}		V_I=V_{CCB} or GND; I_O=0	1.1 to 3.6	0		-10	
			0	1.1 to 3.6		10	
$\Delta I_{CCA/B}$	Increase in I_{CC} per Input; Other Inputs at V_{CC} or GND	V_{IH}=3.0	3.6	3.6		500	µA

Notes:

3. V_{CCI} = the V_{CC} associated with the data input under test.
4. V_{CCO} = the V_{CC} associated with the output under test.
5. An external driver must source at least the specified current to switch LOW-to-HIGH.
6. An external driver must source at least the specified current to switch HIGH-to-LOW.
7. Don't care = any valid logic level.
8. Reflects current per supply, V_{CCA} or V_{CCB}.

© 2004 Fairchild Semiconductor Corporation

chanhvinh.com

AC Electrical Characteristics

V_{CCA}=3.0V to 3.6V

Symbol	Parameter	T_A= -40 to +85°C										Units
		V_{CCB}=3.0V to 3.6V		V_{CCB}=2.3V to 2.7V		V_{CCB}=1.65V to 1.95V		V_{CCB}=1.4V to 1.6V		V_{CCB}=1.1V to 1.3V		
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	
t_{PLH}, t_{PHL}	Propagation Delay A to B	0.5	3.9	0.5	4.5	0.9	5.9	1.0	7.4	1.6	22.0	ns
	Propagation Delay B to A	0.2	3.5	0.2	3.8	0.3	4.0	0.5	4.3	0.8	13.0	
t_{PZH}, t_{PZL}	Output Enable $\overline{OE}$ to B	0.7	4.8	01.0	5.1	1.5	6.7	1.5	7.1	2.0	18.0	ns
	Output Enable $\overline{OE}$ to A	0.5	4.0	0.5	4.0	0.5	4.0	0.5	4.0	0.5	4.0	
t_{PHZ}, t_{PLZ}	Output Disable $\overline{OE}$ to B	0.4	4.3	0.4	4.4	0.9	5.2	1.7	6.8	2.0	19.0	ns
	Output Disable $\overline{OE}$ to A	0.2	3.7	0.2	3.7	0.2	3.7	0.2	3.7	0.2	3.7	

V_{CCA}=2.3V to 2.7V

Symbol	Parameter	T_A= -40 to +85°C										Units
		V_{CCB}=3.0V to 3.6V		V_{CCB}=2.3V to 2.7V		V_{CCB}=1.65V to 1.95V		V_{CCB}=1.4V to 1.6V		V_{CCB}=1.1V to 1.3V		
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	
t_{PLH}, t_{PHL}	Propagation Delay A to B	0.5	4.3	0.6	4.8	0.9	6.0	1.0	7.6	1.6	22.0	ns
	Propagation Delay B to A	0.3	3.9	0.4	4.2	0.5	4.5	0.5	4.8	1.0	7.0	
t_{PZH}, t_{PZL}	Output Enable $\overline{OE}$ to B	0.8	5.1	1.0	5.5	1.5	6.9	1.5	7.4	2.0	19.0	ns
	Output Enable $\overline{OE}$ to A	0.6	4.5	0.6	4.5	0.6	4.5	0.6	4.5	0.6	4.5	
t_{PHZ}, t_{PLZ}	Output Disable $\overline{OE}$ to B	0.4	4.6	0.4	4.8	0.9	5.3	1.7	7.1	2.0	19.0	ns
	Output Disable $\overline{OE}$ to A	0.2	4.0	0.2	4.0	0.2	4.0	0.2	4.0	0.2	4.0	

V_{CCA}=1.65V to 1.95V

Symbol	Parameter	T_A= -40 to +85°C										Units
		V_{CCB}=3.0V to 3.6V		V_{CCB}=2.3V to 2.7V		V_{CCB}=1.65V to 1.95V		V_{CCB}=1.4V to 1.6V		V_{CCB}=1.1V to 1.3V		
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	
t_{PLH}, t_{PHL}	Propagation Delay A to B	0.5	4.6	0.7	5.1	1.1	6.2	1.1	7.8	1.7	22.0	ns
	Propagation Delay B to A	0.5	5.4	0.5	5.6	0.8	5.7	1.0	6.0	1.2	8.0	
t_{PZH}, t_{PZL}	Output Enable $\overline{OE}$ to B	0.8	5.4	1.0	5.9	1.5	7.3	1.5	7.7	2.0	20.0	ns
	Output Enable $\overline{OE}$ to A	1.0	6.7	1.0	6.7	1.0	6.7	1.0	6.7	1.0	6.7	
t_{PHZ}, t_{PLZ}	Output Disable $\overline{OE}$ to B	0.4	4.7	0.4	4.9	1.0	5.4	1.7	7.2	2.0	19.0	ns
	Output Disable $\overline{OE}$ to A	0.5	5.0	0.5	5.0	0.5	5.0	0.5	5.0	0.5	5.0	

© 2004 Fairchild Semiconductor Corporation

chanhvinh.com

AC Electrical Characteristics (Continued)

V_{CCA}=1.4V to 1.6V

Symbol	Parameter	T_A= -40 to +85°C										Units
		V_{CCB}=3.0V to 3.6V		V_{CCB}=2.3V to 2.7V		V_{CCB}=1.65V to 1.95V		V_{CCB}=1.4V to 1.6V		V_{CCB}=1.1V to 1.3V		
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	
t_{PLH}, t_{PHL}	Propagation Delay A to B	0.7	4.8	0.8	5.3	1.2	6.4	1.3	7.9	2.0	22.0	ns
	Propagation Delay B to A	0.6	6.8	0.8	6.9	0.9	7.1	1.0	7.3	1.3	9.5	
t_{PZH}, t_{PZL}	Output Enable $\overline{OE}$ to B	1.1	5.8	1.3	6.3	1.5	7.8	2.0	8.1	2.0	20.0	ns
	Output Enable $\overline{OE}$ to A	1.0	7.5	1.0	7.5	1.0	7.5	1.0	7.5	1.0	7.5	
t_{PHZ}, t_{PLZ}	Output Disable $\overline{OE}$ to B	0.6	4.8	0.6	5.1	1.1	5.8	2.0	7.7	2.0	18.0	ns
	Output Disable $\overline{OE}$ to A	1.0	6.0	1.0	6.0	1.0	6.0	1.0	6.0	1.0	6.0	

V_{CCA}=1.1V to 1.3V

Symbol	Parameter	T_A= -40 to +85°C										Units
		V_{CCB}=3.0V to 3.6V		V_{CCB}=2.3V to 2.7V		V_{CCB}=1.65V to 1.95V		V_{CCB}=1.4V to 1.6V		V_{CCB}=1.1V to 1.3V		
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	
t_{PLH}, t_{PHL}	Propagation Delay A to B	1.0	13.8	1.0	7.8	1.0	8.4	1.0	10.4	2.0	24.0	ns
	Propagation Delay B to A	1.4	22.0	1.4	22.0	1.5	22.0	1.5	22.0	2.0	24.0	
t_{PZH}, t_{PZL}	Output Enable $\overline{OE}$ to B	1.5	12.6	1.5	9.6	1.5	10.6	2.0	11.6	2.0	24.0	ns
	Output Enable $\overline{OE}$ to A	2.0	22.0	2.0	22.0	2.0	22.0	2.0	22.0	2.0	22.0	
t_{PHZ}, t_{PLZ}	Output Disable $\overline{OE}$ to B	1.2	15.0	0.9	7.6	1.2	8.6	2.0	10.6	3.0	21.0	ns
	Output Disable $\overline{OE}$ to A	2.0	15.0	2.0	12.0	2.0	12.0	2.0	12.0	2.0	12.0	

Capacitance

Symbol	Parameter	Conditions	T_A=+25°C Typical	Units
C_{IN}	Input Capacitance Control Pins ($\overline{OE}$, T/R)	V_{CCA}=V_{CCB}=3.3V, V_I=0V or $V_{CCA/B}$	4	pF
$C_{I/O}$	Input/Output Capacitance A_n, B_n Port	V_{CCA}=V_{CCB}=3.3V, V_I=0V or $V_{CCA/B}$	5	pF
C_{PD}	Power Dissipation Capacitance	V_{CCA}=V_{CCB}=3.3V, V_I=0V or V_{CC}, f=10MHz	20	pF

© 2004 Fairchild Semiconductor Corporation

chanhvinh.com

AC Loadings and Waveforms



Figure 2. AC Test Circuit

Test	Switch
t_{PLH},t_{PHL}	Open
t_{PLZ},t_{PZL}	V_{CCO} • 2 at V_{CCO}=3.3 ± 0.3V, 2.5V ± 0.2V, 1.8V ± 0.15V, 1.5V ± 0.1V, 1.2V ± 0.1V
t_{PHZ},t_{PZH}	GND

Table 1. AC Load Table

V_{CCO}	C_L	R_L	Rtr1
1.2V ± 0.1V	15pF	2kΩ	2kΩ
1.5V ± 0.1V	15pF	2kΩ	2kΩ
1.8V ± 0.15V	30pF	500Ω	500Ω
2.5V ± 0.2V	30pF	500Ω	500Ω
3.3V ± 0.3V	30pF	500Ω	500Ω



Note:

9. Input t_R=t_F=2.0ns, 10% to 90%

Figure 3. Waveform for Inverting and Non-Inverting Functions



Note:

10. Input t_R=t_F=2.0ns, 10% to 90%

Figure 4. 3-State Output High Enable and Disable for Low Voltage Logic



Note:

11. Input t_R=t_F=2.0ns, 10% to 90%

Figure 5. 3-State Output High Enable and Disable for Low Voltage Logic

Symbol	V_{CC}				
	3.3V ± 0.3V	2.5V ± 0.2V	1.8V ± 0.15V	1.5V ± 0.1V	1.2V ± 0.1V
V_{MI}	V_{CCI}/2	V_{CCI}/2	V_{CCI}/2	V_{CCI}/2	V_{CCI}/2
V_{MO}	V_{CCO}/2	V_{CCO}/2	V_{CCO}/2	V_{CCO}/2	V_{CCO}/2
V_X	V_{OH} - 0.3V	V_{OH} – 0.15V	V_{OH} – 0.15V	V_{OH} – 0.1V	V_{OH} – 0.1V
V_Y	V_{OL} + 0.3V	V_{OL} + 0.15V	V_{OL} + 0.15V	V_{OL} + 0.1V	V_{OL} + 0.1V

Note:

12. For V_{MI} V_{CCO}=V_{CCA} for control pins T/$\overline{R}$ and $\overline{OE}$ or V_{CCA}/2.

© 2004 Fairchild Semiconductor Corporation

chanhvinh.com

Functional Description

Power-Up/Power-Down Sequencing

FXL translators offer an advantage in that either V_{CC} may be powered up first. This benefit derives from the chip design. When either V_{CC} is at 0V, outputs are in a High-impedance state. The control inputs (T/$\overline{R}$ and $\overline{OE}$) are designed to track the V_{CCA} supply. A pull-up resistor tying $\overline{OE}$ to V_{CCA} should be used to ensure that bus contention, excessive currents, or oscillations do not occur during power-up/power-down. The size of the pull-up resistor is based upon the current-sinking capability of the OE driver.

The recommended power-up sequence is:

1. Apply power to either V_{CC}.
2. Apply power to the T/$\overline{R}$ input (logic HIGH for A-to-B operation; logic LOW for B-to-A operation) and to the respective data inputs (A port or B port). This may occur at the same time as step 1.
3. Apply power to the other V_{CC}.
4. Drive the $\overline{OE}$ input LOW to enable the device.

The recommended power-down sequence is:

1. Drive $\overline{OE}$ input HIGH to disable the device.
2. Remove power from either V_{CC}.
3. Remove power from the other V_{CC}.

© 2004 Fairchild Semiconductor Corporation

chanhvinh.com

Physical Dimensions



NOTES:

A. CONFORMS TO JEDEC REGISTRATION MO-220, VARIATION WFSD-2 FOR DIMENSIONS ONLY. PIN NUMBERING DOES NOT COMPLY.

B. DIMENSIONS ARE IN MILLIMETERS.

C. DIMENSIONS AND TOLERANCES PER ASME Y14.5M, 1994

MLP24Brev4

Figure 6. 24-Pin Molded Leadless Package (MLP), JEDEC MO-220, 3.5 x 4.5mm

Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.

Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings:
http://www.fairchildsemi.com/packaging/.

For current tape and reel specifications, visit Fairchild Semiconductor's online packaging area:
http://www.fairchildsemi.com/packaging/MLP24B_TNR.pdf.

© 2004 Fairchild Semiconductor Corporation

chanhvinh.com

FAIRCHILD SEMICONDUCTOR®

TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

Auto-SPM™
Build it Now™
CorePLUS™
CorePOWER™
CROSSVOLT™
CTL™
Current Transfer Logic™
EcoSPARK®
EfficentMax™
EZSWITCH™*
™*
®
Fairchild®
Fairchild Semiconductor®
FACT Quiet Series™
FACT®
FAST®
FastvCore™
FETBench™
FlashWriter®*
FPS™
F-PFS™
FRFET®
Global Power Resource℠
Green FPS™
Green FPS™ e-Series™
Gmax™
GTO™
IntelliMAX™
ISOPLANAR™
MegaBuck™
MICROCOUPLER™
MicroFET™
MicroPak™
MillerDrive™
MotionMax™
Motion-SPM™
OPTOLOGIC®
OPTOPLANAR®
®
PDP SPM™
Power-SPM™
PowerTrench®
PowerXS™
Programmable Active Droop™
QFET®
QS™
Quiet Series™
RapidConfigure™
™
Saving our world, 1mW/W/kW at a time™
SmartMax™
SMART START™
SPM®
STEALTH™
SuperFET™
SuperSOT™-3
SuperSOT™-6
SuperSOT™-8
SupreMOS™
SyncFET™
Sync-Lock™
SYSTEM GENERAL ®*
The Power Franchise®
the power franchise
TinyBoost™
TinyBuck™
TinyLogic®
TINYOPTO™
TinyPower™
TinyPWM™
TinyWire™
TriFault Detect™
TRUECURRENT™*
µSerDes™
SerDes
UHC®
Ultra FRFET™
UniFET™
VCX™
VisualMax™
XS™

* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.

Rev. I40

© 2004 Fairchild Semiconductor Corporation