chanhvinh.com

MMBT4403L, SMMBT4403L

Switching Transistor


PNP Silicon


ON Semiconductor®

www.onsemi.com

Features

- S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC−Q101 Qualified and PPAP Capable
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant





SOT−23 (TO−236)
CASE 318
STYLE 6

MAXIMUM RATINGS


Rating	Symbol	Value	Unit
Collector−Emitter Voltage	V_{CEO}	−40	Vdc
Collector−Base Voltage	V_{CBO}	−40	Vdc
Emitter−Base Voltage	V_{EBO}	−5.0	Vdc
Collector Current − Continuous	I_C	−600	mAdc
Collector Current − Peak	I_{CM}	−900	mAdc

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation FR−5 Board (Note 1) @T_A = 25°C Derate above 25°C	P_D	225 1.8	mW mW/°C
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$	556	°C/W
Total Device Dissipation Alumina Substrate, (Note 2) @T_A = 25°C Derate above 25°C	P_D	300 2.4	mW mW/°C
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$	417	°C/W
Junction and Storage Temperature	T_J, T_{stg}	−55 to +150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.
*Transient pulses must not cause the junction temperature to be exceeded.
1. FR−5 = 1.0 × 0.75 × 0.062 in.
2. Alumina = 0.4 × 0.3 × 0.024 in. 99.5% alumina.

MARKING DIAGRAM



2T = Specific Device Code*
M = Date Code*
▪ = Pb−Free Package

(Note: Microdot may be in either location)

*Specific Device Code, Date Code or overbar orientation and/or location may vary depending upon manufacturing location. This is a representation only and actual devices may not match this drawing exactly.

ORDERING INFORMATION

Device	Package	Shipping†
MMBT4403LT1G	SOT−23 (Pb−Free)	3000 / Tape & Reel
SMMBT4403LT1G	SOT−23 (Pb−Free)	3000 / Tape & Reel
MMBT4403LT3G	SOT−23 (Pb−Free)	10,000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 1994

chanhvinh.com

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Max	Unit
OFF CHARACTERISTICS					
Collector−Emitter Breakdown Voltage (Note 3)	(I_C = −1.0 mAdc, I_B = 0)	$V_{(BR)CEO}$	−40	−	Vdc
Collector−Base Breakdown Voltage	(I_C = −0.1 mAdc, I_E = 0)	$V_{(BR)CBO}$	−40	−	Vdc
Emitter−Base Breakdown Voltage	(I_E = −0.1 mAdc, I_C = 0)	$V_{(BR)EBO}$	−5.0	−	Vdc
Base Cutoff Current	(V_{CE} = −35 Vdc, V_{EB} = −0.4 Vdc)	I_{BEV}	−	−0.1	μAdc
Collector Cutoff Current	(V_{CE} = −35 Vdc, V_{EB} = −0.4 Vdc)	I_{CEX}	−	−0.1	μAdc
ON CHARACTERISTICS					
DC Current Gain		h_{FE}			−
	(I_C = −0.1 mAdc, V_{CE} = −1.0 Vdc)		30	−	
	(I_C = −1.0 mAdc, V_{CE} = −1.0 Vdc)		60	−	
	(I_C = −10 mAdc, V_{CE} = −1.0 Vdc)		100	−	
(Note 3)	(I_C = −150 mAdc, V_{CE} = −2.0 Vdc)		100	300	
(Note 3)	(I_C = −500 mAdc, V_{CE} = −2.0 Vdc)		20	−	
Collector−Emitter Saturation Voltage (Note 3)		$V_{CE(sat)}$			Vdc
	(I_C = −150 mAdc, I_B = −15 mAdc)		−	−0.4	
	(I_C = −500 mAdc, I_B = −50 mAdc)		−	−0.75	
Base−Emitter Saturation Voltage (Note 3)		$V_{BE(sat)}$			Vdc
	(I_C = −150 mAdc, I_B = −15 mAdc)		−0.75	−0.95	
	(I_C = −500 mAdc, I_B = −50 mAdc)		−	−1.3	
SMALL−SIGNAL CHARACTERISTICS					
Current−Gain − Bandwidth Product	(I_C = −20 mAdc, V_{CE} = −10 Vdc, f = 100 MHz)	f_T	200	−	MHz
Collector−Base Capacitance	(V_{CB} = −10 Vdc, I_E = 0, f = 1.0 MHz)	C_{cb}	−	8.5	pF
Emitter−Base Capacitance	(V_{BE} = −0.5 Vdc, I_C = 0, f = 1.0 MHz)	C_{eb}	−	30	pF
Input Impedance	(I_C = −1.0 mAdc, V_{CE} = −10 Vdc, f = 1.0 kHz)	h_{ie}	1.5	15	kΩ
Voltage Feedback Ratio	(I_C = −1.0 mAdc, V_{CE} = −10 Vdc, f = 1.0 kHz)	h_{re}	0.1	8.0	X 10^{-4}
Small−Signal Current Gain	(I_C = −1.0 mAdc, V_{CE} = −10 Vdc, f = 1.0 kHz)	h_{fe}	60	500	−
Output Admittance	(I_C = −1.0 mAdc, V_{CE} = −10 Vdc, f = 1.0 kHz)	h_{oe}	1.0	100	μMhos
SWITCHING CHARACTERISTICS					
Delay Time	(V_{CC} = −30 Vdc, V_{EB} = −2.0 Vdc, I_C = −150 mAdc, I_{B1} = −15 mAdc)	t_d	−	15	ns
Rise Time		t_r	−	20	
Storage Time	(V_{CC} = −30 Vdc, I_C = −150 mAdc, I_{B1} = I_{B2} = −15 mAdc)	t_s	−	225	ns
Fall Time		t_f	−	30	

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

3. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%.

SWITCHING TIME EQUIVALENT TEST CIRCUIT




Figure 1. Turn−On Time




Figure 2. Turn−Off Time

Scope rise time < 4.0 ns

*Total shunt capacitance of test jig connectors, and oscilloscope

chanhvinh.com

TRANSIENT CHARACTERISTICS




Figure 3. Charge Data




Figure 4. Turn−On Time




Figure 5. Rise Time




Figure 6. Storage Time

SMALL−SIGNAL CHARACTERISTICS NOISE FIGURE

V_{CE} = −10 Vdc, T_A = 25°C; Bandwidth = 1.0 Hz




Figure 7. Frequency Effects




Figure 8. Source Resistance Effects

chanhvinh.com

h PARAMETERS

V_{CE} = 10 Vdc, f = 1.0 kHz, T_A = 25°C

This group of graphs illustrates the relationship between h_{fe} and other “h” parameters for this series of transistors. To obtain these curves, a high−gain and a low−gain unit were selected from the MMBT4403LT1 lines, and the same units were used to develop the correspondingly numbered curves on each graph.




Figure 9. Input Impedance




Figure 10. Voltage Feedback Ratio




Figure 11. Output Admittance

chanhvinh.com

STATIC CHARACTERISTICS




Figure 12. DC Current Gain




Figure 13. Collector Saturation Region




Figure 14. Collector−Emitter Saturation Voltage vs. Collector Current




Figure 15. Temperature Coefficients

chanhvinh.com

STATIC CHARACTERISTICS




Figure 16. Base−Emitter Saturation Voltage vs. Collector Current




Figure 17. Base−Emitter Turn On Voltage vs. Collector Current




Figure 18. Input Capacitance vs. Emitter Base Voltage




Figure 19. Output Capacitance vs. Collector Base Voltage




Figure 20. Safe Operating Area





Figure 21. Current−Gain−Bandwidth Product

chanhvinh.com

MMBT4403L, SMMBT4403L

PACKAGE DIMENSIONS

SOT−23 (TO−236)
CASE 318−08
ISSUE AR




NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF THE BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

	MILLIMETERS			INCHES		
DIM	MIN	NOM	MAX	MIN	NOM	MAX
A	0.89	1.00	1.11	0.035	0.039	0.044
A1	0.01	0.06	0.10	0.000	0.002	0.004
b	0.37	0.44	0.50	0.015	0.017	0.020
c	0.08	0.14	0.20	0.003	0.006	0.008
D	2.80	2.90	3.04	0.110	0.114	0.120
E	1.20	1.30	1.40	0.047	0.051	0.055
e	1.78	1.90	2.04	0.070	0.075	0.080
L	0.30	0.43	0.55	0.012	0.017	0.022
L1	0.35	0.54	0.69	0.014	0.021	0.027
H_E	2.10	2.40	2.64	0.083	0.094	0.104
T	0°	−−−	10°	0°	−−−	10°

STYLE 6:
PIN 1. BASE
2. EMITTER
3. COLLECTOR

RECOMMENDED SOLDERING FOOTPRINT*



DIMENSIONS: MILLIMETERS

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative