chanhvinh.com

DATA SHEET
www.onsemi.com


MOSFET - Power, Single N-Channel, SUPERFET®, with Zener Diode, DPAK
600 V, 280 mΩ, 13 A
NTD280N60S5Z

$V_{(BR)DSS}$	$R_{DS(ON)}$ MAX	I_D MAX
600 V	280 mΩ @ V_{GS} = 10 V	13 A


Description
SUPERFET V MOSFET Easy Drive series combines excellent switching performance without sacrificing ease of use and EMI issues for both hard and soft switching topologies.

Features
- 650 V @ T_J = 150°C, Typ.
- $R_{DS(on)}$ = 224 mΩ
- 100% Avalanche Tested
- Pb−Free, Halogen Free / BFR Free and are RoHS Compliant

Applications
- Computing / Display Power Supplies
- Telecom / Server Power Supplies
- Lighting / Charger / Adapter / Industrial Power Supplies




N−CHANNEL MOSFET



DPAK
CASE 369AS

MARKING DIAGRAM



T280N60S5Z = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
ZZ = Lot Code

ABSOLUTE MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

Parameter		Symbol	Value	Unit
Drain−to−Source Voltage		V_{DSS}	600	V
Gate−to−Source Voltage	DC	V_{GS}	±20	V
	AC (f > 1 Hz)		±20	
Continuous Drain Current	T_C = 25°C	I_D	13	A
	T_C = 100°C		8	
Power Dissipation	T_C = 25°C	P_D	89	W
Pulsed Drain Current (Note 1)	T_C = 25°C	I_{DM}	39	A
Pulsed Source Current (Body Diode) (Note 1)		I_{SM}	39	A
Operating Junction and Storage Temperature Range		T_J, T_{STG}	−55 to +150	°C
Source Current (Body Diode)		I_S	13	A
Single Pulse Avalanche Energy	I_L = 2.9 A, R_G = 25 Ω	E_{AS}	82	mJ
Avalanche Current		I_{AS}	2.9	A
Repetitive Avalanche Energy (Note 1)		E_{AR}	0.89	mJ
MOSFET dv/dt		dv/dt	120	V/ns
Peak Diode Recovery dv/dt (Note 2)			50	
Lead Temperature for Soldering Purposes (1/8″ from case for 10 s)		T_L	260	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.
*Drain current limited by maximum junction temperature.
1. Repetitive rating: pulse−width limited by maximum junction temperature.
2. I_{SD} ≤ 5.5 A, di/dt ≤ 200 A/s, V_{DD} ≤ 400 V, starting T_J = 25°C.

ORDERING INFORMATION

Device	Package	Shipping†
NTD280N60S5Z	DPAK (Pb−Free)	2500 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2022

chanhvinh.com

THERMAL CHARACTERISTICS

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction–to–Case	$R_{\theta JC}$	1.4	°C/W
Thermal Resistance, Junction–to–Ambient	$R_{\theta JA}$	52	

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Drain–to–Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0 V, I_D = 1 mA, T_J = 25°C	600	–	–	V
Drain–to–Source Breakdown Voltage Temperature Coefficient	$\Delta V_{(BR)DSS}/\Delta T_J$	I_D = 10 mA, Referenced to 25°C	–	630	–	mV/°C
Zero Gate Voltage Drain Current	I_{DSS}	V_{GS} = 0 V, V_{DS} = 600 V, T_J = 25°C	–	–	1	μA
Gate–to–Source Leakage Current	I_{GSS}	V_{GS} = ±20 V, V_{DS} = 0 V	–	–	±5	μA
ON CHARACTERISTICS						
Drain–to–Source On Resistance	$R_{DS(on)}$	V_{GS} = 10 V, I_D = 5.5 A, T_J = 25°C	–	224	280	mΩ
Gate Threshold Voltage	$V_{GS(th)}$	V_{GS} = V_{DS}, I_D = 1 mA, T_J = 25°C	2.4	–	4	V
Forward Trans–conductance	g_{FS}	V_{DS} = 20 V, I_D = 5.5 A	–	10.6	–	S
CHARGES, CAPACITANCES & GATE RESISTANCE						
Input Capacitance	C_{ISS}	V_{DS} = 400 V, V_{GS} = 0 V, f = 250 kHz	–	978	–	pF
Output Capacitance	C_{OSS}		–	16.8	–	
Time Related Output Capacitance	$C_{OSS(tr)}$	I_D = Constant, V_{DS} = 0 V to 400 V, V_{GS} = 0 V	–	276	–	
Energy Related Output Capacitance	$C_{OSS(er)}$	V_{DS} = 0 V to 400 V, V_{GS} = 0 V	–	30.5	–	
Total Gate Charge	$Q_{G(TOT)}$	V_{DD} = 400 V, I_D = 5.5 A, V_{GS} = 10 V	–	17.9	–	nC
Gate–to–Source Charge	Q_{GS}		–	4.53	–	
Gate–to–Drain Charge	Q_{GD}		–	4.8	–	
Gate Resistance	R_G	f = 1 MHz	–	5.11	–	Ω
SWITCHING CHARACTERISTICS						
Turn-On Delay Time	$t_{d(ON)}$	V_{GS} = 0/10 V, V_{DD} = 400 V, I_D = 5.5 A, R_G = 12 Ω	–	15.5	–	ns
Rise Time	t_r		–	4.27	–	
Turn-Off Delay Time	$t_{d(OFF)}$		–	52	–	
Fall Time	t_f		–	4.53	–	
SOURCE-TO–DRAIN DIODE CHARACTERISTICS						
Forward Diode Voltage	V_{SD}	I_{SD} = 5.5 A, V_{GS} = 0 V, T_J = 25°C	–	–	1.2	V
Reverse Recovery Time	t_{RR}	V_{GS} = 0 V, I_{SD} = 5.5 A, dI/dt = 100 A/μs, V_{DD} = 400 V	–	229	–	ns
Reverse Recovery Charge	Q_{RR}		–	2114	–	nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

chanhvinh.com

TYPICAL CHARACTERISTICS




Figure 1. On−Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On−Resistance Variation vs. Drain Current and Gate Voltage




Figure 4. Diode Forward Voltage vs. Source Current




Figure 5. Capacitance Characteristics




Figure 6. Gate Charge Characteristics

chanhvinh.com

TYPICAL CHARACTERISTICS




Figure 7. Breakdown Voltage Variation vs. Temperature




Figure 8. On−Resistance Variation vs. Temperature




Figure 9. Maximum Safe Operating Area




Figure 10. Maximum Drain Current vs. Case Temperature




Figure 11. Eoss vs. Drain−to−Source Voltage

chanhvinh.com

TYPICAL CHARACTERISTICS




Figure 12. Transient Thermal Impedance


SUPERFET is a registered trademark of Semiconductor Components Industries, LLC or its subsidiaries in the United States and/or other countries.

chanhvinh.com


NTD280N60S5Z

PACKAGE DIMENSIONS

DPAK3 (TO−252 3 LD)
CASE 369AS
ISSUE A




NOTES: UNLESS OTHERWISE SPECIFIED
A) THIS PACKAGE CONFORMS TO JEDEC, TO-252, ISSUE C, VARIATION AA.
B) ALL DIMENSIONS ARE IN MILLIMETERS.
C) DIMENSIONING AND TOLERANCING PER ASME Y14.5M-2009.
D) SUPPLIER DEPENDENT MOLD LOCKING HOLES OR CHAMFERED CORNERS OR EDGE PROTRUSION.
E) FOR DIODE PRODUCTS, L4 IS 0.25 MM MAX.
F) DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH AND TIE BAR EXTRUSIONS.
G) LAND PATTERN RECOMMENDATION IS BASED ON IPC7351A STD TO228P991X239-3N.




DETAIL A
(ROTATED -90°)
SCALE: 12X


DIM	MILLIMETERS		
	MIN.	NOM.	MAX.
A	2.18	2.29	2.39
A1	0.00	-	0.127
b	0.64	0.77	0.89
b2	0.76	0.95	1.14
b3	5.21	5.34	5.46
c	0.45	0.53	0.61
c2	0.45	0.52	0.58
D	5.97	6.10	6.22
D1	5.21	—	—
E	6.35	6.54	6.73
E1	4.32	—	—
e	2.286 BSC		
e1	4.572 BSC		
H	9.40	9.91	10.41
L	1.40	1.59	1.78
L1	2.90 REF		
L2	0.51 BSC		
L3	0.89	1.08	1.27
L4	—	—	1.02
θ	0°	---	10°

NON-DIODE PRODUCTS VERSION



NON-DIODE PRODUCTS VERSION





LAND PATTERN RECOMMENDATION

*FOR ADDITIONAL INFORMATION ON OUR PB-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERRM/D.

chanhvinh.com

NTD280N60S5Z

onsemi, ONSEMI., and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi's** product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Email Requests to: orderlit@onsemi.com

onsemi Website: www.onsemi.com

TECHNICAL SUPPORT
North American Technical Support:
Voice Mail: 1 800−282−9855 Toll Free USA/Canada
Phone: 011 421 33 790 2910

Europe, Middle East and Africa Technical Support:
Phone: 00421 33 790 2910
For additional information, please contact your local Sales Representative

◊