chanhvinh.com

MOSFET – Power, Single N-Channel, DFNW8

150 V, 6.4 mΩ, 135 A

NTMTS6D0N15MC

ON Semiconductor®

www.onsemi.com


Features

- Small Footprint (8x8 mm) for Compact Design
- Low $R_{DS(on)}$ to Minimize Conduction Losses
- Low Q_G and Capacitance to Minimize Driver Losses
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant


Typical Applications

- Power Tools, Battery Operated Vacuums
- UAV/Drones, Material Handling
- BMS/Storage, Home Automation

$V_{(BR)DSS}$	$R_{DS(ON)}$ MAX	I_D MAX
150 V	6.4 mΩ @ 10 V	135 A
	6.9 mΩ @ 8 V	



N−CHANNEL MOSFET



Top Bottom

DFNW8 8.3x8.4, 2P
PQFN88
CASE 507AP


MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

Symbol	Parameter			Value	Unit
V_{DSS}	Drain−to−Source Voltage			150	V
V_{GS}	Gate−to−Source Voltage			±20	V
I_D	Continuous Drain Current $R_{\theta JC}$ (Note 2)	Steady State	T_C = 25°C	135	A
P_D	Power Dissipation $R_{\theta JC}$ (Note 2)			245	W
I_D	Continuous Drain Current $R_{\theta JA}$ (Note 1, 2)	Steady State	T_A = 25°C	19	A
P_D	Power Dissipation $R_{\theta JA}$ (Note 1, 2)			4.9	W
I_{DM}	Pulsed Drain Current	T_A = 25°C, t_p = 10 μs		900	A
T_J, T_{stg}	Operating Junction and Storage Temperature Range			−55 to +175	°C
I_S	Source Current (Body Diode)			204	A
E_{AS}	Single Pulse Drain−to−Source Avalanche Energy (I_L = 46.2 A_{pk}, L = 0.3 mH)			320	mJ
T_L	Lead Temperature Soldering Reflow for Soldering Purposes (1/8" from case for 10 s)			260	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Surface−mounted on FR4 board using 1 in^2 pad size, 1 oz Cu pad.
2. The entire application environment impacts the thermal resistance values shown, they are not constants and are only valid for the particular conditions noted

MARKING DIAGRAM



6D0N15MC	= Specific Device Code
A	= Assembly Location
WL	= Wafer Lot Code
Y	= Year Code
WW	= Work Week Code

ORDERING INFORMATION

Device	Package	Shipping†
NTMTS6D0N15MC	DFNW8 PQFN88 (Pb−Free)	3000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2019

chanhvinh.com

THERMAL RESISTANCE RATINGS

Symbol	Parameter	Max	Unit
$R_{\theta JC}$	Junction–to–Case – Steady State (Note 2)	0.6	°C/W
$R_{\theta JA}$	Junction–to–Ambient – Steady State (Note 2)	30.2	

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Symbol	Parameter	Test Condition		Min	Typ	Max	Unit
OFF CHARACTERISTICS							
$V_{(BR)DSS}$	Drain – to – Source Breakdown Voltage	V_{GS} = 0 V, I_D = 250 μA		150	–	–	V
$V_{(BR)DSS}$ / T_J	Drain – to – Source Breakdown Voltage Temperature Coefficient	I_D = 250 μA, ref to 25°C		–	58.67	–	mV/°C
I_{DSS}	Zero Gate Voltage Drain Current	V_{GS} = 0 V, V_{DS} = 120 V	T_J = 25°C	–	–	1	μA
			T_J = 125°C	–	–	10	μA
I_{GSS}	Gate – to – Source Leakage Current	V_{DS} = 0 V, V_{GS} = ±20 V		–	–	±100	nA
ON CHARACTERISTICS (Note 3)							
$V_{GS(TH)}$	Gate Threshold Voltage	V_{GS} = V_{DS}, I_D = 379 μA		2.5	3.6	4.5	V
$V_{GS(TH)}$ / T_J	Negative Threshold Temperature Coefficient	I_D = 250 μA, ref to 25°C		–	–9.14	–	mV/°C
$R_{DS(on)}$	Drain – to – Source On Resistance	V_{GS} = 10 V, I_D = 69 A		–	4.6	6.4	mΩ
		V_{GS} = 8 V, I_D = 34 A		–	5.0	6.9	
g_{FS}	Forward Transconductance	V_{DS} = 5 V, I_D = 69 A		–	127	–	S
R_G	Gate–Resistance	T_A = 25°C		–	1.1	–	Ω
CHARGES & CAPACITANCES							
C_{ISS}	Input Capacitance	V_{GS} = 0 V, f = 1 MHz, V_{DS} = 75V		–	4815	–	pF
C_{OSS}	Output Capacitance			–	1482	–	
C_{RSS}	Reverse Transfer Capacitance			–	9.7	–	
$Q_{G(TOT)}$	Total Gate Charge	V_{GS} = 10 V, V_{DS} = 75 V, I_D = 69 A		–	58	–	nC
$Q_{G(TH)}$	Threshold Gate Charge			–	34	–	
Q_{GS}	Gate–to–Source Charge			–	26	–	
Q_{GD}	Gate–to–Drain Charge			–	8	–	
Q_{OSS}	Output Charge	V_{GS} = 0 V, V_{DS} = 75 V		–	173	–	nC
SWITCHING CHARACTERISTICS, VGS = 10 V (Note 3)							
$t_{d(ON)}$	Turn – On Delay Time	V_{GS} = 10 V, V_{DS}=75 V, I_D = 69 A, R_G = 6 Ω		–	30	–	ns
t_r	Rise Time			–	7	–	
$t_{d(OFF)}$	Turn – Off Delay Time			–	38	–	
t_f	Fall Time			–	6	–	
DRAIN–SOURCE DIODE CHARACTERISTICS							
V_{SD}	Forward Diode Voltage	V_{GS} = 0 V, I_S = 69 A	T_J = 25°C	–	0.87	1.2	V
			T_J = 125°C	–	0.7	–	
t_{RR}	Reverse Recovery Time	V_{GS} = 0 V, dI_S/dt = 100 A/μs, I_S = 69 A		–	72	–	ns
t_a	Charge Time			–	49	–	
t_b	Discharge Time			–	23	–	
Q_{RR}	Reverse Recovery Charge			–	125	–	nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

3. Switching characteristics are independent of operating junction temperatures

chanhvinh.com

TYPICAL CHARACTERISTICS




Figure 1. On−Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On−Resistance vs. Gate−to−Source Voltage




Figure 4. On−Resistance vs. Drain Current and Gate Voltage




Figure 5. On−Resistance Variation with Temperature




Figure 6. Drain−to−Source Leakage Current vs. Voltage

chanhvinh.com

TYPICAL CHARACTERISTICS




Figure 7. Capacitance Variation




Figure 8. Gate−to−Source and Drain−to−Source Voltage vs. Total Charge




Figure 9. Resistive Switching Time Variation vs. Gate Resistance




Figure 10. Diode Forward Voltage vs. Current




Figure 11. Safe Operating Area




Figure 12. I_{PEAK} vs. Time in Avalanche

chanhvinh.com

TYPICAL CHARACTERISTICS





Figure 13. Thermal Characteristics

chanhvinh.com

NTMTS6D0N15MC


PACKAGE DIMENSIONS

DFNW8 8.3x8.4, 2P
CASE 507AP
ISSUE C



NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009.
2. CONTROLLING DIMENSION: MILLIMETERS
3. COPLANARITY APPLIES TO THE EXPOSED PADS AS WELL AS THE TERMINALS.
4. DIMENSIONS D1 AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.
5. SEATING PLANE IS DEFINED BY THE TERMINALS. "A1" IS DEFINED AS THE DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT ON THE PACKAGE BODY.



RECOMMENDED LAND PATTERN*

*FOR ADDITIONAL INFORMATION ON OUR PB-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERRM/D.

DIM	MILLIMETERS		
	MIN.	NOM.	MAX.
A	1.00	1.10	1.20
A1	0.00	---	0.05
b	0.90	1.00	1.10
b1	0.43	0.53	0.63
c	0.23	0.28	0.33
D	8.20	8.30	8.40
D1	7.90	8.00	8.10
D2	6.80	6.90	7.00
D3	6.90	7.00	7.10
E	8.30	8.40	8.50
E1	7.80	7.90	8.00
E2	5.24	5.34	5.44
E3	0.25	0.35	0.45
e	2.00 BSC		
e/2	1.00 BSC		
e1	2.70 BSC		
e1/2	1.35 BSC		
K	1.50	1.57	1.70
L	0.64	0.74	0.84
L1	0.67	0.77	0.87
θ	0°	---	12°

chanhvinh.com

NTMTS6D0N15MC

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Email Requests to: orderlit@onsemi.com

ON Semiconductor Website: www.onsemi.com

TECHNICAL SUPPORT
North American Technical Support:
Voice Mail: 1 800−282−9855 Toll Free USA/Canada
Phone: 011 421 33 790 2910

Europe, Middle East and Africa Technical Support:
Phone: 00421 33 790 2910
For additional information, please contact your local Sales Representative

◊