
chanhvinh.com

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



PANDUIT * PART NO.	BUNDLE DIA. MIN in (mm)	BUNDLE DIA. MAX in (mm)	A in. (mm)	B in. (mm)	C in. (mm)	D in. (mm)	E in. (mm)	F in. (mm)	MIN. LOOP TENSILE lbs (N)	CROSS-SECTION	WEIGHT lbs/100pcs (g)
CBR1M	.070 (1.8)	1.0 (25.4)	.038 (1.0)	.098 (2.5)	.140 (3.6)	.208 (5.3)	.195 (5.0)	4.1 (104.1)	18 (80)	MINIATURE	.061 (27.7)
A CBR1.5M	.070 (1.8)	1.5 (38.1)	.042 (1.1)	.098 (2.5)	.146 (3.7)	.208 (5.3)	.209 (5.3)	5.8 (147.3)	18 (80)	MINIATURE	.084 (38.3)
A CBR2M	.070 (1.8)	2.0 (50.8)	.042 (1.1)	.098 (2.5)	.146 (3.7)	.208 (5.3)	.209 (5.3)	7.3 (185.4)	18 (80)	MINIATURE	.108 (48.8)
CBR1.5I	.070 (1.8)	1.5 (38.1)	.040 (1.0)	.140 (3.6)	.180 (4.6)	.250 (6.4)	.250 (6.4)	5.9 (149.9)	40 (178)	INTERMEDIATE	.129 (58.5)
CBR3I	.070 (1.8)	3.0 (76.2)	.052 (1.3)	.140 (3.6)	.192 (4.9)	.250 (6.4)	.262 (6.7)	10.4 (264.2)	40 (178)	INTERMEDIATE	.26 (119.3)
A CBR4I	.070 (1.8)	4.0 (101.6)	.052 (1.3)	.140 (3.6)	.192 (4.9)	.250 (6.4)	.262 (6.7)	13.6 (345.4)	40 (178)	INTERMEDIATE	.34 (153.2)

*SEE www.panduit.com FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE, PART MATERIAL, PART COLOR AND ANY THIRD PARTY RECOGNITION OR COMPLIANCE.

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
6	6/16/17	BWG	MPH	JADE	A ADDED CBR1.5/2M TIP DESIGN VIEWS. REVISED WEBSITE NOTE. REVISED DIM. "F" FOR CBR1.5M AND CBR2M.	013188/00
5	6/18/15	BWG	MPH	JADE	CORRECTED MATERIAL NOTE.	SS-27318/05
4	11.18.14	BDK	MPH	JADE	UPDATED TITLE BORDER AND UPDATED NOTES	SS-27318

TITLE

CBR SERIES CABLE TIE

CUSTOMER DRAWING

ITEM REVISION NAME: 10B0150T/02

DATASET FILE NAME: 10B0150T_DC/02 - SS-27318_REV06

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]

.X ± .01 [.25] .XXX ± .020 [.51]

.XX ± .02 [.5] ANGLES ±

THIRD ANGLE PROJECTION

PANDUIT

MATERIAL: NYLON 6.6

DRAWING NUMBER: SS-27318

DRAWN BY	DATE	CHK	SCALE	SIZE
JABO	6/22/01	JRJR	NONE	A

SHT 1 OF 1

D10100DA/16