
chanhvinh.com

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



NOTES, UNLESS OTHERWISE SPECIFIED:

PANDUIT CT-1550 TOOL:

TOOL WEIGHT: 27.2 oz. [77] kg

Crimps most Panduit #22-#10 AWG insulated terminals & splices; and specific insulated disconnects.

Reduced crimp effort advantage for #22-#14 AWG terminations.

Provides UL Listed and CSA Certified terminations with applicable Panduit terminals.

DIMENSIONS SHOWN IN BRACKETS [ ] ARE METRIC, AND ARE FOR REFERENCE ONLY.

CRIMP POCKET AWG / mm²	ENGLISH GO / NO GO GAGE MEMBERS		METRIC GO / NO GO GAGE MEMBERS	
	"G" Dia. (GO)	"NG" Dia. (NO GO)	"G" Dia. (GO)	"NG" Dia. (NO GO)
22-14/0,5-2,5	0.101"	0.109"	2,56 mm	2,76 mm
12-10/4,0-6,0	0.147"	0.155"	3,73 mm	3,93 mm

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
---	---	---	---	---	ADDED GO – NO GO CHART	---
01	12/12/16	BWG	BJPU	JADE	REMOVED GLOBAL LOGO MOVED MADE IN GERMANY TO FRAME.	4857/ 02
00	5-07-15	BLR	BJPU	ABJ	RELEASED	4857

CT-1550 Contour Crimp™ Crimping Tool

CUSTOMER DRAWING

ITEM REVISION NAME: TP27602B01_01

PANDUIT

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:
(.x) ± --- (.xxx) ± ---
(.xx) ± --- ANGLES ± ---
THIRD ANGLE PROJECTION

MATERIAL: ----------

DRAWING NUMBER: TP27602B01

DRAWN BY:	DATE:	CHK	SCALE		SIZE
BLR	5-07-15	BJPU	NONE	SHT 1 OF 1	B