
chanhvinh.com


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.


Material	High Conductivity Seamless Copper Tube
Plating	Electro-Tin
Wire Size	2/0 AWG
Wire Type	Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric
Wire Strip Length	1-1/16 in.
Stud Size	3/8 in.
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.
UL Temperature Rating	90˚ C
C.S.A Certified Wire Connector	Yes
Panduit Color Code on Barrel	BLACK
Panduit Die Index No. on Barrel	P45
Alternate Industry Die Index No. ( ) on Barrel	(13)

CERTIFIED

LISTED
Wire Connector







REV	DATE	BY	CHK	DESCRIPTION	ECN
01	7/04	DRL	DRL	ADDED UL, CSA AND PART NO. TO STAMP	11969

PANDUIT CORP. TINLEY PARK, ILLINOIS

LCA2/0-38F-X
Copper Lug - One-Hole, Standard Barrel, 90° Angle Tongue

SCALE	DRAWING NO / CAD FILE
N/A	LCA2_0-38F-CUST