chanhvinh.com

EMPPR (27X15) - Touch protection

0829535

https://www.phoenixcontact.com/gb/products/0829535

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Touch protection, Sheet, transparent, unlabeled, mounting type: latching, Number of individual labels: 1, text field height: 15 mm, text field width: 27 mm

Your advantages

- High level of mechanical and chemical stability
- Suitable for permanent outdoor use
- Stuck or snapped onto labeled CARRIER ... to protect the labeling
- Extremely thick, yet flexible and transparent shock protection

Commercial data

Item number	0829535
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	BG241B
Product key	BG241B
Catalog page	Page 349 (C-3-2019)
GTIN	4046356614931
Weight per piece (including packing)	0.193 g
Weight per piece (excluding packing)	0.1 g
Customs tariff number	39204910
Country of origin	DE

chanhvinh.com

EMPPR (27X15) - Touch protection

0829535

https://www.phoenixcontact.com/gb/products/0829535

Technical data

Product properties

Product type	Cover
Type of packaging	PE bag

Marking

Number of individual labels	1

Dimensions

Width	27 mm
Length	15 mm

Text field

Text field width	27 mm
Text field height	15 mm

Material specifications

RoHS compliant	yes
Foil strength	300 µm
Color	transparent
Material	PVC
Flammability rating according to UL 94	V0
Components	Silicone-free

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05 (following)
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-30 °C ... 70 °C

chanhvinh.com

EMPPR (27X15) - Touch protection

0829535

https://www.phoenixcontact.com/gb/products/0829535

Recommended storage conditions	10-30 °C / 40-70 % relative humidity. Storage in a cool and dry place is recommended.
Recommended ambient temperature (storage/transport)	-10 °C ... 30 °C
Recommended humidity (storage/transport)	70 %
Shelf life	12 months (see packaging date)

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)

Mounting

Mounting type	latching

chanhvinh.com

EMPPR (27X15) - Touch protection

0829535

https://www.phoenixcontact.com/gb/products/0829535

Classifications

ECLASS

ECLASS-13.0	24292214

ETIM

ETIM 9.0	EC002113

UNSPSC

UNSPSC 21.0	39131500

chanhvinh.com

EMPPR (27X15) - Touch protection

0829535

https://www.phoenixcontact.com/gb/products/0829535

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk