chanhvinh.com

SAC-5P-P12MS/ 1,5-PUR/P12FS - Sensor/actuator cable

1224208

https://www.phoenixcontact.com/pc/products/1224208

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 5-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12 Push Pull, coding: A, on Socket straight M12 Push Pull, coding: A, cable length: 1.5 m

Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Save time, thanks to installation with push-pull fast locking

Commercial data

Item number	1224208
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	AF1CDC
GTIN	4063151315214
Weight per piece (including packing)	76.7 g
Weight per piece (excluding packing)	77 g
Customs tariff number	85444290
Country of origin	PL

chanhvinh.com

SAC-5P-P12MS/ 1,5-PUR/P12FS - Sensor/actuator cable

1224208

https://www.phoenixcontact.com/pc/products/1224208

Technical data

Product properties

Product type	Sensor/actuator cable
Application	Standard
Number of positions	5
No. of cable outlets	1
Shielded	no
Coding	A

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Material	PK (Pin contact carrier)
	(Female connector contact carrier)
Flammability rating according to UL 94	V0
Seal material	FKM
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Material for screw connection	Brass, nickel-plated

Electrical properties

Insulation resistance	≥ 100 MΩ
Nominal voltage U_N	48 V AC
	60 V DC
Nominal current I_N	4 A

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100

Signaling

Status display	no
Status display present	No

Connector

Connection 1

Type	Plug straight M12 Push Pull
Number of positions	5
Locking type	Push Pull

SAC-5P-P12MS/ 1,5-PUR/P12FS - Sensor/actuator cable

1224208

https://www.phoenixcontact.com/pc/products/1224208

Coding type	A

Connection 2

Type	Socket straight M12 Push Pull
Number of positions	5
Locking type	Push Pull
Coding type	A

Cable/line

Cable length	1.5 m

PUR halogen-free black [PUR]

Dimensional drawing	
Cable weight	33 kg/km
UL AWM Style	20549
Number of positions	5
Shielded	no
Cable type	PUR halogen-free black [PUR]
Conductor structure signal line	42x 0.10 mm
AWG signal line	22
Conductor cross section	5x 0.34 mm² (Signal line)
Wire diameter incl. insulation	1.27 mm 0.05 mm (Signal line)
External cable diameter	4.55 mm ±0.15 mm
Outer sheath, material	PUR
External sheath, color	black-gray RAL 7021
Conductor material	Bare Cu litz wires
Material wire insulation	PP
Single wire, color	brown, white, blue, black, green-yellow
Thickness, insulation	approx. 0.50 mm
Max. conductor resistance	max. 58 Ω/km (at 20 °C)
Insulation resistance	≥ 16 GΩ*km (at 20 °C)
Nominal voltage, cable	300 V
Test voltage	3000 V
Smallest bending radius, fixed installation	23 mm
Smallest bending radius, movable installation	46 mm
Dynamic load capacity (bending)	Max. bending cycles: 10000000, Bending radius: 46 mm, Bending radius: 10 x D, Traversing path: 10 m, Traversing rate: 3 m/s, Acceleration: 10 m/s²

chanhvinh.com

SAC-5P-P12MS/ 1,5-PUR/P12FS - Sensor/actuator cable

1224208

https://www.phoenixcontact.com/pc/products/1224208

Dynamic load capacity (torsion)	Torsion: ±360 °/m, Torsion cycles: ≥5000000
Halogen-free	in accordance with DIN VDE 0472 part 815
Flame resistance	in accordance with UL 758/1581 FT2
	DIN EN 60332-2-2 (20 s)
Resistance to oil	in accordance with DIN EN 60811-2-1
Other resistance	Highly resistant to acids, alkaline solutions and solvents
	hydrolysis and microbe resistant
	Resistant to salt water
	partly UV-resistant (in accordance with DIN EN ISO 4892-2-A)
Special properties	Flexible cable conduit capable
	Silicone-free
	Free of substances which would hinder coating with paint or varnish
	flexible
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation)
	-25 °C ... 80 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-25 °C ... 85 °C (Plug / socket)

Standards and regulations

Standard designation	M12-Push-Pull
Standards/specifications	IEC 61076-2-010

chanhvinh.com


SAC-5P-P12MS/ 1,5-PUR/P12FS - Sensor/actuator cable

1224208

https://www.phoenixcontact.com/pc/products/1224208


Drawings

Dimensional drawing



M12 push-pull male connector, straight

Dimensional drawing



M12 push-pull female connector, straight


chanhvinh.com

SAC-5P-P12MS/ 1,5-PUR/P12FS - Sensor/actuator cable

1224208


https://www.phoenixcontact.com/pc/products/1224208

Schematic diagram



Pin assignment M12 male connector

Schematic diagram



Pin assignment socket M 12

chanhvinh.com

SAC-5P-P12MS/ 1,5-PUR/P12FS - Sensor/actuator cable

1224208

https://www.phoenixcontact.com/pc/products/1224208

Circuit diagram



Contact assignment of the M12 plug and the M12 socket

chanhvinh.com

SAC-5P-P12MS/ 1,5-PUR/P12FS - Sensor/actuator cable

1224208

https://www.phoenixcontact.com/pc/products/1224208

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/pc/products/1224208

cULus Recognized
Approval ID: E221474

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	125 V	4 A	- 22	-

chanhvinh.com

SAC-5P-P12MS/ 1,5-PUR/P12FS - Sensor/actuator cable

1224208

https://www.phoenixcontact.com/pc/products/1224208

Classifications

ECLASS

ECLASS-11.0	27060311
ECLASS-12.0	27060311
ECLASS-13.0	27060311

ETIM

ETIM 9.0	EC001855

UNSPSC

UNSPSC 21.0	26121600

chanhvinh.com

SAC-5P-P12MS/ 1,5-PUR/P12FS - Sensor/actuator cable

1224208

https://www.phoenixcontact.com/pc/products/1224208

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com