chanhvinh.com

NBC-R4OC/30,0-BC6A/R4OC - Patch cable

1367336

https://www.phoenixcontact.com/in/products/1367336

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Patch cable, degree of protection: IP20, cable length: 30 m, number of positions: 8, 10 Gbps, $CAT6_A$, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

Your advantages

- Perfect for office, building, and protected industrial applications (e.g., in control cabinets)
- Worldwide approval with CE, UL, WEEE, and EAC
- Secure connection and disconnection with reliable locking clip protection
- Ideal EMC properties, thanks to 360° shielding
- Simultaneous power transmission with PoE++
- Future-proof high-speed data transmission with up to 10 Gbps (CAT6_A)

Commercial data

Item number	1367336
Packing unit	1 pc
Minimum order quantity	10 pc
Sales key	ABN
Product key	ABNABH
GTIN	4063151720469
Weight per piece (including packing)	1,544 g
Weight per piece (excluding packing)	1,485.8 g
Customs tariff number	85444210
Country of origin	CN

chanhvinh.com

NBC-R4OC/30,0-BC6A/R4OC - Patch cable

1367336

https://www.phoenixcontact.com/in/products/1367336

Technical data

Product properties

Product type	Data cable preassembled
Product family	RJ45 STANDARD CAT6A
Sensor type	Ethernet
Number of positions	8
Shielded	yes
Cable outlet	straight

Insulation characteristics

Overvoltage category	I
Degree of pollution	2

Electrical properties

Rated voltage (III/2)	72 V
Transmission medium	Copper
Transmission characteristics (category)	$CAT6_A$
Transmission speed	10 Gbps
Power transmission	PoE++

Mechanical properties

Mechanical data

Insertion force per signal contact	30.00 N
Extraction force per signal contact	50 N

Material specifications

Flammability rating according to UL 94	V0
Contact material	Brass
Contact surface material	Au
Contact carrier material	PC
Outer sheath, material	LSZH

Dimensions

Width	11.6 mm
Height	14.8 mm
Length	40 mm

Connection data

Connection technology

Connection method	Pierce connection

Conductor connection

Connection method	Pierce connection

chanhvinh.com

NBC-R4OC/30,0-BC6A/R4OC - Patch cable

1367336

https://www.phoenixcontact.com/in/products/1367336

Connector

Connection 1

Type	Plug straight RJ45
Shielded	yes
Handle color	gray
Insertion/withdrawal cycles	≥ 750
Degree of protection	IP20
Ambient temperature (operation)	-20 °C ... 80 °C

Connection 2

Type	Plug straight RJ45
Shielded	yes
Handle color	gray
Insertion/withdrawal cycles	≥ 750
Degree of protection	IP20
Ambient temperature (operation)	-20 °C ... 80 °C

Cable/line

Cable length	30.00 m

Ethernet, Type B, 8-pos., CAT6A, LSZH [BC6A]

Number of positions	8
Shielded	yes
Cable type	Ethernet, Type B, 8-pos., CAT6A, LSZH [BC6A]
Conductor structure	4x2xAWG26/7; S/FTP
Conductor structure signal line	7x 0.16 mm
AWG signal line	26
Wire diameter incl. insulation	1 mm
External cable diameter	6.50 mm ±0.3 mm
Outer sheath, material	LSZH
External sheath, color	gray
Conductor material	Bare Cu litz wires
Material wire insulation	PE
Single wires, quantity	8
Single wire, cross section [AWG]	26
Thickness, outer sheath	approx. 0.70 mm
Optical shield covering	70 %
Insulation resistance	≥ 5000 MΩ*km
Loop resistance	≤ 148.00 Ω/km
Wave impedance	100 Ω
Minimum bending radius, fixed installation	8 x D
Smallest bending radius, fixed installation	52 mm
Near end crosstalk attenuation (NEXT)	75 dB (with 1 MHz)
	66.3 dB (at 4 MHz)

chanhvinh.com

NBC-R4OC/30,0-BC6A/R4OC - Patch cable

1367336

https://www.phoenixcontact.com/in/products/1367336

	60.3 dB (at 10 MHz)
	57.2 dB (at 16 MHz)
	55.8 dB (at 20 MHz)
	52.9 dB (at 31.25 MHz)
	48.4 dB (at 62.5 MHz)
	45.3 dB (at 100 MHz)
	40.8 dB (at 200 MHz)
	38.1 dB (at 300 MHz)
	36.3 dB (at 400 MHz)
	34.8 dB (at 500 MHz)
Power-summated near end crosstalk attenuation (PSNEXT)	72.3 dB (with 1 MHz)
	63.3 dB (at 4 MHz)
	58.8 dB (at 8 MHz)
	57.3 dB (at 10 MHz)
	54.2 dB (at 16 MHz)
	52.8 dB (at 20 MHz)
	51.3 dB (at 25 MHz)
	49.9 dB (at 31.25 MHz)
	45.4 dB (at 62.5 MHz)
	42.3 dB (at 100 MHz)
	37.8 dB (at 200 MHz)
	35.1 dB (at 300 MHz)
	33.3 dB (at 400 MHz)
	31.8 dB (at 500 MHz)
Return attenuation (RL)	20 dB (with 1 MHz)
	23 dB (at 4 MHz)
	24.5 dB (at 8 MHz)
	25 dB (at 10 MHz)
	25 dB (at 16 MHz)
	25 dB (at 20 MHz)
	24.2 dB (at 25 MHz)
	23.3 dB (at 31.25 MHz)
	20.7 dB (at 62.5 MHz)
	19 dB (at 100 MHz)
	16.4 dB (at 200 MHz)
	15.6 dB (at 300 MHz)
	15.6 dB (at 400 MHz)
	15.6 dB (at 500 MHz)
Shield attenuation	3.1 dB (with 1 MHz)
	5.7 dB (at 4 MHz)
	8.9 dB (at 10 MHz)
	11.2 dB (at 16 MHz)
	12.6 dB (at 20 MHz)
	15.8 dB (at 31.25 MHz)

chanhvinh.com

NBC-R4OC/30,0-BC6A/R4OC - Patch cable

1367336

https://www.phoenixcontact.com/in/products/1367336

	22.5 dB (at 62.5 MHz)
	28.7 dB (at 100 MHz)
	41.4 dB (at 200 MHz)
	51.4 dB (at 300 MHz)
	60.1 dB (at 400 MHz)
	67.9 dB (at 500 MHz)
Halogen-free	complying with IEC 60754-1/2
Flame resistance	IEC 60332-1-2/IEC 60332-3-24/CM
Ambient temperature (operation)	-20 °C ... 80 °C (cable, fixed installation)
	-20 °C ... 80 °C (Cable, flexible installation)
Ambient temperature (installation)	0 °C ... 60 °C

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-20 °C ... 80 °C
Ambient temperature (storage/transport)	0 °C ... 40 °C

Standards and regulations

Flame resistance	IEC 60332-1-2

chanhvinh.com

NBC-R4OC/30,0-BC6A/R4OC - Patch cable

1367336

https://www.phoenixcontact.com/in/products/1367336

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/in/products/1367336

EAC
Approval ID: 19060508

UL Listed
Approval ID: E335024_20210804

cUL Listed
Approval ID: E335024_20210804

cULus Listed

chanhvinh.com

NBC-R4OC/30,0-BC6A/R4OC - Patch cable

1367336

https://www.phoenixcontact.com/in/products/1367336

Classifications

ECLASS

ECLASS-11.0	27060308
ECLASS-12.0	27060308
ECLASS-13.0	27060307

ETIM

ETIM 9.0	EC001855

chanhvinh.com

NBC-R4OC/30,0-BC6A/R4OC - Patch cable

1367336

https://www.phoenixcontact.com/in/products/1367336

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

chanhvinh.com

NBC-R4OC/30,0-BC6A/R4OC - Patch cable

1367336


https://www.phoenixcontact.com/in/products/1367336

Accessories

HC-M-RJ45-AD-PC2-M - Contact insert module

1435214

https://www.phoenixcontact.com/in/products/1435214



Contact insert module, adapter for patch cables, the matching patch cables can be found in the accessories list

NBC-R4OC/0,3-BC6A/R4OC - Patch cable

1227572

https://www.phoenixcontact.com/in/products/1227572



Patch cable, degree of protection: IP20, cable length: 0.3 m, number of positions: 8, 10 Gbps, CAT6$_A$, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

chanhvinh.com

NBC-R4OC/30,0-BC6A/R4OC - Patch cable

1367336

https://www.phoenixcontact.com/in/products/1367336

NBC-R4OC/0,5-BC6A/R4OC - Patch cable

1227573

https://www.phoenixcontact.com/in/products/1227573



Patch cable, degree of protection: IP20, cable length: 0.5 m, number of positions: 8, 10 Gbps, $CAT6_A$, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

NBC-R4OC/1,0-BC6A/R4OC - Patch cable

1227575

https://www.phoenixcontact.com/in/products/1227575



Patch cable, degree of protection: IP20, cable length: 1 m, number of positions: 8, 10 Gbps, $CAT6_A$, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

chanhvinh.com

NBC-R4OC/30,0-BC6A/R4OC - Patch cable

1367336

https://www.phoenixcontact.com/in/products/1367336

NBC-R4OC/1,5-BC6A/R4OC - Patch cable

1227578

https://www.phoenixcontact.com/in/products/1227578



Patch cable, degree of protection: IP20, cable length: 1.5 m, number of positions: 8, 10 Gbps, CAT6$_A$, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

NBC-R4OC/2,0-BC6A/R4OC - Patch cable

1227580

https://www.phoenixcontact.com/in/products/1227580



Patch cable, degree of protection: IP20, cable length: 2 m, number of positions: 8, 10 Gbps, CAT6$_A$, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

chanhvinh.com

NBC-R4OC/30,0-BC6A/R4OC - Patch cable

1367336

https://www.phoenixcontact.com/in/products/1367336

NBC-R4OC/3,0-BC6A/R4OC - Patch cable

1227581

https://www.phoenixcontact.com/in/products/1227581



Patch cable, degree of protection: IP20, cable length: 3 m, number of positions: 8, 10 Gbps, $CAT6_A$, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

NBC-R4OC/5,0-BC6A/R4OC - Patch cable

1227583

https://www.phoenixcontact.com/in/products/1227583



Patch cable, degree of protection: IP20, cable length: 5 m, number of positions: 8, 10 Gbps, $CAT6_A$, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

chanhvinh.com

NBC-R4OC/30,0-BC6A/R4OC - Patch cable

1367336

https://www.phoenixcontact.com/in/products/1367336

NBC-R4OC/7,5-BC6A/R4OC - Patch cable

1227585

https://www.phoenixcontact.com/in/products/1227585



Patch cable, degree of protection: IP20, cable length: 7.5 m, number of positions: 8, 10 Gbps, $CAT6_A$, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

NBC-R4OC/10,0-BC6A/R4OC - Patch cable

1227588

https://www.phoenixcontact.com/in/products/1227588



Patch cable, degree of protection: IP20, cable length: 10 m, number of positions: 8, 10 Gbps, $CAT6_A$, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

chanhvinh.com

NBC-R4OC/30,0-BC6A/R4OC - Patch cable

1367336

https://www.phoenixcontact.com/in/products/1367336

NBC-R4OC/0,3-BC5/R4OC - Patch cable

1227558

https://www.phoenixcontact.com/in/products/1227558



Patch cable, degree of protection: IP20, cable length: 0.3 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

NBC-R4OC/0,5-BC5/R4OC - Patch cable

1227559

https://www.phoenixcontact.com/in/products/1227559



Patch cable, degree of protection: IP20, cable length: 0.5 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

chanhvinh.com

NBC-R4OC/30,0-BC6A/R4OC - Patch cable

1367336

https://www.phoenixcontact.com/in/products/1367336

NBC-R4OC/1,0-BC5/R4OC - Patch cable

1227560

https://www.phoenixcontact.com/in/products/1227560



Patch cable, degree of protection: IP20, cable length: 1 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

NBC-R4OC/1,5-BC5/R4OC - Patch cable

1227561

https://www.phoenixcontact.com/in/products/1227561



Patch cable, degree of protection: IP20, cable length: 1.5 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

chanhvinh.com

NBC-R4OC/30,0-BC6A/R4OC - Patch cable

1367336

https://www.phoenixcontact.com/in/products/1367336

NBC-R4OC/2,0-BC5/R4OC - Patch cable

1227562

https://www.phoenixcontact.com/in/products/1227562



Patch cable, degree of protection: IP20, cable length: 2 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

NBC-R4OC/3,0-BC5/R4OC - Patch cable

1227563

https://www.phoenixcontact.com/in/products/1227563



Patch cable, degree of protection: IP20, cable length: 3 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

chanhvinh.com

NBC-R4OC/30,0-BC6A/R4OC - Patch cable

1367336

https://www.phoenixcontact.com/in/products/1367336

NBC-R4OC/5,0-BC5/R4OC - Patch cable

1227564

https://www.phoenixcontact.com/in/products/1227564



Patch cable, degree of protection: IP20, cable length: 5 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

NBC-R4OC/7,5-BC5/R4OC - Patch cable

1227565

https://www.phoenixcontact.com/in/products/1227565



Patch cable, degree of protection: IP20, cable length: 7.5 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

chanhvinh.com

NBC-R4OC/30,0-BC6A/R4OC - Patch cable

1367336

https://www.phoenixcontact.com/in/products/1367336

NBC-R4OC/10,0-BC5/R4OC - Patch cable

1227566

https://www.phoenixcontact.com/in/products/1227566



Patch cable, degree of protection: IP20, cable length: 10 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

Phoenix Contact 2025 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in