chanhvinh.com

Sensor/actuator cable - SAC-8P-M 8MS/ 3,0-PUR/M 8FS

1404200

https://www.phoenixcontact.com/gb/products/1404200

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Sensor/actuator cable, 8-position, PUR halogen-free, black-gray RAL 7021, Plug straight M8, on Socket straight M8, cable length: 3 m

Your advantages

- Easy and safe: 100% electrically tested plug-in components
- Save space – with high-pos. connectors

Commercial Data

Item number	1404200
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	BF1BGA
Product Key	BF1BGA
Catalog Page	Page 207 (C-2-2019)
GTIN	4046356681209
Weight per Piece (including packing)	108 g
Weight per Piece (excluding packing)	104.5 g
Customs tariff number	85444290
Country of origin	PL

chanhvinh.com

Sensor/actuator cable - SAC-8P-M 8MS/ 3,0-PUR/M 8FS

1404200

https://www.phoenixcontact.com/gb/products/1404200

Technical Data

Product properties

Product type	Sensor/actuator cable
Number of positions	8
Application	Standard
No. of cable outlets	1
Shielded	no
Coding	A - standard

Insulation characteristics

Degree of pollution	3

Material specifications

Flammability rating according to UL 94	HB
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Cable gland material	Zinc die-cast, nickel-plated

Electrical properties

Contact resistance	≤ 5 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U_N	30 V AC
	30 V DC
Nominal current I_N	1.5 A
Protective circuit	unwired

Connection data

Conductor connection

Tightening torque	0.2 NmM8 connectors

Connector

Insertion/withdrawal cycles	≥ 100

Connection 1

Head design	Plug
Head cable outlet	straight
Head thread type	M8

Head 2

Head design	Socket
Head cable outlet	straight
Head thread type	M8

chanhvinh.com

Sensor/actuator cable - SAC-8P-M 8MS/ 3,0-PUR/M 8FS

1404200

https://www.phoenixcontact.com/gb/products/1404200

LED signaling

Status display	No
Status display present	No

Cable / line

Cable length	3 m
UL AWM Style	20549
Number of positions	8
Shielded	no
Cable type	PUR halogen-free black [PUR]
Conductor structure signal line	18x 0.10 mm
AWG signal line	26
Conductor cross section	8x 0.14 mm² (Signal line)
Wire diameter incl. insulation	1 mm ±0.02 mm (Signal line)
External cable diameter	5.1 mm ±0.15 mm
Outer sheath, material	PUR
External sheath, color	black-gray RAL 7021
Conductor material	Bare Cu litz wires
Material wire insulation	PP
Single wire, color	white, brown, green, yellow, gray, pink, blue, red
Thickness, insulation	≥ 0.21 mm (Signal line)
	≥ 0.38 mm (Outer cable sheath)
Overall twist	8 wires around filler to the core
Length of twist, overall twist	58 mm
Max. conductor resistance	139 Ω/km (at 20 °C)
Insulation resistance	1 GΩ*km (at 20 °C)
Nominal voltage, cable	≤ 300 V AC
Test voltage	≥ 3000 V AC (Spark test)
Smallest bending radius, fixed installation	25.5 mm
Smallest bending radius, movable installation	51 mm
Max. bending cycles	4000000
Halogen-free	in accordance with DIN VDE 0472 part 815
	in accordance with DIN EN 50267-2-1
Flame resistance	according to UL 758/1581 (horizontal)
	in accordance with UL 758/1581 FT2
Resistance to oil	According to DIN EN 60811-2-1, 168 h at 100°C
Other resistance	hydrolysis and microbe resistant
	Resistant to salt water
	Low adhesion
	abrasion-resistant
	partly UV-resistant in accordance with DIN EN ISO 4892-2-A
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation)
	-25 °C ... 80 °C (Cable, flexible installation)

chanhvinh.com

Sensor/actuator cable - SAC-8P-M 8MS/ 3,0-PUR/M 8FS

1404200

https://www.phoenixcontact.com/gb/products/1404200

Cable structure

Cable type	PUR halogen-free black
Outer sheath, material	PUR
External sheath, color	black-gray RAL 7021

Ambient conditions

Degree of protection	IP65
	IP67
	IP68
Ambient temperature (operation)	-25 °C ... 85 °C (Plug / socket)

Standards and regulations

M8

Standards/specifications	IEC 61076-2-104

chanhvinh.com


Sensor/actuator cable - SAC-8P-M 8MS/ 3,0-PUR/M 8FS

1404200

https://www.phoenixcontact.com/gb/products/1404200


Drawings

Dimensional drawing



M8 x 1 male plug, straight version

Schematic diagram



Connector pin assignment of M8 socket, 8-pos., view of socket side


chanhvinh.com

Sensor/actuator cable - SAC-8P-M 8MS/ 3,0-PUR/M 8FS

1404200

https://www.phoenixcontact.com/gb/products/1404200

Schematic diagram



M8 plug pin assignment, 8-pos., view of pin side

Circuit diagram



Contact assignment of M8 plugs/sockets


chanhvinh.com

Sensor/actuator cable - SAC-8P-M 8MS/ 3,0-PUR/M 8FS

1404200

https://www.phoenixcontact.com/gb/products/1404200

Dimensional drawing



Socket M8 x 1, straight

chanhvinh.com

Sensor/actuator cable - SAC-8P-M 8MS/ 3,0-PUR/M 8FS

1404200

https://www.phoenixcontact.com/gb/products/1404200

Approvals

EAC
Approval ID: RU C-DE.BL08.B.00286

UL Listed
Approval ID: FILE E 221474

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	30 V	1.5 A	-	-

cUL Listed
Approval ID: FILE E 221474

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	30 V	1.5 A	-	-

EAC
Approval ID: RU D-DE.HB35.B.00387

cULus Listed

chanhvinh.com

Sensor/actuator cable - SAC-8P-M 8MS/ 3,0-PUR/M 8FS

1404200

https://www.phoenixcontact.com/gb/products/1404200

Classifications

ECLASS

ECLASS-9.0	27060311
ECLASS-10.0.1	27060311
ECLASS-11.0	27060311

ETIM

ETIM 8.0	EC001855

UNSPSC

UNSPSC 21.0	26121600

chanhvinh.com

Sensor/actuator cable - SAC-8P-M 8MS/ 3,0-PUR/M 8FS

1404200

https://www.phoenixcontact.com/gb/products/1404200

Environmental Product Compliance

REACh SVHC	Lead 7439-92-1

China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer’s declaration available under “Downloads”

chanhvinh.com

Sensor/actuator cable - SAC-8P-M 8MS/ 3,0-PUR/M 8FS

1404200

https://www.phoenixcontact.com/gb/products/1404200

Accessories

Sealing cap

Sealing cap - PROT-M 8 FS-PA-CHAIN - 1430857

https://www.phoenixcontact.com/gb/products/1430857

M8 sealing cap made of plastic with fixing band for sensor cables, for M8 plugs



Torque screwdriver

Torque screwdriver - TSD 02 SAC - 1208487

https://www.phoenixcontact.com/gb/products/1208487

Torque screwdriver, with preset torque of 0.2 Nm and 4 mm hexagonal drive for M8 connectors



chanhvinh.com

Sensor/actuator cable - SAC-8P-M 8MS/ 3,0-PUR/M 8FS

1404200

https://www.phoenixcontact.com/gb/products/1404200

Tool

Tool - SAC BIT M8-D10 - 1208461

https://www.phoenixcontact.com/gb/products/1208461



Nut for assembling M8 connectors with longitudinal knurl and a knurl diameter of 10 mm, for 4 mm hexagonal drive

Insert label

Insert label - PABA WH/23 - 1013779

https://www.phoenixcontact.com/gb/products/1013779



Insert label, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, mounting type: slide-on, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 20

chanhvinh.com

Sensor/actuator cable - SAC-8P-M 8MS/ 3,0-PUR/M 8FS


1404200

https://www.phoenixcontact.com/gb/products/1404200

Insert label

Insert label - PABA YE/23 - 1013782

https://www.phoenixcontact.com/gb/products/1013782



Insert label, Strip, yellow, unlabeled, can be labeled with: CMS-P1-PLOTTER, mounting type: slide-on, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 20

Marker pen

Marker pen - B-STIFT - 1051993

https://www.phoenixcontact.com/gb/products/1051993



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm

chanhvinh.com

Sensor/actuator cable - SAC-8P-M 8MS/ 3,0-PUR/M 8FS

1404200

https://www.phoenixcontact.com/gb/products/1404200

Screw plug

Screw plug - PROT-M 8 MS-PA-CHAIN - 1430860

https://www.phoenixcontact.com/gb/products/1430860

M8 sealing cap made of plastic with fixing band for sensor cables, for M8 sockets



Phoenix Contact 2022 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk