chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Network cable, Ethernet CAT5 (1 Gbps), 8-position, shielded, Plug straight M12 SPEEDCON / IP67, coding: A, on free cable end, cable length: 2 m

Commercial Data

Item number	1407405
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	BF1CMI
Product Key	BF1CMI
Catalog Page	Page 401 (C-2-2019)
GTIN	4046356775335
Weight per Piece (including packing)	119.1 g
Weight per Piece (excluding packing)	89.98 g
Customs tariff number	85444210
Country of origin	PL

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

Technical Data

Notes

General	Further products with variable cable type and variable cable length can be found in the accessories section

Product properties

Product type	Data cable preassembled
Number of positions	8
Application	Standard
No. of cable outlets	1
Shielded	yes
Coding	A - standard

Interfaces

Bus system	Ethernet
Signal type/category	Ethernet CAT5 (on the basis of IEC 11801), 1 Gbps

LED signaling

Status display	No
Status display present	No

Electrical properties

Nominal voltage U_N	48 V AC
	60 V DC
Nominal current I_N	2 A
Transmission medium	Copper

Material specifications

Color Handle area	black
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Cable gland material	Zinc die-cast, nickel-plated

Connector

Header 1

Type	Plug straight M12 SPEEDCON / IP67
Number of positions	8
Coding type	A (Standard)
Handle color	black
Material	CuZn (Contact)
	Ni/Au (Contact surface)

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

	TPU GF (Contact carriers)
	TPU, hardly inflammable, self-extinguishing (Grip)
	Zinc die-cast, nickel-plated (Screw connection)
Insertion/withdrawal cycles	≥ 100
Contact resistance	≤ 5 mΩ
Insulation resistance	≥ 100 MΩ
Tightening torque	0.4 Nm
Degree of protection	IP67
Ambient temperature (operation)	-25 °C ... 90 °C

Head 2

Type	free cable end

Cable / line

Cable length	2 m
Cable weight	47 kg/km
UL AWM Style	20963 (80°C/30 V)
Number of positions	8
Shielded	yes
Cable type	Ethernet flexible CAT5, 4-pair [94B]
Signal runtime	5.3 ns/m
Conductor structure signal line	7x 0.16 mm
AWG signal line	26
Conductor cross section	4x 2x 0.14 mm²
Wire diameter incl. insulation	0.96 mm
External cable diameter	6.4 mm ±0.2 mm
Outer sheath, material	PUR
External sheath, color	water blue RAL 5021
Conductor material	Bare Cu litz wires
Material wire insulation	Foamed PE
Single wire, color	white/blue-blue, white/orange-orange, white/green-green, white/brown-brown
Thickness, outer sheath	1.05 mm
Twisted pairs	2 cores to the pair
Overall twist	4 pairs for core
Optical shield covering	70 %
Insulation resistance	≥ 5 GΩ*km
Coupling resistance	≤ 100.00 mΩ/m (at 10 MHz)
Loop resistance	≤ 290.00 Ω/km
Wave impedance	100 Ω ±5 Ω (at 100 MHz)
Cable capacity	48 nF/km (at 1 kHz)
Nominal voltage, cable	≤ 100 V
Test voltage Core/Core	700 V (50 Hz, 1 min.)
Test voltage Core/Shield	700 V (50 Hz, 1 min.)
Minimum bending radius, fixed installation	4 x D

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

Minimum bending radius, flexible installation	8 x D
Tensile strength	≤ 100 N
Near end crosstalk attenuation (NEXT)	71.3 dB (with 1 MHz)
	62.3 dB (at 4 MHz)
	56.3 dB (at 10 MHz)
	53.2 dB (at 16 MHz)
	51.8 dB (at 20 MHz)
	48.9 dB (at 31.25 MHz)
	44.4 dB (at 62.5 MHz)
	41.3 dB (at 100 MHz)
Power-summated near end crosstalk attenuation (PSNEXT)	62.3 dB (with 1 MHz)
	53.3 dB (at 4 MHz)
	47.3 dB (at 10 MHz)
	44.2 dB (at 16 MHz)
	42.8 dB (at 20 MHz)
	39.9 dB (at 31.25 MHz)
	35.4 dB (at 62.5 MHz)
	32.3 dB (at 100 MHz)
Return loss (RL)	23 dB (at 4 MHz)
	24.1 dB (at 8 MHz)
	25 dB (at 10 MHz)
	25 dB (at 16 MHz)
	25 dB (at 20 MHz)
	23.6 dB (at 31.25 MHz)
	21.5 dB (at 62.5 MHz)
	20.1 dB (at 100 MHz)
Shield attenuation	3.2 dB (with 1 MHz)
	6 dB (at 4 MHz)
	9.5 dB (at 10 MHz)
	12.1 dB (at 16 MHz)
	13.6 dB (at 20 MHz)
	17.1 dB (at 31.25 MHz)
	24.8 dB (at 62.5 MHz)
	32 dB (at 100 MHz)
Halogen-free	according to IEC 60754-1
Flame resistance	according to IEC 60332-1-2
Resistance to oil	according to EN 60811-2-1
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation)
	-20 °C ... 80 °C (Cable, flexible installation)
Ambient temperature (installation)	-20 °C ... 80 °C

Cable structure

Signal type/category	Ethernet CAT5 (on the basis of IEC 11801), 1 Gbps

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

Ambient conditions

Degree of protection	IP65
	IP67
Degree of protection	IP65/IP67
Ambient temperature (operation)	-25 °C ... 90 °C (M12 connector)

Standards and regulations

M12

Standards/specifications	IEC 61076-2-101

chanhvinh.com


Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

Drawings

Circuit diagram



Contact assignment of the M12 plug


chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405


https://www.phoenixcontact.com/gb/products/1407405

Schematic diagram



Pin assignment M12 plug, 8-pos., A-coded, view plug side

Dimensional drawing



Plug, M12 x 1, straight, shielded

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

Approvals

cUL Recognized
Approval ID: FILE E 335024

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	30 V	1.5 A	-	-

UL Recognized
Approval ID: FILE E 335024

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	30 V	1.5 A	-	-

EAC
Approval ID: RU D-DE.HB35.B.00387

cULus Recognized

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

Classifications

ECLASS

ECLASS-9.0	27060308
ECLASS-10.0.1	27060308
ECLASS-11.0	27060307

ETIM

ETIM 8.0	EC001855

UNSPSC

UNSPSC 21.0	26121600

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

Environmental Product Compliance

REACh SVHC	Lead 7439-92-1

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

Accessories

Network cable

Network cable - NBC-MS SCO-IE/.../... - 1408682

https://www.phoenixcontact.com/gb/products/1408682



Network cable, Ethernet CAT5 (1 Gbps), 8-position, Variable cable type, shielded, Plug straight M12 SPEEDCON / IP67, coding: A, on free cable end, cable length: Free input (0.2 ... 40.0 m)

Torque screwdriver

Torque screwdriver - TSD 04 SAC - 1208429

https://www.phoenixcontact.com/gb/products/1208429



Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

Network cable

Network cable - NBC-MR SCO-IE/.../... - 1408675

https://www.phoenixcontact.com/gb/products/1408675



Network cable, Ethernet CAT5 (1 Gbps), 8-position, Variable cable type, shielded, Plug angled M12 SPEEDCON / IP67, coding: A, on free cable end, cable length: Free input (0.2 ... 40.0 m)

Torque screwdriver

Torque screwdriver - TSD-M 1,2NM - 1212224

https://www.phoenixcontact.com/gb/products/1212224



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 0.3 - 1.2 Nm

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO


1407405

https://www.phoenixcontact.com/gb/products/1407405

Network cable

Network cable - NBC-FS SCO-IE/.../... - 1408665

https://www.phoenixcontact.com/gb/products/1408665



Network cable, Ethernet CAT5 (1 Gbps), 8-position, Variable cable type, shielded, free cable end, on Socket straight M12 SPEEDCON / IP67, coding: A, cable length: Free input (0.2 ... 40.0 m)

Adapter insert

Adapter insert - TSD-M SAC-BIT ADAPTER - 1212600

https://www.phoenixcontact.com/gb/products/1212600



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

Network cable

Network cable - NBC-FR SCO-IE/.../... - 1408657

https://www.phoenixcontact.com/gb/products/1408657



Network cable, Ethernet CAT5 (1 Gbps), 8-position, Variable cable type, shielded, free cable end, on Socket angled M12 SPEEDCON / IP67, coding: A, cable length: Free input (0.2 ... 40.0 m)

Tool

Tool - SAC BIT M12-D15 - 1208432

https://www.phoenixcontact.com/gb/products/1208432



Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, with a knurl diameter of 15 mm, for 4 mm hexagonal drive

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

Sealing cap

Sealing cap - PROT-M12 FS-PA-CHAIN - 1430873

https://www.phoenixcontact.com/gb/products/1430873

M12 sealing cap made of plastic with fixing band, for sensor cables, for free M12 plugs



Locking clip

Locking clip - SAC-M12-EXCLIP-M - 1558988

https://www.phoenixcontact.com/gb/products/1558988

Locking clip for the pin side of sensor/actuator cables with M12 connector and M12 connectors for assembly, for knurl diameter: 15 mm or for Allen key with a wrench size of 14 mm, prevents the disconnection of plug-in connections without tools



chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

Cable-cutting tool

Cable-cutting tool - CUTFOX 12 - 1212128

https://www.phoenixcontact.com/gb/products/1212128



Cable cutter, for copper and aluminum up to 12 mm diameter (up to 35 mm^2)

Diagonal cutter

Diagonal cutter - CUTFOX-S VDE - 1212207

https://www.phoenixcontact.com/gb/products/1212207



Diagonal cutter for hard (piano wire) and soft wires, VDE 1000 V AC/1500 V DC tested

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

Stripping tool

Stripping tool - VS-CABLE-STRIP-VARIO - 1657407

https://www.phoenixcontact.com/gb/products/1657407

Stripping tool, for the multi-level stripping of shielded cables



Diagonal cutter

Diagonal cutter - MICROFOX-SP-1 - 1212487

https://www.phoenixcontact.com/gb/products/1212487



Electronic diagonal cutter, tapered head, without chamfer, with opening spring, non-reflective phosphate-treated surface, punched version

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

Stripping tool

Stripping tool - WIREFOX 4 - 1212156

https://www.phoenixcontact.com/gb/products/1212156



Stripping tool, for cables and conductors (especially for rubber and silicone insulations) from 0.1 - 4 mm^2, self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm^2 stranded/1.5 mm^2 solid, replaceable stripping blade

Stripping tool

Stripping tool - WIREFOX-E 4 - 1212704

https://www.phoenixcontact.com/gb/products/1212704



Stripping tool, for cables and conductors (especially for rubber and silicone insulations) from 0.1 - 4 mm^2, self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm^2 stranded/1.5 mm^2 solid, replaceable stripping blade

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

Stripping tool

Stripping tool - WIREFOX 10 - 1212150

https://www.phoenixcontact.com/gb/products/1212150



Stripping tool, for cables and conductors from 0.02 - 10 mm^2, self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm^2 stranded/1.5 mm^2 solid, replaceable stripping blade

Protective hose adapter

Protective hose adapter - WP-CTA POM 13,0 BK - 1422884

https://www.phoenixcontact.com/gb/products/1422884



Protective hose adapter, for corrugated hoses with a nominal size of 13 (10 x 13), corrugated in parallel

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

Protective hose

Protective hose - WP-PA HF 13,0 BK - 3240681

https://www.phoenixcontact.com/gb/products/3240681



Protective hose, material: PA 6, filament: without, UV-resistant: yes, flexible, degree of protection: IP68, color: black, inflammability class in acc. with UL 94: V0, inner diameter: 10 mm, Total length: 50 m

Protective hose

Protective hose - WP-PA HF-HB 13,0 BK - 3240839

https://www.phoenixcontact.com/gb/products/3240839



Protective hose, material: PA 6, filament: without, UV-resistant: yes, flexible, degree of protection: IP68, color: black, inflammability class in acc. with UL 94: HB, inner diameter: 10 mm, Total length: 50 m

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

Data connector

Data connector - SACC-M12MS-8QO SH ETH - 1421679

https://www.phoenixcontact.com/gb/products/1421679



Data connector, Ethernet CAT5 (1 Gbps), 8-position, halogen-free, shielded, Plug straight M12 SPEEDCON, Coding: A, Insulation displacement connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 5 mm ... 9.7 mm

Data connector

Data connector - SACC-M12MR-8Q SH - 1553653

https://www.phoenixcontact.com/gb/products/1553653



Data connector, Ethernet CAT5 (1 Gbps), 8-position, shielded, Plug angled M12, Coding: A, Insulation displacement connection, knurl material: Nickel-plated brass, external cable diameter 4 mm ... 8 mm

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

Data connector

Data connector - SACC-M12FS-8QO SH ETH - 1421680

https://www.phoenixcontact.com/gb/products/1421680



Data connector, Ethernet CAT5 (1 Gbps), 8-position, halogen-free, shielded, Socket straight M12 SPEEDCON, Coding: A, Insulation displacement connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 5 mm ... 9.7 mm

Data connector

Data connector - SACC-M12FR-8Q SH - 1553666

https://www.phoenixcontact.com/gb/products/1553666



Data connector, Ethernet CAT5 (1 Gbps), 8-position, shielded, Socket angled M12, Coding: A, Insulation displacement connection, knurl material: Nickel-plated brass, external cable diameter 4 mm ... 8 mm

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

RJ45 connector

RJ45 connector - VS-08-RJ45-5-Q/IP20 - 1656725

https://www.phoenixcontact.com/gb/products/1656725



RJ45 connector, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5 (IEC 11801:2002), material: PA, connection method: IDC fast connection, connection cross section: AWG 26- 23, cable outlet: straight, color: traffic grey A RAL 7042, Ethernet

RJ45 connector

RJ45 connector - VS-08-RJ45-5-Q/IP20 BK - 1658008

https://www.phoenixcontact.com/gb/products/1658008



RJ45 connector, type: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5 (IEC 11801:2002), material: PA, connection method: IDC fast connection, connection cross section: AWG 26- 23, cable outlet: straight, color: black, Ethernet

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

RJ45 connector

RJ45 connector - CUC-IND-C1ZNI-S/R4IE8 - 1421607

https://www.phoenixcontact.com/gb/products/1421607



RJ45 connector, type: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5 (IEC 11801:2002), material: Zinc die-cast, connection method: IDC fast connection, connection cross section: AWG 26- 24, cable outlet: straight, color: green, Ethernet

RJ45 connector

RJ45 connector - CUC-IND-C1ZNI-T/R4IE8 - 1421877

https://www.phoenixcontact.com/gb/products/1421877



RJ45 connector, type: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5 (IEC 11801:2002), material: Zinc die-cast, connection method: IDC fast connection, connection cross section: AWG 26- 24, cable outlet: angled, Ethernet

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

RJ45 connector

RJ45 connector - CUC-IND-C1ZNI-B/R4IE8 - 1421876

https://www.phoenixcontact.com/gb/products/1421876




RJ45 connector, type: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5 (IEC 11801:2002), material: Zinc die-cast, connection method: IDC fast connection, connection cross section: AWG 26- 24, cable outlet: angled, Ethernet

RJ45 connector

RJ45 connector - CUC-V06-C1PGY-S/R4CE8:1 - 1414383

https://www.phoenixcontact.com/gb/products/1414383



RJ45 connector, type: RJ45, degree of protection: IP67, number of positions: 8, 1 Gbps, CAT6, material: PA, connection method: Crimp connection, connection cross section: AWG 27- 24, cable outlet: straight, color: gray, Ethernet/PROFINET

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

RJ45 connector

RJ45 connector - CUC-V06-C1PBK-S/R4CE8:1 - 1414408

https://www.phoenixcontact.com/gb/products/1414408



RJ45 connector, type: RJ45, degree of protection: IP67, number of positions: 8, 1 Gbps, CAT6, material: PA, connection method: Crimp connection, connection cross section: AWG 24- 27, cable outlet: straight, color: black, Ethernet/PROFINET

RJ45 connector

RJ45 connector - CUC-V14-C1ZNI-S/R4E8 - 1422661

https://www.phoenixcontact.com/gb/products/1422661



Push-pull connector (version 14), die-cast zinc, with RJ45 connector insert, 8-pos., with IDC fast connection technology, for 1 and 7-wire cores, 26 ... 24 AWG, for cable diameter of 5.5 mm ... 10 mm

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

RJ45 connector

RJ45 connector - CUC-V14-C1ZNI-T/R4E8 - 1422663

https://www.phoenixcontact.com/gb/products/1422663



Push-pull connector (version 14), die-cast zinc, with RJ45 connector insert, 8-pos., with IDC fast connection technology, for 1 and 7-wire cores, 26 ... 24 AWG, for cable diameter of 5.5 mm ... 10 mm

RJ45 connector

RJ45 connector - CUC-V14-C1ZNI-B/R4E8 - 1422662

https://www.phoenixcontact.com/gb/products/1422662



Push-pull connector (version 14), die-cast zinc, with RJ45 connector insert, 8-pos., with IDC fast connection technology, for 1 and 7-wire cores, 26 ... 24 AWG, for cable diameter of 5.5 mm ... 10 mm

chanhvinh.com

Network cable - NBC-MS/ 2,0-94B SCO

1407405

https://www.phoenixcontact.com/gb/products/1407405

RJ45 connector

RJ45 connector - VS-PPC-C1-RJ45-POBK-PG9-8Q5 - 1657834

https://www.phoenixcontact.com/gb/products/1657834



RJ45 connector, IP67, with push/pull interlocking, plastic housing, 1 Gbps, 8-pos. , QUICKON fast connection technology, for 26 ... 24 AWG 1-wire and 7-wire conductors

Phoenix Contact 2022 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk