chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Network cable, PROFINET CAT5 (100 Mbps), EtherCAT® CAT5 (100 Mbps), 4-position, shielded (Advanced Shielding Technology), free cable end, on Socket straight M12 / IP67, coding: D, cable length: 5 m

## Commercial Data

| | |
|---|---|
| Item number | 1407530 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales Key | BF1CJN |
| Product Key | BF1CJN |
| Catalog Page | Page 198 (C-6-2019) |
| GTIN | 4046356778350 |
| Weight per Piece (including packing) | 345 g |
| Weight per Piece (excluding packing) | 344 g |
| Customs tariff number | 85444210 |
| Country of origin | PL |

chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## Technical Data

### Notes

| | |
|---|---|
| General | This product corresponds to the PROFINET Cabling and Interconnection Technology Guideline for PROFINET regulations, version 2.00, order no: 2.252, Chapter 10.1 Cord Sets for Balanced Cabling |
| General | Further products with variable cable type and variable cable length can be found in the accessories section |

### Product properties

| | |
|---|---|
| Product type | Data cable preassembled |
| Number of positions | 4 |
| Application | Standard |
| No. of cable outlets | 1 |
| Shielded | yes |
| Coding | D - data |

#### Insulation characteristics

| | |
|---|---|
| Overvoltage category | II |
| Degree of pollution | 3 |

### Interfaces

| | |
|---|---|
| Bus system | PROFINET |
| Signal type/category | PROFINET CAT5 (IEC 11801), 100 Mbps |
| | EtherCAT® CAT5 (IEC 11801), 100 Mbps |
| | PROFINET CAT5 (IEC 11801), 100 Mbps |
| | EtherCAT® CAT5 (IEC 11801), 100 Mbps |

### LED signaling

| | |
|---|---|
| Status display | No |
| Status display present | No |

### Electrical properties

| | |
|---|---|
| Nominal voltage $U_N$ | 48 V AC |
| | 60 V DC |
| Nominal current $I_N$ | 4 A |
| Transmission medium | Copper |

### Material specifications

| | |
|---|---|
| Color Handle area | black |
| Flammability rating according to UL 94 | V0 |

### Connector

#### Connection 1

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

| | |
|---|---|
| Type | free cable end |

Connection 2

| | |
|---|---|
| Type | Socket straight M12 / IP67 |
| Number of positions | 4 |
| Coding type | D (Data) |
| Handle color | black |
| Material | CuSn (Contact) |
| | Ni/Au (Contact surface) |
| | PA (Contact carriers) |
| | TPU, hardly inflammable, self-extinguishing (Grip) |
| | Zinc die-cast, nickel-plated (Screw connection) |
| | FKM (Seal) |
| Insertion/withdrawal cycles | ≥ 100 |
| Contact resistance | ≤ 5 mΩ |
| Insulation resistance | ≥ 100 MΩ |
| Tightening torque | 0.4 Nm |
| Ambient temperature (operation) | -25 °C ... 90 °C |

## Cable / line

| | |
|---|---|
| Cable length | 5 m |
| Cable weight | 67 kg/km |
| UL AWM Style | 21694 |
| Number of positions | 4 |
| Shielded | yes |
| Cable type | PROFINET PVC stranded CAT5 [93B] |
| Signal runtime | 5.3 ns/m |
| Signal speed | 0.66 c |
| Conductor structure signal line | 7x 0.25 mm |
| AWG signal line | 22 |
| Conductor cross section | 4x 0.34 mm² |
| Wire diameter incl. insulation | 1.55 mm |
| External cable diameter | 6.5 mm ±0.2 mm |
| Outer sheath, material | PVC |
| External sheath, color | green RAL 6018 |
| Conductor material | Tin-plated Cu litz wires |
| Material wire insulation | PE |
| Single wire, color | White, yellow, blue, orange |
| Thickness, outer sheath | approx. 0.9 mm |
| Overall twist | Star quad |
| Optical shield covering | 85 % |
| Insulation resistance | ≥ 500 MΩ*km |
| Coupling resistance | ≤ 20.00 mΩ/m (at 10 MHz) |
| Loop resistance | ≤ 120.00 Ω/km |

chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

| | |
|---|---|
| Wave impedance | 100 Ω ±15 Ω (at 100 MHz) |
| Nominal voltage, cable | 600 V |
| Test voltage Core/Core | 2000 V (50 Hz, 1 min.) |
| Test voltage Core/Shield | 2000 V (50 Hz, 1 min.) |
| Minimum bending radius, fixed installation | 3 x D |
| Minimum bending radius, flexible installation | 7 x D |
| Near end crosstalk attenuation (NEXT) | 80 dB (with 1 MHz) |
| | 76 dB (at 4 MHz) |
| | 70 dB (at 10 MHz) |
| | 65 dB (at 16 MHz) |
| | 63 dB (at 20 MHz) |
| | 60 dB (at 31.25 MHz) |
| | 55 dB (at 62.5 MHz) |
| | 50 dB (at 100 MHz) |
| Shield attenuation | 2.1 dB (with 1 MHz) |
| | 4 dB (at 4 MHz) |
| | 6.3 dB (at 10 MHz) |
| | 8 dB (at 16 MHz) |
| | 9 dB (at 20 MHz) |
| | 11.4 dB (at 31.25 MHz) |
| | 16.5 dB (at 62.5 MHz) |
| | 21.3 dB (at 100 MHz) |
| Flame resistance | according to UL 1685 (CSA FT 4) |
| Resistance to oil | Resistant to oil to a limited extent |
| Other resistance | UV resistant According to UL 1581, Section 1200 |
| Ambient temperature (operation) | -40 °C ... 70 °C (cable, fixed installation) |
| | -40 °C ... 70 °C (Cable, flexible installation) |
| Ambient temperature (installation) | -20 °C ... 60 °C |
| Signal type/category | PROFINET CAT5 (IEC 11801), 100 Mbps |
| | EtherCAT® CAT5 (IEC 11801), 100 Mbps |

## Ambient conditions

| | |
|---|---|
| Degree of protection | IP65 |
| | IP67 |

## Standards and regulations

M12

| | |
|---|---|
| Standards/specifications | IEC 61076-2-101 |

chanhvinh.com


# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530


## Drawings

Circuit diagram




Contact assignment of the M12 socket

Schematic diagram




Pin assignment M12 socket, 4-pos., D-coded, female side


chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

Dimensional drawing




M12 x 1 socket, straight, shielded

chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## Approvals

**cUL Recognized**
Approval ID: FILE E 335024

| | Nominal Voltage $U_N$ | Nominal Current $I_N$ | Cross Section AWG | Cross Section $mm^2$ |
|---|---|---|---|---|
| | 250 V | 4 A | - | - |

**UL Recognized**
Approval ID: FILE E 335024

| | Nominal Voltage $U_N$ | Nominal Current $I_N$ | Cross Section AWG | Cross Section $mm^2$ |
|---|---|---|---|---|
| | 250 V | 4 A | - | - |

**EAC**
Approval ID: RU D-DE.HB35.B.00387

**cULus Recognized**

chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-9.0 | 27060308 |
| ECLASS-10.0.1 | 27060308 |
| ECLASS-11.0 | 27060307 |

### ETIM

| | |
|---|---|
| ETIM 8.0 | EC001855 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 26121600 |

chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## Environmental Product Compliance

| | |
|---|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## Accessories

### Network cable

Network cable - NBC-MSD SCO-PN/.../... - 1408640

https://www.phoenixcontact.com/gb/products/1408640



Network cable, PROFINET CAT5 (100 Mbps), EtherCAT® CAT5 (100 Mbps), 4-position, Variable cable type, shielded, Plug straight M12 SPEEDCON / IP67, coding: D, on free cable end, cable length: Free input (0.2 ... 40.0 m)

### Network cable

Network cable - NBC-MRD SCO-PN/.../... - 1408633

https://www.phoenixcontact.com/gb/products/1408633



Network cable, PROFINET CAT5 (100 Mbps), EtherCAT® CAT5 (100 Mbps), 4-position, Variable cable type, shielded, Plug angled M12 SPEEDCON / IP67, coding: D, on free cable end, cable length: Free input (0.2 ... 40.0 m)

chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## Network cable

Network cable - NBC-FSD SCO-PN/.../... - 1408623

https://www.phoenixcontact.com/gb/products/1408623



Network cable, PROFINET CAT5 (100 Mbps), EtherCAT® CAT5 (100 Mbps), 4-position, Variable cable type, shielded, free cable end, on Socket straight M12 SPEEDCON / IP67, coding: D, cable length: Free input (0.2 ... 40.0 m)

## Network cable

Network cable - NBC-FRD SCO-PN/.../... - 1408615

https://www.phoenixcontact.com/gb/products/1408615



Network cable, PROFINET CAT5 (100 Mbps), EtherCAT® CAT5 (100 Mbps), 4-position, Variable cable type, shielded, free cable end, on Socket angled M12 SPEEDCON / IP67, coding: D, cable length: Free input (0.2 ... 40.0 m)

chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## Torque screwdriver

Torque screwdriver - TSD 04 SAC - 1208429

https://www.phoenixcontact.com/gb/products/1208429



Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors

## Torque screwdriver

Torque screwdriver - TSD-M 1,2NM - 1212224

https://www.phoenixcontact.com/gb/products/1212224



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 0.3 - 1.2 Nm

chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## Adapter insert

Adapter insert - TSD-M SAC-BIT ADAPTER - 1212600

https://www.phoenixcontact.com/gb/products/1212600



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits

## Tool

Tool - SAC BIT M12-D15 - 1208432

https://www.phoenixcontact.com/gb/products/1208432




Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, with a knurl diameter of 15 mm, for 4 mm hexagonal drive

chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## Screw plug

Screw plug - PROT-M12 MS-PA-CHAIN - 1430899

https://www.phoenixcontact.com/gb/products/1430899

M12 sealing cap with fixing band, for sensor cables, for free M12 sockets



## Locking clip

Locking clip - SAC-M12-EXCLIP-F - 1558991

https://www.phoenixcontact.com/gb/products/1558991

Locking clip for the socket side of sensor/actuator cables with M12 connector and M12 connectors for assembly, for knurl diameter: 15 mm or for Allen key with a wrench size of 14 mm, prevents the disconnection of plug-in connections without tools



chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## Cable-cutting tool

Cable-cutting tool - CUTFOX 12 - 1212128

https://www.phoenixcontact.com/gb/products/1212128



Cable cutter, for copper and aluminum up to 12 mm diameter (up to 35 $mm^2$)

## Diagonal cutter

Diagonal cutter - CUTFOX-S VDE - 1212207

https://www.phoenixcontact.com/gb/products/1212207



Diagonal cutter for hard (piano wire) and soft wires, VDE 1000 V AC/1500 V DC tested

chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## Stripping tool

Stripping tool - VS-CABLE-STRIP-VARIO - 1657407

https://www.phoenixcontact.com/gb/products/1657407

Stripping tool, for the multi-level stripping of shielded cables



## Diagonal cutter

Diagonal cutter - MICROFOX-SP-1 - 1212487

https://www.phoenixcontact.com/gb/products/1212487

Electronic diagonal cutter, tapered head, without chamfer, with opening spring, non-reflective phosphate-treated surface, punched version



chanhvinh.com



## Stripping tool

Stripping tool - WIREFOX 4 - 1212156

https://www.phoenixcontact.com/gb/products/1212156



Stripping tool, for cables and conductors (especially for rubber and silicone insulations) from 0.1 - 4 $mm^2$, self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 $mm^2$ stranded/1.5 $mm^2$ solid, replaceable stripping blade

## Stripping tool

Stripping tool - WIREFOX-E 4 - 1212704

https://www.phoenixcontact.com/gb/products/1212704



Stripping tool, for cables and conductors (especially for rubber and silicone insulations) from 0.1 - 4 $mm^2$, self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 $mm^2$ stranded/1.5 $mm^2$ solid, replaceable stripping blade

chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## Stripping tool

Stripping tool - WIREFOX 10 - 1212150

https://www.phoenixcontact.com/gb/products/1212150



Stripping tool, for cables and conductors from 0.02 - 10 $mm^2$, self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 $mm^2$ stranded/1.5 $mm^2$ solid, replaceable stripping blade

## Protective hose adapter

Protective hose adapter - WP-CTA POM 13,0 BK - 1422884

https://www.phoenixcontact.com/gb/products/1422884



Protective hose adapter, for corrugated hoses with a nominal size of 13 (10 x 13), corrugated in parallel

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## Protective hose

Protective hose - WP-PA HF 13,0 BK - 3240681

https://www.phoenixcontact.com/gb/products/3240681



Protective hose, material: PA 6, filament: without, UV-resistant: yes, flexible, degree of protection: IP68, color: black, inflammability class in acc. with UL 94: V0, inner diameter: 10 mm, Total length: 50 m

## Protective hose

Protective hose - WP-PA HF-HB 13,0 BK - 3240839

https://www.phoenixcontact.com/gb/products/3240839



Protective hose, material: PA 6, filament: without, UV-resistant: yes, flexible, degree of protection: IP68, color: black, inflammability class in acc. with UL 94: HB, inner diameter: 10 mm, Total length: 50 m

chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## Data connector

Data connector - SACC-M12MSD-4QO SH PN - 1411068

https://www.phoenixcontact.com/gb/products/1411068



Data connector, PROFINET CAT5 (100 Mbps), 4-position, halogen-free, shielded, Plug straight M12 SPEEDCON, Coding: D, Insulation displacement connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 5 mm ... 9.7 mm

## Data connector

Data connector - SACC-M12MRD-4Q SH PN - 1554539

https://www.phoenixcontact.com/gb/products/1554539



Data connector, PROFINET CAT5 (100 Mbps), 4-position, shielded, Plug angled M12, Coding: D, Insulation displacement connection, knurl material: Nickel-plated brass, external cable diameter 4 mm ... 8 mm

chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## Data connector

Data connector - SACC-M12FSD-4QO SH PN - 1411071

https://www.phoenixcontact.com/gb/products/1411071



Data connector, PROFINET CAT5 (100 Mbps), 4-position, halogen-free, shielded, Socket straight M12 SPEEDCON, Coding: D, Insulation displacement connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 5 mm ... 9.7 mm

## Data connector

Data connector - SACC-M12FRD-4Q SH PN - 1554542

https://www.phoenixcontact.com/gb/products/1554542



Data connector, PROFINET CAT5 (100 Mbps), 4-position, shielded, Socket angled M12, Coding: D, Insulation displacement connection, knurl material: Nickel-plated brass, external cable diameter 4 mm ... 8 mm

chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## Conductor connectors

Conductor connectors - SACC-CC-4QO SH PN - 1414416

https://www.phoenixcontact.com/gb/products/1414416



Cable connector, PROFINET CAT5 (100 Mbps), 4-pos., halogen-free, shielded, insulation displacement connection, housing material: zinc die-cast, nickel-plated, outer cable diameter of 5 mm ... 9.7 mm

## Data connector

Data connector - SACC-M12MSD-4PL SH PN - 1424682

https://www.phoenixcontact.com/gb/products/1424682



Data connector, PROFINET CAT5 (100 Mbps), 4-position, shielded, Plug straight M12, Coding: D, Push-lock spring connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 4 mm ... 8 mm

chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## Data connector

Data connector - SACC-M12MRD-4PL SH PN - 1424684

https://www.phoenixcontact.com/gb/products/1424684



Data connector, PROFINET CAT5 (100 Mbps), 4-position, shielded, Plug angled M12, Coding: D, Push-lock spring connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 4 mm ... 8 mm

## Data connector

Data connector - SACC-M12FSD-4PL SH PN - 1424683

https://www.phoenixcontact.com/gb/products/1424683



Data connector, PROFINET CAT5 (100 Mbps), 4-position, shielded, Socket straight M12, Coding: D, Push-lock spring connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 4 mm ... 8 mm

chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## Data connector

Data connector - SACC-M12FRD-4PL SH PN - 1424685

https://www.phoenixcontact.com/gb/products/1424685



Data connector, PROFINET CAT5 (100 Mbps), 4-position, shielded, Socket angled M12, Coding: D, Push-lock spring connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 4 mm ... 8 mm

## Data connector

Data connector - SACC-M12MSD-4CT-CM SH PN - 1422846

https://www.phoenixcontact.com/gb/products/1422846



Data connector, PROFINET CAT5 (100 Mbps), 4-position, shielded, Plug straight M12, Coding: D, Crimp connection, knurl material: Zinc die-cast, tin-plated, external cable diameter 4.5 mm ... 7.5 mm, without crimp contacts

chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## Data connector

Data connector - SACC-M12MRD-4CT-CM SH PN - 1422847

https://www.phoenixcontact.com/gb/products/1422847



Data connector, PROFINET CAT5 (100 Mbps), 4-position, shielded, Plug angled M12, Coding: D, Crimp connection, knurl material: Zinc die-cast, tin-plated, external cable diameter 4.5 mm ... 7.5 mm, without crimp contacts

## Data connector

Data connector - SACC-M12FSD-4CT-CM SH PN - 1422848

https://www.phoenixcontact.com/gb/products/1422848



Data connector, PROFINET CAT5 (100 Mbps), 4-position, shielded, Socket straight M12, Coding: D, Crimp connection, knurl material: Zinc die-cast, tin-plated, external cable diameter 4.5 mm ... 7.5 mm, without crimp contacts

chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## Data connector

Data connector - SACC-M12FRD-4CT-CM SH PN - 1422849

https://www.phoenixcontact.com/gb/products/1422849



Data connector, PROFINET CAT5 (100 Mbps), 4-position, shielded, Socket angled M12, Coding: D, Crimp connection, knurl material: Zinc die-cast, tin-plated, external cable diameter 4.5 mm ... 7.5 mm, without crimp contacts

## RJ45 connector

RJ45 connector - VS-PN-RJ45-5-Q/IP20 - 1658435

https://www.phoenixcontact.com/gb/products/1658435



RJ45 connector, type: RJ45, degree of protection: IP20, number of positions: 4, 100 Mbps, CAT5 (IEC 11801:2002), material: PA, connection method: IDC fast connection, cable outlet: straight, color: traffic grey A RAL 7042, PROFINET

chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## RJ45 connector

RJ45 connector - CUC-IND-C1ZNI-S/R4IP8 - 1421126

https://www.phoenixcontact.com/gb/products/1421126



RJ45 connector, type: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5 (IEC 11801:2002), material: Zinc die-cast, connection method: IDC fast connection, connection cross section: AWG 23- 22, cable outlet: straight, color: green, PROFINET

## RJ45 connector

RJ45 connector - CUC-IND-C1ZNI-T/R4IP8 - 1421128

https://www.phoenixcontact.com/gb/products/1421128



RJ45 connector, type: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5 (IEC 11801:2002), material: Zinc die-cast, connection method: IDC fast connection, connection cross section: AWG 23- 22, cable outlet: angled, Ethernet/PROFINET

chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## RJ45 connector

RJ45 connector - CUC-IND-C1ZNI-B/R4IP8 - 1421127

https://www.phoenixcontact.com/gb/products/1421127



RJ45 connector, type: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5 (IEC 11801:2002), material: Zinc die-cast, connection method: IDC fast connection, connection cross section: AWG 23- 22, cable outlet: angled, Ethernet/PROFINET

## RJ45 connector

RJ45 connector - CUC-V14-C1ZNI-S/R4P8 - 1422664

https://www.phoenixcontact.com/gb/products/1422664



Push-pull connector (version 14), die-cast zinc, with RJ45 connector insert, 8-pos., with IDC fast connection technology, for 1 and 7-wire cores, 23 ... 22 AWG, for cable diameter of 5.5 mm ... 10 mm

chanhvinh.com

# Network cable - NBC- 5,0-93B/M12FSD

1407530

https://www.phoenixcontact.com/gb/products/1407530

## RJ45 connector

RJ45 connector - CUC-V14-C1ZNI-T/R4P8 - 1422667

https://www.phoenixcontact.com/gb/products/1422667



Push-pull connector (version 14), die-cast zinc, with RJ45 connector insert, 8-pos., with IDC fast connection technology, for 1 and 7-wire cores, 23 ... 22 AWG, for cable diameter of 5.5 mm ... 10 mm

## RJ45 connector

RJ45 connector - CUC-V14-C1ZNI-B/R4P8 - 1422665

https://www.phoenixcontact.com/gb/products/1422665



Push-pull connector (version 14), die-cast zinc, with RJ45 connector insert, 8-pos., with IDC fast connection technology, for 1 and 7-wire cores, 23 ... 22 AWG, for cable diameter of 5.5 mm ... 10 mm

Phoenix Contact 2022 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk