chanhvinh.com

Network cable - VS-IP67/B-IP20-94B-LI/5,0

1407961

https://www.phoenixcontact.com/gb/products/1407961

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Assembled Ethernet cable, shielded, 4-pair, AWG 26 stranded (7-wire), RAL 5021 (sea blue), RJ45 connector/IP67, black to RJ45 connector/IP20, black, line, length 5 m

Commercial Data

Item number	1407961
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	ABNDAJ
Product Key	ABNDAJ
Catalog Page	Page 301 (PC-2011)
GTIN	4046356475433
Weight per Piece (including packing)	261.42 g
Weight per Piece (excluding packing)	261.42 g
Customs tariff number	85444210
Country of origin	PL

Network cable - VS-IP67/B-IP20-94B-LI/5,0

1407961

https://www.phoenixcontact.com/gb/products/1407961

Technical Data

Product properties

Product type	Data cable preassembled
Number of positions	8
No. of cable outlets	1
Number of slots	1
Shielded	yes
Cable outlet	straight

Insulation characteristics

Degree of pollution	2

Electrical properties

Transmission medium	Copper

Material specifications

Flammability rating according to UL 94	V2

Connector

Insertion/withdrawal cycles	≥ 750

Connection 1

Handle color	black
Degree of protection	IP67

Connection 2

Handle color	gray

Cable / line

Cable length	5.00 m
Cable type	Ethernet
Cable structure	4x2xAWG26/7; S/FTP
External cable diameter	6.40 mm
Outer sheath, material	PUR
External sheath, color	water blue RAL 5021
Conductor material	Bare Cu litz wires
Conductor structure signal line	7x 0.16 mm
AWG signal line	26
Wire diameter incl. insulation	1 mm
Single wire, color	White-blue, white-orange, white-green, white-brown
Wave impedance	100 Ω ±15 % (at 1 ... 100 MHz)
Smallest bending radius, fixed installation	min. 32 mm (cable, fixed installation)
Smallest bending radius, movable installation	min. 32 mm (Cable, flexible installation)
Smallest bending radius, fixed installation	min. 32 mm (cable, fixed installation)

chanhvinh.com

Network cable - VS-IP67/B-IP20-94B-LI/5,0

1407961

https://www.phoenixcontact.com/gb/products/1407961

Smallest bending radius, movable installation	min. 32 mm (Cable, flexible installation)

Ambient conditions

Degree of protection	IP20
	IP67
Degree of protection	IP67/IP20

chanhvinh.com


Network cable - VS-IP67/B-IP20-94B-LI/5,0

1407961


https://www.phoenixcontact.com/gb/products/1407961

Drawings

Circuit diagram



Dimensional drawing




chanhvinh.com

Network cable - VS-IP67/B-IP20-94B-LI/5,0

1407961

https://www.phoenixcontact.com/gb/products/1407961

Dimensional drawing



chanhvinh.com

Network cable - VS-IP67/B-IP20-94B-LI/5,0

1407961

https://www.phoenixcontact.com/gb/products/1407961

Approvals

EAC
Approval ID: 19060508

chanhvinh.com

Network cable - VS-IP67/B-IP20-94B-LI/5,0

1407961

https://www.phoenixcontact.com/gb/products/1407961

Classifications

ECLASS

ECLASS-9.0	27060308
ECLASS-10.0.1	27060308
ECLASS-11.0	27060308

ETIM

ETIM 8.0	EC002599

UNSPSC

UNSPSC 21.0	26121600

chanhvinh.com

Network cable - VS-IP67/B-IP20-94B-LI/5,0

1407961

https://www.phoenixcontact.com/gb/products/1407961

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2022 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk