chanhvinh.com

Network cable - VS-PPC/ME-IP20-94C-LI/2,0

1412943

https://www.phoenixcontact.com/gb/products/1412943

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Assembled Ethernet cable, shielded, 4-pair, AWG 26 flexible cable conduit capable (19-wire), RAL 5021 (sea blue), RJ45 connector/IP67 push/pull metal housing to RJ45 connector/IP20, line, length 2 m

Commercial Data

Item number	1412943
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	ABNEAJ
Product Key	ABNEAJ
Catalog Page	Page 303 (PC-2011)
GTIN	4046356475723
Weight per Piece (including packing)	199 g
Weight per Piece (excluding packing)	199 g
Customs tariff number	85444210
Country of origin	PL

chanhvinh.com

Network cable - VS-PPC/ME-IP20-94C-LI/2,0

1412943

https://www.phoenixcontact.com/gb/products/1412943

Technical Data

Product properties

Product type	Data cable preassembled
Number of positions	8
No. of cable outlets	1
Number of slots	1
Shielded	yes
Cable outlet	straight

Insulation characteristics

Degree of pollution	2

Electrical properties

Transmission medium	Copper

Material specifications

Flammability rating according to UL 94	V2

Connector

Insertion/withdrawal cycles	≥ 200

Connection 1

Material	Metal
Degree of protection	IP67

Connection 2

Material	Plastic

Cable / line

Cable length	2.00 m
Cable weight	70.00 kg/km
Cable type	Ethernet
Cable structure	4x2xAWG26/19; S/UTP
External cable diameter	7.70 mm
Outer sheath, material	PUR
Conductor material	Bare Cu litz wires
Conductor structure signal line	19x 0.10 mm
AWG signal line	26
Single wire, color	White-blue, white-orange, white-green, white-brown
Wave impedance	100 Ω ±5 Ω (at 100 MHz)
Smallest bending radius, fixed installation	39 mm (cable, fixed installation)
Smallest bending radius, movable installation	39 mm (Cable, flexible installation)
Smallest bending radius, fixed installation	39 mm (cable, fixed installation)
Smallest bending radius, movable installation	39 mm (Cable, flexible installation)

chanhvinh.com

Network cable - VS-PPC/ME-IP20-94C-LI/2,0

1412943

https://www.phoenixcontact.com/gb/products/1412943

Ambient conditions

Degree of protection	IP20
	IP67
Degree of protection	IP67/IP20

chanhvinh.com


Network cable - VS-PPC/ME-IP20-94C-LI/2,0

1412943


https://www.phoenixcontact.com/gb/products/1412943

Drawings

Circuit diagram



Dimensional drawing



Push-pull RJ45 connector IP65/67

chanhvinh.com

Network cable - VS-PPC/ME-IP20-94C-LI/2,0

1412943

https://www.phoenixcontact.com/gb/products/1412943

Approvals

EAC
Approval ID: 19060508

chanhvinh.com

Network cable - VS-PPC/ME-IP20-94C-LI/2,0

1412943

https://www.phoenixcontact.com/gb/products/1412943

Classifications

ECLASS

ECLASS-9.0	27060308
ECLASS-10.0.1	27060308
ECLASS-11.0	27060308

ETIM

ETIM 8.0	EC002599

UNSPSC

UNSPSC 21.0	26121600

chanhvinh.com

Network cable - VS-PPC/ME-IP20-94C-LI/2,0

1412943

https://www.phoenixcontact.com/gb/products/1412943

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer’s declaration available under “Downloads”

Phoenix Contact 2022 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk