chanhvinh.com

# SAC-5P-M12MRL/ 5,0-500 FE SH - Power cable

1414861

https://www.phoenixcontact.com/gb/products/1414861

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Power cable, 5-position, PVC, gray RAL 7001, shielded (Advanced Shielding Technology), Plug angled M12, coding: L, on free cable end, cable length: 5 m, for direct current up to 16 A/63 V

## Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Protection against mismatching, thanks to special L-coding
- Shield power reliably – 360° shielding to reduce electromagnetic loads

## Commercial data

| | |
|---|---|
| Item number | 1414861 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | BF1CDP |
| Product key | BF1CDP |
| GTIN | 4055626034935 |
| Weight per piece (including packing) | 1,248 g |
| Weight per piece (excluding packing) | 1,248 g |
| Customs tariff number | 85444290 |
| Country of origin | PL |

chanhvinh.com

# SAC-5P-M12MRL/ 5,0-500 FE SH - Power cable

1414861

https://www.phoenixcontact.com/gb/products/1414861

## Technical data

### Product properties

| | |
|---|---|
| Product type | Power cable |
| Application | Power supply |
| Number of positions | 5 |
| No. of cable outlets | 1 |
| Shielded | yes |
| Coding | L |

Insulation characteristics

| | |
|---|---|
| Overvoltage category | III |
| Degree of pollution | 3 |

### Material specifications

| | |
|---|---|
| Flammability rating according to UL 94 | V0 |
| Material of grip body | PP |
| Contact material | CuZn |
| Contact surface material | Ni/Au |
| Contact carrier material | PA |
| Material for screw connection | Zinc die-cast, nickel-plated |

### Electrical properties

| | |
|---|---|
| Insulation resistance | ≥ 100 MΩ |
| Nominal voltage $U_N$ | 63 V DC |
| Nominal current $I_N$ | 16 A |

### Mechanical properties

Mechanical data

| | |
|---|---|
| Insertion/withdrawal cycles | ≥ 100 |

### Connector

Connection 1

| | |
|---|---|
| Type | Plug angled M12 |
| Coding type | L (Power) |

Connection 2

| | |
|---|---|
| Type | free cable end |

### Cable/line

| | |
|---|---|
| Cable length | 5 m |


PVC gray [500]

chanhvinh.com

# SAC-5P-M12MRL/ 5,0-500 FE SH - Power cable

1414861

https://www.phoenixcontact.com/gb/products/1414861

| | |
|---|---|
| Dimensional drawing |  |
| Cable weight | 231 kg/km |
| UL AWM Style | 20233 / 10493 (80°C/300 V) |
| Number of positions | 5 |
| Shielded | yes |
| Cable type | PVC gray [500] |
| Conductor cross section | 5x 2.5 mm² |
| Wire diameter incl. insulation | 3 mm ±0.1 mm |
| External cable diameter | 10.80 mm ±0.3 mm |
| Outer sheath, material | PVC |
| External sheath, color | gray RAL 7001 |
| Conductor material | Bare Cu litz wires |
| Material wire insulation | PVC |
| Single wire, color | brown, white, blue, black, gray |
| Thickness, insulation | ≥ 0.36 mm |
| Thickness, outer sheath | approx. 0.76 mm |
| Max. conductor resistance | ≤ 8 Ω/km (at 20 °C) |
| Insulation resistance | ≥ 100 MΩ*km (at 20 °C) |
| Nominal voltage, cable | ≤ 300 V AC |
| Test voltage | ≥ 3000 V AC (Spark test) |
| Minimum bending radius, fixed installation | 5 x D |
| Minimum bending radius, flexible installation | 10 x D |
| Smallest bending radius, fixed installation | 54 mm |
| Smallest bending radius, movable installation | 108 mm |
| Dynamic load capacity (bending) | Max. bending cycles: 1000000, Bending radius: 10 x D, Traversing path: 10 m, Traversing rate: 3 m/s, Acceleration: 10 m/s² |
| Flame resistance | According to UL 758/1581 (Cable Flame) |
| | according to UL 758/1581 FT1 |
| | According to DIN EN 60332-1-2 |
| Resistance to oil | according to DIN EN 60811-404, 168 h at 60 °C |
| Ambient temperature (operation) | -40 °C ... 80 °C (cable, fixed installation) |
| | -20 °C ... 80 °C (Cable, flexible installation) |

## Environmental and real-life conditions

| Ambient conditions | |
|---|---|
| | IP65 |

chanhvinh.com

# SAC-5P-M12MRL/ 5,0-500 FE SH - Power cable

1414861

https://www.phoenixcontact.com/gb/products/1414861

| | |
|---|---|
| Degree of protection | IP67 |
| | IP68 |
| Ambient temperature (operation) | -25 °C ... 85 °C (Plug / socket) |

## Standards and regulations

| | |
|---|---|
| Standard designation | M12 connector |
| Standards/specifications | IEC 61076-2-111 |

chanhvinh.com


# SAC-5P-M12MRL/ 5,0-500 FE SH - Power cable

1414861

https://www.phoenixcontact.com/gb/products/1414861


## Drawings

Schematic diagram




Pin assignment of M12 connector, 5-pos., L-coded, pin side view

Circuit diagram




chanhvinh.com

# SAC-5P-M12MRL/ 5,0-500 FE SH - Power cable

1414861


https://www.phoenixcontact.com/gb/products/1414861

Diagram




Base curve

Dimensional drawing




M12 x 1 male plug, angled

chanhvinh.com

# SAC-5P-M12MRL/ 5,0-500 FE SH - Power cable

1414861

https://www.phoenixcontact.com/gb/products/1414861

## Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/gb/products/1414861

**UL Listed**
Approval ID: E468743

**cUL Listed**
Approval ID: E468743

**EAC-RoHS**
Approval ID: RU D-DE.HB35.B.00387

**cULus Listed**

chanhvinh.com

# SAC-5P-M12MRL/ 5,0-500 FE SH - Power cable

1414861

https://www.phoenixcontact.com/gb/products/1414861

## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-11.0 | 27060311 |
| ECLASS-12.0 | 27060311 |
| ECLASS-13.0 | 27060327 |

### ETIM

| | |
|---|---|
| ETIM 9.0 | EC001855 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 26121600 |

chanhvinh.com

# SAC-5P-M12MRL/ 5,0-500 FE SH - Power cable

1414861

https://www.phoenixcontact.com/gb/products/1414861

## Environmental product compliance

EU RoHS

| | |
|---|---|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |

China RoHS

| | |
|---|---|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|---|---|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |

Phoenix Contact 2024 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk