chanhvinh.com

SAC-6P- 5,0-PUR/M12FSM PE - Power cable

1414918

https://www.phoenixcontact.com/gb/products/1414918

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Power cable, 6-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket straight M12, coding: M, cable length: 5 m, for AC current up to 8 A/690 V

Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Protection against mismatching, thanks to special M-coding
- Our standard: robust halogen-free PUR cable

Commercial data

Item number	1414918
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF1CGP
Product key	BF1CGP
Catalog page	Page 298 (C-2-2019)
GTIN	4055626035468
Weight per piece (including packing)	741.68 g
Weight per piece (excluding packing)	741.68 g
Customs tariff number	85444290
Country of origin	PL

chanhvinh.com

SAC-6P- 5,0-PUR/M12FSM PE - Power cable

1414918

https://www.phoenixcontact.com/gb/products/1414918

Technical data

Product properties

Product type	Power cable
Application	Power supply
Number of positions	6
No. of cable outlets	1
Shielded	no
Coding	M

Data management status

Article revision	05

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	V0
Material of grip body	PP
Contact material	CuZn
Contact surface material	Ni/Au
Contact carrier material	PA
Material for screw connection	Zinc die-cast, nickel-plated

Electrical properties

Insulation resistance	≥ 100 MΩ
Nominal voltage U_N	690 V AC
Nominal current I_N	8 A

Connector

Connection 1

Type	free cable end

Connection 2

Type	Socket straight M12
Coding type	M (Power)

Cable/line

Cable length	5 m


PUR halogen-free black [PUR]

chanhvinh.com

SAC-6P- 5,0-PUR/M12FSM PE - Power cable

1414918

https://www.phoenixcontact.com/gb/products/1414918

Dimensional drawing	
Cable weight	130 kg/km
Number of positions	6
Shielded	no
Cable type	PUR halogen-free black [PUR]
Conductor cross section	6x 1.5 mm²
Wire diameter incl. insulation	2.35 mm ±0.1 mm
External cable diameter	8.80 mm ±0.25 mm
Outer sheath, material	PUR
External sheath, color	black-gray RAL 7021
Conductor material	Bare Cu litz wires
Material wire insulation	PP
Single wire, color	black 1, black 2, black 3, black 4, black 5, green/yellow
Thickness, insulation	≥ 0.36 mm
Thickness, outer sheath	approx. 0.90 mm
Max. conductor resistance	≤ 14.1 Ω/km (at 20 °C)
Insulation resistance	≥ 1 GΩ*km (at 20 °C)
Nominal voltage, cable	≤ 1000 V AC
Test voltage	≥ 3000 V AC (Spark test)
Minimum bending radius, fixed installation	5 x D
Minimum bending radius, flexible installation	10 x D
Smallest bending radius, fixed installation	44 mm
Smallest bending radius, movable installation	88 mm
Dynamic load capacity (bending)	Max. bending cycles: 4000000, Bending radius: 10xD, Traversing path: 10 m, Traversing rate: 3 m/s, Acceleration: 10 m/s²
Halogen-free	in accordance with DIN VDE 0472 part 815
	according to DIN EN 60754-1
Flame resistance	in accordance with UL 758/1581 FT2
	according to DIN EN 60332-2-2
Resistance to oil	according to DIN EN 60811-404, 168 h at 100 °C
Other resistance	Hydrolysis and microbe resistant as per VDE 0282 section 10
	Low adhesion
	abrasion-resistant
	Resistant to salt water
Ambient temperature (operation)	-50 °C ... 85 °C (cable, fixed installation)
	-30 °C ... 85 °C (Cable, flexible installation)

chanhvinh.com

SAC-6P- 5,0-PUR/M12FSM PE - Power cable

1414918

https://www.phoenixcontact.com/gb/products/1414918

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
	IP67 (without preloading, as additional test in accordance with IEC 60529)
Ambient temperature (operation)	-25 °C ... 85 °C (Plug / socket)

Standards and regulations

Standard designation	M12 connector
Standards/specifications	IEC 61076-2-111

chanhvinh.com


SAC-6P- 5,0-PUR/M12FSM PE - Power cable

1414918


https://www.phoenixcontact.com/gb/products/1414918

Drawings

Circuit diagram



Diagram



Current carrying capacity


chanhvinh.com

SAC-6P- 5,0-PUR/M12FSM PE - Power cable

1414918


https://www.phoenixcontact.com/gb/products/1414918

Schematic diagram



Pin assignment of M12 socket, 6-pos., M-coded, socket side view

Dimensional drawing



M12 x 1 socket, straight

chanhvinh.com

SAC-6P- 5,0-PUR/M12FSM PE - Power cable

1414918

https://www.phoenixcontact.com/gb/products/1414918

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/gb/products/1414918

UL Listed
Approval ID: E468743

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	600 V	10 A	-	- 16

cUL Listed
Approval ID: E468743

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	600 V	10 A	- 16	-

EAC-RoHS
Approval ID: RU D-DE.HB35.B.00387

cULus Listed

chanhvinh.com

SAC-6P- 5,0-PUR/M12FSM PE - Power cable

1414918

https://www.phoenixcontact.com/gb/products/1414918

Classifications

ECLASS

ECLASS-11.0	27060311
ECLASS-12.0	27060311
ECLASS-13.0	27060327

ETIM

ETIM 9.0	EC001855

UNSPSC

UNSPSC 21.0	26121600

chanhvinh.com

SAC-6P- 5,0-PUR/M12FSM PE - Power cable

1414918

https://www.phoenixcontact.com/gb/products/1414918

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk