chanhvinh.com

# SAC-6P- 5,0-PVC/M12FRM PE - Power cable

1414920

https://www.phoenixcontact.com/gb/products/1414920

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Power cable, 6-position, PVC, black-gray RAL 7021, free cable end, on Socket angled M12, coding: M, cable length: 5 m, for AC current up to 8 A/690 V

## Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Protection against mismatching, thanks to special M-coding

## Commercial data

| | |
|---|---|
| Item number | 1414920 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | BF1CGP |
| Product key | BF1CGP |
| Catalog page | Page 299 (C-2-2019) |
| GTIN | 4055626035482 |
| Weight per piece (including packing) | 878.36 g |
| Weight per piece (excluding packing) | 878.36 g |
| Customs tariff number | 85444290 |
| Country of origin | PL |

chanhvinh.com

# SAC-6P- 5,0-PVC/M12FRM PE - Power cable

1414920

https://www.phoenixcontact.com/gb/products/1414920

## Technical data

### Product properties

| | |
|---|---|
| Product type | Power cable |
| Application | Power supply |
| Number of positions | 6 |
| No. of cable outlets | 1 |
| Shielded | no |
| Coding | M |

Data management status

| | |
|---|---|
| Article revision | 00 |

Insulation characteristics

| | |
|---|---|
| Overvoltage category | III |
| Degree of pollution | 3 |

### Material specifications

| | |
|---|---|
| Flammability rating according to UL 94 | V0 |
| Material of grip body | PP |
| Contact material | CuZn |
| Contact surface material | Ni/Au |
| Contact carrier material | PA |
| Material for screw connection | Zinc die-cast, nickel-plated |

### Electrical properties

| | |
|---|---|
| Insulation resistance | ≥ 100 MΩ |
| Nominal voltage $U_N$ | 690 V AC |
| Nominal current $I_N$ | 8 A |

### Connector

Connection 1

| | |
|---|---|
| Type | free cable end |

Connection 2

| | |
|---|---|
| Type | Socket angled M12 |
| Coding type | M (Power) |

### Cable/line


| | |
|---|---|
| Cable length | 5 m |

PVC black [PVC]

# SAC-6P- 5,0-PVC/M12FRM PE - Power cable

1414920

https://www.phoenixcontact.com/gb/products/1414920

| | |
|---|---|
| Dimensional drawing |  |
| Cable weight | 220 kg/km |
| UL AWM Style | 2570 / 10914 (80°C/1000 V) |
| Number of positions | 6 |
| Shielded | no |
| Cable type | PVC black [PVC] |
| Conductor cross section | 6x 1.5 mm² |
| Wire diameter incl. insulation | 2.4 mm ±0.05 mm |
| External cable diameter | 9.75 mm ±0.25 mm |
| Outer sheath, material | PVC |
| External sheath, color | black-gray RAL 7021 |
| Conductor material | Bare Cu litz wires |
| Material wire insulation | PVC |
| Single wire, color | black 1, black 2, black 3, black 4, black 5, green/yellow |
| Thickness, insulation | ≥ 0.36 mm |
| Thickness, outer sheath | approx. 0.76 mm |
| Max. conductor resistance | ≤ 15 Ω/m (at 20 °C) |
| Insulation resistance | ≥ 100 MΩ*km (at 20 °C) |
| Nominal voltage, cable | ≤ 1000 V AC |
| Test voltage | ≥ 10000 V AC (Spark test) |
| Minimum bending radius, fixed installation | 5 x D |
| Minimum bending radius, flexible installation | 10 x D |
| Smallest bending radius, fixed installation | 49 mm |
| Smallest bending radius, movable installation | 98 mm |
| Dynamic load capacity (bending) | Max. bending cycles: 2000000, Bending radius: 10 x D, Traversing path: 10 m, Traversing rate: 3 m/s, Acceleration: 10 m/s² |
| Flame resistance | According to UL 758/1581 (Cable Flame) |
| | according to UL 758/1581 FT1 |
| | According to DIN EN 60332-1-2 |
| Resistance to oil | according to DIN EN 60811-404, 168 h at 60 °C |
| Ambient temperature (operation) | -40 °C ... 80 °C (cable, fixed installation) |
| | -20 °C ... 80 °C (Cable, flexible installation) |

## Environmental and real-life conditions

### Ambient conditions

| | |
|---|---|
| Degree of protection | IP65 |

chanhvinh.com

# SAC-6P- 5,0-PVC/M12FRM PE - Power cable

1414920

https://www.phoenixcontact.com/gb/products/1414920

| | |
|---|---|
| | IP67 (without preloading, as additional test in accordance with IEC 60529) |
| Ambient temperature (operation) | -25 °C ... 85 °C (Plug / socket) |

## Standards and regulations

| | |
|---|---|
| Standard designation | M12 connector |
| Standards/specifications | IEC 61076-2-111 |

chanhvinh.com

# SAC-6P- 5,0-PVC/M12FRM PE - Power cable

1414920


https://www.phoenixcontact.com/gb/products/1414920

## Drawings

Circuit diagram




Dimensional drawing




M12 x 1 socket, angled


chanhvinh.com

# SAC-6P- 5,0-PVC/M12FRM PE - Power cable

1414920


https://www.phoenixcontact.com/gb/products/1414920

Schematic diagram




Pin assignment of M12 socket, 6-pos., M-coded, socket side view

Diagram




Derating diagram

chanhvinh.com

# SAC-6P- 5,0-PVC/M12FRM PE - Power cable

1414920

https://www.phoenixcontact.com/gb/products/1414920

## Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/gb/products/1414920

**UL Listed**
Approval ID: E468743

| | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $mm^2$ |
|---|---|---|---|---|
| | 600 V | 10 A | - | - 16 |

**cUL Listed**
Approval ID: E468743

| | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $mm^2$ |
|---|---|---|---|---|
| | 600 V | 10 A | - 16 | - |

**EAC-RoHS**
Approval ID: RU D-DE.HB35.B.00387

**cULus Listed**

chanhvinh.com

# SAC-6P- 5,0-PVC/M12FRM PE - Power cable

1414920

https://www.phoenixcontact.com/gb/products/1414920

## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-11.0 | 27060311 |
| ECLASS-12.0 | 27060311 |
| ECLASS-13.0 | 27060327 |

### ETIM

| | |
|---|---|
| ETIM 9.0 | EC001855 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 26121600 |

chanhvinh.com

# SAC-6P- 5,0-PVC/M12FRM PE - Power cable

1414920

https://www.phoenixcontact.com/gb/products/1414920

## Environmental product compliance

EU RoHS

| | |
|---|---|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |

China RoHS

| | |
|---|---|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|---|---|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |

Phoenix Contact 2024 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk