chanhvinh.com

SAC-8P-M12MS/ 1,5-PVC/M12FR - Sensor/actuator cable

1415747

https://www.phoenixcontact.com/gb/products/1415747

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 8-position, PVC, black RAL 9005, Plug straight M12, coding: A, on Socket angled M12, coding: A, cable length: 1.5 m

Your advantages

- Easy and safe: 100 % electrically tested plug-in components

Commercial data

Item number	1415747
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF1CFA
Product key	BF1CFA
Catalog page	Page 209 (C-2-2019)
GTIN	4055626052601
Weight per piece (including packing)	95.2 g
Weight per piece (excluding packing)	95.2 g
Customs tariff number	85444290
Country of origin	PL

chanhvinh.com

SAC-8P-M12MS/ 1,5-PVC/M12FR - Sensor/actuator cable

1415747

https://www.phoenixcontact.com/gb/products/1415747

Technical data

Product properties

Product type	Sensor/actuator cable
Application	Standard
Number of positions	8
No. of cable outlets	1
Shielded	no
Coding	A

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	HB
Seal material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuZn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material for screw connection	Zinc die-cast, nickel-plated

Electrical properties

Insulation resistance	≥ 100 MΩ
Nominal voltage U_N	30 V AC
	30 V DC
Nominal current I_N	2 A

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100

Signaling

Status display	no
Status display present	No

Connector

Connection 1

Type	Plug straight M12
Number of positions	8
Coding type	A

Connection 2

chanhvinh.com

SAC-8P-M12MS/ 1,5-PVC/M12FR - Sensor/actuator cable

1415747

https://www.phoenixcontact.com/gb/products/1415747

Type	Socket angled M12
Number of positions	8
Coding type	A

Cable/line

Cable length	1.5 m

PVC black [PVC]

Dimensional drawing	
Cable weight	54 kg/km
UL AWM Style	2464 / 1729 (80°C/300 V)
Number of positions	8
Shielded	no
Cable type	PVC black [PVC]
Conductor structure signal line	14x 0.15 mm
AWG signal line	24
Conductor cross section	8x 0.25 mm² (Signal line)
Wire diameter incl. insulation	1.17 mm ±0.05 mm
External cable diameter	5.90 mm ±0.2 mm
Outer sheath, material	PVC
External sheath, color	black RAL 9005
Conductor material	Bare Cu litz wires
Material wire insulation	PVC
Single wire, color	white, brown, green, yellow, gray, pink, blue, red
Thickness, insulation	≥ 0.23 mm
Thickness, outer sheath	≥ 0.76 mm
Overall twist	8 wires around filler to the core
Max. conductor resistance	79 Ω/km (at 20 °C)
Insulation resistance	≥ 200 MΩ*km (at 20 °C)
Nominal voltage, cable	≤ 300 V AC
Test voltage	≥ 3000 V AC
Minimum bending radius, fixed installation	5 x D
Minimum bending radius, flexible installation	10 x D
Smallest bending radius, fixed installation	30 mm
Smallest bending radius, movable installation	59 mm
Flame resistance	as per VW-1 in accordance with UL 758
Resistance to oil	in accordance with DIN EN 60811-2-1

chanhvinh.com

SAC-8P-M12MS/ 1,5-PVC/M12FR - Sensor/actuator cable

1415747

https://www.phoenixcontact.com/gb/products/1415747

Ambient temperature (operation)	-25 °C ... 80 °C (cable, fixed installation)
	-10 °C ... 80 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
	IP67
	IP68
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)

Standards and regulations

Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101

chanhvinh.com

SAC-8P-M12MS/ 1,5-PVC/M12FR - Sensor/actuator cable

1415747


https://www.phoenixcontact.com/gb/products/1415747

Drawings

Circuit diagram



Schematic diagram



Pin assignment M12 plug, 8-pos., view plug side


chanhvinh.com

SAC-8P-M12MS/ 1,5-PVC/M12FR - Sensor/actuator cable

1415747


https://www.phoenixcontact.com/gb/products/1415747

Schematic diagram



Pin assignment M12 socket, 8-pos., A-coded, view female side

Dimensional drawing



M12 x 1 socket, angled


chanhvinh.com

SAC-8P-M12MS/ 1,5-PVC/M12FR - Sensor/actuator cable

1415747

https://www.phoenixcontact.com/gb/products/1415747

Dimensional drawing



Plug, M12 x 1, straight, shielded

chanhvinh.com

SAC-8P-M12MS/ 1,5-PVC/M12FR - Sensor/actuator cable

1415747

https://www.phoenixcontact.com/gb/products/1415747

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/gb/products/1415747

UL Listed
Approval ID: FILE E 221474

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	30 V	2 A	-	-

cUL Listed
Approval ID: FILE E 221474

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	30 V	2 A	-	-

EAC-RoHS
Approval ID: RU D-DE.HB35.B.00387

cULus Listed

chanhvinh.com

SAC-8P-M12MS/ 1,5-PVC/M12FR - Sensor/actuator cable

1415747

https://www.phoenixcontact.com/gb/products/1415747

Classifications

ECLASS

ECLASS-11.0	27060311
ECLASS-12.0	27060311
ECLASS-13.0	27060311

ETIM

ETIM 9.0	EC001855

UNSPSC

UNSPSC 21.0	26121600

chanhvinh.com

SAC-8P-M12MS/ 1,5-PVC/M12FR - Sensor/actuator cable

1415747

https://www.phoenixcontact.com/gb/products/1415747

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

EF3.0 Climate Change

CO2e kg	1.659 kg CO2e

Phoenix Contact 2024 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk