chanhvinh.com

Network cable - VS-OE-PPC/ME-93C-LI/5,0

1416216

https://www.phoenixcontact.com/gb/products/1416216

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Assembled PROFINET cable, CAT5e, shielded, star quad, AWG 22 flexible cable conduit capable (7-wire), RAL 6018 (yellow-green), RJ45 plug/IP67 push-pull metal housing on free conductor end, line, length 5 m

Commercial Data

Item number	1416216
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	ABNEAI
Product Key	ABNEAI
Catalog Page	Page 308 (PC-2011)
GTIN	4046356474764
Weight per Piece (including packing)	392 g
Weight per Piece (excluding packing)	332.1 g
Customs tariff number	85444210
Country of origin	PL

chanhvinh.com

Network cable - VS-OE-PPC/ME-93C-LI/5,0

1416216

https://www.phoenixcontact.com/gb/products/1416216

Technical Data

Product properties

Product type	Data cable preassembled
Number of positions	4
Connection profile	RJ45 8(4)
No. of cable outlets	1
Locking type	Push Pull
Shielded	yes
Cable outlet	straight

Insulation characteristics

Overvoltage category	I
Degree of pollution	2

Electrical properties

Transmission medium	Copper

Material specifications

Flammability rating according to UL 94	V0

Connector

Insertion/withdrawal cycles	≥ 250

Connection 2

Material	Metal

Cable / line

Cable length	5.00 m
Cable weight	61.00 kg/km
Cable type	PROFINET
Cable structure	1x4xAWG22/7; SF/TQ
External cable diameter	6.50 mm
Outer sheath, material	PUR
External sheath, color	green RAL 6018
Conductor material	Tin-plated Cu litz wires
Conductor structure signal line	7x 0.25 mm
AWG signal line	22
Wire diameter incl. insulation	approx. 1.5 mm
Single wire, color	White, yellow, blue, orange
Wave impedance	100 Ω ±15 Ω (at 1 ... 100 MHz)
Smallest bending radius, fixed installation	33 mm
Smallest bending radius, movable installation	50 mm
Number of bending cycles	3000000
Bending radius	200 mm

chanhvinh.com

Network cable - VS-OE-PPC/ME-93C-LI/5,0

1416216

https://www.phoenixcontact.com/gb/products/1416216

Traversing rate	4 m/s
Acceleration	4 m/s²
Smallest bending radius, fixed installation	33 mm
Smallest bending radius, movable installation	50 mm
Number of bending cycles	3000000
Bending radius	200 mm
Traversing rate	4 m/s
Acceleration	4 m/s²

Ambient conditions

Degree of protection	IP65
	IP67
Degree of protection	IP65/IP67

Standards and regulations

Standards/specifications	IEC PAS 61076-3-117

chanhvinh.com


Network cable - VS-OE-PPC/ME-93C-LI/5,0

1416216

https://www.phoenixcontact.com/gb/products/1416216

Drawings

Dimensional drawing



Push-pull RJ45 connector IP65/67

chanhvinh.com

Network cable - VS-OE-PPC/ME-93C-LI/5,0

1416216

https://www.phoenixcontact.com/gb/products/1416216

Approvals

EAC
Approval ID: 19060508

chanhvinh.com

Network cable - VS-OE-PPC/ME-93C-LI/5,0

1416216

https://www.phoenixcontact.com/gb/products/1416216

Classifications

ECLASS

ECLASS-9.0	27060308
ECLASS-10.0.1	27060308
ECLASS-11.0	27060308

ETIM

ETIM 8.0	EC002599

UNSPSC

UNSPSC 21.0	26121600

chanhvinh.com

Network cable - VS-OE-PPC/ME-93C-LI/5,0

1416216

https://www.phoenixcontact.com/gb/products/1416216

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer’s declaration available under “Downloads”

Phoenix Contact 2022 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk