chanhvinh.com

Patch cable - VS-PPC/ME-PPC/ME-93K-LI/5,0

1419178

https://www.phoenixcontact.com/gb/products/1419178

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Sercos III cable, shielded, star quad, AWG 22 stranded (7-wire), RAL 3020 (traffic red), RJ45 connector/IP67 push-pull, metal on RJ45 connector/IP67, metal, D-coded, length: 5 m

Commercial Data

Item number	1419178
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	ABNEAI
Product Key	ABNEAI
Catalog Page	Page 316 (PC-2011)
GTIN	4046356541237
Weight per Piece (including packing)	471.4 g
Weight per Piece (excluding packing)	471.4 g
Customs tariff number	85444210
Country of origin	PL

chanhvinh.com

Patch cable - VS-PPC/ME-PPC/ME-93K-LI/5,0

1419178

https://www.phoenixcontact.com/gb/products/1419178

Technical Data

Product properties

Product type	Data cable preassembled
Number of positions	4
Application	Standard
No. of cable outlets	1
Locking type	Push Pull
Shielded	yes
Cable outlet	straight

Insulation characteristics

Overvoltage category	I

LED signaling

Status display	No

Electrical properties

Transmission medium	Copper

Connector

Insertion/withdrawal cycles	≥ 250

Connection 1

Material	Metal
Degree of protection	IP67

Connection 2

Material	Metal

Cable / line

Cable length	5.00 m
Cable type	Sercos III
Cable structure	1x4xAWG22/7; SF/TQ
External cable diameter	6.50 mm
Outer sheath, material	PVC
External sheath, color	Red RAL 3020
Conductor material	Tin-plated Cu litz wires
Conductor structure signal line	7x 0.25 mm
AWG signal line	22
Wire diameter incl. insulation	1.55 mm
Smallest bending radius, fixed installation	55 mm (cable, fixed installation)
Smallest bending radius, movable installation	55 mm (Cable, flexible installation)
Smallest bending radius, fixed installation	55 mm (cable, fixed installation)
Smallest bending radius, movable installation	55 mm (Cable, flexible installation)

chanhvinh.com

Ambient conditions

Degree of protection	IP65/IP67
Ambient temperature (operation)	-10 °C ... 60 °C (cable, fixed installation)
	-10 °C ... 60 °C (Cable, flexible installation)

chanhvinh.com


Patch cable - VS-PPC/ME-PPC/ME-93K-LI/5,0

1419178


https://www.phoenixcontact.com/gb/products/1419178

Drawings

Circuit diagram



Dimensional drawing



Push-pull RJ45 connector IP65/67

chanhvinh.com

Patch cable - VS-PPC/ME-PPC/ME-93K-LI/5,0

1419178

https://www.phoenixcontact.com/gb/products/1419178

Approvals

EAC
Approval ID: 19060508

chanhvinh.com

chanhvinh.com

Patch cable - VS-PPC/ME-PPC/ME-93K-LI/5,0

1419178

https://www.phoenixcontact.com/gb/products/1419178

Classifications

ECLASS

ECLASS-9.0	27060311
ECLASS-10.0.1	27060311
ECLASS-11.0	27060311

ETIM

ETIM 8.0	EC001855

UNSPSC

UNSPSC 21.0	26121600

chanhvinh.com

Patch cable - VS-PPC/ME-PPC/ME-93K-LI/5,0

1419178

https://www.phoenixcontact.com/gb/products/1419178

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer’s declaration available under “Downloads”

Phoenix Contact 2022 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk